INTERNATIONAL BOUNDARY AND WATER COMMISSION UNITED STATES AND MEXICO

UNITED STATES SECTION

JOSEPH F. FRIEDKIN, Commissioner El Paso, Texas

WILLARD L. ERICSON, Resident Engineer Yuma, Arizona

JOSEPH F. BURKHOLDER, Resident Engineer San Diego, California

MEXICAN SECTION

DAVID HERRERA JORDAN, Commissioner Cd. Juarez, Chihuahua

EDUARDO ARGUELLES C., Resident Engineer Mexicali, Baja California

WESTERN WATER BULLETIN 1971

Flow of The Colorado River and other Western Boundary Streams and Related Data

COLORADO RIVER
TIJUANA RIVER
SANTA CRUZ RIVER
SAN PEDRO RIVER
WHITEWATER DRAW

1971

CONTENTS

| Foreword and Acknowledgments | , , |
|---|--------------------|
| General Hydrologic Conditions for 1971 | . 50 |
| Map of Western Boundary | , , |
| | |
| | |
| I – Colorado River – Imperial Dam to Gulf of California | |
| | |
| Map of Colorado River Basin below Imperial Dam Following Page | 98 |
| | |
| Quantity of Water | |
| | |
| Stream-Flow and Stage Records | ٠ |
| Cohorado River at Yuma, Arizona - Stages Tributary - Reservation Main Drain No. 4 (California Drain) | . 6 |
| Yuma Main Canal Wasteway to Colorado River at Yuma, Arizona | |
| Colorado River below Yuma Main Canal Wasteway at Yuma, Arizona - Discharges below Yuma Main Canal Wasteway at Yuma, Arizona - Stages | . 11 |
| below Yuma Main Canal Wasteway at Yuma, Arizona - Stages | . 12 . 13 |
| Tributary - Drain No. 8-B (Araz Drain) | 1 |
| Wellton-Mohawk Drainage Water Discharged to Colorado River above Morelos Dam . | 15 |
| Colorado River at Northerly International Boundary - Discharges | |
| at Northerly International Boundary - Stages | . 17 |
| immediately above Morelos Dam - Stages | . 19 |
| at Morelos Diversion Structure - Stages | . 20 |
| Colorado River immediately below Morelos Dem - Stages | . 21 |
| Tributary - Wellton-Mohawk Drainage Water Discharged to Colorado River below Morelos Dam . | . 23 |
| Cooper Wasteway (Valley Division, Yuma Project) Colorado River at Morelos Gaging Station - Discharges | 24 |
| at Morelos Gaging Station - Stages | 25 |
| Tributary - Eleven Mile Wasteway (Valley Division, Yuma Project). Colorado River at Eleven Mile Gage - Stages | . 26 |
| Colorado River at Eleven Mile Gage - Stages | 27 |
| Tributary - Twenty-one Mile Wasteway (Valley Division, Yuma Project) Diversions by Pumps in the United States - Limitrophe Section | 29 |
| East Main Canal Wasteway (Valley Division, Yuma Project) | 36 |
| Yuma Main Drain (Valley Division, Yuma Project) West Main Canal Wasteway (Valley Division, Yuma Project) | 30 31 32 |
| West Main Canal Wasteway (Valley Division, Yuma Project) | 33 |
| Total Flows Crossing International Boundary into Mexico near San Luis, Sonora Colorado River at Southerly International Boundary - Discharges | 34 |
| at Southerly International Boundary - Stages | 35 |
| Tributary - Wasteway to Colorado River at Kilometer 27 in Mexico | . 36 |
| Wasteway to Colorado River at Colonia Elias in Mexico | 37 |
| Colorado River at Miguel C. Rodriguez in Mexico - Discharges | 38 39 |
| Tributary - Wastewey to Colorado River at Union in Mexico | 40 |
| Colorado River at El Maritimo in Mexico - Stages | 41 |
| Stored Water in Large Reservoirs of the Colorado River | 42 |
| | |
| Quality of Water | |
| Quality of Water | |
| Suspended Silt in the Colorado River and Intake Canal at Morelos Diversion Structure | 43 |
| Chemical Analyses of Water Samples | 45 |
| Electrical Conductivity of Water Samples | 46 |
| | |
| | |
| Climatological Data and Irrigated Areas | |
| | |
| Rainfall on the Colorado River Watershed | . 49 5 2 |
| Location of Rainfall Stations on the Colorado River Watershed. | 7e 53 |
| Evaporation in the Colorado River Basin | 53 54 56 |
| Irrigated Areas along Colorado River below Imperial Dam | 56 |
| | |
| | |
| | |
| II - Alamo and New Rivers | |
| | |
| Quantity of Water | |
| Stream-Flow and Stage Records | |
| Alamo River at International Boundary | 57 58 |
| New River at International Boundary Tributary - Wastes from Mexicali Potable Water Flant to New River in Mexico | 50 50 |
| Wisteria Wasteway to New River in Mexico | 59 60 |
| Waste Waters from Mexican System of Canals entering the United States | 61 |
| Salton Sea - Elevations of Water Surface | 62 |

CONTENTS

| | Q | uality | of V | Vate | r | | | | | | | | |
|--|----------------------|---------------|---------------|---------|-------|------------|--------|-------|--------|-------|----|---|------------------|
| Chemical Analyses of Water Samples . Electrical Conductivity of Water Samples | : | : | : | : | : | | | : | : | : | : | : | 6 3 64 |
| | III - | - Tiji | uana | Riv | ær | | | | | | | | |
| Map of Tijuana River Basin | , | | | | | | | | | | | | 65 |
| | | | | | | | | | | | | | |
| Stream-Flow Records | Qua | intity | of \ | Nate | r | | | | | | | | |
| Cottonwood Creek above Morena Dam, Ca below Morena Dam, Ca | liforni: liforni: | e. e. | : | : | : | : | | | : | | : | | 66 67 |
| above Barrett Dam, Co Diversions from Cottonwood Creek - Dulzura | aliforn a Condu | ia it belo | ow Bar | rett | Dem, | Cali | forni | e. | : | : | : | | 68 69 |
| Cottonwood Creek below Barrett Dam, Co above Tecate Creek na | ear Dul: | zura, (| Califo | rnia | : | : | | : | : | : | : | : | 70 71 |
| Tributary - Campo Creek near Campo Cottonwood Creek near International B | Cali: | fornia | | • | • | • | | • | • | • | | • | 72 |
| Inflows to Rodriguez Reservoir, Baja (| Californ | nia | | | : | : | | : | : | : | : | : | 73 74 |
| Diversions from Rodriguez Reservoir, Baja | Califor | rnia | • | ٠ | | | | • | | • | • | • | 75 76 |
| Tijuana River at International Bounda: near Nestor, California | | : | : | : | : | : | | : | : | : | • | : | 70 |
| Stored Water in Reservoirs, Tijuana River | | | • | • | ٠ | • | | • | • | • | | • | 78 |
| Climatological Date | on the | - Tiine | ana Ri | ver W | ster | shed | lrrig | ate | d Ar | eas | • | | 79 |
| Evaporation in the Tijuana River Basin Temperature in the Tijuana River Basin | : | • | • | • | • | • | | • | • | • | • | • | 81 82 |
| Drainage Areas above Gaging Stations and I | | ed Ares | as alo | ng Ti | juens | a Riv | er and | d Tr | ibutar | ies | : | • | 84 |
| IV - Whitewater | r Drav | v, Sar | Ped | lro a | and | San | ta C | ruz | Rive | ers | | | |
| Map of Western Boundary - Whitewater Draw, | San Pe | edro Ri | ver, | and S | anta | Cruz | River | r Bas | sins | • | • | • | 85 |
| | Qua | ntity | of V | Vate | r | | | | | | | | |
| Stream-Flow Records | | | | | | | | | | | | | |
| Whitewater Draw near Douglas, Arizona Sewage Influent, Douglas, Arizona Inte | rnstion | al Tre | et.meni | t. Plar | nt. | • | | • | • | • | • | • | 86 87 |
| Sewage Influent, Agua Prieta, Sonora I | nternat | ional | Oxidat | tion h | Ponds | | | | : | : | : | : | 88 |
| San Pedro River at Palominas, Arizona | | • | • | | • | • | | • | | • | • | • | 89 |
| Santa Cruz River near Lochiel, Arizona at El Cajon, Sonora. | : | : | | : | : | : | | • | • | • | : | • | 90 91 |
| at El Cajon, Sonora . near Nogales, Arizona | | | | : | ÷ | ÷ | | | ÷ | • | : | ÷ | 92 |
| Sewage Effluent, Nogales International | Treatm | ent Pl | ant | • | • | • | | • | ٠ | • | ٠ | • | 93 |
| Climatological Data | and | Drain | age | Basi | in a | nd I | rriga | atec | l Are | as | | | |
| Rainfall on the Santa Cruz River Watershed Location of Rainfall Stations in the Santa | | | | | | | | | | | | | 94 |
| Location of Rainfall Stations in the Santa Temperature, Humidity, Evaporation, and Wi | Cruz R | iver B | asin to Cm | . 1941 | | · contr | • | | • | • | • | • | 95 96 |
| Drainage Areas above Gaging Stations and I | rrigate | d Area | s alor | ng Sar | ita C | ruz F | iver. | San | Pedr | River | ٠, | • | 90 |
| and Whitewater Draw | • | | • | • | • | | | | | • | • | | 97 |
| | | | | | | | | | | | | | |
| Correction | s to | Prev | ious | Wa | ter | Bul | letin | 8 | | | | | |

Corrections to Previous Water Bulletins

FOREWORD

This bulletin is the twelfth annual compilation of stream discharges and other hydrographic data relating to the international aspects of the Colorado River below Imperial Dam, the Tijuana River and other streams crossing the western land boundary of the United States and Mexico. The compilation was prepared jointly by the United States and Mexican Sections of the International Boundary and Weter Commission, solely for the purpose of presenting statistical data relating to stream flow and kindred subjects for the Colorado River from Imperial Dam to the Gulf of California, the Tijuana River and its important tributaries in the United States and Mexico, and other streams, including the Alamo and New Rivers which cross the California-Baja California boundary, and the Santa Cruz River and Whitewater Draw which cross the Arizona-Sonora boundary. This volume contains the information for the year 1971.

Stream gaging on the Colorado River below Imperial Dam began in 1902 when the station at Yuma, Arizona was established. Stage records have been obtained at this station since January 1878. Continuous stream gaging on the Tijuana River and its important tributaries in the United States and in Mexico began in 1936. Each government operates the gaging stations located within its own country.

Colorado River below Imperial Dam

Below Imperial Dam, the Colorado River flows southward 10 miles to the mouth of the Gila River, thence westward 11 miles to Pilot Knob Mountain, and south 1 mile to the point where the northerly international land boundary, between Celifornia and Baja California, intersects the river. From this point the river continues to flow southward and forms the boundary between the United States and Mexico for a distance of about 22 miles to the point where the southerly international land boundary between Arizons and Sonora intersects the river. From this point the river continues to flow southward about 90 miles to discharge into the Gulf of California.

The ordinary flows of Colorado River below Imperial Dam are largely controlled by releases at Hoover Dam, completed in 1935. The releases are further regulated at Davis Dam, completed in 1950, and by Parker and Imperial Dams, completed in 1936. Small amounts of runoff may occasionally be contributed to the flow in the lower river from the usually dry arroyso draining the 10,900 square miles along the river from Hoover Dam to the mouth of the Gila River, not including 5,500 square miles in the Bill Williams River watershed. In addition, flows ranging from usually minor amounts to infrequent torrential floods may enter the lower Colorado River from the Bill Williams River and from the Gila River, draining about 7,300 square miles below Painted Rock Dam and Reservoir, completed in January 1960.

At Imperial Dam, diversions are made to Gila Gravity Main Canal and All-American Canal for irrigation projects in Arizona, including the Yuma Valley, Gila and Wellton-Mohawk projects, and in California, including the Imperial Valley, Coachella Valley and Reservation Division of Yuma Project. Also, under the provisions of the 1944 Water Treaty, there may be diverted to the All-American Canal at Imperial Dam for delivery to Mexico in the Alamo Canal, or substitute canal, at the northerly boundary, a portion of Mexico's guaranteed annual allotment of waters of the Colorado River. No such diversions were made in 1971.

Below Laguna Dam, measured and unmeasured flows are returned to the river principally as waste and drainage water from the irrigation projects in the United States. Waste and drainage waters from irrigation projects in the United States also cross the boundary into Mexico near San Luis, Arizona without returning to the river in the United States.

In the limitrophe section of the river, 1.1 miles downstream from the northerly boundary, Morelos Dam, the principal diversion structure for Mexico, was completed and piaced in operation on November 8, 1950. Since that date all of Mexico's guaranteed treaty allotment of Colorado River water has been delivered in the limitrophe section of the river. The greater portion of such deliveries has been diverted to the Alamo Canal at Morelos Dam.

Tijuana River Basin

The total drainage area of the Tijuana River basin is 1,731 square miles of which 27 percent lies in the United States and 73 percent in Mexico. This river is formed by the principal tributaries, Cottonwood Creek, which rises in the United States and Rio de las Palmas, which rises in Mexico. Cottonwood Creek crosses the international land boundary 21 miles from the Pacific Ocean to join the Rio de las Palmas in Mexico. From the confluence of these tributaries, the Tijuana River flows northwesterly 5 miles to cross the land boundary into the United States near San Ysidro, California, and Tijuana, Baja California, and then flows westerly 6 miles to discharge into the Pacific Ocean 2 miles north of the boundary. The flow of Cottonwood Creek is partially controlled by Barrett and Morena Reservoirs in the United States and the flow of the Rio de las Palmas is partially controlled by Rodriguez Reservoir in Mexico.

Whitewater Draw near Douglas, Arizona

Whitewater Draw rises in the United States and flows south into Mexico crossing the international boundary near Douglas, Arizona, eventually discharging into the Gulf of California through the Yaqui River in Mexico. The total drainage area above the Douglas Gaging Station is 1,023 square miles. A number of mountain streams in the upper reaches of the basin are diverted for irrigation but they would normally sink or go to ground water before reaching the main water course.

FOREWORD

San Pedro River at Palominas, Arizona

The San Pedro River rises in Mexico and flows north into the United States crossing the boundary near Palominas, Arizona, and thence northwesterly into the Gila River. The river in the vicinity of the intermational boundary drains an area of 741 square miles of which 649 square miles are in Mexico.

Santa Cruz River near Nogales and Lochiel, Arizona

The Santa Cruz River rises in the United States and flows south into Mexico crossing the international boundary near Lochiel, Arizona, and returns to the United States near Nogales, Arizona, eventually discharging into the Gila River southwest of Phoenix, Arizona. The drainage area of the Santa Cruz River above Nogales station is 533 square miles. Of this amount, 348 square miles lie in Mexico. There are a few ground water irrigation diversions above the Lochiel station in Arizona and an unknown amount of water diverted for irrigation in Mexico.

Acknowledgments

Other agencies which have contributed to the data published herein include the Bureau of Reclamation and the Geological Survey of the U. S. Department of the Interior; the National Weather Service, Department of Commerce; the Yuma County Water Users' Association; the Imperial Irrigation District; the city of San Diego, California; and the Ministry of Hydraulic Resources of Mexico. Specific notation is made of each of the abovenamed agencies, where the data appear. The courtesy and cooperation of those who have made these contributions are acknowledged with appreciation.

Units of Measure

Data collected by the Mexican Section are computed and published in a Spanish version of the water bulletin in metric units. The Mexican data are converted and reported in this bulletin in English units. Conversion factors conform generally to those in the National Bureau of Standards Miscellaneous Publication 286 "Units of Weight and Measure (United States Customary and Metric) - Definitions and Tables of Equivalents". However, for convenience some of the factors have been shortened and modified to facilitate conversion, reconversion to the original units when necessary, and checking of data. Conversion of the mean daily discharges, the monthly average discharge, and the monthly and annual volumes from metric to English units is direct. For this reason the monthly average discharge in cubic feet per second and monthly volumes in acre-feet shown for gaging stations operated by the Mexican Section cannot necessarily be obtained in the usual manner from the total monthly flow in second-foot days. For the same reason, evaporation and rainfall data, when totaled, may not be equivalent to the direct conversion from metric to English units. The following factors have been used for data in this bulletin:

ENCLICH INTEG

| М | TRIC UNITS | | ENGLISH U | <u>INITS</u> |
|----------------|--|---------|---------------------------------------|---|
| | | LENGTHS | | |
| 1 | Centimeter Meter Kilometer | | 0.393701 1 3.28084 1 0.621371 1 | Feet |
| | | AREAS | | |
| 1 | Square Meter Hectare Square Kilometer | | 2.471054 | Square Feet Acres Square Mile |
| | | VOLUME | | |
| 1 1 1000 | Cubic Meter Cubic Meter Cubic Meter Cubic Meters Liter | | 1.30795 0.81071 | Cubic Inches Cubic Feet Cubic Yards Acre-Foot U.S. Gallon |
| | | WEIGHTS | | |
| 1 | Kilogram Metric Ton Metric Ton | | 2.204623 2204.623 1.102311 | |

GENERAL HYDROLOGIC CONDITIONS FOR 1971

Colorado River

Normally, there is no measurable amount of runoff from the portion of the Colorado River basin in the United States and Mexico below Hoover Dam, not including Bill Williams and Gila Rivers. There was no significant amount in 1971. The average seasonal (October 1970-September 1971) rainfall over the upper basin, as gaged at 13 index stations, was about 12.1 inches compared to a seasonal average of about 13.75 inches for the 49 seasons (1983-1971). In the lower basin of the Colorado River in Mexico, from Morelos Diversion Dam to the Gulf of California, the average precipitation (1971) measured at 6 index stations was 2.48 inches compared to an average of 2.24 inches during the last 13 years (1959-1971).

The flow of the Colorado River reaching Imperial Dam was 5,828,800 acre-feet, about 70% of the 37-year average (1935-1971) of 8,341,849 acre-feet. At the northerly international boundary, the total flow of the river during 1971 was 1,316,193 acre-feet, about 3% of the 1935-1971 average of 3,856,830 acre-feet. At the southerly international boundary, the flow during 1971 was only 85,172 acre-feet, or about 3% of the 1935-1971 average of 3,049,107 acre-feet. The total flow of the Colorado River reaching the M. C. Rodriguez gaging station, 24.5 miles downstream from the southerly international boundary, and 4.5 miles upstream from the Sonora-Baja California railroad bridge, was 25,036 acre-feet in 1971, about 2.1% of the 1951-1971 average of 1,211,241 acre-feet.

The total of all flows of the Colorado River entering Mexico in 1971 amounted to 1,561,622 acre-feet, 35% of the 1935-1971 average of 4,493,407 acre-feet, as measured 1) in the Colorado River at the northerly international boundary, 2) in the Wellton-Mobawk Main Outlet Drain Extension near Morelos Dam, 3) in the wasteways that discharge into the limitrophe section of the river from the United States bank, and 4) in the canal which discharges waste and drainage waters from the Yuma Project across the southerly land boundary into Mexico near San Luis, Arizona, less diversions in the United States by pumps in the limitrophe section.

No flood peaks of importance occurred in streams of the lower Colorado River basin during 1971. A maximum instantaneous flow of 3,430 second-feet occurred in the Colorado River at the northerly boundary station on April 10.

Stored waters at the end of the year in the three major reservoirs on the Colorado River below Lee's Ferry amounted to 19,724,600 acre-feet, 69% of the usable capacity of 28,588,400 acre-feet. The greater part (17,545,000 acre-feet) of the storage was contained in Lake Mead (Hoover Dam). There were no reported shortages of Colorado River water for irrigation during 1971 due to drought or accident to the irrigation system.

The total reported acreage irrigated from waters of the Colorado River below Imperial Dam in 1971 was 1,087,786 acres; 658,698 acres in the United States and 429,088 acres in Mexico. An estimated one-third of acreage in Mexico is served by pumping from ground water.

The suspended sediment load passing the northerly boundary station in 1971 was 75.0 acre-feet, about 26% of the 1956-1971 average of 288 acre-feet.

Tijuana River Basin

During 1971, the temperatures at Barrett Dam, California (elevation 1,750 feet) in the upper portion of the basin in the United States averaged 60.2 degrees, 1.1 degrees below the 41-year mean. In the extreme upper portion of the basin in Mexico at San Juan de Dios, Baja California (elevation 3,280 feet), the recorded temperatures during the year averaged 54 degrees, 1.8 degrees below the long-term average, and at Rodriguez Dam, Baja California (elevation 459 feet), the recorded temperatures averaged 63 degrees, equal to the mean of many years.

At Barrett Dam in the upper portion of the basin in the United States, the recorded precipitation was 11.54 inches, 66% of normal, and at Chula Vista near the lower end of the basin, 5.87 inches, or 61% of normal. The recorded precipitation at San Juan de Dios in the upper portion of the basin in Mexico, was 11.93 inches, approximately 76% of the normal during the 16-year period, and at Rodriguez Dam in the lower portion of the basin in Mexico, 4.61 inches, 58% of the 34-year average.

Runoff in the basin during 1971 averaged less than 6% of normal. Above Morena Reservoir the runoff was 658 acre-feet, or about 11% of the 35-year 1937-1971 mean of 5,924 acre-feet. At Rodriguez Reservoir, the runoff was 615 acre-feet, or about 4% of the 34-year mean of 13,854 acre-feet.

The flow of the Tijuana River at the international boundary was 153 acre-feet during 1971, and the flow in the Tijuana River near Nestor was 0 acre-feet.

Whitewater Draw

During 1971, the average annual temperature over the watershed was slightly below normal, while the annual precipitation was about normal. Runoff for the year at the gaging station near Douglas, Arizona, of 10,353 acre-feet was about 149% of average.

GENERAL HYDROLOGIC CONDITIONS FOR 1971

San Pedro River

During 1971, the average annual temperature was below normal. The annual precipitation, as measured at Coronado National Monument Headquarters, was 102% of the 1961-1971 mean of 20.02 inches. The stream flow at the international boundary was 37,952 acre-feet, 170% of the 1951-1971 normal.

Santa Cruz River

During 1971, the average annual temperature over the watershed was somewhat below normal and the annual precipitation was about 115% of the 33-year 1939-1971 mean. Runoff measured at the Nogales gaging station where the stream re-enters the United States was 21,100 acre-feet. The total runoff for the year measured at the gaging station near Localel, Arizons, where the stream enters Mexico from the United States, was 2,405 acre-feet. Therefore, neglecting stream flow depletions in Mexico, the records indicate a contribution of about 18,965 acre-feet from the loop of the river lying in Mexico, or approximately 89% of the flow reaching the Nogales station.

Alamo and New Rivers

During 1971, the average annual temperature over the drainage areas of the Alamo and New Rivers, as recorded at El Centro, California, and at Mexicali, Baja-California, was 71.0 and 70.0 degrees, respectively, 1.3 and 1.8 degrees below the respective normals.

At El Centro, the precipitation was 0.44 inches, about 18% of the 41-year average, and in Mexicali, the annual precipitation was 1.10 inches, 37% of the 46-year average. The total flow of the New River at the international boundary in 1971 was 107,281 acre-feet, which was about 144% of the 1943-1971 normal.

Salton Sea

During 1971, the average annual temperature around the Salton Sea was about 96% of the long-term average, while the annual precipitation recorded at Brawley, California was approximately 70% of the long-term mean of 2.33 inches. The water surface of the Salton Sea remained more or less the same during the year. The maximum stage, 231.7 feet below mean sea level, was recorded on April 6-17, inclusive. The minimum stage, 232.6 feet below mean sea level, was recorded on January 1-4 and October 19 to November 18, inclusive.

COLORADO RIVER AT YUMA, ARIZONA - STAGES

DESCRIPTION: Water-stage recorder 200 feet upstream from lower highway bridge, 6.9 miles upstream from the northerly international land boundary, 2,100 feet downstream from the upper highway and railroad bridges at Yume, Arizona, 4.7 miles downstream from the mouth of the Gila River, 19.1 miles downstream from Imperial Dam, and 0.3 mile upstream from the mouth of the Yuma Main Canal Wasteway. Zero of gage is at mean sea level, U. S. C. & G. S. datum.

RECORDS: Mean deily gage heights are based on continuous water-stage records. Records available: Gage heights, January 1878 through August 10, 1965, furnished by the U. S. Geological Survey. From August 11, 1965 through 1971, records obtained by the United States Section of the Commission.

EXTREMENS: Prior to 1935: Maximum gage height 136.79 feet on January 22, 1916; minimum gage height 115.49 feet on September 17, 1917. Since 1935: Maximum gage height 127.36 feet on September 7, 1939; minimum gage height 111.22 feet on July 16, 1947.

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|
| 1 2 8 4 5 | 112.92 112.93 112.94 112.91 * 112.93 | 112.97 112.94 112.96 113.22 113.43 | 112.99 112.87 112.88 112.96 113.12 | 113.68 113.58 113.21 113.17 113.35 | 113.33 113.36 113.30 113.29 113.31 | 113.63 113.42 113.46 113.42 112.75 | 112.86 113.07 113.62 113.46 113.07 | 113.07 113.09 113.10 113.09 113.16 | 113.52 113.56 113.51 113.51 113.50 | 114.85 113.58 113.21 112.97 112.93 | 112.89 112.88 112.91 112.84 112.88 | 112.98 112.97 112.97 112.99 112.97 |
| 7 8 9 | " 113.55 " 113.20 " 113.10 " 113.02 " 113.35 | 113.47 113.49 113.54 113.50 113.58 | 113.11 113.10 113.10 113.11 113.10 | 113.67 113.68 113.57 113.24 113.26 | 113.36 113.30 113.31 113.29 113.25 | 112.79 112.80 112.77 112.75 112.79 | 113.03 113.00 113.05 112.98 112.97 | 113.21 113.25 113.29 113.23 113.09 | 113.49 113.44 113.47 113.50 113.49 | 112.96 112.94 112.93 112.92 112.88 | 112.87 112.87 112.83 112.82 112.85 | 112.90 112.89 112.95 113.08 113.10 |
| 12 18 14 | " 113.15 " 113.05 " 113.02 " 113.03 " 113.00 | 113.59 113.51 113.04 113.02 113.15 | 113.12 113.13 113.11 113.12 113.12 | 113.28 113.18 113.11 113.09 113.12 | 113.29 113.29 113.28 113.27 113.26 | 112.79 112.68 112.51 112.51 112.59 | 112.99 112.99 112.98 113.10 113.16 | 113.07 113.09 113.17 113.21 113.23 | 113.45 113.32 113.07 113.10 113.09 | 112.87 112.87 112.86 112.85 112.85 | 112.82 112.82 112.83 112.96 112.89 | 112.85 112.82 112.82 112.79 112.79 |
| 16 17 18 19 20 | " 112.98 " 112.99 " 112.96 " 112.95 * 112.97 | 112.99 112.93 112.88 112.90 112.91 | 113.20 113.33 113.28 113.26 113.27 | 113.13 113.23 113.27 113.34 113.46 | 113.26 113.28 113.29 113.23 113.23 | 112.72 112.83 112.95 113.12 113.05 | 113.14 113.20 113.20 113.18 113.13 | 113.03 113.24 *113.46 #113.30 #113.11 | 112.80 112.71 112.70 112.71 112.71 | 112.83 112.87 112.82 112.81 112.83 | 113.02 113.11 112.88 112.87 112.85 | 112.79 112.79 112.79 112.80 112.79 |
| 21 22 23 24 25 | 112.99 112.99 112.95 112.95 112.96 | 113.21 113.39 113.27 113.13 113.16 | 113.20 113.16 113.13 113.17 113.19 | 113.24 113.30 113.21 113.12 113.10 | 113.31 113.28 113.25 113.22 113.24 | 112.99 112.95 112.93 112.96 112.86 | 113.12 113.09 113.09 113.09 113.06 | "113.20 "113.21 *114.51 113.47 113.37 | 112.72 112.70 112.70 112.70 112.63 | 112.87 112.88 112.83 112.82 112.85 | 112.89 112.87 112.87 112.86 112.84 | 112.80 112.80 112.80 112.79 112.77 |
| 26 27 28 29 80 81 | 112.97 112.97 112.99 112.95 112.97 112.98 | 113.20 113.16 113.13 | 113.19 113.20 113.44 113.67 113.66 113.68 | 113.09 113.07 113.03 113.09 113.78 | 113.24 113.29 113.25 113.24 113.19 113.26 | 112.79 112.82 112.82 112.74 112.85 | 113.04 113.03 112.98 113.04 113.05 | 113.76 113.37 112.91 112.84 112.86 113.66 | 112.63 112.68 112.74 112.91 114.96 | 112.82 112.83 112.88 112.83 112.88 112.89 | 112.84 112.83 112.83 112.89 112.94 | 112.76 112.77 112.77 112.77 112.80 112.85 |
| Avg | | 113.20 | 113.19 | 113.29 | 113.28 | 112.90 | 113.09 | 113.25 | 113.13 | 112.97 | 112.88 | 112.86 |

^{*} Partly Estimated "Estimated

RESERVATION MAIN DRAIN NO. 4 (CALIFORNIA DRAIN)

DESCRIPTION: Water-stage recorder (digital) located 500 feet upstream from the U.S. Highway No. 80 crossing and one mile northwest of Yuma, Arizona. Discharge measurements are made from a footbridge immediately below the gage. The drainage canal discharges into the outfall channel of the Yuma Main Canal Wasteway 200 feet downstream from the spillway structure, and thence into the Colorado River on the right bank, 1,000 feet upstream from Colorado River below Yuma Main Canal Wasteway, and 6.5 miles upstream from the northerly international boundary. Prior to October 1955, published as "California Drainage Canal near Yuma, Arizona."

RECORDS: Based on current meter measurements and a continuous record of gage heights. Records are computed and furnished by the U. S. Geological Survey. Records available: Monthly discharge, January 1913 to April 1920, October 1921 to March 1925, and January 1934 to September 1947; daily and monthly discharge, October 1947 through 1971.

through 1971.

REMARKS: Reservation Main Drain No. 4 collects drainage and wastewater from the area east of the Yuma Main Canal on the Reservation Division of the Yuma Project, located in California. Since 1939, collection of seepage from the All-American Canal has caused large increases in drainage flows. Average annual flow prior to 1937 was 12,500 acre-feet. Monthly and annual averages since 1937 are shown in the table below.

EXTREMES: Prior to 1937: Maximum annual flow 20,190 acre-feet, 1916; minimum annual flow 8,920 acre-feet, 1913.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | .Oct. | Nov. | Dec. |
|----------------------------------|----------------------------------|----------------------------|----------------------------------|----------------------------------|----------------------------------|----------------------------|----------------------------------|----------------------------------|----------------------------|----------------------------------|----------------------------|----------------------------------|
| 1 2 3 4 5 | 38 41 39 42 38 | 38 39 41 46 45 | 46 45 44 40 40 | 55 60 60 55 55 | 49 54 49 50 49 | 55 52 52 55 64 | 52 47 50 54 54 | 53 48 48 56 54 | 49 62 60 60 59 | 76 60 57 56 65 | 67 64 64 61 66 | 59 56 53 54 53 |
| 6 7 8 9 10 | 41 41 38 48 50 | 43 43 42 43 42 | 39 39 38 49 47 | 55 55 55 55 55 55 | 51 50 50 50 49 | 68 47 48 52 57 | 52 52 56 64 58 | 50 50 54 48 52 | 58 57 61 60 61 | 61 56 62 53 56 | 61 58 62 60 82 | 56 60 54 51 55 |
| 11 12 13 14 15 | 45 40 40 43 39 | 42 43 53 49 46 | 38 38 36 44 41 | 55 55 50 55 55 | 50 52 53 52 52 52 | 50 62 62 56 55 | 59 60 57 48 50 | 54 54 56 55 57 | 58 55 48 51 54 | 57 56 57 58 61 | 59 54 53 59 59 | 60 56 54 53 58 |
| 16 17 18 19 20 | 41 43 44 41 41 | 46 48 40 44 41 | 40 38 40 42 44 | 55 50 60 47 47 | 49 48 50 53 51 | 53 49 45 44 45 | 57 56 53 48 51 | 64 60 59 58 64 | 78 66 67 67 61 | 62 69 66 68 66 | 57 57 64 58 61 | 52 48 49 48 48 |
| 21 22 23 24 25 | 42 42 41 42 42 | 41 43 42 49 51 | 46 48 46 53 50 | 49 52 53 56 66 | 51 59 51 50 49 | 49 55 65 56 54 | 53 50 48 54 51 | 84 78 67 57 57 | 68 63 68 58 61 | 68 64 62 73 68 | 61 56 56 56 54 | 53 49 49 52 48 |
| 26 27 28 29 30 31 | 41 43 48 39 40 41 | 47 49 49 | 47 48 59 55 55 55 | 58 61 58 59 55 | 49 50 54 51 49 | 53 62 50 52 54 | 51 50 51 50 52 59 | 57 60 63 61 56 63 | 67 58 53 67 72 | 63 65 67 61 60 71 | 54 54 53 51 53 | 48 47 47 50 51 48 |
| Sum | 1,294 | 1,245 | 1,390 | 1,656 | 1,573 | 1,621 | 1,648 | 1,797 | 1,827 | 1,944 | 1,774 | 1,619 |

| | | | | Current | Year 19 | 71 | | | Per | iod 1937-197 | 1 | |
|---------|------|--------|-----|---------|----------|------------------|---------|-----------|-----------|--------------|---------|--|
| Month_ | | e Gage | ø | Extreme | Second F | eet | Average | Total | Acre Feet | | | |
| Month L | Fe | et | | High | | Low | Second | 10.5. | | ACIE TECT | , | |
| | High | Low | Day | | Day | | Feet | Acre Feet | Average | Maximum | Minimum | |
| Jan. | | | 10 | 50 | 1 1 | 38 | 41.7 | 2,567 | 3,227 | 4,780 | 877 | |
| Feb. | | | 13 | 53 | 1 | 3 8 38 | 44.5 | 2,469 | 3,074 | 4,320 | 563 | |
| Mar. | | | 28 | 59 | 13 | 36 | 44.8 | 2,757 | 3,744 | 5,240 | 1,240 | |
| Apr. | | | 25 | 66 | 119 | 47 | 55.2 | 3,285 | 3,786 | 5,250 | 1,160 | |
| May | | | 22 | 59 | 17 | 48 | 50.7 | 3,120 | 3,891 | 5,590 | 992 | |
| June | | | 6 | 68 | 19 | يلبة | 54.0 | 3,215 | 3,786 | 5,580 | 885 | |
| July | | | 9 | 64 | 2 | 47 | 53.2 | 3,269 | 4,079 | 6,550 | 816 | |
| Aug. | | | 21 | 84 | 1 2 | 48 | 58.0 | 3,564 | 4,048 | 6,810 | 861 | |
| Sept. | | | 16 | 78 | 13 | 48 | 60.9 | 3,624 | 3,808 | 6,220 | 889 | |
| Oct. | | | 1 | 76 | 9 | 53 | 62.7 | 3,856 | 3,817 | 5,740 | 1,040 | |
| Nov. | | | 10 | 82 | 29 | 51 | 59.1 | 3,519 | 3,552 | 5,490 | 994 | |
| Dec. | | | 7 7 | 60 | 127 | 47 | 52.2 | 3,211 | 3,440 | 4,960 | 966 | |
| Yearly | | | | 84 | | 36 | 53.1 | 38,456 | 44,252 | 63,700 | 12,840 | |

Ø Mean daily

f And other days

YUMA MAIN CANAL WASTEWAY TO COLORADO RIVER AT YUMA. ARIZONA

SECRIFIION: The wasteway receives water from the Yuma Main Canal at the check structure on the canal, 1,645 feet upstream from the intake of the Colorado River siphon, and 3.2 miles downstream from the Siphon Drop Power Plant. This wasteway discharges into the Colorado River on the California side, 1,000 feet upstream from Colorado River below Yuma Main Canal Wasteway, and 6.5 miles upstream from the DESCRIPTION: northerly international land boundary.

RECORDS: Discharge is computed as the difference between the measured discharge of the Yuma Main Canal at the Siphon Drop Power Plant upstream and that of the same canal below the Colorado River siphon, with deductions for small irrigation diversions from the canal between the two gaging stations. 1971 records good except those below 125 second-feet, which are fair. Records obtained and furnished by U.S.Geological Survey. Records available: April 1913 through 1971.

REMARKS: The wasteway discharges to the river the flow in excess of irrigation water in the Yuma Main Canal. This excess flow, in addition to the irrigation water, was diverted from the All-American Canal into the Yuma Main Canal and utilized for power purposes at the Siphon Drop Power Plant.

EXTREMES: Prior to 1935, when storage began in Lake Mead: Average annual flow, 297,800 acre-feet; maximum annual flow, 913,700 acre-feet, 1932; minimum annual flow, 114,900 acre-feet, 1917. Since 1935: Maximum mean daily discharge, 2,020 second-feet, December 24-25, 1948; minimum mean daily discharge, no flow on numerous occasions.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|---|---|---|--------------------------------------|--|-------------------------------------|--|--|---|---|------------------------------------|--|
| 1 2 3 4 5 | 6.1 6.1 6.1 6.1 | 273 280 320 680 823 | 6.7 6.7 6.7 6.7 6.7 | 9.7 9.9 9.8 12.0 9.2 | 542 569 567 662 592 | 850 836 922 826 11.0 | 7.7 11.0 11.0 12.0 10.0 | 9.5 10.0 11.0 11.0 | 857 895 818 811 808 | 11.0 11.0 11.0 11.0 | 54.0 76.0 98.0 126 134 | 80.0 78.0 100 110 106 |
| 6 7 8 9 | 7.1 6.7 6.7 70.0 830 | 931 886 834 913 918 | 6.7 6.7 6.7 6.8 6.7 | 9.2 9.2 9.0 9.1 9.5 | 658 650 691 635 624 | 12.0 11.0 11.0 9.0 8.8 | 9.5 9.5 9.5 9.5 9.5 | 11.0 11.0 11.0 11.0 | 819 834 8 52 863 806 | 14.0 11.0 13.0 16.0 20.0 | 127 132 141 152 165 | 94.0 124 157 449 360 |
| 11 12 13 14 15 | 519 300 305 288 2 81 | 817 6 3 8 10.0 8.9 9.5 | 16.0 6.7 6.7 6.7 6.7 | 13.0 11.0 9.7 15.0 14.0 | 702 694 683 686 676 | 9.3 12.0 15.0 16.0 15.0 | 9.5 9.5 9.5 11.0 9.5 | 11.0 12.0 11.0 11.0 | 790 676 496 577 511 | 28.0 30.0 36.0 50.0 53.0 | 118 154 132 41.0 7.7 | 9.5 8.4 8.4 8.4 |
| 16 17 18 19 20 | 203 193 204 195 209 | 10.0 11.0 14.0 15.0 16.0 | 6.7 6.7 7.2 6.7 6.7 | 12.0 14.0 18.0 18.0 14.0 | 666 665 588 618 568 | 15.0 15.0 14.0 11.0 | 9.5 10.0 10.0 9.5 9.9 | 11.0 11.0 11.0 11.0 | 17.0 19.0 18.0 16.0 20.0 | 70.0 77.0 91.0 96.0 | 0 0 41.0 110 89.0 | 8.4 8.4 8.5 8.9 |
| 21 22 23 24 25 | 207 235 270 254 261 | 20.0 15.0 14.0 13.0 9.5 | 6.7 6.7 8.4 9.2 7.4 | 18.0 18.0 17.0 17.0 | 610 531 548 596 708 | 11.0 11.0 11.0 11.0 | 12.0 10.0 10.0 9.9 9.5 | 11.0 11.0 11.0 11.0 | 20.0 16.0 15.0 12.0 28.0 | 91.0 70.0 82.0 77.0 87.0 | 104 114 125 133 170 | 8.9 8.9 8.9 14.0 |
| 26 27 28 29 30 31 | 272 277 264 239 270 281 | 7.2 7.2 6.8 | 8.3 8.0 9.0 9.4 10.0 9.6 | 13.0 15.0 16.0 178 925 | 709 700 682 689 674 758 | 12.0 11.0 11.0 11.0 | 9.5 9.5 12.0 12.0 9.5 9.5 | 11.0 11.0 11.0 11.0 156 898 | 24.0 27.0 28.0 40.0 13.0 | 87.0 87.0 87.0 96.0 111 91.0 | 144 138 125 198 125 | 15.0 12.0 9.5 9.5 9.5 9.5 |
| Sum | 6.478.0 | 8,500.1 | 236.6 | 1,467.3 | 19,941 | 3,741.1 | 310.5 | 1,372.5 | 11,726.0 | 1,727.0 | 3,273.7 | 1,859.8 |

6,478.0 236.6 19,941 11,726.0

Paried 1025-1071

Current Vons

| | | | | Current 1 | ear lo | 971 | | | ren | 100 1937-197 | 1 |
|--|------------|-----|--|--|--|--|--|--|--|---|---|
| | Extrem | | ø | Extreme Se | cond F | | Average | Total | | Acre Feet | |
| Month | Fe High | Low | Day | High | Day | Low | Second Feet | Acre Feet | Average | Maximum | Minimum |
| Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec. | | | 10 6 11 30 31 3 † 4 31 2 30 29 | 830 931 16 925 758 922 12 898 895 111 198. | † 1 28 † 1 8 22 10 1 1 24 † 1 † 16 † 13 | 6.1 6.8 6.7 9.0 531 8.8 7.7 9.5 12 | 209 304 7.63 48.9 643 125 10.0 44.3 391 55.7 109 60.0 | 12,849 16,860 469 2,910 39,552 7,420 616 2,722 23,258 3,425 6,493 3,677 | 61,752 54,036 56,390 56,840 64,383 56,370 55,806 56,223 56,988 54,209 54,600 61,259 | 110,700 89,140 90,190 86,580 88,280 86,960 91,220 89,890 83,660 90,050 101,500 108,800 | 3,230 2,856 469 2,500 5,480 3,330 452 456 12,419 2,176 3,850 918 |
| Yearly | | | | 931 | | 0 | 167 | 120,251 | 688,856 | 1,042,850 | 75,950 |

^{*} And other days

Ø Mean daily

COLORADO RIVER BELOW YUMA MAIN CANAL WASTEWAY AT YUMA, ARIZONA - DISCHARGES

DESCRIPTION: Water-stage recorder located in California on the right bank of the river, 1,000 feet down-stream from the mouth of the Yuma Main Canal Wasteway, 0.6 mile downstream from the abandoned gaging station on the Colorado River at Yuma, 5.2 miles downstream from the mouth of the Gila River, 19.6 miles downstream from Imperial Dam and 6.4 miles upstream from the northerly international boundary. Zero of gage is 101.99 feet above mean sea level, U. S. C. & G. S. datum.

RECORDS: Based on current meter measurements and a continuous record of gage heights. Computations by shifting control methods. Records obtained and furnished by U. S. Geological Survey. Records available: October 1963 through 1971. Records from January 1951 through September 1963, deduced from "Colorado River at Yuma" plus flows from "Reservation Main Drain No. 4", and "Yuma Main Canal Wasteway."

REMARKS: Reservoirs on the Colorado River, including Lake Mead where storage began in 1935, transmoun-

tain diversions, reservoirs on the Gila River, irrigation diversions and return flows modify the river flow at this station.

Mean Daily Discharge in Second Feet 1971 — Annual and Period Summary

| Day | Jan. | P.L | 141 | A14 | May | | | | | | | |
|----------------------------------|--|---|--|---|--|---|--|--|---|--|---------------------------------|--|
| Uzy | Jan. | Feb. | March | April | may | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
| 1 2 3 4 5 | 505 520 510 505 505 | 708 697 722 1,090 1,320 | 570 530 524 564 646 | 995 890 611 583 675 | 1,120 1,170 1,100 1,120 1,100 | 1,460 1,280 1,330 1,270 495 | 499 603 880 815 594 | 634 648 643 657 675 | 1,350 1,270 1,230 1,230 1,230 | 1,710 879 681 592 595 | 589 567 594 580 628 | 633 627 640 648 642 |
| 6 7 8 9 10 | 839 629 545 618 1,500 | 1,380 1,370 1,380 1,400 1,440 | 641 637 633 645 631 | 922 945 880 6 3 8 6 5 5 | 1,140 1,110 1,140 1,100 1,080 | 513 499 482 486 504 | 576 576 594 571 562 | 710 725 750 730 666 | 1,220 1,210 1,230 1,250 1,230 | 613 592 599 591 588 | 617 617 602 588 601 | 613 626 657 844 795 |
| 11 12 13 14 15 | 1,050 755 749 755 749 | 1,400 1,250 520 510 585 | 649 629 644 647 641 | 690 627 574 585 598 | 1,120 1,130 1,120 1,110 1,110 | 490 466 386 370 410 | 576 576 576 634 666 | 639 65 7 695 715 720 | 1,210 1,110 932 962 936 | 605 603 597 630 622 | 557 574 601 650 545 | 528 511 507 482 492 |
| 16 17 18 19 20 | 719 7 3 1 719 707 695 | 515 495 476 495 5 05 | 675 769 744 714 719 | 602 683 713 746 836 | 1,090 1,100 1,080 1,050 1,020 | 462 504 562 634 607 | 648 670 670 661 634 | 625 730 840 780 670 | 565 534 506 505 526 | 624 643 617 610 615 | 588 645 595 636 623 | 487 490 482 487 471 |
| 22 23 24 25 | 690 707 695 695 701 | 668 783 719 640 651 | 677 650 638 668 682 | 687 719 675 605 605 | 1,080 1,050 1,040 1,030 1,080 | 571 558 558 562 504 | 643 630 630 639 621 | 720 720 1,470 845 770 | 533 501 499 489 515 | 619 604 588 595 615 | 636 629 628 630 634 | 488 474 475 471 456 |
| 26 27 28 29 30 31 | 701 707 713 679 701 701 | 684 662 657 | 684 693 839 1,010 970 978 | 590 592 578 669 1,600 | 1,100 1,110 1,090 1,090 1,040 1,110 | 470 482 478 446 495 | 612 607 625 612 625 639 | 995 815 567 535 607 1,310 | 506 530 563 647 1,830 | 586 586 614 589 625 619 | 644 637 625 664 662 | 460 446 448 459 472 496 |
| Sum | 21,995 | 23,722 | 21,341 | 21,768 | 33,930 | 18,334 | 19,464 | 23,263 | 26,849 | 20,246 | 18,386 | 16,807 |

| | | | | Current | Year 19 | 71 | | | Per | iod 1951-197 | 1 |
|--------|-------|--------|-----|-----------|-------------|----------|----------------|-----------------|-----------|--------------|---|
| | | e Gage | ø | Extreme S | econd F | eet | Average | Total | | Acre Feet | |
| Month | re | et Law | Day | High | | Low | Second Feet | Acre Feet | Average | Maximum | Minimum |
| | півн | Low | Day | | Day | <u> </u> | reei | 71070 7 001 | | | *************************************** |
| Jan. | 11.28 | 9.72 | 10 | 1,500 | 1 1 | 505 | 710 | 43,6 2 6 | 244,071 | 979,890 | 29,857 |
| Feb. | 11.23 | 9.69 | 10 | 1,440 | 18 | 476 | 847 | 47,052 | 182,255 | 826,600 | 33,790 |
| Mar. | 10.59 | 9.74 | 29 | 1.010 | 3 | 524 | 688 | 42,329 | 200,820 | 1,073,270 | 35,002 |
| Apr. | 11.53 | 9.92 | 30 | 1,600 | 13 | 574 | 726 | 43,176 | 189,920 | 843,010 | 42,831 |
| May | 11.16 | 10.61 | 2 | 1,170 | 20 | 1,020 | 1,095 | 67,299 | 178,663 | 863,860 | 56,493 |
| June | 11.39 | 9.35 | 1 | 1,460 | 14 | 370 | 611 | 36,365 | 167,228 | 833,970 | 36,365 |
| July | 10.55 | 9.62 | 3 | 880 | 1 | 499 | 628 | 38,606 | 182,462 | 649,820 | 34,413 |
| Aug. | 11.85 | 9.64 | 23 | 1,470 | 29 | 535 | 750 | 46,141 | 188,428 | 670,050 | 36,426 |
| Sept. | 11.20 | 9.53 | 30 | 1,830 | 24 | 489 | 895 | 53,254 | 157,227 | 775,930 | 43,182 |
| Oct. | 11.75 | 9.81 | 1 | 1,710 | †2 6 | 586 | 653 | 40,157 | 129,871 | 802,210 | 34,965 |
| Nov. | 10.91 | 9.71 | 29 | 664 | 15 | 545 | 613 | 36,468 | 154,152 | 911,370 | 36,468 |
| Dec. | 11.13 | 9.58 | 9 | 844 | 27 | 446 | 542 | 33,336 | 198,067 | 1,114,550 | 33,023 |
| Yearly | 11.85 | 9.35 | | 1,830 | | 370 | 730 | 527,809 | 2,173,164 | 10,220,870 | 515,749 |

[†] And other days

COLORADO RIVER BELOW YUMA MAIN CANAL WASTEWAY AT YUMA, ARIZONA - STAGES

(See Preceding Page For Description)

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|--|---|--|---|--|--------------------------------------|--------------------------------------|---|---|--|--|--|
| 1 | 9.74 | 10.18 | 9.85 | 10.55 | 10.81 | 11.25 | 9.64 | 9.89 | 11.09 | 11.81 | 9.93 | 10.02 |
| 2 | 9.77 | 10.18 | 9.76 | 10.45 | 10.87 | 11.04 | 9.85 | 9.91 | 11.16 | 10.42 | 9.89 | 10.00 |
| 8 | 9.76 | 10.21 | 9.75 | 10.03 | 10.78 | 11.10 | 10.43 | 9.92 | 11.08 | 10.03 | 9.95 | 10.03 |
| 4 | 9.75 | 10.74 | 9.83 | 9.99 | 10.82 | 11.01 | 10.28 | 9.95 | 11.09 | 9.84 | 9.92 | 10.05 |
| 5 | 9.75 | 11.03 | 9.98 | 10.15 | 10.80 | 9.70 | 9.83 | 9.99 | 11.07 | 9.84 | 10.03 | 10.05 |
| 6 7 8 9 | 10.33 10.00 9.84 9.94 11.17 | 11.10 11.09 11.10 11.12 11.17 | 9.97 9.96 9.96 9.98 9.95 | 10.55 10.58 10.48 10.11 10.14 | 10.87 10.82 10.86 10.82 10.78 | 9.74 9.71 9.67 9.68 9.72 | 9.78 9.77 9.81 9.75 9.73 | 10.06 10.09 10.14 10.10 9.97 | 11.07 11.04 11.08 11.12 11.08 | 9.89 9.85 9.86 9.85 9.85 | 9.99 9.99 9.96 9.93 9.96 | 9.98 10.01 10.08 10.46 10.36 |
| 11 | 10.62 | 11.13 | 9.98 | 10.20 | 10.84 | 9.69 | 9.76 | 9.92 | 11.05 | 9.89 | 9.85 | 9.80 |
| 12 | 10.22 | 10.93 | 9.95 | 10.09 | 10.85 | 9.62 | 9.76 | 9.96 | 10.87 | 9.89 | 9.89 | 9.76 |
| 18 | 10.23 | 9.84 | 9.98 | 9.99 | 10.84 | 9.42 | 9.76 | 10.03 | 10.52 | 9.88 | 9.95 | 9.75 |
| 14 | 10.24 | 9.81 | 9.98 | 10.01 | 10.83 | 9.38 | 9.89 | 10.08 | 10.58 | 9.95 | 10.06 | 9.69 |
| 14 | 10.23 | 9.95 | 9.97 | 10.03 | 10.83 | 9.48 | 9.96 | 10.09 | 10.53 | 9.94 | 9.82 | 9.72 |
| 16 | 10.19 | 9.80 | 10.03 | 10.04 | 10.80 | 9.60 | 9.92 | 9.89 | 9.77 | 9.95 | 9.92 | 9.71 |
| 17 | 10.21 | 9.75 | 10.19 | 10.18 | 10.81 | 9.70 | 9.97 | 10.11 | 9.70 | 10.00 | 10.03 | 9.72 |
| 18 | 10.19 | 9.71 | 10.15 | 10.24 | 10.70 | 9.83 | 9.97 | 10.33 | 9.63 | 9.94 | 9.92 | 9.70 |
| 19 | 10.18 | 9.74 | 10.10 | 10.29 | 10.75 | 9.98 | 9.95 | 10.21 | 9.63 | 9.93 | 10.01 | 9.71 |
| 20 | 10.15 | 9.75 | 10.11 | 10.42 | 10.71 | 9.91 | 9.89 | 9.99 | 9.68 | 9.95 | 9.99 | 9.67 |
| 21 | 10.15 | 10.04 | 10.04 | 10.19 | 10.79 | 9.84 | 9.91 | 10.09 | 9.70 | 9.96 | 10.02 | 9.72 |
| 22 | 10.18 | 10.23 | 9.99 | 10.25 | 10.75 | 9.81 | 9.88 | 10.09 | 9.62 | 9.92 | 9.99 | 9.68 |
| 23 | 10.17 | 10.11 | 9.97 | 10.17 | 10.74 | 9.80 | 9.88 | 11.45 | 9.62 | 9.90 | 9.99 | 9.68 |
| 24 | 10.17 | 9.97 | 10.02 | 10.05 | 10.72 | 9.81 | 9.90 | 10.33 | 9.60 | 9.91 | 9.99 | 9.67 |
| 25 | 10.18 | 9.99 | 10.05 | 10.05 | 10.79 | 9.68 | 9.86 | 10.18 | 9.65 | 9.96 | 10.00 | 9.63 |
| 26 27 28 29 30 31 | 10.19 10.20 10.21 10.15 10.19 10.19 | 10.05 10.01 10.00 | 10.05 10.07 10.31 10.56 10.53 10.56 | 10.02 10.02 10.00 10.12 11.37 | 10.81 10.83 10.80 10.80 10.74 10.83 | 9.59 9.62 9.61 9.52 9.63 | 9.84 9.83 9.87 9.84 9.87 | 10.65 10.28 9.77 9.70 9.81 11.21 | 9.64 9.69 9.76 9.94 11.92 | 9.90 9.90 9.97 9.91 9.99 9.98 | 10.02 10.01 9.98 10.07 10.06 | 9.65 9.61 9.63 9.65 9.69 9.74 |
| Avg | | 10.31 | 10.05 | 10.23 | 10.80 | 9.87 | 9.88 | 10.14 | 10.40 | 10.00 | 9.97 | 9.83 |

DRAIN NO. 8-B (ARAZ DRAIN)

DESCRIPTION: This drain discharges into the Colorado River 3.9 miles downstream from Colorado River below Yuma Main Canal Wasteway, and 2.5 miles upstream from the northerly international boundary. Prior to October 1955, published as "Araz Drain".

RECORDS: Records are furnished by U. S. Geological Survey from current meter measurements during the year.

Records available: May 1948 through 1971.

REMARKS: Drain 8-B, which was constructed in February 1948, collects seepage in the westerly section of the Reservation Division of the Yuma Project which lies in California. Flow in the drain between the mouth and the U.S. Highway No. 80 culvert, about 3,200 feet upstream, is affected by backwater from the river during ordinary high stages.

EXTREMES: Mean daily discharge: Maximum, 24 second-feet on September 1, 1953; minimum, 0.1 second-foot

several days in February 1966.

Mean Daily Discharge in Second Feet 1971 — Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|---------------------------------|--------------------------|--|--|--|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|--|
| 1 2 3 4 5 | 1.9 1.8 1.8 1.8 | 1.3 1.3 1.3 1.3 | 1.5 1.6 1.6 1.6 1.7 | 2.5 2.5 2.5 2.5 2.5 | 3.0 2.9 2.9 2.8 | 2.0 2.0 2.0 2.0 | 1.3 1.3 1.4 1.4 | 2.0 2.1 2.1 2.2 | 2.9 2.9 3.0 3.0 | 3.5 3.6 3.6 3.6 | 3.9 3.8 3.8 3.7 3.7 | 2.5 2.5 2.4 2.4 |
| 6 7 8 9 | 1.8 1.7 1.7 1.7 1.7 | 1.3 1.3 1.3 1.4 | 1.7 1.7 1.8 1.8 | 2.5 2.5 2.5 2.5 3.5 5.5 5.5 5.5 5.5 5.5 5.5 5.5 5.5 5 | 2.8 2.7 2.7 2.7 2.6 | 1.9 1.9 1.9 1.9 | 1.4 1.4 1.5 1.5 | 2.2 2.2 2.3 2.3 2.3 | 3.0 3.0 3.0 3.0 | 3.7 3.7 3.7 3.8 3.8 | 3.6 3.6 3.5 3.5 3.4 | 2.4 2.4 2.3 2.3 |
| 11 12 13 14 15 | 1.7 1.6 1.6 1.6 1.6 | 1.4 1.4 1.4 1.4 | 1.9 1.9 1.9 2.0 2.0 | 2.5 2.5 2.5 2.5 2.5 | 2.6 2.6 2.5 2.5 2.4 | 1.9 1.9 1.8 1.8 | 1.5 1.5 1.6 1.6 1.6 | 2.4 2.4 2.5 2.5 | 3.1 3.1 3.1 3.1 3.1 | 3.9 3.9 3.9 3.9 | 3.4 3.3 3.3 3.2 | 2.3 2.3 2.2 2.2 2.2 |
| 16 17 18 19 20 | 1.6 1.5 1.5 1.5 | 1.4 1.4 1.4 1.4 | 2.0 2.1 2.1 2.1 2.2 | 2.5 2.5 2.6 2.7 2.8 | 2.4 2.4 2.3 2.3 2.3 | 1.8 1.8 1.8 1.8 | 1.6 1.7 1.7 1.7 | 2.5 2.6 2.6 2.6 2.7 | 3.1 3.2 3.2 3.2 3.2 | 3.9 3.9 3.9 3.9 | 3.2 3.1 3.0 3.0 | 2.2 2.1 2.1 2.1 2.1 |
| 21 22 23 24 25 | 1.5 1.4 1.4 1.4 | 1.5 1.5 1.5 1.5 | 2.2 2.3 2.3 2.3 2.4 | 2.8 2.9 3.0 3.0 | 2.2 2.1 2.1 2.1 | 1.8 1.8 1.8 1.8 | 1.8 1.8 1.8 1.8 | 2.7 2.7 2.8 2.8 2.8 | 3.2 3.2 3.2 3.3 | 3.9 3.9 3.9 3.9 | 2.9 2.9 2.8 2.8 2.7 | 2.1 2.1 2.1 2.1 2.1 |
| 26 27 28 29 30 31 | 1.4 1.3 1.3 1.3 1.3 | 1.5 1.5 1.5 | 2.4 2.4 2.5 2.5 2.5 2.5 | 3.0 3.0 3.0 3.0 3.0 | 2.0 2.0 2.0 2.0 2.0 2.0 | 1.6 1.5 1.4 1.3 1.3 | 1.9 1.9 1.9 1.9 1.9 | 2.8 2.8 2.8 2.8 2.8 | 3.3 3.3 3.3 3.3 3.3 | 3.9 3.9 3.9 3.9 3.9 | 2.7 2.6 2.6 2.6 2.5 | 2.1 2.1 2.1 2.1 2.1 2.1 |
| Sum | 48.4 | 39.1 | 63.3 | 80.3 | 75.0 | 53.7 | 50.6 | 77.5 | 93.8 | 118.4 | 95.6 | 69.0 |

Current Year 1071 Period 1019 1071

| | | | | Current | ines. To | 3/1 | | 1 | rer | 1 00 1948-197. | 1 |
|--------|---------|-----|-------------|-----------|-------------|-----|----------------|--------------|-------------|-----------------------|---------|
| | Extreme | | ø | Extreme S | Second I | | Average | Total | | Acre Feet | |
| Month_ | High | Low | Day | High | Day | Low | Second Feet | Acre Feet | Average | Maximum | Minimum |
| Jan. | | | 1 | 1.9 | 127 | 1.3 | 1.6 | 96.0 | 381 | 899 | 39.3 |
| Feb. | | | 121 | 1.5 | 7 1 | 1.3 | 1.4 | 77.6 | 331 | 746 | 40.5 |
| Mar. | | | 128 | 2.5 | 1 | 1.5 | 2.0 | 1 2 6 | 404 | 853 | 73.8 |
| Apr. | | | †23 | 3.0 | 11 | 2.5 | 2.7 | 159 | 428 | 1,000 | 66.8 |
| May | | | 1 1 | 3.0 | 126 | 2.0 | 2.4 | 149 | 42 6 | 966 | 61.5 |
| June | | | 1 1 | 2.0 | 129 | 1.3 | 1.8 | 107 | 445 | 1,030 | 67.4 |
| July | | | †2 6 | 1.9 | † 1 | 1.3 | 1.6 | 100 | 50 6 | 1,260 | 72.8 |
| Aug. | | | †23 | 2.8 | 1 1 | 2.0 | 2.5 | 154 | 561 | 1,350 | 73.8 |
| Sept. | | | 125 | 3.3 | 1 1 | 2.9 | 3.1 | 186 | 533 | 1,370 | 53.6 |
| Oct. | | | 711 | 3.9 | 1 1 | 3.5 | 3.7 | 235 | 543 | 1,220 | 55.3 |
| Nov. | | | 1 1 | 3.9 | 30 | 2.5 | 3.2 | 190 | 489 | 1,240 | 57.7 |
| Dec. | | | 1 1 | 2.5 | †17 | 2.1 | 2.2 | 137 | 445 | 1,050 | 51.0 |
| Yearly | | | | 3.9 | | 1.3 | 2.3 | 1,716.6 | 5,492 | 12,429 | 834 |

Mean daily

[†] And other days

PILOT KNOB POWER PLANT AND WASTEWAY NEAR PILOT KNOB, CALIFORNIA

DESCRIPTION: The Pilot Knob Power Plant and Wasteway is located on the All-American Canal, 20.8 miles down-Stream from the intake at Imperial Dam, 6 miles west of Yuma, about one mile north of the northerly inter-national boundary and empties into the old Alamo Canal in the United States and thence into the Colorado River through Rockwood gates, about one mile upstream from the northerly international boundary. Water-stage niver through notations gates, about one mare upstream from the information and interest and recorder is located in forebay on right bank of the All-American Canal, 550 feet upstream from wasteway gates and 1,800 feet from entrance to the power plant. Datum of gage is 150.00 feet above mean sea level. Tailrace gage is on left bank, 680 feet downstream from power plant with automatic recording equipment in control bouse. All bypass gates are equipped with calibrated openings which are read on all gate changes. Datum of tailrace gage is at mean sea level; elevation of sill of wasteway gates is 147.68 feet, U. S. C. & G. S. datum. Prior to October 1956, this station was published as "Pilot Knob Wasteway near Pilot Knob, California." datum. Prior to October 1950, this station was published as "Miot Ambo wasteway hear First Miob California."

ECORDS: Delly discharge is computed from flowmeter equipment and head and openings on wasteway gates or from head and gate opening on wicket and wasteway gates. Records furnished by the U.S. Geological Survey. Records available: July 1944 through 1971. The wasteway was operated for the purpose of diverting Colorado River water to the Alamo Canal for use in Mexico from July 1944 to November 8, 1950, in accordance with arrangements between the United States and Mexico for emergency use of the All-American Canal facilities.

Records since 1950 show water released through Pilot Knob Power Plant and Wasteway from the All-American RECORDS: Canal and returned to the Colorado River through Rockwood gates.

MARKS: Pilot Knob Wasteway was completed in 1938 and the first flow occurred on February 5, 1939. Pilot Knob Power Plant was completed in January 1957 and the first flow occurred on January 14, 1957.
TREMES: Maximum mean daily discharge, 8,350 second-feet on January 26, 1958; minimum mean daily discharge,

EXTREMES: no flow during long periods.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|---|---|--|---|------------------|---|--|---|-------------------------|------------------|------------------|--|
| 1 2 3 4 5 | 1,300 1,070 1,080 1,350 1,670 | 0 0 0 | 1,440 1,810 2,090 2,120 2,010 | 2,350 2,350 2,350 2,360 2,400 | 0 0 0 0 | 0 0 0 0 1,090 | 1,840 1,800 1,460 1,520 1,750 | 1,910 1,940 1,950 2,000 1,940 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 |
| 6 7 8 9 | 1,360 1,280 1,330 1,100 | 0 0 0 0 | 2,040 2,010 2,040 2,020 2,030 | 2,370 2,380 2,360 2,340 2,310 | 0 0 0 0 | 1,030 1,000 1,020 1,040 1,040 | 1,800 1,800 1,780 1,800 1,800 | 1,870 1,880 1,840 1,880 1,930 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 483 |
| 11 12 13 14 15 | 0 0 0 0 | 0 36 1,030 1,010 961 | 2,030 2,050 2,020 1,960 2,310 | 2,260 2,320 2,360 2,380 2,390 | 0 0 0 0 | 1,040 1,000 1,050 1,100 1,030 | 1,800 2,030 2,080 2,060 2,000 | 1,870 1,830 1,830 1,820 1,780 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 1,040 1,380 1,470 1,480 1,480 |
| 16 17 18 19 20 | 0 0 0 0 | 1,080 1,150 1,150 1,130 1,090 | 2,330 2,200 2,260 2,260 2,270 | 2,110 1,910 1,850 1,800 1,730 | 0 0 0 0 | 1,260 1,270 1,270 1,440 1,450 | 2,040 2,080 2,110 2,080 2,070 | 1,850 1,760 1,620 1,600 1,820 | 0 0 0 0 | 0000 | 0 0 0 0 | 1,490 1,450 1,430 1,420 1,450 |
| 21 22 23 24 25 | 0 0 0 0 | 1,180 1,200 1,140 1,080 1,040 | 2,260 2,310 2,320 2,330 2,320 | 1,890 1,720 1,500 1,540 1,500 | 0 0 0 0 | 1,680 1,680 1,720 1,710 1,810 | 2,070 2,080 2,130 2,100 2,100 | 1,840 1,780 1,170 1,520 1,740 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 1,460 1,460 1,450 1,470 1,470 |
| 26 27 28 29 30 31 | 0 0 0 0 | 1,000 1,060 1,110 | 2,320 2,290 2,290 2,270 2,330 2,290 | 1,580 1,620 1,340 1,130 | 0 0 0 0 0 | 1,860 1,840 1,790 1,840 1,800 | 2,130 2,140 2,140 2,160 2,170 2,140 | 1,480 1,590 1,590 1,290 1,070 | 0 0 0 0 104 | 0 0 0 0 | 0 0 0 0 | 1,480 1,490 1,510 1,480 1,480 1,640 |
| Sum | 11,540 | 17,447 | 66,630 | 58,500 | 0 | 35,860 | 61,060 | 51,990 | 104 | 0 | 0 | 30,963 |

1944-1971 Current Year 1971 Period Average Extreme Gage Total Acre Feet Second Month High Low Acre Feet Average Maximum Minimum Feet High Day Day 22,889 400,200 1,670 110 Ω 372 43,291 Jan. 623 34,606 132,159 18,876 149,500 † 1 1 Feb. 22 1,200 0 116 2,149 68,007 279,300 n 1.440 Mar. 2,330 95,162 19,794 64,474 ō ō 116,033 260,900 2,400 30 1,950 Apr. 5 165,400 0 0 0 0 May 204,300 Ö 71,127 26 1,860 1 1 O 1,195 June 114,327 260,000 0 1,460 121,111 30 3 31 1,970 July 2,170 103,121 117,768 270,100 0 2,000 0 Aug. ō 173,300 51,460 182,600 1 1 206 56,012 0 3.5 Sept 30 104 ٥ õ 0 11,287 0 Oct. 0 15,862 ٥ ٥ 0 Nov. 37,049 1,640 61,414 319,700 0 Dec. 31 **†** 1 n 999 1.944.700 O 912 2,400 O 662,666 661,909 Yearly

Ø Mean daily 1 And other days

WELLTON-MOHAWK DRAINAGE WATER DISCHARGED TO COLORADO RIVER ABOVE MORELOS DAM

DESCRIPTION: Diversion structure (Main Outlet Drain Extension No. 1) in Wellton-Mohawk Drainage Extension Channel for diverting water to the Gila River, 0.5 mile upstream from the confluence of the Gila and Colorado Rivers. A continuous water-stage recorder immediately upstream from outlet structure (Main Outlet Drain Extension No. 2), 0.4 mile downstream from diversion structure which diverts water from the Extension Channel directly to the Colorado River at a point 0.8 mile upstream from the northerly international boundary, and 1.9 miles upstream from Morelos Dam. The Gila River enters the Colorado River 13 miles upstream from Morelos Dam.

RECORDS: Partial diversions of the Extension Channel flow at M. O. D. E. No. 1 were determined from the gate openings, rated by discharge measurements below the outlet. Diversions of the total Extension Channel flow were determined at an upstream measuring station at channel station 9+00. Flows diverted at M. O. D. E. No. 2 were based on discharge measurements during the year and a continuous record of gage heights. Records furnished by Bureau of Reclamation through September 30, 1969. Beginning October 1, 1969 records furnished by U. S. Geological Survey. The record shown below is the combination of diversions at M. O. D. E. No. 1 and M. O. D. E. No. 2. Records available: February 10, 1961 through 1971.

REMARKS: Pursuant to Minute No. 218 of the Commission, an extension to the Wellton-Mohawk Drainage Conveyance

REMARKS: Pursuant to Minute No. 218 of the Commission, an extension to the Wellton-Mohawk Drainage Conveyance Channel was constructed along the left bank of the Colorado River to a point immediately below Morelos Dam, a distance of about 12 miles, and placed in operation on November 16, 1965. Drainage flows may be discharged to the Gila River and thence to the Colorado River at the diversion structure, M. O. D. E. No. 1, at the upstream end of the extension; and directly to the Colorado River at the structure above Morelos Dam, M. O. D. E. No. 2, and at the structure immediately below Morelos Dam, M. O. D. E. No. 3, the record of which is shown on page 22.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|----------------------------------|---------------------------------|--|---------------------------------|--|---------------------------------|--|---------------------------------|---------------------------------|-----------------------|---------|--|
| 1 2 3 4 5 | 154 141 139 160 176 | 0 0 0 69.0 104 | 287 293 294 296 300 | 300 268 292 285 310 | 130 122 118 117 124 | 174 176 173 170 195 | 298 296 298 303 298 | 303 296 300 296 297 | 182 172 171 175 179 | 0 0 0 0 | 0000 | 0 0 0 0 |
| 6 7 8 9 | 180 168 158 133 99.0 | 106 105 108 108 109 | 300 301 300 299 299 | 283 285 259 254 282 | 127 127 125 125 125 | 197 200 201 198 197 | 295 288 281 293 307 | 292 291 290 289 286 | 178 179 175 169 172 | 0000 | 0 0 0 0 | 0 0 0 35.0 78.0 |
| 11 12 13 14 15 | 62.0 1.6 .1 0 | 120 130 155 158 158 | 298 296 298 304 300 | 289 292 291 290 286 | 126 124 124 125 123 | 197 197 196 196 200 | 303 300 156 152 155 | 300 297 298 303 299 | 173 157 129 126 129 | 0 0 0 0 | 0 0 0 0 | 76.0 108 158 171 188 |
| 16 17 18 19 20 | 0 0 0 0 | 164 173 211 219 239 | 301 299 301 302 300 | 284 282 285 283 288 | 124 124 122 127 126 | 255 246 246 284 288 | 151 150 148 205 255 | 296 289 280 163 150 | 5.2 0 0 0 | 0 0 0 0 | 0 0 0 0 | 196 204 212 205 199 |
| 21 22 23 24 25 | 0 0 0 0 | 319 264 204 259 254 | 304 301 300 297 295 | 281 287 292 296 295 | 126 125 126 127 125 | 184 302 296 296 302 | 257 257 257 257 247 262 | 155 152 31.0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 198 196 196 198 195 |
| 26 27 28 29 30 31 | 0 0 0 0 | 257 254 266 | 291 303 361 313 304 311 | 292 279 258 227 176 | 126 127 126 123 125 126 | 303 302 302 302 307 | 258 260 293 302 302 301 | 0 0 0 0 169 170 | 0 0 0 | 0 0 0 0 0 | 0 0 0 | 195 184 173 173 174 179 |
| Sum | 1,571.7 | 4,513.0 | 9,348 | 8,371 | 3,867 | 7,082 | 7,928 | 6,292.0 | 2,471.2 | 0 | 0 | 3,891.0 |

Current Year 1971 Period 1961-1971 Extreme Second Feet Extreme Gage Average Total Acre Feet Feet Month Second High Average Acre Feet Maximum Minimum High Day Day Feet 19,452 16,784 18,742 180 3,117 6 114 50.7 8,019 0 Jan. 8,951 18,541 16,604 7,814 15,155 15,574 † 1 1 0 Feb. 21 319 0 162 8,434 361 310 287 302 Mar. 28 30 279 18,573 11,948 176 Anr. 5 4 117 125 7,670 12,277 19,783 5,944 ĭ30 May 9,523 15,062 19,186 19,295 June 30 307 170 236 14,047 14,252 July 10 307 18 148 256 15,725 16,919 12,480 † 1 1 303 182 † 2<u>1</u>1 16,230 18,887 12,480 Aug. ۵ 203 4,902 10,799 6,460 18,313 3,052 Ó 82.4 Sept. 117 0 o ٥ 0 18,625 Oct. 17,627 ō Ö ٥ n 6,177 7,440 Nov. 18,988 930 **†** 1 126 7,718 18 212 O Dec. 86,306 0 137,116 215,087 361 155 109,755 Yearly

[†] And other days Ø Mean daily

COLORADO RIVER AT NORTHERLY INTERNATIONAL BOUNDARY - DISCHARGES

SSCRIFTION: Water-stage recorder on the left (Arizona) bank and cableway at the point where the northerly international land boundary (California-Baja California) intersects the Colorado River, about 6.4 miles downstream from Colorado River below Yuma Main Canal Wasteway, 5 miles west of Yuma, Arizona, 1.1 miles upstream from Moreloo Diversion Structure, and about one mile downstream from Rockwood Gate. Zero of the gage is at mean sea level, U. S. C. & G. S. datum. Station is operated by the United States DESCRIPTION: Section of the Commission.

Section of the Commission.

RECORDS: Based on 359 current meter measurements during the year, 205 by the United States Section, 144 by the Mexican Section of the Commission, 10 by the U. S. Geological Survey, and a continuous record of gage heights. Computations by shifting control methods. Discharges are computed on the basis of a water-stage recorder located 1,680 feet upstream from the northerly international boundary where the remains of an old weir serve as a partial controlling section. A continuous gage height record is available November 15, 1948 through 1971; daily discharge records available January 1, 1950 through 1971.

REMARKS: Reservoirs on the Colorado River, including Lake Mead above Hover Dam, where storage began in 1935, reservoirs on the Gila River, and many irrigation diversions and return flows regulate the river flow at this station except for infrequent flood flows. During 1971, the flow at this point represented the total semunt of Colorado River water which crossed the northerly international boundary.

total amount of Colorado River water which crossed the northerly international boundary

EXTREMES: rior to January 1935: Maximum instantaneous discharge estimated about 250,000 second-feet, January 22, 1916; minimum discharge, no flow several days during August and September 1934; average annual flow 13,443,000 acre-feet; maximum annual flow 25,480,000 acre-feet, 1907; minimum annual flow 1,174,000 acre-feet, 1934. Since January 1935: Maximum mean daily discharge, about 33,000 second-feet; February 7, 1942; minimum discharge, no flow during April 1935.

Mean Daily Discharge in Second Feet 1971 — Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|---|---|--|---|--|---|--|--|---|--|---------------------------------|--|
| 1 2 3 4 5 | 2,030 | 740 | 2,320 | 3,320 | 1,200 | 1,500 | 2,660 | 2,880 | 1,500 | 1,970 | 700 | 710 |
| | 1,760 | 720 | 2,620 | 3,340 | 1,180 | 1,460 | 2,660 | 2,900 | 1,520 | 1,250 | 681 | 700 |
| | 1,740 | 700 | 2,890 | 3,320 | 1,140 | 1,440 | 2,650 | 2,920 | 1,500 | 782 | 700 | 710 |
| | 2,030 | 1,080 | 2,960 | 3,300 | 1,140 | 1,480 | 2,670 | 2,980 | 1,490 | 662 | 690 | 728 |
| | 2,370 | 1,340 | 2,960 | 3,310 | 1,140 | 1,760 | 2,640 | 2,950 | 1,500 | 624 | 728 | 728 |
| 6 7 8 9 | 2,370 2,130 2,070 1,830 1,470 | 1,380 1,400 1,410 1,410 1,440 | 2,980 2,960 2,960 2,950 2,960 | 3,320 3,360 3,340 3,310 3,340 | 1,190 1,190 1,200 1,180 1,160 | 1,710 1,710 1,730 1,730 1,740 | 2,660 2,680 2,670 2,660 2,670 | 2,900 2,890 2,920 2,940 2,900 | 1,500 1,490 1,500 1,520 1,500 | 662 634 652 652 643 | 710 710 710 690 700 | 690 681 719 962 1,440 |
| 11 | 1,100 | 1,470 | 2,960 | 3,340 | 1,160 | 1,740 | 2,670 | 2,820 | 1,500 | 662 | 664 | 1,690 |
| 12 | 728 | 1,430 | 2,960 | 3,320 | 1,180 | 1,770 | 2,950 | 2,840 | 1,400 | 662 | 662 | 2,030 |
| 13 | 710 | 1,740 | 2,980 | 3,320 | 1,170 | 1,730 | 2,890 | 2,840 | 1,170 | 662 | 672 | 2,170 |
| 14 | 750 | 1,730 | 2,920 | 3,340 | 1,170 | 1,750 | 2,920 | 2,840 | 1,180 | 690 | 752 | 2,180 |
| 15 | 740 | 1,730 | 3,250 | 3,340 | 1,170 | 1,730 | 2,920 | 2,840 | 1,190 | 690 | 634 | 2,210 |
| 16 | 730 | 1,770 | 3,280 | 3,090 | 1,170 | 2,060 | 2,920 | 2,800 | 690 | 700 | 643 | 2,210 |
| 12 | 740 | 1,840 | 3,260 | 2,880 | 1,180 | 2,110 | 2,920 | 2,800 | 618 | 719 | 719 | 2,190 |
| 13 | 730 | 1,880 | 3,280 | 2,890 | 1,180 | 2,110 | 2,940 | 2,760 | 567 | 710 | 681 | 2,180 |
| 19 | 730 | 1,880 | 3,280 | 2,860 | 1,140 | 2,380 | 2,950 | 2,640 | 567 | 700 | 700 | 2,180 |
| 20 | 700 | 1,880 | 3,300 | 2,840 | 1,130 | 2,390 | 2,960 | 2,700 | 596 | 700 | 690 | 2,190 |
| ជ % ជា ភ ស | 710 | 1,980 | 3,260 | 2,860 | 1,170 | 2,450 | 2,960 | 2,740 | 605 | 710 | 710 | 2,210 |
| | 720 | 2,000 | 3,260 | 2,740 | 1,170 | 2,540 | 2,960 | 2,710 | 576 | 710 | 690 | 2,190 |
| | 730 | 2,040 | 3,260 | 2,520 | 1,170 | 2,570 | 3,010 | 2,590 | 576 | 681 | 690 | 2,210 |
| | 730 | 2,020 | 3,280 | 2,480 | 1,180 | 2,590 | 2,980 | 2,510 | 567 | 672 | 690 | 2,220 |
| | 730 | 2,000 | 3,300 | 2,480 | 1,190 | 2,610 | 2,960 | 2,470 | 573 | 710 | 681 | 2,190 |
| 26 27 28 29 30 31 | 730 730 * 740 !! 720 !! 720 !! 740 | 1,990 2,000 2,060 | 3,310 3,300 3,280 3,280 3,280 3,250 | 2,500 2,520 2,220 1,940 1,570 | 1,190 1,200 1,200 1,220 1,180 1,190 | 2,610 2,610 2,590 2,590 2,610 | 3,010 3,010 3,060 3,060 3,080 3,070 | 2,490 2,470 2,210 1,880 1,810 1,510 | 576 586 643 732 1,600 | 690 690 700 681 719 719 | 710 710 690 719 748 | 2,220 2,180 2,210 2,210 2,190 2,360 |
| Sum | 35,458 | 45,060 | 96,090 | 88,310 | 36,430 | 61,800 | 88,820 | 82,410 | 31,532 | 23,108 | 20,874 | 53,688 |

| | | | | Current 1 | fear 19 | 71 | | | Per | iod 1935-197: | 1. |
|--------|--------|--------|--------------|-----------|----------|-------|---------|-----------|-----------|---------------|---------|
| | | e Gage | | Extreme S | econd F | cet | Average | Total | | Acre Feet | |
| Month | Fe | et | | High | <u> </u> | Low | Second | | | | 1 |
| | High | Low | Day | | Day | | Feet | Acre Feet | Average | Maximum | Minimum |
| Jan. | 103.84 | 102.12 | 6 | 2,470 | 12 | 690 | 1,140 | 70,330 | 443.775 | 1,644,000 | 31,900 |
| Feb. | 103.84 | 102.05 | 123 | 2,100 | 1 3 | 640 | 1,610 | 89,375 | 370,323 | 1,378,000 | 60,400 |
| Mar. | 104.51 | 103.52 | 116 | 3,380 | l ĭ | 2.040 | 3,100 | 190,592 | 368,598 | 1,120,000 | 19,400 |
| Apr. | 104.55 | 102.96 | 10 | 3,430 | 30 | 1,420 | 2,940 | 175,160 | 286,150 | 823,850 | 0 |
| May | 103.05 | 102.64 | 1 | 1,500 | 20 | 1,080 | 1,180 | 72,258 | 294,355 | 1,151,000 | 72,258 |
| June | 104.04 | 102.76 | 30 | 2,730 | 5 | 1,220 | 2,060 | 122,579 | 276,720 | 1,175,000 | 8,500 |
| July | 104.32 | 103.90 | 128 | 3,120 | 7 4 | 2,570 | 2,870 | 176,172 | 266,967 | 763,800 | 24,400 |
| Aug. | 104.25 | 102.87 | 1 1 | 3,040 | 31 | 1,360 | 2,660 | 163,458 | 283,758 | 791,600 | 43,800 |
| Sept. | 107.05 | 101.82 | 30 | 2,080 | 25 | 520 | 1,050 | 62,543 | 257,144 | 1,029,000 | 60,000 |
| Oct. | 107.05 | 101,99 | 1 | 2,070 | 1 5 | 624 | 745 | 45,834 | 260,538 | 1,186,000 | 42,956 |
| Nov. | 102.36 | 101.91 | 14. | 990 | 15 | 596 | 696 | 41,403 | 328,068 | 1,422,000 | 41,403 |
| Dec. | 103.85 | 102.01 | 31 | 2,420 | 7 | 652 | 1,730 | 106,489 | 422,434 | 1,832,000 | 42,000 |
| Yearly | 107.05 | 101.82 | | 3,430 | | 520 | 1,815 | 1,316,193 | 3,858,830 | 10,596,900 | 722,100 |

^{*} Partly estimated

[!] Estimated

f And other days

COLORADO RIVER AT NORTHERLY INTERNATIONAL BOUNDARY - STAGES

(See Preceding Page for Description)

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|--|--|--|--|--|--|--|--|---|--|--|--|
| 1 2 8 4 5 | 103.50 103.28 103.27 103.51 103.77 | 102.17 102.16 102.14 102.69 103.10 | 103.72 103.95 104.14 104.19 104.18 | 104.45 104.47 104.44 104.42 104.44 | 102.74 102.71 102.68 102.69 102.70 | 103.05 103.02 103.01 103.04 103.29 | 103.97 103.98 103.97 103.98 103.97 | *104.18 *104.16 *104.20 *104.18 | *102.98 *103.01 102.99 102.98 102.99 | 106.60 104.27 102.21 102.02 102.00 | 102.04 102.02 102.05 102.05 102.10 | 102.04 102.05 102.06 102.07 102.08 |
| 6 7 8 9 10 | 103.78 103.59 103.55 103.35 103.00 | 102.88 102.91 102.94 102.93 103.00 | 104.18 104.18 104.19 104.19 104.20 | 104.48 104.50 104.49 104.46 104.49 | 102.74 102.75 102.75 102.73 102.69 | 103.26 103.25 103.26 103.26 103.28 | 103.97 103.99 103.98 103.98 103.98 | *104.15 *104.14 *104.16 *104.17 104.16 | 102.99 102.96 102.99 103.00 | 102.04 102.00 102.03 102.03 102.01 | 102.08 102.07 102.07 102.04 102.05 | 102.06 102.05 102.10 102.36 102.85 |
| 11 12 18 14 15 | 102.63 102.20 102.17 102.21 102.20 | 103.01 103.00 103.30 103.28 103.28 | 104.20 104.20 104.21 104.16 104.40 | 104.48 104.48 104.48 104.48 104.49 | 102.69 102.71 102.71 102.70 102.70 | 103.27 103.22 103.18 103.19 103.20 | 103.99 104.21 104.17 104.18 104.17 | 104.10 104.09 104.11 104.11 104.11 | 102.99 102.88 102.65 102.65 102.67 | 102.03 102.03 102.04 102.07 102.07 | 102.01 102.00 102.01 102.10 101.95 | 103.16 103.47 103.60 103.61 103.65 |
| 17 18 19 20 | 102.20 102.18 102.17 102.14 | 103.36 103.39 103.40 103.39 | 104.43 104.42 104.42 104.44 | 104.15 104.15 104.12 104.11 | 102.71 102.73 102.69 102.69 | 103.51 103.52 103.75 103.75 | 104.18 104.18 104.20 104.22 | 104.09 104.06 103.95 103.98 | #101.99 #101.89 #101.92 *101.95 | 102.10 102.08 102.07 102.08 | 102.07 102.01 102.03 102.02 | 103.65 103.65 103.65 103.65 |
| 21 22 28 24 25 | 102.15 102.15 102.16 102.17 102.15 | 103.47 103.50 103.51 103.50 103.49 | 104.42 104.42 104.43 104.44 104.46 | 104.12 104.04 103.86 103.84 103.85 | 102.73 102.74 102.72 102.71 102.73 | 103.80 103.88 103.91 103.91 103.93 | 104.21 104.22 104.24 104.22 104.22 | 103.99 103.93 103.86 103.80 103.76 | *101.97 *101.93 *101.93 101.90 101.90 | 102.08 102.07 102.03 102.04 102.07 | 102.06 102.04 102.04 102.04 102.03 | 103.66 103.67 103.67 103.67 103.65 |
| 26 27 28 29 80 31 | 102.15 102.15 *102.20 #102.18 #102.19 #102.20 | 103.48 103.50 103.55 | 104.46 104.45 104.43 104.41 104.42 104.39 | 103.85 103.87 103.66 103.44 103.09 | 102.73 102.74 102.75 102.76 102.74 102.74 | 103.94 103.93 103.91 103.91 103.95 | 104.24 104.23 104.28 104.28 104.30 104.30 | 103.76 103.77 103.60 103.33 103.24 103.01 | 101.91 101.88 101.97 102.07 104.66 | 102.04 102.04 102.06 102.02 102.07 102.08 | 102.06 102.06 102.04 102.07 102.10 | 103.67 103.65 103.67 103.67 103.66 103.79 |
| Avg | 102.60 | 103.13 | 104.30 | 104.18 | 102.72 | 103.49 | 104.14 | 103.95 | 102.52 | 102.27 | 102.04 | 103.16 |

^{*} Partly Estimated "Estimated

COLORADO RIVER IMMEDIATELY ABOVE MORELOS DAM - STAGES

DESCRIPTION: Water-stage recorder located on the right bank of the Colorado River in Mexico attached to the upstream abutment of the gates of the Intake Canal at Morelos Dam, 1.1 miles downstream from the northerly international boundary, and about 7.5 miles downstream from the Colorado River below Yuma Main Canal Wasteway. Since April 17, 1969, zero of the gage is at mean sea level, U. S. C. & G. S. datum; prior to that date zero of the gage was 0.16 foot below mean sea level.

Records obtained and furnished by the Mexican Section of the Commission. Records available: Staff gage height records November 8, 1950 to June 3, 1951; a continuous record of gage heights June 4, 1951

through 1971.

REMARKS: Prior to June 4, 1951, when a continuous water-stage recorder was installed, mean daily gage height records were determined from hourly readings of a staff gage.

EXTERMES: Since November 8, 1950: Maximum mean daily elevation above mean sea level, 112.70 on January 2,

1958; minimum mean daily elevation above mean sea level, 101.51 on February 17, 1957.

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|
| 1 2 8 4 5 | 102.85 102.72 102.69 102.85 103.05 | 101.90 101.90 101.87 102.36 102.79 | 103.02 103.18 103.35 103.41 103.41 | 103.58 103.58 103.58 103.58 103.58 | 102.30 102.26 102.23 102.23 102.23 | 102.53 102.49 102.49 102.49 102.66 | 103.22 103.22 103.22 103.22 103.22 | 103.31 103.35 103.35 103.38 103.35 | 102.49 102.49 102.46 102.46 102.46 | 106.56 104.20 102.00 101.80 101.77 | 101.84 101.84 101.84 101.84 101.90 | 101.90 101.90 101.90 101.94 101.94 |
| 6 7 8 9 | 103.08 102.95 102.89 102.72 102.49 | 102.43 102.43 102.43 102.43 102.46 | 103.41 103.38 103.41 103.41 103.44 | 103.61 103.61 103.61 103.58 103.61 | 102.26 102.26 102.26 102.23 102.23 | 102.66 102.66 102.66 102.66 102.66 | 103.22 103.22 103.22 103.22 103.25 | 103.35 103.31 103.31 103.35 103.35 | 102.49 102.49 102.49 102.49 102.49 | 101.80 101.77 101.80 101.80 101.77 | 101.87 101.87 101.87 101.84 101.87 | 101.90 101.90 101.94 102.10 102.46 |
| 11 12 18 14 15 | 102.20 101.90 101.87 101.90 101.90 | 102.49 102.49 102.66 102.66 102.69 | 103.44 103.44 103.44 103.41 103.58 | 103.58 103.54 103.58 103.58 103.58 | 102.23 102.26 102.26 102.26 102.26 | 102.66 102.62 102.62 102.59 102.59 | 103.25 103.38 103.35 103.35 103.35 | 103.28 103.28 103.28 103.28 103.28 | 102.46 102.40 102.23 102.23 102.23 | 101.80 101.80 101.80 101.84 101.84 | 101.84 101.84 101.84 101.90 101.80 | 102.62 102.89 102.99 102.99 103.02 |
| 16 17 18 19 20 | 101.90 101.90 101.90 101.87 101.87 | 102.72 102.76 102.76 102.76 102.76 | 103.61 103.61 103.58 103.61 103.61 | 103.44 103.35 103.35 103.31 103.31 | 102.26 102.26 102.30 102.26 102.26 | 102.79 102.85 102.85 103.02 103.02 | 103.35 103.35 103.35 103.38 103.38 | 103.28 103.28 103.28 103.22 103.22 | 101.80 101.74 101.71 101.71 | 101.84 101.87 101.84 101.84 101.84 | 101.84 101.90 101.84 101.87 101.87 | 103.02 102.99 102.99 102.99 102.99 |
| 21 23 23 24 24 | 101.87 101.87 101.87 101.87 | 102.82 102.82 102.85 102.82 102.82 | 103.58 103.61 103.64 103.61 103.61 | 103.31 103.25 103.12 103.08 103.08 | 102.30 102.30 102.30 102.26 102.30 | 103.08 103.15 103.15 103.18 103.18 | 103.38 103.38 103.41 103.38 103.38 | 103.15 103.05 103.05 103.02 102.95 | 101.71 101.71 101.71 101.71 101.71 | 101.84 101.84 101.80 101.84 101.84 | 101.87 101.90 101.90 101.90 | 102.99 103.02 103.02 103.02 102.99 |
| 26 27 28 29 30 | 101.87 101.87 101.90 101.87 101.90 101.90 | 102.82 102.82 102.85 | 103.61 103.61 103.54 103.54 103.58 103.54 | 103.08 103.08 102.95 102.79 102.56 | 102.30 102.30 102.30 102.30 102.30 | 103.22 103.22 103.18 103.18 103.22 | 103.38 103.41 103.41 103.44 103.44 | 102.92 102.95 102.95 102.72 102.66 102.49 | 101.71 101.77 101.87 104.66 | 101.84 101.84 101.84 101.87 101.87 | 101.90 101.90 101.90 101.90 101.97 | 103.02 102.99 102.99 102.99 102.95 103.08 |
| _ | 102.20 | 102.59 | 103.48 | 103.35 | 102.26 | 102.85 | 103.31 | 103.15 | 102.17 | 102.07 | 101.87 | 102.66 |

INTAKE CANAL AT MORELOS DIVERSION STRUCTURE - DISCHARGES

Water-stage recorder and staff gage on left bank of Intake Canal, 200 feet downstream from the DESCRIPTION: intake at Morelos Dam, 1,350 feet upstream from the point where it joins the old Alamo Canal, 2.2 miles upstream from Matamoros Check, and about one mile south of the northerly international boundary. Zero of gage

is 0.16 foot below mean sea level, U. S. C. & G. S. datum. CORDS: The records are deduced from the flows arriving in the limitrophe section of the Colorado River at RECORDS: the northerly international boundary, the flows that pass downstream from the structure, and leakage through the structure. Records available: November 8, 1950 through 1971. Records obtained and furnished by the Mexican Section of the Commission.

REMARKS: The canal is operated with a minimum hydraulic slope to permit the maximum retention of silt above Metamoros Check and the lower velocities in the canal do not permit measuring the flow with a current meter. Records for this station show the amounts of Colorado River water diverted at Morelos Diversion Dam to the Intake Canal and thence to the Alamo Canal for use in Mexico. Water for use in Mexico may also be diverted to the Alamo Canal in the United States directly from the river at Rockwood Heading also be diverted to the Alamo Canal in the United States directly from the river at Rockwood Heading or by means of Imperial Dam, the All-American Canal, and certain facilities of the Imperial Irrigation District under conditions set forth in the 19¹⁴ Water Treaty. No diversions of the above nature have been made during the years 1951 through 1971 and consequently the records reported below show the total water diverted from the Colorado River to the Alamo Canal during those years. Other diversions from the Colorado River are made by Mexico downstream from Morelos Dam by means of pumps.

XTREMES: Maximum mean daily discharge, 6,5¹⁴0 second-feet, August 3, 1958; maximum mean daily gage height, 107.22 feet November 8, 1950. Minimum daily discharge, no flow on various occasions.

EXTREMES:

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|---|---|--|---|--|---|--|--|---|--|---------------------------------|--|
| 1 2 3 4 5 | 2,030 | 735 | 2,310 | 3,310 | 1,200 | 1,490 | 2,650 | 2,870 | 1,500 | 650 | 696 | 706 |
| | 1,760 | 713 | 2,610 | 3,330 | 1,180 | 1,450 | 2,650 | 2,890 | 1,520 | 607 | 678 | 696 |
| | 1,740 | 692 | 2,880 | 3,310 | 1,140 | 1,430 | 2,640 | 2,910 | 1,490 | 731 | 699 | 706 |
| | 2,020 | 1,060 | 2,950 | 3,290 | 1,130 | 1,470 | 2,660 | 2,970 | 1,490 | 636 | 689 | 727 |
| | 2,360 | 1,320 | 2,950 | 3,300 | 1,130 | 1,750 | 2,630 | 2,940 | 1,500 | 611 | 7 2 4 | 724 |
| 6 7 8 9 | 2,360 2,130 2,070 1,830 1,470 | 1,370 1,390 1,410 1,410 1,430 | 2,970 2,950 2,950 2,940 2,950 | 3,310 3,350 3,330 3,300 3,330 | 1,180 1,180 1,200 1,180 1,160 | 1,710 1,700 1,720 1,720 1,730 | 2,650 2,670 2,670 2,650 2,660 | 2,890 2,880 2,910 2,930 2,890 | 1,500 1,490 1,490 1,510 1,490 | 646 622 646 643 636 | 706 706 706 682 696 | 685 678 717 953 1,430 |
| 11 | 1,100 | 1,460 | 2,950 | 3,330 | 1,160 | 1,730 | 2,660 | 2,810 | 1,490 | 657 | 660 | 1,680 |
| 12 | 724 | 1,430 | 2,950 | 3,310 | 1,180 | 1,760 | 2,940 | 2,790 | 1,400 | 653 | 660 | 2,020 |
| 13 | 706 | 1,730 | 2,970 | 3,310 | 1,170 | 1,720 | 2,890 | 2,830 | 1,170 | 657 | 671 | 2,160 |
| 14 | 749 | 1,730 | 2,910 | 3,330 | 1,170 | 1,740 | 2,920 | 2,830 | 1,180 | 689 | 749 | 2,170 |
| 15 | 738 | 1,730 | 3,240 | 3,330 | 1,170 | 1,720 | 2,920 | 2,830 | 1,190 | 685 | 629 | 2,210 |
| 16 | 727 | 1,760 | 3,270 | 3,080 | 1,170 | 2,050 | 2,920 | 2,790 | 689 | 696 | 639 | 2,200 |
| 17 | 738 | 1,830 | 3,250 | 2,870 | 1,180 | 2,100 | 2,920 | 2,790 | 611 | 713 | 717 | 2,180 |
| 18 | 727 | 1,870 | 3,270 | 2,880 | 1,170 | 2,100 | 2,940 | 2,750 | 558 | 703 | 678 | 2,170 |
| 19 | 727 | 1,870 | 3,270 | 2,850 | 1,130 | 2,370 | 2,940 | 2,640 | 565 | 692 | 713 | 2,180 |
| 20 | 696 | 1,870 | 3,290 | 2,830 | 1,120 | 2,380 | 2,950 | 2,690 | 590 | 696 | 689 | 2,190 |
| 21 | 706 | 1,970 | 3,260 | 2,850 | 1,160 | 2,440 | 2,950 | 2,630 | 597 | 706 | 706 | 2,210 |
| 22 | 717 | 1,990 | 3,260 | 2,730 | 1,160 | 2,530 | 2,950 | 2,400 | 569 | 706 | 685 | 2,190 |
| 23 | 727 | 2,030 | 3,250 | 2,510 | 1,160 | 2,560 | 3,000 | 2,380 | 590 | 685 | 685 | 2,210 |
| 24 | 727 | 2,010 | 3,270 | 2,470 | 1,170 | 2,580 | 2,970 | 2,320 | 565 | 671 | 689 | 2,220 |
| 25 | 727 | 2,000 | 3,290 | 2,470 | 1,180 | 2,600 | 2,950 | 2,230 | 565 | 706 | 678 | 2,190 |
| 26 27 28 29 30 31 | 727 724 735 713 713 735 | 1,980 2,000 2,060 | 3,300 3,290 3,270 3,270 3,270 3,240 | 2,490 2,510 2,210 1,940 1,570 | 1,180 1,200 1,190 1,210 1,170 1,190 | 2,600 2,600 2,580 2,580 2,600 | 3,010 3,000 3,050 3,050 3,070 3,070 | 2,200 2,250 1,920 1,720 1,780 1,500 | 565 579 636 682 848 | 689 689 696 678 717 717 | 706 710 689 717 745 | 2,220 2,180 2,210 2,210 2,190 2,360 |
| Sum | 35,336 | 860,44 | 95,837 | 88,078 | 36,254 | 61,553 | 88,612 | 80,171 | 30,583 | 20,927 | 20,797 | 53,548 |

95,837 35,336

| | | | | Current Y | ear 19 | 71 | | | Per | iod 1950-197. | L |
|--------|--------|--------|-------------|------------|--------|-------|---------|--------------|-----------|---------------|-----------|
| | Extrem | e Gage | ø | Extreme Se | cond l | eet | Average | Total | | Acre Feet | |
| Month | Fe | et | <u> </u> | High | | Low | Second | . <u>.</u> . | A | 1 14 10 00 | 1 |
| | High | Low | Day | | Day | | Feet | Acre Feet | Average | Maximum | Minimum |
| Jan. | 102.36 | 99.84 | 16 | 2,360 | 20 | 696 | 1.141 | 70,088 | 60,769 | 116,737 | 966 |
| Feb. | 103.58 | 100.75 | 28 | 2.060 | 3 | 692 | 1,603 | 88,979 | 56,594 | 101,685 | 9,232 |
| Mar. | 103.15 | 101.41 | 26 | 3,300 | l ī | 2,310 | 3,090 | 190,089 | 167,757 | 216,994 | 97,902 |
| Apr. | 102.99 | 101.54 | 7 | 3,350 | 30 | 1,570 | 2,935 | 174,700 | 196,061 | 264,127 | 158,162 |
| May | 101.64 | 101.31 | 29 | 1,210 | 20 | 1,123 | 1,169 | 71,903 | 474, 95 | 159,010 | 66,207 |
| June | 102.20 | 101.41 | † 25 | 2,600 | 3 | 1,430 | 2,052 | 122,089 | 165,439 | 269,632 | 102,000 |
| July | 102.07 | 101.77 | 130 | 3,070 | 1 5 | 2,630 | 2,857 | 175,758 | 234,746 | 304,263 | 154,478 |
| Aug. | 102.03 | 100,89 | 4 | 2,970 | 31 | 1,500 | 2,585 | 159,017 | 233,634 | 341,044 | 153,925 |
| Sept. | 101.38 | 99.74 | 2 | 1,520 | 18 | 558 | 1,021 | 60,659 | 132,317 | 198,095 | 53,633 |
| Oct. | 100.10 | 99.80 | 3 | 731 | 2 | 607 | 675 | 41,509 | 48,572 | 90,639 | 10,453 |
| Nov. | 100.10 | 99.74 | 14 | 749 | 15 | 629 | 692 | 41,250 | 36,605 | 103,954 | 7,516 |
| Dec. | 101.28 | 99.64 | 31 | 2,360 | 7 | 678 | 1,727 | 106,211 | 61,084 | 131,440 | 8,825 |
| Yearly | 103.58 | 99.64 | | 3,350 | T | 558 | 1,794 | 1,302,254 | 1,491,763 | 1,961,556 | 1,290,627 |

[†] And other days Ø Mean daily

INTAKE CANAL AT MORELOS DIVERSION STRUCTURE - STAGES

(See Preceding Page for Description)

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|--|--|--|--|--|--|--|--|--|--|---|--|
| 1 2 3 4 5 | 101.80 101.64 101.61 101.77 102.13 | 101.15 101.12 101.12 102.07 102.20 | 101.90 102.53 102.69 102.82 102.76 | 102.82 102.82 102.85 102.89 102.85 | 101.48 101.48 101.44 101.48 101.44 | 101.80 101.80 101.84 101.84 101.90 | 101.87 101.87 101.87 101.87 101.84 | 101.90 101.94 101.90 101.94 101.94 | 101.05 101.18 101.18 101.08 101.05 | 99.97 99.93 99.97 99.90 99.90 | 99.90 99.87 99.93 99.93 99.97 | 99.97 99.93 99.93 99.93 99.97 |
| 6 7 8 9 10 | 102.10 101.90 101.80 101.67 101.44 | 101.15 101.12 101.12 101.02 100.98 | 102.79 102.79 102.76 102.79 102.76 | 102.92 102.89 102.89 102.85 102.89 | 101.48 101.44 101.48 101.44 101.44 | 101.90 101.94 101.90 101.77 101.61 | 101.84 101.84 101.84 101.84 101.84 | 101.90 101.90 101.94 101.94 101.94 | 101.02 101.02 101.05 101.05 101.02 | 99.97 99.90 99.97 99.97 99.90 | 99.93 99.93 99.97 99.90 99.90 | 99.93 99.93 99.84 99.93 100.46 |
| 11 12 18 14 15 | 100.52 100.03 100.03 100.03 100.13 | 100.95 100.92 101.18 101.15 101.18 | 102.72 102.79 102.82 102.79 103.02 | 102.85 102.85 102.85 102.82 102.89 | 101.48 101.44 101.48 101.48 101.44 | 101.61 101.61 101.61 101.61 101.51 | 101.84 101.97 101.97 101.97 | 101.87 101.87 101.90 101.90 | 101.05 100.98 100.92 100.89 100.89 | 99.93 99.90 99.93 99.93 99.90 | 99.90 99.90 99.90 99.93 99.90 | 100.75 101.05 101.12 101.02 101.02 |
| 16 17 18 19 20 | 100.30 100.13 100.10 100.07 100.10 | 101.21 101.28 101.31 101.35 101.28 | 103.02 103.02 102.95 103.05 103.08 | 102.89 102. 76 102.69 102.69 | 101.44 101.48 101.48 101.48 101.48 | 101.54 101.67 101.67 101.74 101.74 | 101.94 101.97 101.97 101.97 | 101.90 101.94 101.90 101.87 101.87 | 100.59 100.56 100.36 100.23 100.30 | 99.93 99.93 99.90 99.90 99.90 | 99.93 99.93 99.90 99.90 99.87 | 100.95 100.98 100.98 100.98 100.98 |
| 21 22 28 24 24 | 100.23 100.13 100.10 100.20 100.16 | 101.38 101.38 101.41 101.38 101.35 | 103.05 103.05 103.08 103.05 103.06 | 102.72 102.46 102.36 102.36 102.36 | 101.51 101.48 101.48 101.48 101.51 | 101.80 101.80 101.84 101.84 101.87 | 101.97 101.97 101.97 101.97 101.97 | 101.84 101.77 101.77 101.84 101.90 | 100.39 99.90 100.00 99.84 99.84 | 99.90 99.87 99.90 99.87 99.93 | 99.97 99.93 99.93 99.93 99.93 | 100.98 100.98 101.02 101.02 100.98 |
| 26 27 28 29 30 31 | 100.13 100.20 100.23 100.20 100.36 100.72 | 101.38 101.41 101.44 | 103.08 103.02 102.82 102.82 102.79 102.76 | 102.36 102.36 102.33 102.13 101.77 | 101.44 101.51 101.48 101.48 101.44 101.44 | 101.87 101.84 101.84 101.87 101.84 | 101.97 101.97 102.03 102.00 101.97 102.00 | 101.90 101.94 101.54 101.12 101.18 101.05 | 99.84 99.84 99.87 99.97 100.00 | 99.90 99.93 99.93 99.90 99.93 99.93 | 99.93 99.97 99.93 100.00 100.00 | 101.02 101.02 101.02 101.05 101.02 101.18 |
| Avg. | 100.69 | 101.28 | 102.85 | 102.66 | 101.48 | 101.77 | 101.94 | 101.80 | 100.56 | 99.93 | 99•93 | 100.69 |

COLORADO RIVER IMMEDIATELY BELOW MORELOS DAM - STAGES

DESCRIPTION: Water-stage recorder located on the right bank of the Colorado River in Mexico immediately downstream from Morelos Dam, 1.1 miles downstream from the northerly international boundary, and about 7.5 miles downstream from the Colorado River below Yuma Mein Canal Wasteway. Since April 17, 1969, zero of the gage is at mean sea level, U.S.C. & G.S. datum; prior to that date zero of the gage was 0.16 foot below an sea level.

RECORDS: Records obtained and furnished by the Mexican Section of the Commission. Records available: Staff gage heights, February 20, 1951 to June 6, 1966; continuous record of gage heights June 7, 1966 through 1971.

REMARKS: On June 7, 1966 a continuous water-stage recorder was installed; prior to this date mean daily gage heights were determined from hourly readings of staff gage.

EXTREMES: Maximum mean daily gage height, 112.63 feet on January 2, 1958; minimum mean gage height, 98.13 feet several days during March and April 1967.

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|--|--|--|---|--|---|--|--|--|--|--|--|
| 1 2 8 4 5 | 99.48 99.54 99.57 99.44 99.34 | 100.20 100.20 100.20 99.93 99.74 | 98.56 98.59 98.59 98.59 93.56 | 98.56 98.59 98.59 98.56 98.56 | 99.41 99.51 99.48 99.41 99.38 | 98.59 98.59 98.59 98.59 99.41 | 98.59 98.59 98.59 98.59 98.59 | 98.72 98.72 98.72 98.72 98.75 | 99.18 99.31 99.31 99.28 99.28 | 106.40 104.04 100.85 100.69 100.66 | 100.52 100.52 100.52 100.52 100.56 | 100.49 100.49 100.52 100.52 100.52 |
| 6 7 8 9 | 99.31 99.44 99.51 99.61 99.74 | 99.67 99.64 99.67 99.61 99.57 | 98.56 98.56 98.56 98.56 98.56 | 98.56 98.56 98.56 98.56 98.56 | 99.34 99.34 99.51 99.54 99.54 | 99.44 99.34 99.38 99.38 99.34 | 98.59 98.59 98.59 98.59 98.59 | 98.75 98.75 98.75 98.75 98.79 | 99.25 99.28 99.28 99.25 99.15 | 100.66 100.62 100.62 100.62 100.62 | 100.52 100.56 100.56 100.49 100.49 | 100.52 100.52 100.52 100.36 100.16 |
| 11 12 18 14 15 | 99.93 100.16 100.20 100.16 100.16 | 99.54 99.48 99.34 99.31 99.31 | 98.56 98.59 98.59 98.59 98.59 | 98.56 98.56 98.56 98.56 98.56 | 99.57 99.61 99.61 99.57 | 99.34 99.31 99.31 99.34 99.28 | 98.59 98.62 99.48 99.67 99.67 | 98.79 98.79 98.82 98.82 98.82 | 99.18 99.31 99.51 99.57 99.57 | 100.52 100.59 100.52 100.52 100.52 | 100.49 100.49 100.52 100.52 | 100.10 99.93 99.57 99.51 99.34 |
| 16 17 18 19 20 | 100.20 100.20 100.20 100.20 100.20 | 99.28 99.21 98.98 98.92 93.79 | 98.59 98.56 98.52 98.52 98.52 | 98.59 98.59 98.59 98.59 98.59 | 99.57 99.57 99.61 99.54 99.57 | 98.92 99.11 99.11 98.72 98.59 | 99.70 99.70 99.70 99.34 98.92 | 98.82 98.82 98.82 99.38 99.67 | 100.46 100.66 100.72 100.72 | 100.52 100.56 100.52 100.49 100.49 | 100.52 100.52 100.56 100.49 100.52 | 99.28 99.08 99.08 99.18 99.15 |
| 21 22 28 24 25 | 100.23 100.20 100.20 100.20 100.20 | 98.69 98.62 98.59 98.56 98.69 | 98.52 98.56 98.52 98.52 98.52 | 98.59 98.59 98.62 98.62 98.62 | 99.57 99.57 99.57 99.64 99.67 | 99.41 98.59 98.59 98.59 98.59 | 98.88 98.89 98.89 98.85 98.72 | 100.56 101.90 101.87 101.90 102.30 | 100.75 100.72 100.66 100.72 100.75 | 100.49 100.49 100.49 100.49 100.49 | 100.52 100.52 100.49 100.49 100.52 | 99.21 99.25 99.25 99.21 99.28 |
| 26 27 28 29 80 81 | 100.20 100.20 100.20 100.20 100.16 100.16 | 98.62 98.72 98.59 | 98.56 93.56 98.56 98.56 98.56 98.56 | 98.62 98.62 98.62 98.75 99.08 | 99.70 99.70 99.74 99.74 99.74 99.77 | 98.59 98.59 98.59 98.59 98.59 | 98.75 98.75 98.72 98.72 98.72 98.72 | 102.62 102.23 102.62 101.64 99.67 99.31 | 100.69 100.69 100.72 101.15 104.46 | 100.52 100.52 100.52 100.49 100.49 100.52 | 100.52 100.52 100.52 100.49 100.46 | 99.28 99.34 99.41 99.41 99.38 99.31 |
| Avg | 99.97 | 99.28 | 98.56 | 98.59 | 99.57 | 99.08 | 98.88 | 99.80 | 100.03 | 100.85 | 100.52 | 99.70 |

WELLTON-MOHAWK DRAINAGE WATER DISCHARGED TO COLORADO RIVER BELOW MORELOS DAM

DESCRIPTION: Water-stage recorder located on downstream end of the Wellton-Mohawk Drainage Extension Channel on the Arizona bank of the Colorado River at the east end of the weir section of Morelos Dam, 1.1 miles downstream from the northerly international boundary. The elevation of the zero of the gage has not been determined.

determined.

Based on discharge measurements and a continuous record of gage heights. Station is operated by ted States Section of the Commission. Records available: November 16, 1965 through 1971. RECORDS: become: Based on discharge measurements and a continuous record of gage heights. Station is operated by the United States Section of the Commission. Records available: November 16, 1965 through 1971. EMARKS: Rursuant to Minute 216 of the Commission, an extension to the Wellton-Mohawk Drainage Conveyance Channel was constructed along the left bank of the Colorado River to a point immediately below Morelos Dam, a distance of about 12 miles, and placed in operation on November 16, 1965. Drainage flows may be discharged to the Gila River and thence to the Colorado River at the diversion structure, Main Outlet Drain Extension No. 1, at the upstream end of the extension; directly to the Colorado River at Main Outlet Drain Extension No. 2, 1.9 miles upstream from Morelos Dam; and immediately below Morelos Dam at this station, Main Outlet Drain Extension No. 3. The combined 1971 record of discharges to the river above Morelos Dam through M. O. D. E. No. 1 and No. 2 is shown on page 15. REMARKS:

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|--|------------------------------------|----------------------|--------------------------|--|--------------------------------------|--------------------------------------|---|--------------------------------------|--|---------------------------------|--|
| 1 2 3 4 5 | 150 167 167 1 3 9 119 | 308 309 306 238 196 | 2.9 .1 .1 0 | 0 0 0 | 130 138 136 117 110 | 103 104 106 105 83.2 | 0 0 0 0 | 0 0 0 | 81.5 99.4 98.2 97.2 98.2 | 300 295 304 304 308 | 308 308 308 311 314 | 303 308 314 316 311 |
| 6 7 8 9 | 117 140 149 174 206 | 188 188 189 180 171 | 0 0 0 0 | 00000 | 108 110 136 136 141 | 80.9 73.9 78.1 77.6 71.9 | 0 0 0 0 | 0 0 0 | 97.2 97.2 98.2 96.0 85.6 | 308 309 309 309 311 | 311 311 311 303 304 | 308 311 309 271 234 |
| 11 12 13 14 15 | 244 299 300 298 296 | 162 156 132 127 130 | 00000 | 00000 | 143 147 143 143 141 | 71.9 71.9 71.9 71.9 65.0 | 0 0 115 139 141 | 0 0 0 0 | 89.4 106 132 135 138 | 311 304 303 303 301 | 306 306 309 308 309 | 230 199 142 132 117 |
| 16 17 18 19 20 | 298 303 303 303 304 | 122 110 70.1 59.9 35.8 | 0000 | 0 0 0 0 | 136 138 135 126 126 | 29.9 52.2 55.2 16.9 11.4 | 144 144 142 91.1 45.0 | 0 0 0 107 137 | 271 287 296 300 300 | 304 306 300 300 301 | 308 312 314 312 311 | 105 84.6 87.3 99.8 95.5 |
| 21 22 23 24 25 | 308 304 304 306 303 | 13.2 3.3 3.2 10.8 30.4 | 00000 | 00000 | 127 126 126 130 134 | 103 2.8 .7 0 | 42.1 42.1 42.8 41.3 25.9 | 142 136 252 290 295 | 298 295 288 294 296 | 303 304 306 306 304 | 309 304 300 303 308 | 106 109 107 106 110 |
| 26 27 28 29 30 31 | 303 303 304 303 303 300 | 29.7 31.8 17.9 | 00000 | 0 6.8 34.1 83.6 | 134 135 138 136 136 140 | 0 0 0 0 | 33.1 31.8 3.7 .4 0 | 300 298 296 284 121 93.7 | 286 289 295 303 308 | 304 308 308 304 304 308 | 311 311 309 304 303 | 112 121 134 136 129 124 |
| Sum | 7,817 | 3,518.1 | 3.5 | 124.5 | 4,102 | 1,508.3 | 1,224.3 | 2,751.7 | 5,955.1 | 9,449 | 9,246 | 5,571.2 |

Current Year 1971 Period 1966-1971

| | | | | | | | | , , , , | 100 | | |
|-----------------------|----------------------|-------------------|-----------------|--------------------|-----------------|------------------|--------------------|---------------------------|--------------------------|---------------------------|-------------------------|
| Month | | e Gage | ø | Extreme S High | econd l | Feet Low | Average Second | Total | | Acre Feet | |
| | High | Low | Day | l IIIgii | Day | Low | Feet | Acre Feet | Average | Maximum | Minimum |
| Jan. Feb. | 3.21 3.22 | 1.75 | 21 | 308 309 | 6 23 | 117 3.2 | 252 126 | 15,505 6,978 | 14,497 11,067 | 17,740 15,154 | 11,029 6,978 |
| Mar. Apr. May | .11 1.46 2.07 | 0 0 1.72 | 30 12 | 2.9 83.6 147 | † 4 † 1 6 | 0 108 | 4.2 132 | 6.9 247 8,136 | 3,503 1,611 7,325 | 8,083 3,977 11,207 | 6.9 247 3,160 |
| June July | 1.69 2.0 2 | 0 | 116 | 106 144 | 124 | 0 | 50.3 39.5 | 2,992 2,428 | 3,963 1,760 | 7,529 3,461 | 2,098 |
| Aug. Sept. Oct. | 3.18 3.24 3.22 | 0 1.42 3.15 | 26 30 110 | 300 303 311 | 1 2 | 0 81.5 295 | 88.8 199 305 | 5,458 11,812 18,742 | 2,102 9,666 18,172 | 5,458 13,565 18,742 | 34.9 3,575 17,599 |
| Nov. Dec. | 3.24 3.25 | 3.15 1.48 | † 5 | 314 316 | 23 17 | 300 84.6 | 308 180 | 18,339 11,050 | 17,959 14,493 | 18,478 16,374 | 17,234 11,050 |
| Yearly | 3.25 | 0 | | 316 | | 0 | 140 | 101,694 | 106,118 | 126,160 | 100,028 |

Ø Mean daily

[†] And other days

COOPER WASTEWAY (VALLEY DIVISION, YUMA PROJECT)

DESCRIPTION: Water-stage recorder and control weir on wasteway for discharging regulatory waste water from the Cooper Canal to the Colorado River. This wasteway is located 0.5 mile downstream from the northerly international boundary and 0.6 mile upstream from Morelos Diversion Dam. Prior to July 14, 1971, the wasteway was located 0.4 mile downstream from Morelos Diversion Dam. This wasteway discharges waste water from the Valley Division of the Yuma Project in the United States into the Colorado River. Since July 14, 1971 zero of the gage is 117.64 feet above mean sea level, U.S.C. & Go, datum.

1971 zero of the gage is 117.64 feet above mean sea level, U.S.C. & G.S. datum.

RECORDS: Flow is computed from head on the weir measured by the water-stage recorder and weir rating determined by current meter measurements. Station operated by the United States Section of the Commission. Records available: Daily discharge, March 1950 through 1971, obtained by the United States Section; monthly discharge, January 1934 through March 1950, by the Bureau of Reclamation.

EXTREMES: Prior to March 1950, maximum monthly discharge 914 acre-feet in January 1940; minimum monthly discharge, zero for various months. Since March 1950, maximum instantaneous discharge, 79.3 second-feet on June 19, 1965, at a maximum gage height of 114.13 feet (old datum); minimum instantaneous discharge, zero during parts of each month.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| | | | | ige in | | reer 1 | J11 | | and re | | ımmary | |
|----------------------------------|-----------------------------------|--------------------------------|---------------------------------|------------------------------|---------------------------------|---------------------------------------|--------------------------------------|---------------------------------|-------------------------|----------------------------|--------------------------------|------------------------------|
| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
| 1 2 3 4 5 | 0.6 .5 .5 .5 2.2 | 0.8 * 1.4 * .5 | 0.8 1.4 2.6 1.3 5.2 | 0.6 1.6 1.3 3.3 | 2.2 1.6 .4 1.6 3.7 | 1.8 3.2 2.0 1.0 1.2 | 1.8 1.8 * .8 = 3.2 = 1.6 | 2.1 .1 0 0 | 2.7 3.7 0 0 | * 0.2 2 .2 .1 3.3 | 1.1 .4 2.9 3.7 1.6 | 0 0 0 3.9 |
| 6 7 8 9 | 3.9 3.4 1.7 1.3 | .4 .5 1.0 3.8 2.8 | 1.6 1.9 5.6 .6 | .4 .2 0 .4 .7 | .4 .1 1.3 4.5 | 6.1 .9 .4 .3 | * 1.4 1.0 3.8 1.7 2.8 | 0 0 0 0 | 0 0 0 0 | 1.3 0 * 5.6 * 1.6 | 1.6 .2 1.4 0 | 0 0 0 .7 |
| 11 12 13 14 15 | 2.3 1.7 .8 2.5 2.3 | .8 1.2 1.0 1.2 1.4 | .5 4.9 4.0 3.1 1.0 | 3.8 .4 .3 .2 1.4 | .8 .9 1.0 2.2 1.8 | 1.8 1.1 •3 * 8.8 * 4.0 | .2 .7 .3 0 | 0 0 2.4 .8 .7 | 0 0 0 0 | * 1.7 .6 .2 4.3 | .6 1.6 1.5 1.8 | 0 2.7 3.7 .5 1.1 |
| 16 17 18 19 20 | 2.2 * .5 * 2.8 4.4 .8 | .4 .3 1.0 2.8 | .5 .6 .8 2.0 1.1 | .8 .6 1.1 .7 .8 | 1.7 1.7 2.6 1.0 | 2.1 .4 * .4 * .5 | 1.0 4.7 .6 .1 | .4 0 0 2.4 -5 | 0 0 0 3.2 0 | 0 0 .1 0 | 0 0 0 14.6 1.0 | .1 .1 .1 0 |
| 집 왕 왕 왕 왕 | 5.4 2.4 .4 .6 | 5.2 1.0 .4 1.3 3.3 | 7.2 6.7 .7 1.0 2.3 | 5.3 1.3 .8 .7 .6 | 2.0 1.3 1.4 2.2 1.5 | 1.0 .6 * 2.7 2.3 * 1.7 | .1 1.1 .6 .2 0 | 2.4 1.6 .5 0 1.2 | 0 0 0 •5 0 | 0 •5 7.8 .7 .4 | .3 .2 .1 3.3 | 0 0 0 0 |
| 26 27 28 29 30 31 | 4.9 1.1 .6 1.8 .9 | 1.5 7.0 4.7 | 1.9 .5 2.8 4.3 .6 | 3.8 1.3 .6 .5 | 2.4 2.3 .8 1.1 1.8 | # 1.3 # 1.8 * 1.5 1.5 2.3 | 1.1 0 0 0 .3 2.7 | 0 0 .4 2.7 0 2.4 | 0 0 0 2.0 | .2 .1 0 1.6 .3 | .3 1.9 1.1 .3 | 0 0 0 3.4 .5 |
| Sum | 58.0 | 47.9 | 68.5 | 34.8 | 48.2 | 53.5 | 33.7 | 20.6 | 12.5 | 32.3 | 42.5 | 17.0 |

Current Year 1971 Period 1935-1971 Extreme Gage Extreme Second Feet Average Total Acre Feet Month Feet High Second Low High Day Acre Feet Average Maximum Minimum Low Feet Day Jan. 112.20 111.03 21 18.1 13 0.2 1.9 115 187 914 Feb. 112.35 112.54 111.00 27 21.8 18 0 95.0 400 165 Mar. 111.03 26.6 .2 1**3**6 517 425 8 17 2.2 177 0 Apr. 112.24 111.00 26 **†** 7 19.1 0 1.2 190 40 May 112.50 1 7 111.00 18 25.6 0 1.6 95.6 106 182 440 76 June 112.60 111.00 6 28.1 19 1.8 595 516 47 171 July 2.38 Ω 17 44.0 †12 0 66.8 155 0 Aug. 31 19 f 1 40.9 24.8 1.60 Ω 26.6 O .7 121 617 0 Sept. 2.30 0 42.2 f 3 0 .4 121 462 Ω Oct. 2.25 5 19 41.0 0 ō 1.0 64.1 150 490 Ω Nov. 2.13 0 38.3 1 2 ō 1.4 Dec. 2.34 ۵ 12 43.1 1 1 n .5 199 592 33.7 Yearly 112.60 0 44.0 1,988 931.2 4,500 931.2 1.3

^{*} Partly estimated

Estimated

¹ And other days

COLORADO RIVER AT MORELOS GAGING STATION - DISCHARGES

DESCRIPTION: Water-stage recorder on the left (Arizona) bank of the river, and cableway 1.8 miles downstream from the northerly international boundary, 0.7 mile downstream from Morelos Diversion Dam, and about 9 miles downstream from Yuma, Arizona, along the river levee. The cableway and recorder are 1,260 feet and 1,300 feet, respectively, below the mouth of Cooper Wasteway. Zero of gage is at mean sea level, U. S. C. & G. S. datum.

CORDS: Based on 147 current meter measurements during the year, 99 by the United States Section, 48 by the Mexican Section of the Commission, and a continuous record of gage heights. Computations by shifting control methods. Records available: Daily discharges, January 1, 1954 through 1971; continuous record of RECORDS: gage heights, July 20, 1952 through 1971.

gage neights, July 20, 1972 through 1971.

REMARKS: Reservoirs, diversions in the United States and Mexico, drainage returns, and waste flows modify the river flow at this station. The record at this station, less that of Cooper Wasteway and Main Outlet Drain Extension No. 3, represents the river flow passing Morelos Diversion Dam.

EXTREMES: Meximum instantaneous discharge, 22,240 second-feet on January 4,1955; maximum gage height, 112.18 feet on January 28, 105A. Minimum discharge or flow on vertices considered.

feet on January 28, 1958. Minimum discharge, no flow on various occasions.

Mean Daily Discharge in Second Feet 1971 — Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------|---|--------------------------------------|---|--------------------------------------|---|---|---|--|-----------------------------------|--|---------------------------------|--|
| 1 2 3 4 5 | 151 164 164 145 131 | 314 316 316 257 211 | 13.4 10.4 11.3 11.8 12.6 | 8.5 9.0 9.2 9.0 8.8 | 121 133 133 124 120 | 116 115 118 116 92.0 | 9.0 9.2 8.8 11.8 10.4 | 8.8 9.0 9.0 9.0 9.2 | 86.5 103 103 101 101 | 1,620 939 357 331 326 | 312 312 312 315 318 | 306 306 312 313 310 |
| 6 7 8 9 | 127 141 151 171 203 | 195 193 196 190 180 | 10.0 9.5 13.8 10.4 10.4 | 8.8 8.5 8.2 8.5 8.5 | 118 120 138 142 142 | 93.0 83.9 86.5 87.8 82.6 | 9.5 9.2 9.2 9.2 9.5 | 9.2 9.0 8.8 9.2 10.0 | 101 102 103 103 93.0 | 324 321 319 319 319 | 315 315 315 310 307 | 312 308 308 280 244 |
| 11 12 13 14 15 | 246 292 301 301 299 | 171 160 139 133 135 | 10.8 13.1 10.8 12.6 11.3 | 9.5 9.0 8.8 9.2 10.0 | 145 148 145 149 146 | 81.3 82.6 81.3 87.8 78.7 | 9.0 10.0 121 142 142 | 10.4 * 10.8 * 10.4 * 10.0 * 10.0 | 94.3 108 130 137 138 | 319 313 308 310 308 | 310 310 313 313 315 | 238 211 154 142 122 |
| 16 17 18 19 20 | 299 301 304 304 301 | 129 116 82.6 72.2 46.2 | 10.4 10.0 8.8 9.0 9.0 | 10.4 9.5 9.5 10.4 10.0 | 144 145 145 136 135 | 39.5 59.8 62.2 30.8 23.6 | 148 149 146 105 52.8 | * 11.8 11.8 11.8 107 148 | 266 295 304 306 306 | 308 312 308 307 306 | 313 315 316 313 312 | 114 97.4 96.1 100 97.4 |
| 21 22 23 24 25 | 308 306 306 310 308 | 29.8 15.2 12.6 17.9 36.0 | 11.8 11.8 8.8 9.2 10.0 | 13.6 10.8 10.4 10.0 | 137 137 137 140 142 | * 109 * 12.2 12.2 10.4 10.8 | 49.5 49.5 50.6 49.5 * 33.2 | 254 450 462 479 535 | 308 304 295 297 304 | 307 307 307 307 307 | 313 310 306 306 307 | 108 113 110 108 113 |
| 26 27 28 29 30 | 312 310 310 310 310 310 308 | 36.0 42.0 29.0 | 10.0 9.0 12.6 12.2 8.8 8.8 | 12.1 10.9 16.0 41.0 87.2 | 142* 142 144 144 145 146 | 10.4 9.2 9.0 9.0 10.0 | * 40.0 * 39.0 * 15.0 9.5 9.0 8.8 | 595 522 588 447 147 105 | 297 295 304 356 1,060 | 307 310 312 310 308 312 | 312 312 310 308 307 | 115 124 136 136 132 122 |
| Sum | | 3,770,5 | | 405.3 | | 1,820.6 | L | 5,017.2 | | 11,668 | 0.050 | 5,687.9 |

3,770.5 1,474.2 9.352 6,900.8 4.285 7,894 332.4

| | | | | Current Y | ear 19 | 71 | | | Per | iod 1954-1971 | |
|--|---|---|--|--|--|---|--|---|--|--|--|
| | Extrem | e Gage | | Extreme Se | cond l | eet | Average | Total | | Acre Feet | |
| Month | Fe | et | ļ | High | | Low | Second | Acre Feet | Average | Maximum | Minimum |
| | High | Low | Day | | Day | | Feet | Acre reei | | | |
| Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec. | 99.82 99.82 98.05 98.54 99.21 99.57 99.23 102.49 106.09 100.14 100.11 | 98.83 97.80 97.65 97.64 98.55 97.84 97.80 97.83 98.78 100.10 | 26 1 30 18 21 13 28 30 1 | 320 322 26.8 95.6 160 185 155 682 1,810 1,810 318 313 | 6 23 18 7 1 †28 3 †3 1 15 10 18 | 123 10.4 8.5 8.2 95.6 8.8 83.9 304 94.8 | 255 135 10.7 13.5 138 60.7 47.6 162 230 376 312 183 | 15,658 7,479 659 804 8,499 3,611 2,924 9,951 13,688 23,143 18,549 11,282 | 172,682 87,837 56,358 43,144 52,135 12,611 11,695 20,041 18,054 48,371 87,304 118,791 | 969,540 414,310 630,230 532,320 375,970 119,980 89,430 125,590 87,830 172,940 356,390 643,850 | 949 977 659 804 460 834 654 702 113 9,750 4,869 1,111 |
| Yearly | 106.09 | 97.64 | | 1,810 | | 8.2 | 160.3 | 116,247 | 729,023 | 3,957,730 | 101,758 |

^{*} Partly estimated

Estimated

[†] And other days

COLORADO RIVER AT MORELOS GAGING STATION - STAGES

(See Preceding Page For Description)

| | By Jan. Feb. March April May June July Aug Sant Oct Nov. D. | | | | | | | | | | | | | |
|----------------------------------|---|---|--|---|--|---|--|--|--|--|--|--|--|--|
| Day | | | | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. | | |
| 1 2 3 4 5 | 98.99 99.09 99.10 98.98 98.88 | 99.78 99.79 99.79 99.53 99.29 | 97.85 97.80 97.81 97.81 97.83 | 97.65 97.67 97.68 97.67 97.66 | 98.82 98.94 98.94 98.85 98.81 | 99.01 99.01 99.03 99.03 98.88 | 97.84 97.84 97.81 97.88 97.84 | 97.85 97.85 97.85 97.85 97.86 | 98.82 98.95 98.95 98.92 98.91 | 105.66 103.52 100.58 100.39 100.36 | 100.12 100.12 100.12 100.13 100.14 | 100.06 100.06 100.10 100.11 100.09 | | |
| 6 7 8 9 10 | 98.86 98.97 99.04 99.15 99.32 | 99.21 99.20 99.22 * 99.18 * 99.14 | 97.77 97.76 97.82 97.76 97.76 | 97.66 97.65 97.64 97.65 97.65 | 98.79 98.81 98.99 99.03 99.03 | 98.89 98.82 98.84 98.85 98.82 | 97.82 97.81 97.81 97.81 97.82 | 97.86 97.85 97.84 97.85 97.86 | 98.90 98.90 98.90 98.89 98.80 | 100.35 100.33 100.32 100.31 100.30 | 100.12 100.12 100.12 100.09 100.07 | 100.10 100.08 100.08 99.92 99.71 | | |
| 11 12 18 14 15 | 99.53 99.75 99.78 99.77 99.76 | * 99.10 99.03 98.91 98.87 98.88 | 97.77 97.82 97.77 *97.81 *97.77 | 97.69 97.66 97.66 97.68 97.69 | 99.05 99.08 99.06 99.09 99.07 | 98.81 98.82 98.81 98.85 98.78 | 97.80 97.83 98.93 99.14 99.14 | 97.86 * 97.87 * 97.86 * 97.85 | 98.81 98.94 99.14 99.21 99.22 | 100.29 100.24 100.20 100.20 100.18 | 100.08 100.08 100.10 100.10 100.11 | 99.67 99.50 99.14 99.05 98.91 | | |
| 16 17 18 19 20 | 99.76 99.77 99.78 99.78 99.76 | 98.85 98.77 98.54 98.47 98.26 | 97.75 97.74 97.70 97.71 97.70 | 97.70 97.68 97.68 97.70 97.69 | 99.06 99.07 99.08 99.02 99.02 | 98.42 98.62 98.63 98.32 98.23 | 99.18 99.19 99.17 98.85 98.44 | * 97 .89 97 .89 97 .89 98 .86 99 .21 | 100.05 100.22 100.27 100.28 100.29 | 100.17 100.19 100.16 100.15 100.14 | 100.10 100.11 100.12 100.10 100.09 | 98.85 98.73 98.72 98.75 98.75 | | |
| 21 22 23 24 25 | 99.79 99.78 99.77 99.79 99.77 | 98.07 *97.89 *97.84 97.92 98.15 | 97.77 97.77 *97.69 *97.70 | 97.77 97.71 97.70 97.69 97.69 | 99.04 99.05 99.05 99.08 99.10 | *98.95 *97.98 97.97 97.92 97.92 | 98.40 98.39 98.39 98.37 98.21 | 99.90 101.13 101.21 101.30 101.64 | 100.31 100.30 100.26 100.28 100.33 | 100.15 100.15 100.15 100.15 100.15 | 100.10 100.08 100.05 100.05 100.06 | 98.79 98.82 98.80 98.79 98.82 | | |
| 26 27 28 29 80 81 | 99.78 99.77 99.77 99.76 99.76 99.75 | 98.15 98.21 98.07 | *97.70 *97.67 #97.76 *97.75 #97.66 *97.66 | 97.73 97.71 97.76 98.05 98.47 | 99.12 99.14 99.17 99.18 99.19 99.20 | 97.90 97.86 97.85 97.85 97.88 | 98.28 98.27 97.96 97.88 97.86 97.85 | 101.99 101.57 101.95 101.12 99.26 98.96 | 100.30 100.29 100.34 100.66 103.68 | 100.14 100.15 100.14 100.13 100.11 100.12 | 100.09 100.09 100.08 100.08 100.07 | 93.84 98.90 98.99 98.99 98.96 98.89 | | |
| Avg. | 99.53 | 98.79 | 97.75 | 97.72 | 99.03 | 98.52 | 98.25 | 99.02 | 99.74 | 100.50 | 100.10 | 99.29 | | |

^{*} Partly Estimated "Estimated

ELEVEN MILE WASTEWAY (VALLEY DIVISION, YUMA PROJECT)

DESCRIPTION: Water-stage recorder and control weir on wasteway for discharging water from the West Main Canal to the Colorado River. This wasteway is located in Arizona, 4.3 miles downstream from the northerly international boundary and 3.2 miles downstream from Morelos Diversion Dam. It is the largest of three wasteways discharging waste water from the Valley Division of the Yuma Project in the United States into the limitrophe section of the Colorado River.

into the limitrophe section of the Colorado River.

RECORDS: Flow is computed from head on the weir measured by the water-stage recorder and weir rating determined by current meter measurements. Station operated by the United States Section of the Commission. Records available: Daily discharge, January 1951 through 1971, obtained by the United States Section; monthly discharge, January 1924 through 1950, by Bureau of Reclamation.

EXTREMES: Prior to January 1951, maximum monthly discharge, 9,740 acre-feet in August 1940; minimum monthly discharge, zero in April 1941. Since January 1, 1951, maximum instantaneous discharge, 800 second-feet on December 3, 1951, at a maximum gage height of 117.60 feet; minimum instantaneous discharge, zero during parts of most years. of most years.

Mean Daily Discharge in Second Feet 1971 --- Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|--|-----------------------------------|-----------------------------------|-----------------------------------|---------------------------------|-----------------------------------|---------------------------------|-------------------------------------|----------------------------------|--|-----------------------------------|--|
| 1 2 3 4 5 | 15.8 1.5 5.9 1.2 3.9 | 1.2 1.2 3.0 2.6 1.2 | 4.5 1.9 1.3 1.7 | 1.7 1.7 1.7 16.0 28.5 | 0.4 .4 .5 .5 | 1.3 1.2 1.2 3.3 1.4 | 1.4 1.3 1.2 1.5 | 24.5 21.1 3.8 4.9 * 1.2 | 1.4 1.3 1.3 1.3 | 6.6 2.5 2.2 7.2 1.2 | 1.2 1.2 1.1 1.1 | 1.3 1.5 1.6 1.5 47.9 |
| 6 7 8 9 | 16.9 8.0 7.8 1.4 1.6 | 1.2 1.2 4.7 1.3 1.3 | 3.1 8.8 5.1 1.5 | 5.7 2.9 1.3 1.3 | .9 1.0 1.1 1.2 1.2 | 47.8 21.2 4.8 3.8 1.3 | 1.4 1.3 1.2 1.5 | 1.2 1.3 1.2 1.2 1.2 | 1.6 1.7 1.6 1.6 | 2.3 3.8 1.2 1.3 2.8 | 1.2 1.4 1.4 1.3 1.3 | 32.9 4.5 2.2 1.5 1.4 |
| 11 12 13 14 15 | 2.1 1.2 1.1 3.6 10.4 | 2.5 8.2 1.2 42.2 25.5 | 1.4 1.5 1.8 33.6 25.1 | 3.7 6.8 2.2 6.2 1.8 | 1.1 .8 .7 .7 | 1.3 1.2 1.4 1.3 1.4 | 1.4 1.6 1.6 1.4 | 1.2 1.2 1.2 1.3 3.1 | 1.7 1.6 2.0 1.7 1.5 | 6.8 1.3 5.5 1.2 1.4 | 1.3 1.4 2.1 46.0 25.4 | 1.6 1.5 1.6 1.6 1.4 |
| 16 17 18 19 20 | 2.0 1.2 1.3 1.4 | 4.2 2.6 1.0 1.2 8.4 | 4.4 2.8 1.2 1.2 1.1 | 2.1 5.6 7.1 2.4 1.9 | 1.4 2.0 2.1 2.1 1.1 | 1.3 1.0 .8 1.0 | 1.4 1.3 1.4 1.4 | 1.4 1.4 1.5 1.6 | 1.3 1.3 1.1 1.2 1.5 | 1.3 3.5 1.3 1.2 1.2 | 1.3 .5 1.0 1.3 1.3 | 1.3 1.3 1.2 1.2 1.3 |
| 21 22 23 24 25 | 1.9 1.2 1.2 18.1 7.0 | 8.5 13.4 1.9 12.1 6.7 | 1.6 1.3 1.3 1.3 | 1.9 1.9 1.8 1.7 | .6 •5 •5 •5 | 1.1 1.2 1.4 1.2 1.3 | 1.3 1.3 1.3 1.3 | # 1.3 * 1.3 * 1.4 1.5 | 1.6 1.6 1.6 1.6 | 1.2 1.2 3.8 12.2 3.8 | 2.8 1.5 1.4 1.4 | 1.7 2.5 2.1 1.6 1.6 |
| 26 27 28 29 30 31 | 1.2 1.1 1.1 1.1 3.2 1.5 | 3.1 2.6 6.3 | 6.8 6.5 8.2 5.1 1.7 | 1.3 1.1 .8 .6 | .3 .3 .2 .1 2.2 | 1.4 1.4 1.3 1.4 1.6 | 1.3 1.3 1.2 1.2 1.2 | 3.7 1.4 1.5 1.3 1.4 | 1.6 1.5 1.4 23.3 2.6 | 1.6 3.0 1.2 3.8 2.2 3.2 | 1.2 1.2 1.4 1.4 1.4 | 1.6 1.6 2.0 1.6 1.9 2.0 |
| Sum | 128.8 | 170.5 | 141.9 | 114.7 | 27.9 | 112.4 | 41.9 | 98.0 | 68.3 | 93.0 | 108.9 | 130.5 |

| | | | | Current ' | Year 19 | 71 | | | Per | iod 1935-197 | 1 |
|---|--|--|---|--|---|--|--|--|--|--|---|
| | Extrem | e Gage | | Extreme S | econd F | eet | Average | Total | | Acre Feet | |
| Month | Fe High | et | Day | High | Day | Low | Second Feet | Acre Feet | Average | Maximum | Minimum |
| Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec. | 113.58 115.45 114.53 113.49 113.18 115.71 111.92 114.07 114.42 112.58 115.92 | 111.85 111.31 111.31 111.73 111.82 111.86 111.86 111.86 111.86 111.86 111.86 | 3 14 14 30 6 12 1 29 1 14 5 | 103 236 160 98.0 81.9 226 1.9 132 153 42.5 293 | †27 17 17 30 29 30 4 18 † 9 †16 8 | 1.0 .6 .6 .4 .1 .7 1.1 .6 1.1 1.1 | 4.2 6.1 4.6 3.3 3.7 1.4 3.2 2.3 3.6 4.2 | 255 338 281 228 55.3 223 83.1 194 135 184 216 259 | 3,614 2,902 2,732 2,524 3,035 2,871 2,908 2,474 1,814 2,468 2,934 3,884 | 9,570 8,430 6,230 6,300 9,320 7,440 8,320 9,740 6,140 5,680 8,220 9,430 | 215 193 171 0 55-3 130 83.1 194 117 184 216 |
| Yearly | 115.92 | 111.73 | | 298 | | 0.1 | 3.4 | 2,451.4 | 34,160 | 82,900 | 2,451.4 |

^{*} Partly estimated

Estimated

[†] And other days

COLORADO RIVER AT ELEVEN MILE GAGE - STAGES

DESCRIPTION: Water-stage recorder on the left (Arizona) bank of the river, 4.3 miles downstream from northerly international boundary, 3.2 miles downstream from Morelos Diversion Dam, about 50 feet downstream from the mouth of Eleven Mile Wasteway of the Yuma Project, and 11 miles downstream from Yuma, Arizona, along the river levee. Zero of gage is at mean sea level, U.S.C.&G.S. datum.

RECORDS: Mean daily gage heights based on continuous water-stage records. Records available: Continuous record of gage heights, November 1947 through 1971; once weekly readings obtained by the U.S.Bureau of Reclamation, January 1940 through October 1947.

REMARKS: This station is maintained by the United States Section of the Commission as part of the continuing study of channel conditions in the limitrophe section of the river.

EXTREMES: Since November 1947, maximum mean daily gage height, 108.20 feet on January 2, 1958; minimum mean daily gage height, 94.95 feet on June 22, 1968.

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|--|---|--|---|--|--|--|--|---|--|--|--|
| 1 | 96.31 | 96.95 | * 95.19 | 95.01 | 95.96 | 96.08 | 95.06 | 95.23 | 96.03 | 102.29 | 97 •58 | 97.30 |
| 2 | 96.32 | 96.98 | * 95.08 | 95.01 | 96.07 | 96.05 | 95.05 | 95.28 | 96.12 | 100.78 | 97 •57 | 97.29 |
| 8 | 96.37 | 96.99 | 95.08 | 95.03 | 96.09 | 96.05 | 95.04 | 95.12 | 96.15 | 98.00 | 97 •56 | 97.31 |
| 4 | 96.22 | 96.76 | * 95.09 | 95.17 | 96.03 | 96.05 | 95.05 | 95.11 | 96.15 | 97.68 | 97 •55 | 97.32 |
| 5 | 96.13 | 96.55 | 95.07 | 95.24 | 95.96 | 95.91 | 95.03 | 95.08 | 96.14 | 97.63 | 97 •55 | 97.47 |
| 6 7 8 9 | 96.19 96.21 96.28 96.36 96.52 | 96.47 96.45 96.48 96.44 96.38 | * 95.10 # 95.15 * 95.10 * 95.04 95.07 | 95.06 95.02 94.99 94.99 94.99 | 95.93 95.94 96.07 96.12 96.12 | 96.08 95.96 95.84 95.84 95.78 | 95.03 95.02 95.05 95.02 95.03 | 95.09 95.10 95.10 95.12 95.14 | 96.14 96.18 96.17 96.18 96.13 | 97.62 97.64 97.64 97.64 97.64 | 97 .53 97 .53 97 .52 97 .49 97 .44 | 97.46 97.32 97.30 97.18 96.99 |
| 11 | 96.72 | 96.34 | 95.07 | 95.05 | 96.14 | 95.78 | 95.02 | 95.13 | 96.13 | 97.67 | 97 .45 | 96.93 |
| 12 | 96.91 | 96.33 | 95.11 | 95.06 | 96.18 | 95.77 | 95.05 | 95.10 | 96.21 | 97.65 | 97 .45 | 96.79 |
| 13 | 96.97 | 96.19 | 95.10 | 95.01 | 96.18 | 95.76 | 95.74 | 95.10 | 96.37 | 97.64 | 97 .46 | 96.51 |
| 14 | 96.96 | 96.29 | 95.30 | 95.05 | 96.20 | 95.80 | 96.01 | 95.10 | 96.45 | 97.62 | 97 .59 | 96.43 |
| 15 | 96.98 | 96.33 | 95.31 | 95.03 | 96.19 | 95.74 | 96.03 | 95.12 | 96.49 | 97.62 | 97 .60 | 96.29 |
| 16 | 96.96 | 96.16 | 95.14 | 95.04 | 96.18 | 95.48 | 96.09 | 95.10 | 97.08 | 97.62 | 97.45 | 96.25 |
| 17 | 96.96 | 96.06 | 95.09 | 95.07 | 96.21 | 95.59 | 96.11 | 95.13 | 97.31 | 97.66 | 97.43 | 96.09 |
| 18 | 96.96 | 95.88 | 95.03 | 95.09 | 96.22 | 95.60 | 96.13 | 95.15 | 97.39 | 97.65 | 97.44 | 96.07 |
| 19 | 96.95 | 95.81 | 95.05 | 95.06 | 96.17 | 95.38 | 95.95 | 95.75 | 97.43 | 97.62 | 97.43 | 96.14 |
| 20 | 96.93 | *95.64 | 95.05 | 95.04 | 96.15 | 95.24 | 95.55 | 96.05 | 97.46 | 97.62 | 97.41 | 96.11 |
| 21 | 96.95 | 295.47 | 95.10 | 95.10 | 96.16 | 95.88 | 95.51 | 96.51 | 97.49 | 97.62 | 97.40 | 96.15 |
| 22 | 96.95 | 295.35 | 95.11 | 95.05 | 96.15 | *95.20 | 95.49 | 97.58 | 97.50 | 97.63 | 97.38 | 96.19 |
| 23 | 96.94 | 295.24 | 95.05 | 95.05 | 96.15 | *95.13 | 95.48 | 97.70 | 97.49 | 97.62 | 97.34 | 96.18 |
| 24 | 97.00 | 95.32 | 95.04 | 95.05 | 96.17 | *95.12 | 95.47 | 97.82 | 97.50 | 97.67 | 97.33 | 96.16 |
| 25 | 96.97 | 95.45 | 95.04 | 95.06 | 96.19 | *95.12 | 95.35 | 98.06 | 97.56 | 97.63 | 97.34 | 96.17 |
| 26 27 28 29 80 81 | 96.94 96.94 96.93 96.93 96.92 96.91 | 95.41 95.46 95.38 | 95.11 95.09 95.14 95.12 95.04 95.02 | 95.07 95.09 95.10 95.33 95.66 | 96.19 96.21 96.23 96.22 96.24 96.23 | #95.11 #95.10 *95.09 95.08 95.08 | 95.39 95.40 95.20 95.08 95.08 95.09 | 98.49 98.13 98.41 97.99 96.52 96.19 | 97.56 97.56 97.62 97.63 99.90 | 97.62 97.63 97.61 97.60 97.59 97.58 | 97.35 97.35 97.35 97.33 97.31 | 96.19 96.22 96.29 96.29 96.28 96.20 |
| Avg | 96.73 | 96.09 | 95.10 | 95.09 | 96.14 | 95 • 59 | 95.37 | 96.05 | 96.92 | 97.89 | 97.45 | 96.61 |

^{*} Partly Estimated

Estimated

TWENTY-ONE MILE WASTEWAY (VALLEY DIVISION, YUMA PROJECT)

DESCRIPTION: ESCRIPTION: Water-stage recorder and control weir on wasteway for discharging water from the West Main Canal to the Colorado River. Prior to May 1, 1971, water-stage recorder and control weir were Located at a site 200 feet upstream on wasteway. This wasteway is located in Arizona 18.5 miles downstream from the mortherly international boundary, 17.4 miles downstream from Morelos Diversion Dam, and 2.2 miles upstream from the southerly international boundary. It is the farthest downstream of the two wasteways discharging waste water from the Valley Division of the Yung Project in the United States into the limitrophe section of the Colorado River. The elevation of the zero of the gage at the new location has not been determined.

RECORDS: Flow is computed from head on the weir measured by the water-stage recorder and weir rating determined by current meter measurements. Station operated by the United States Section of the Commission. Records available: Daily discharge, January 1951 through 1971, obtained by the United States Section; monthly discharge, March 1939 through 1950, by Bureau of Reclamation.

EMARKS: This wasteway was completed and flow began March 14, 1939. Since May 13, 1944, waste water from the West Main Canal which previously discharged across the southerly land boundary has been returned

REMARKS: to the Colorado River through this wasteway.

EXTREMES: Prior to January 1951, maximum monthly discharge, 2,860 acre-feet, in January 1946; minimum monthly discharge, 122 acre-feet in September 1950. Since January 1, 1951, maximum instantaneous discharge, 102 second-feet on January 24, 1954, at a maximum gage height of 95.46 feet (old datum); minimum instantaneous discharge, zero during a pert of most months.

Mean Daily Discharge in Second Feet 1971 --- Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|-------------------------------------|----------------------------------|---------------------------|--------------------|---------------------------|------------------------------|-------------------------|--------------------|--------------------|-----------------------|-----------------------------|------------------|
| 1 2 3 4 5 | 7.0 .5 .1 1.5 2.6 | 2.8 3.7 4.3 8.7 | 4.3 0 0 0 | 0 0 0 8.4 | 0 0 1.8 0 | 0 0 0 | 0 .l .l 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 |
| 6 7 8 9 | 10.5 3.4 4.9 2.2 .7 | .2 4.6 4.7 2.6 4.0 | 0000 | | 00000 | 0 22.5 1.4 .3 .1 | 0000 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 00000 | 0 0 0 0 |
| 11 12 13 14 15 | 0 0 1.3 1.4 5.7 | 2.1 3.4 1.2 8.0 23.4 | 0 0 0 2.9 3.2 | 00000 | 0 0 0 1.9 8.3 | 0000 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 17.2 15.7 | 0 0 0 0 |
| 16 17 18 19 20 | 4.0 2.7 1.8 1.2 | .2 0 0 3.7 | 00000 | 00000 | 5.7 6.4 0 0 | 0 2.1 .1 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 6.9 10.6 | 0 0 0 0 | 0000 |
| 21 22 23 24 25 | 1.3 1.8 .9 1.5 0 | 5.8 3.4 3.4 6.3 2.4 | 00000 | 0 0 0 .7 | 0 0 0 0 | 00000 | 0000 | .1 0 .3 0 | 0 0 0 | 2.0 0 0 0 | 0 0 0 0 | 0 0 0 0 |
| 26 27 28 29 30 31 | .6 2.1 0 3.9 1.5 5.8 | 0 0 1.2 | 0000 | 00000 | 0 0 0 0 0 | 00000 | 0 0 0 .3 .1 | 00000 | 0 0 0 3.1 | 0 0 0 0 0 | 0 0 0 0 | 0 0 0 0 0 |
| Sum | 71.2 | 100.0 | 11.5 | 11.4 | 24.8 | 26.5 | 0.6 | 0.5 | 3.1 | 19.6 | 32.9 | 0 |

| | | | | Current | Year 19 | | Per | iod 1939-197 | 1 | | |
|--------|-------|--------|-----|--------------|------------|-----|---------|--------------|---------|---|--------------|
| | | e Gage | | Extreme S | Second F | eet | Average | Total | | Acra Foot | |
| Month | Fe | et | | High | | Low | Second | | | ACIE I CEI | , |
| | High | Low | Day | | Day | | Feet | Acre Feet | Average | Acre Feet Maximum 2,860 2,510 1,660 1,940 2,470 2,350 1,950 2,180 2,180 2,180 2,180 2,680 | Minimum |
| Jan. | 94.68 | 92.92 | 22 | 45.7 | † 3 | 0 | 2.3 | 141 | 913 | 2,860 | 141 |
| Feb. | 94.77 | 92.92 | 15 | 49.3 | † 6 | 0 | 3.6 | 198 | 786 | 2,510 | 138 |
| Mar. | 93.79 | 92.92 | li. | 14.7 | 1 1 | 0 | .4 | 22.8 | 723 | 1,660 | 22.8 |
| Apr. | 94.26 | 92.92 | 5 | 29. 6 | 7 1 | 0 | .4 | 22.6 | 779 | 1,940 | 22.6 |
| May | 1.05 | 0 | 17 | 25.2 | 7 1 | 0 | .8 | 49.2 | 949 | 2,470 | 49.2 |
| June | 1.56 | 0 | 7 | 51.3 | 7 1 | 0 | .9 | 52.6 | 827 | 2,350 | 52.6 |
| July | .57 | 0 | 29 | 9.1 | 7 1 | 0 | 0 | 1.2 | 715 | 1,950 | 1.2 |
| Aug. | .27 | 0 | 23 | 2.6 | 7 1 | 0 | 0 | 1.0 | 751 | 2,530 | 1.0 |
| Sept. | .92 | 0 | 29 | 20.7 | 7 1 | 0 | .1 | 6.1 | 674 | | 6.1 |
| Oct. | 1.20 | 0 | 19 | 32.0 | † 1 | 0 | .6 | 38.9 | 817 | | 3 8.9 |
| Nov. | 1.17 | 0 | 14 | 30.6 | 7.1 | 0 | 1.1 | 65.3 | 944 | | 65.3 |
| Dec. | 0 | 0 | † 1 | 0 | 1 1 | 0 | 0 | 0 | 1,042 | 2,680 | 0 |
| Yearly | 94.77 | 0 | | 51.3 | | 0 | •9 | 598.7 | 9,920 | 24,370 | 598.7 |

DIVERSIONS BY PUMPS IN THE UNITED STATES - LIMITROPHE SECTION

DESCRIPTION: One privately operated pump located on the left bank of the Colorado River in the limitrophe section pumps water for irrigating land in the river floodway in the United States.

RECORDS: Quantities of water pumped are estimated by the United States Section of the Commission from weekly readings of a running time meter attached to the pump, and pump capacity. Records available: January 1966. 1956 through 1971.

REMARKS: These records are used in the computations of water delivered to Mexico.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|---------------------------|----------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| 1 2 3 4 5 | 0 0 0 0 | 4.8 5.4 0 0 | 0000 | 0000 | 0000 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 |
| 6 7 8 9 | 0 0 0 0 | 0000 | 0 0 0 0 | 0000 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 |
| 11 12 13 14 15 | 0 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 |
| 16 17 18 19 20 | 0 0 0 0 | 7.2 1.5 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 |
| 21 22 23 24 25 | 3.6 0 0 4.8 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 |
| 26 27 28 29 30 31 | 0 0 0 4.2 0 0 | 0 0 0 | 0 0 0 0 0 | 0 0 0 0 | 0 0 0 0 0 | 0 0 0 0 0 | 000000 | 0 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 0 |
| Sum | 12.6 | 18.9 | 0 | 0 | 0 | Ģ | 0 | 0 | 0 | 0 | 0 | 0 |

| | | | | Current | Year 19 | 971 | | | Per | iod 1956-197 | 1 |
|---------|--------|--------|-----|-----------|------------|-----|---------|-----------|---------|--------------|---------|
| | Extrem | e Gage | ø | Extreme S | econd F | eet | Average | Total | | Acre Feet | |
| Month L | Fe | et | | High | | Low | Second | | | ACIC TOOL | , |
| | High | Low | Day | | Day | | Feet | Acre Feet | Average | Maximum | Minimum |
| Jan. | | | 24 | 4.8 | 1 1 | 0 | 0.4 | 25 | 120 | 280 | 0 |
| Feb. | | | 16 | 7.2 | † 3 | 0 | .7 | 37.5 | 215 | 500 | 26.2 |
| Mar. | | 1 | | 0 | 1 | 0 | 0 | 0 | 264 | 600 | 0 |
| Apr. | | | | 0 | | 0 | 0 | 0 | 332 | 670 | 1 0 |
| May | | | 1 | 0 | | 0 | 0 | 0 | 370 | 770 | 1 6 |
| June | | | | 0 | - | 0 | 0 | 0 | 386 | 800 | 0 |
| July | | | 1 | 0 | } | 0 | 0 | 0 | 399 | 820 | 0 |
| Aug. | | | 1 | 0 | | 0 | 0 | 0 | 263 | 800 | 0 |
| Sept. | | i | 1 | 0 | i | 0 | 0 | 0 | 248 | 940 | 0 |
| Oct. | | i | 1 | 0 | 1 | 0 | 0 | 0 | 174 | 390 | 0 |
| Nov. | | | | 0 | 1 | 0 | 0 | 0 | 137 | 330 | 0 |
| Dec. | | | 1 | 0 | | 0 | 0 | 0 | 97 | 230 | 0 |
| Yearly | | | | 7.2 | | 0 | 0 | 62.5 | 3,005 | 6,480 | 62.5 |

[#] And other days

EAST MAIN CANAL WASTEWAY (VALLEY DIVISION, YUMA PROJECT)

Water-stage recorder and control weir located about 300 feet north of the international boundary DESCRIPTION: near San Luis, Arizona, and 1.5 miles east of the Colorado River.
RECORDS: Wasteway discharges computed by United States Section of the Commission beginning November

1, 1953, from head on control weir as measured by water-stage recorder and weir ratings as determined by current meter measurements. Records available: October 1946 through 1971. Records of monthly discharges also are available for the periods January 1924 through June 1928, January 1932 through 1933, and April 1935 through September 1946.

REMARKS: Wasteway discharges from the East Main Canal comprise regulatory waste and drainage waters from the eastern half of the Valley Division of the Yuma Project and are considered as part of the volumes arriving at the limitrophe section of the Colorado River.

Mean Daily Discharge in Second Feet 1971 — Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|---|------------------------------------|--|---------------------------------|---------------------------------|----------------------------------|---|---|--|--|---------------------------------------|--|
| 1 2 3 4 5 | 13.9 7.3 4.3 6.1 3.3 | .8 .9 3.5 .4 2.9 | 2.4 5.1 7.3 11.3 | 16.7 .8 3.9 1.0 | 2.9 6.9 6.3 7.8 2.3 | 15.2 8.0 19.8 .4 7.1 | 11.5 8.3 1.3 4.4 11.6 | 12.6 2.7 3.8 8.6 15.1 | 7.2 3.2 3.7 3.9 | 2.1 .2 7.6 16.6 4.1 | 10.3 4.6 2.2 .9 7.7 | .9 5.9 8.8 5.2 2.9 |
| 6 7 8 9 | 6.4 3.8 6.0 5.1 2.9 | 9.5 7.3 .8 12.0 1.0 | 10.4 4.8 10.6 7.7 3.5 | .8 3.8 4.9 0 | + N N O O | 2.1 6.6 6.6 0 | 10.0 8.6 5.0 1.6 1.7 | 4.5 4.8 .1 10.5 3.4 | .5 5.2 7.1 .3 0 | .4 11.6 8.8 5.1 6.9 | 6.4 10.5 * .5 * 11.2 21.3 | 8.5 4.9 1.8 .1 |
| 11 12 13 14 15 | 1.3 1.4 9.1 5.3 7.4 | .9 7.9 9.7 2.8 5.4 | 6.6 12.0 6.5 2.9 | 0 12.2 4.6 6.2 3.2 | 0 5.1 4.0 4.6 2.3 | 12.8 •3 4.2 11.5 4.3 | 1.7 .9 .7 7.6 8.0 | 2.1 1.6 2.9 .8 8.0 | 2.1 7.1 7.6 1.1 4.6 | 6.9 4.7 2.8 3.1 | 5.5 10.4 9.8 6.8 26.9 | 4.8 17.8 10.2 3.8 1.0 |
| 16 17 18 19 20 | 4.4 5.5 2.3 3.1 6.6 | 3.6 6.1 10.1 9.2 12.1 | 2.6 5.4 1.5 5.8 .3 | 4.4 •3 0 10.7 3.2 | 3.8 6.6 2.0 3.8 4.7 | 4.4 3.5 4.8 .4 13.0 | 21.6 3.9 4.7 12.6 13.1 | 26.4 4.4 0 4.0 19.1 | 4.0 * 4.4 ! 2.7 ! 7.2 * 14.2 | 1.3 2.7 8.9 5.0 11.5 | 6.2 1.7 .6 4.0 8.4 | .1 0 .1 10.6 28.5 |
| 21 22 23 24 25 | .5 3.5 11.8 10.5 7.2 | * 9.5 11.4 6.6 1.2 1.0 | 4.2 19.9 7.2 2.0 3.2 | .4 0 .1 1.8 6.4 | 12.0 1.7 .1 7.9 5.3 | 19.4 1.5 0 4.3 5.5 | 5.9 1.7 5.7 3.7 8.5 | 13.4 10.1 5.1 5.1 3.7 | 15.1 11.1 16.8 5.1 7.4 | 11.5 10.7 6.5 4.6 12.6 | 26.2 10.6 6.3 2.3 7.6 | 6.5 3.4 1.2 2.3 |
| 26 27 28 29 30 31 | 5.1 10.1 9.3 13.2 13.3 2.5 | 20.7 10.2 2.3 | 7.5 1.4 12.1 24.4 19.6 11.8 | 7.9 2.6 4.6 4.7 9.4 | .8 4.8 5.3 1.2 3.5 | 3.8 8.4 2.6 .3 8.7 | 7.8 8.9 10.1 8.5 4.7 6.9 | 14.1 8.9 7.3 4.0 9.6 4.3 | 4.8 3.1 10.5 27.1 18.9 | 12.9 3.6 4.1 12.8 7.8 8.3 | 5.8 1.0 .6 16.2 15.1 | 1.1 5.9 1.4 2.3 2.0 4.8 |
| Sum | 192.5 | 169.8 | 221.0 | 116.1 | 123.3 | 180.2 | 211.2 | 221.0 | 206.1 | 206.5 | 247.6 | 147.2 |

Current Year 1971 Period 1935-1971 Extreme Second Feet Extreme Gage Average Total Acre Feet Feet Second Month High Low Acre Feet Average Maximum Minimum Feet High Low Day Day † 5 † 1 † 1 48.5 382 1,254 3,360 Jan. 90.95 6.2 3,360 3,170 2,920 3,170 3,040 3,660 1,048 1,212 48.5 6.1 7.1 337 438 Feb. 90.95 90.88 90.15 26 0 190 197 245 37.3 48.5 29 Mar. 90.15 230 245 1,177 1,293 1,105 Ō 3.9 Apr. 91.00 1 2 May 90.95 90.15 **†**19 43.8 0 357 419 175 182 ŏ 34.8 6.0 June 90.85 90.15 1 3,590 3,960 3,170 3,280 †3 †3 †5 †2 ō 6.8 1,194 July 90.74 90.15 26.0 169 1,216 1,108 1,165 1,281 15 40.9 Ó 438 Aug. 90.92 159 409 Sept. 90.15 29 48.5 0 6.9 91.00 410 410 Oct. 10 43.8 0 6.7 90.95 90.15 3,570 313 8.3 491 Nov. 91.03 90.15 6 51.5 1 5 Ω 292 ō 3,080 Dec. 91.00 90.15 13

90.15

Yearly

6.2

0

4,448

14,307

38,310

4,448

^{91.00} * Partly estimated

^{51.5} # Estimated

^{*} And other days

YUMA MAIN DRAIN (VALLEY DIVISION, YUMA PROJECT)

ESCRIFTION: Water-stage recorders located in the forebay and afterbay, with flow meters in the four dis-charge pipes at the Boundary Pumping Plant on the Main Drain about 200 feet north of the international DESCRIPTION: boundary near San Luis, Arizona, 1.3 miles east of the Colorado River.

RECORDS: Main Drain discharges are lifted 10 to 12 feet at the pumping plant. Prior to April 1, 1969, discharges were computed from pump ratings and the differential head measured by the two gages. Beginning April 1, 1969 discharges were computed from flow meter charts. Pump ratings and flow meter discharges are checked by current meter measurements. Records obtained and computed by the United States Section of the Commission. Records available: Monthly discharges, June 1919 through 1951; daily discharges January 1952 through 1971.

EMMARKS: Flows in the Main Drain are principally drainage waters from the Valley Division of the Yuma Project. Both the Main Drain and the East Main Canal Wasteway discharge into Mexico at the international land boundary near San Luis, Sonora. The water is used for irrigation in Mexico on the left (Sonora) bank of the Colorado River and is considered as part of the volumes arriving at the limitrophe section of the river.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|---------------------------------|---------------------------------|--|---------------------------------|--|---------------------------------|--|---------------------------------|---|---------------------------------|---------------------------------|--|
| 12345 | 173 166 162 160 166 | 181 170 178 176 190 | 175 165 188 186 180 | 194 188 190 182 185 | 178 188 198 183 186 | 197 186 202 191 194 | 180 176 190 186 179 | 179 178 197 178 184 | 199 193 186 192 203 | 197 192 195 203 196 | 183 186 185 190 194 | 177 167 170 171 168 |
| 6 7 8 9 | 167 160 166 164 165 | 179 173 178 174 180 | 190 182 175 180 173 | 182 174 183 187 187 | 180 193 192 195 182 | 197 188 192 196 186 | 182 183 184 192 184 | 172 164 181 201 186 | 19 ¹ 4 189 187 192 190 | 190 200 196 181 187 | 190 189 204 198 196 | 162 159 161 161 162 |
| 11 12 13 14 15 | 164 158 161 166 169 | 188 187 191 200 180 | 174 182 185 182 178 | 202 183 184 174 191 | 177 190 184 186 183 | 187 196 184 192 191 | 182 174 180 176 183 | 187 197 188 187 192 | 187 184 184 191 194 | 187 189 184 195 188 | 193 191 206 206 192 | 160 171 158 170 158 |
| 16 17 18 19 20 | 167 170 159 166 163 | 176 173 181 182 180 | 171 179 172 170 186 | 195 190 196 190 181 | 187 176 192 190 190 | 186 181 186 191 204 | 185 183 184 200 185 | 205 187 176 184 186 | 193 199 193 192 195 | 186 195 194 196 195 | 183 176 177 181 170 | 165 166 182 174 178 |
| 진 22 27 4 25 | 161 160 170 166 166 | 176 196 182 177 168 | 206 184 178 175 173 | 176 164 174 186 182 | 183 187 188 183 190 | 213 186 176 174 178 | 183 182 186 187 185 | 189 195 186 183 186 | 200 201 189 189 200 | 195 193 192 199 193 | 187 184 176 186 172 | 167 163 159 165 164 |
| 26 27 28 29 30 31 | 164 152 166 170 174 | 176 178 178 | 176 178 185 186 178 188 | 190 184 182 180 189 | 186 181 179 194 195 191 | 184 183 186 175 186 | 197 183 177 174 183 181 | 188 182 188 188 210 | 193 192 189 239 203 | 189 186 199 187 190 | 179 173 170 174 181 | 156 154 163 161 161 168 |
| Sum | 5,104 | 5,048 | 5,580 | 5,545 | 5,787 | 5,668 | 5,686 | 5,791 | 5,832 | 5,962 | 5,572 | 5,121 |

Current Year 1971 Period 1935-1971 Extreme Gage **Extreme Second Feet** Average Total Acre Feet Feet Month High Second Acre Feet Average Maximum Minimum Day Feet High Low Day 10,124 11,203 Jan. 30 174 27 165 152 11,988 12,430 11,890 13,140 12,040 7,754 8,874 8,639 8,794 14 200 168 180 10,013 1,640 Feb. 25 1,940 Mar. 21 206 2 165 180 11,068 185 1,920 10,998 11,478 Apr. 11 202 22 164 187 1,950 Mav 3 198 17 176 June 21 213 24 189 11,242 8,130 2,290 11,278 11,486 11,568 11,825 11,052 200 †12 174 183 7,919 11,830 2,530 July 19 7,848 2,560 Aug. 3Ó 210 7 164 187 11,960 7,883 8,920 8,660 11,568 2,280 112 29 4 184 Sept. 239 194 192 12,385 2,940 Oct. 203 206 Q 181 **†**13 12,010 2,800 †20 Nov. 170 2,450 18 182 165 10,157 8,357 11,480 Dec. 27,040

183

152

132,289

99,600

139,380

Yearly

239

Mean daily

f And other days

WEST MAIN CANAL WASTEWAY (VALLEY DIVISION, YUMA PROJECT)

DESCRIPTION: Water-stage recorder located about 150 feet upstream from outlet to Yuma Main Drain, which

is 175 feet upstream from East Main Canal Wasteway and 0.4 mile west of San Luis, Arizona.

RECORDS: Wasteway discharges computed by United States Section of the Commission beginning February 23, 1971, from water-stage recorder and ratings as determined by current meter measurements.
March through December 1971. Records available:

REMARKS: Wasteway discharges from West Main Canal Wasteway comprise regulatory waste from the West Main Canal.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|------------------|--------------------------|----------------------------------|-------------------------------------|------------------------------------|-----------------------------------|---------------------------------|----------------------------------|------------------------------------|---------------------------------------|------------------------------------|---|
| 1 2 3 4 5 | 0 0 0 0 | 00000 | 1.7 3.3 2.8 8.6 7.6 | 2.9 1.2 .7 2.6 .3 | 0.8 6.4 1.9 4.9 8.8 | 0.5 1.0 8.1 4.5 4.2 | 0.1 0 4.3 9.5 4.7 | 0 1.2 .9 .6 4.6 | 0.6 8.5 .1 2.4 16.2 | 20.7 9.4 27.4 22.5 5.0 | 8.1 9.8 6.7 4.6 5.5 | 6.5 2.1 4.4 3.4 28.7 |
| 6 7 8 9 | 0 0 0 0 | 0 0 0 0 | 4.9 .6 1.1 .1 | 0 0 0 0 1.3 | .2 .2 6.6 10.8 9.5 | 26.9 2.7 0 0 | .6 5.9 .9 19.1 4.5 | 1.8 1.2 1.3 5.4 11.4 | .5 5.2 8.6 17.7 3.7 | .7 .2 2.7 .1 | 9.6 11.4 5.2 4.6 12.0 | 37.0 3.7 .6 .2 3.4 |
| 11 12 13 14 15 | 0 0 0 0 | 0 0 0 0 | 0 .1 .5 8.6 17.3 | 3.2 5.5 5.5 2.3 * 3.0 | 4.2 1.7 2.4 2.9 | 0 0 0 14.9 4.6 | 1.0 1.8 .5 5.1 1.4 | 14.2 9.0 1.7 .5 2.7 | .1 0 1.5 2.0 3.1 | 7.8 13.9 17.8 13.7 7.4 | 26.3 1.1 6.0 25.1 23.0 | .6 5.0 5.8 .6 1.7 |
| 16 17 18 19 20 | 0 0 0 0 | 0 0 0 0 | .3 0 2.0 5.0 | * 1.7 2.4 19.5 11.0 4.8 | .1 4.6 7.8 10.4 5.3 | .1 0 6.0 3.6 7.9 | .5 .4 2.5 .5 .4 | .2 1.4 .2 1.7 7.0 | 4.2 8.4 .9 .6 16.7 | 7.8 17.0 7.6 0 | 2.6 5.2 6.2 8.6 11.7 | 9.7 5.6 2.9 .4 2.5 |
| 21 22 23 24 25 | 0 0 0 0 | 0 0 .9 0 1.0 | 1.1 1.1 10.3 4.8 5.1 | 1.5 7.3 1.1 5.3 | 1.6 .4 3.8 .2 | 17.2 .2 2.2 .3 .3 | .9 2.4 5.0 8.0 22.9 | 2.7 3.0 1.2 .5 | 11.4 .4 11.1 .8 12.4 | 1.4 .7 4.8 .9 | 26.0 6.5 13.3 .5 2.4 | .6 5.3 18.4 6.8 4.0 |
| 26 27 28 29 30 31 | 0 0 0 0 | 1.7 .1 0 | 5.8 1.4 .1 6.5 .6 | 2.4 1.6 2.4 1.7 2.1 | .1 0 .2 1.2 5.6 6.7 | 14.8 1.6 6.0 22.7 5.0 | 8.2 5.9 1.4 3.4 .2 | .5 .2 .1 6.7 .4 | 12.4 9.3 3.4 17.3 25.4 | 4.6 4.8 .4 5.0 6.4 1.2 | 1.7 11.0 4.6 3.2 10.3 | 3.5 2.4 2.6 7.6 4.6 16.0 |
| Sum | 0 | 3.7 | 102.2 | 88.4 | 109.6 | 155.3 | 122.0 | 83.5 | 204.9 | 212.7 | 272.8 | 196.6 |

Current Year 1971 Period Extreme Second Feet Average ø Extreme Gage Total Acre Feet Second Month High Low Acre Feet Average Maximum Minimum Feet High Day Day Jan. Feb. 7.3 26 1.7 124 203 175 217 Mar. 17.3 710 3.3 2.9 15 18 Apr. **†** 6 0 19.5 3.5 5.2 3.9 2.7 Мау 10.8 9 27 0 June ŏ 303 † 8 † 2 26.9 July ō 242 25 11 22.9 166 Aug. Ó 14.2 406 25.4 27.4 6.8 Sept. 30 12 0 422 †19 24 Oct. 3 0 541 Nov. 26.3 390 Dec. 37.0 3,077 Yearly 5.1 37.0

^{*} Partly estimated

[†] And other days

Ø Mean daily

TOTAL FLOWS CROSSING INTERNATIONAL BOUNDARY INTO MEXICO NEAR SAN LUIS, SONORA

DESCRIPTION: The tabulated data below are the combined flows of the East Main Canal Wasteway, Yuma Main Drain, and West Main Canal Wasteway (beginning February 23, 1971) and represent the total water crossing the international land boundary into the Sanchez Mejorada Canal near San Luis, Arizona. The Mexican Section maintains a water-stage recorder in Mexico on the right bank of Sanchez Mejorada Canal and obtains check measurements on a bridge located 0.2 mile downstream from the international boundary, 1.2 miles east of the Colorado River and 0.6 mile west of San Luis, Sonora.

Records obtained and computed by the United States Section of the Commission. Records available: RECORDS: January 1935 through 1971.

MMARKS: Descriptions and flows of the individual stations, East Main Canal Wasteway, Yuma Main Drain and West Main Canal Wasteway, are published separately in this bulletin on pages 30, 31, and 32. REMARKS:

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|---------------------------------|---------------------------------|--|---------------------------------|--|---------------------------------|---------------------------------|--|---------------------------------|--|---------------------------------|--|
| 1 | 187 | 182 | 177 | 21 ¹ 4 | 182 | 213 | 192 | 192 | 207 | 220 | 201 | 184 |
| 2 | 173 | 171 | 171 | 190 | 201 | 195 | 184 | 182 | 205 | 202 | 200 | 175 |
| 3 | 166 | 182 | 196 | 195 | 206 | 230 | 196 | 202 | 190 | 230 | 194 | 183 |
| 4 | 166 | 176 | 202 | 186 | 196 | 196 | 200 | 187 | 198 | 242 | 196 | 180 |
| 5 | 169 | 193 | 199 | 186 | 197 | 205 | 195 | 204 | 219 | 205 | 207 | 200 |
| 6 7 8 9 | 173 164 172 169 168 | 189 180 179 186 181 | 205 187 187 188 177 | 183 178 188 187 190 | 180 200 201 208 196 | 226 197 199 196 187 | 193 198 190 213 190 | 178 170 182 217 201 | 195 199 203 210 194 | 191 212 208 186 194 | 206 211 210 214 229 | 208 168 163 161 166 |
| 11 | 165 | 189 | 181 | 205 | 181 | 200 | 185 | 203 | 189 | 202 | 225 | 165 |
| 12 | 159 | 195 | 194 | 201 | 197 | 196 | 177 | 208 | 191 | 208 | 203 | 194 |
| 13 | 170 | 201 | 19 2 | 189 | 190 | 188 | 181 | 193 | 193 | 205 | 222 | 174 |
| 14 | 171 | 203 | 194 | 183 | 194 | 218 | 189 | 188 | 194 | 212 | 238 | 174 |
| 15 | 176 | 185 | 196 | 197 | 185 | 200 | 192 | 203 | 203 | 196 | 242 | 161 |
| 16 | 171 | 180 | 174 | 201 | 191 | 191 | 207 | 232 | 201 | 195 | 192 | 175 |
| 17 | 176 | 179 | 184 | 193 | 187 | 185 | 187 | 193 | 212 | 215 | 183 | 172 |
| 18 | 161 | 191 | 176 | 216 | 202 | 197 | 191 | 176 | 197 | 211 | 184 | 185 |
| 19 | 169 | 191 | 181 | 212 | 204 | 195 | 213 | 190 | 200 | 201 | 194 | 185 |
| 20 | 170 | 192 | 187 | 189 | 200 | 225 | 199 | 212 | 226 | 207 | 190 | 209 |
| 21 | 162 | 186 | 211 | 178 | 197 | 250 | 190 | 205 | 227 | 208 | 239 | 174 |
| 22 | 164 | 207 | 205 | 171 | 189 | 188 | 186 | 208 | 213 | 204 | 201 | 172 |
| 23 | 182 | 190 | 196 | 175 | 192 | 178 | 197 | 192 | 217 | 203 | 196 | 179 |
| 24 | 176 | 178 | 182 | 193 | 191 | 179 | 199 | 189 | 195 | 205 | 189 | 174 |
| 25 | 173 | 170 | 181 | 189 | 196 | 184 | 216 | 191 | 220 | 206 | 182 | 168 |
| 26 27 28 29 30 31 | 169 162 175 183 187 | 198 188 180 | 189 181 197 217 198 200 | 200 188 189 186 201 | 187 186 185 196 204 199 | 203 193 195 198 200 | 213 198 189 186 188 | 203 191 195 199 220 192 | 210 204 203 283 247 | 207 194 204 205 204 203 | 187 185 175 193 206 | 161 162 167 171 168 189 |
| Sum | 5,296 | 5,222 | 5,903 | 5,750 | 6,020 | 6,004 | 6,019 | 6,096 | 6,243 | 6,381 | 6,092 | 5,465 |

Period 1935-1971 Current Year 1971 Extreme Second Feet Average Extreme Gage Total Acre Feet Month Feet Second High Feet Acre Feet Average Maximum Minimum High Low Day Day * 2,123 1 1 1.87 12 159 171 10,505 9,076 12,131 Jan. 10,305 11,709 11,404 11,940 11,907 * 2,023 * 2,322 2,117 22 25 186 8,808 12,970 170 Feb. 207 10,092 9,821 10,093 13,704 12,982 29 21.7 ż 171 190 Mar. 22 6 Apr. 18 216 171 192 13,900 2,473 194 9 21 May 208 180 9,243 9,120 9,069 9,001 12,570 12,420 12,657 2,525 2,927 250 23 12 178 200 June 25 16 216 177 194 11,939 July 2,989 2,602 3,444 3,407 12,090 12,383 12,657 232 7 170 197 Aug. 208 12,450 29 4 283 11 189 Sept. 242 9 186 206 10,096 13,898 Oct. 242 29 173 203 12,084 9,955 9,622 12,712 15 Nov. 2,888 12,050 20 209 19 161 176 10,839 Dec. 31,840 149.010 161 193 139,814 113,996 283 Yearly

Ø Mean daily
* Partly estimated

Q Includes West Main Canal Wasteway

f And other days

COLORADO RIVER AT SOUTHERLY INTERNATIONAL BOUNDARY - DISCHARGES

DESCRIFTION: Water-stage recorder located in Mexico on the right bank of the river about 1,000 feet upstream from the southerly international boundary, 2 miles west of San Luis, Arizons, and 19.4 miles downstream from Morelos Dem. Zero of gage is at mean sea level, U. S. C. & G. S. datum.

RECORDS: Records obtained and furnished by the United States Section of the Commission. Computations by shifting control methods. Records available: Daily discharges, January 1950 through 1971; continuous record of gage heights, January 1947 through 1971. Monthly flows for this station have been derived for the period January 1935 through 1949 based on the computed records of monthly flows of the Colorado River at the northerly international boundary combined with the measured monthly flows from the wasteways discharging into the boundary section of the river from the Yuma Project in Artzona.

REMARKS: Reservoirs, diversions in the United States and Mexico, drainage returns, and waste flows modify the river flow at this station.

EXTREMES: Since January 1950: Maximum instantaneous discharge, 28,610 second-feet on December 18, 1952; maximum gage height, 84.84 feet on November 29, 1957. Minimum discharge, no flow on several occasions since September 1, 1956.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|--|---|--|-------------------------------------|--|--------------------------------------|--------------------------------------|--|---|--|--|---|
| 1 2 3 4 5 | 147 148 148 147 127 | 259 259 257 252 204 | 39.7 25.0 20.6 18.4 15.6 | * 2.4 # 1.9 * .9 .2 9.4 | 41.5 70.8 78.0 78.0 73.2 | 93.9 79.2 75.6 76.8 70.8 | 0 0 0 0 | 0 0 0 0 | 79.0 65.0 64.0 61.0 55.6 | 489 916 771 368 284 | 245 242 242 242 245 | 247 247 249 258 264 |
| 6 7 8 9 | 127 123 134 138 147 | 176 171 167 173 167 | 15.6 15.1 16.2 16.2 12.9 | 11.5 4.0 1.9 .4 | 68.4 66.0 75.1 * 92.6 !! 95.2 | 58.3 93.9 66.0 58.3 54.0 | 0 0 0 0 | 0 0 0 0 | 52.0 46.6 43.9 46.6 43.9 | 264 256 249 245 240 | 247 247 247 247 247 245 | 29 ¹ 4 271 258 253 23 ¹ 4 |
| 11 12 13 14 15 | 176 211 240 245 257 | 157 152 142 126 177 | 12.4 11.8 11.8 11.2 31.1 | 0 * .8 * 2.5 0 3.3 | * 92.6 93.9 96.5 96.5 | 48.4 48.4 46.4 46.4 47.4 | 0 0 0 15.5 46.4 | 0 0 0 0 | 38.5 39.4 50.2 64.0 70.0 | 240 238 234 232 230 | 245 245 247 256 296 | 207 191 159 139 128 |
| 16 17 18 19 20 | 257 259 262 262 259 | 13 ⁴ 115 103 79.2 70.8 | 22.5 12.6 * 9.1 * 7.2 7.6 | 2.4 2.6 2.1 2.2 1.1 | * 95.2 * 102 * 95.2 96.5 92.6 | 41.5 27.8 29.2 28.5 11.8 | 59.4 66.0 68.4 68.4 38.7 | 0 0 0 0 | 77.0 143 168 186 194 | 230 232 238 245 236 | 269 253 253 256 256 | 118 110 101 98.1 99.2 |
| 21 22 23 24 25 | 259 259 257 259 267 | 64.8 54.0 39.7 35.3 40.8 | 7.6 9.8 9.1 6.8 5.6 | •5 0 0 0 | 90.0 88.8 90.0 90.0 93.9 | 7.6 47.8 8.0 0 | 14.4 6.5 5.8 5.3 3.4 | 25.4 98.1 192 230 251 | 200 200 200 200 200 2014 | 238 238 240 245 245 | 253 251 247 245 245 | 97.0 100 101 100 99.2 |
| 26 27 28 29 30 31 | 257 259 259 262 259 264 | 44.1 41.9 44.1 | 5.1 6.1 5.3 5.8 5.3 3.1 | 0 0 0 0 5.6 | 95.2 92.6 92.6 96.5 97.8 97.8 | 0 0 0 0 | 0 0 0 0 | 288 330 330 352 294 115 | 20 ¹ 4 202 20 ¹ 4 213 260 | 238 240 240 238 240 242 | 247 251 253 249 247 | 99.2 98.1 102 107 107 102 |
| Sum | 6,675 | 3,705.7 | 402.2 | 55.7 | 2,725.0 | 1,166.0 | 398.2 | 2,506.0 | 3,674.7 | 9,081 | 7,513 | 5,037.8 |

Period 1935-1971 Current Year 1971 Extreme Gage Extreme Second Feet Average Total Acre Feet Feet Second Month High Acre Feet Average Maximum Minimum High Day Day Feet Low 1,821 1,672,000 16 215 13,240 413,859 76.17 269 Jan. 1,385,000 2,040 74.45 73.86 267 24 31.3 132 **7,3**50 344,423 276,898 Feb. 76.06 798 110 49.6 31 † 3 13.0 Mar. 74.62 176,424 242,550 186,500 74.33 74.93 73.63 74.19 24.8 110 700,900 Apr. May 5,405 2,313 790 1,160,000 1,180,000 87.9 1.045 17 106 ī 23.2 130 69.6 366 **†**21 143 38.9 June 75.09 73.70 † 1 † 1 12.8 136,191 772,800 ŏ ō July 74.57 73.70 118 4,971 796,0**0**0 1,0**33,**000 76.18 73.60 80.8 151,764 Ω 30 Aug. 184,310 235,691 309,962 0 74.24 30 304 **†**11 37.6 122 7.289 75.90 Sept. 1,192,000 9,120 7,180 228 18,012 77 .84 75.64 2 961 **†**16 293 Oct. 14,902 15 6 **†** 1 242 250 76.05 75.72 312 Nov. 163 9,992 390,535 1,839,000 2,320 †21 97.0 76.05 74.80 315 0 118 85,172 3,049,107 10,688,800 83,792 77.84 73.60 961 Yearly

^{*} Partly estimated

Estimated

f And other days

COLORADO RIVER AT SOUTHERLY INTERNATIONAL BOUNDARY - STAGES

(See Preceding Page For Description)

| | | | , | | | | | | , | , | , | |
|----------------------------------|--|-------------------------|--|---|--|---|--|--|---|--|---|--|
| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
| 1 | 75.65 | 76.03 | 74.53 | *73.86 | 74.43 | 74.82 | 73.70 | 73.60 | 74.68 | 76.52 | 75.73 | 75.75 |
| 2 | 75.65 | 76.03 | 74.36 | #73.84 | 74.72 | 74.70 | 73.70 | 73.60 | 74.54 | 71.73 | 75.73 | 75.75 |
| 3 | 75.64 | 76.02 | 74.29 | *73.81 | 74.78 | 74.67 | 73.70 | 73.60 | 74.53 | 77.39 | 75.73 | 75.76 |
| 4 | 75.62 | 76.00 | 74.25 | 73.79 | 74.78 | 74.69 | 73.70 | 73.60 | 74.50 | 76.25 | 75.74 | * 75.80 |
| 5 | 75.49 | 75.79 | 74.20 | 74.02 | 74.74 | 74.64 | 73.70 | 73.60 | 74.44 | 75.90 | 75.75 | # 75.83 |
| 6 | 75.49 | 75.63 | 74.20 | 74.13 | 74.70 | 74.53 | 73.70 | 73.60 | 74.40 | 75.81 | 75.76 | # 75.96 |
| 7 | 75.46 | 75.59 | 74.19 | 73.92 | 74.68 | 74.83 | 73.70 | 73.60 | 74.34 | 75.77 | 75.76 | * 75.86 |
| 8 | 75.54 | 75.59 | 74.21 | 73.81 | 74.73 | 74.60 | 73.70 | 73.60 | 74.31 | 75.74 | 75.76 | 75.80 |
| 9 | 75.56 | 75.58 | 74.21 | 73.67 | *74.85 | 74.53 | 73.70 | 73.60 | 74.34 | 75.72 | 75.76 | 75.77 |
| 10 | 75.62 | 75.54 | 74.15 | 73.63 | #74.87 | 74.49 | 73.70 | 73.60 | 74.31 | 75.70 | 75.76 | 75.68 |
| 11 | 75.79 | 75.48 | 74.14 | 73.63 | *74.85 | 74.43 | 73.70 | 73.60 | 74.25 | 75.70 | 75.75 | *75.54 |
| 12 | 75.96 | 75.45 | 74.13 | *73.68 | 74.86 | 74.43 | 73.70 | 73.60 | 74.26 | 75.69 | 75.75 | "75.46 |
| 18 | 76.09 | 75.39 | 74.13 | *73.82 | 74.88 | 74.41 | 73.70 | 73.60 | 74.37 | 75.67 | 75.76 | "75.28 |
| 14 | 76.11 | 75.28 | 74.12 | 73.63 | 74.88 | 74.41 | 73.93 | 73.60 | 74.52 | 75.66 | 75.80 | *75.16 |
| 15 | 76.16 | 75.61 | 74.40 | 73.88 | 74.90 | 74.42 | 74.35 | 73.60 | 74.57 | 75.65 | 75.98 | 75.09 |
| 16 | 76.15 | 75.33 | 74.30 | 73.86 | *74.86 | 74.35 | 74.48 | 73.60 | 74.63 | 75.65 | 75.86 | 75.00 |
| 17 | 76.15 | 75.19 | 74.15 | 73.83 | #74.90 | 74.17 | 74.54 | 73.60 | 75.09 | 75.66 | 75.79 | 74.92 |
| 18 | 76.15 | 75.10 | *74.08 | 73.84 | *74.84 | 74.20 | 74.56 | 73.60 | 75.23 | 75.69 | 75.79 | 74.84 |
| 19 | 76.14 | 74.91 | *74.03 | 73.85 | 74.85 | 74.19 | 74.56 | 73.60 | 75.33 | 75.72 | 75.80 | 74.81 |
| 20 | 76.13 | 74.84 | 74.04 | 73.75 | 74.82 | 73.95 | 74.25 | 73.62 | 75.38 | 75.68 | 75.80 | 74.82 |
| 21 | 76.12 | 74.78 | 74.04 | 73.69 | 74.80 | 73.84 | 73.94 | 74.11 | 75.42 | 75.69 | 75.79 | 74.80 |
| 22 | 76.11 | 74.68 | 74.10 | 73.63 | 74.79 | 74.41 | 73.79 | 74.81 | 75.42 | 75.69 | 75.78 | 74.83 |
| 28 | 76.09 | 74.53 | 74.08 | 73.63 | 74.80 | 73.88 | 73.78 | 75.38 | 75.42 | 75.70 | 75.76 | 74.84 |
| 24 | 76.09 | 74.49 | 74.02 | 73.63 | 74.80 | 73.70 | 73.76 | 75.56 | 75.42 | 75.72 | 75.75 | 74.83 |
| 25 | 76.11 | 74.54 | 73.98 | 73.63 | 74.82 | 73.70 | 73.70 | 75.66 | 75.44 | 75.72 | 75.75 | 74.82 |
| 26 27 28 29 80 81 | 76.06 76.06 76.05 76.05 76.04 76.05 | 74.57 74.55 74.57 | 73.96 74.00 73.97 73.99 73.97 73.88 | 73.63 73.63 73.63 73.63 73.83 | 74.83 74.81 74.81 74.84 74.85 74.85 | 73.70 73.70 73.70 73.70 73.70 | 73.60 73.60 73.60 73.60 73.60 73.60 | 75.83 76.02 76.02 76.12 75.85 74.96 | 75.44 75.43 75.44 75.48 75.70 | 75.70 75.71 75.71 75.70 75.71 75.72 | 75.76 75.78 75.79 75.77 75.76 | 74.82 74.81 74.85 74.89 74.89 74.85 |
| Avg | 75.92 | 75.25 | 74.13 | 73.76 | 74.80 | 74.25 | 73.85 | 74.27 | 74.89 | 75.87 | 75.77 | 75.23 |

^{*} Partly estimated

Estimated

WASTEWAY TO COLORADO RIVER AT KILOMETER 27 IN MEXICO

DESCRIFTION: Water-stage recorder and cableway located on the left bank of the canal wasteway immediately upstream from where it discharges into the Colorado River, 0.6 mile downstream from the wasteway gates on canal de Conexion, 16.8 miles downstream from Morelos Dam, and 0.2 mile south of the junction of the Mexicali-San Luis and Algodones-Pescaderos highways.

RECORDS: Date obtained and computed by the Colorado River Irrigation District of the Ministry of Hydraulic Resources and furnished by the Mexican Section of the Commission. Records shown in table below are waste returns to the Colorado River. 1971 records good. Records available: April 1956 through 1971. REMARKS: The Colorado River Irrigation District transports water for irrigation of land on the left bank of

EMARKS: The Colorado River Irrigation District transports water for irrigation of land on the left bank of the Colorado River by the Canal de Conexion to a point called Kilometer 27. At this point, flows may be returned to the river through the wasteway or diverted to the Bacanora-Monumentos Canal system through the Sanchez Mejorada Siphon, which was placed in operation on June 28, 1963.

Monthly Discharge in Acre-Feet

| Month | Current Year 1971 | Period 1956-1971 | | | | | | | |
|-----------|-------------------|------------------|---------|---------|--|--|--|--|--|
| Month | Current Year 1971 | Average | Maximum | Minimum | | | | | |
| January | 0 | 6,253 | 69,527 | 0 | | | | | |
| February | 0 | 1,257 | 8,679 | 0 | | | | | |
| March | 0 | 7 ,2 78 | 35,492 | 0 | | | | | |
| April | 0 | 16,542 | 68,714 | 0 | | | | | |
| May | 0 | 7,137 | 22,072 | 0 | | | | | |
| June | 0 | 11 ,3 97 | 28,915 | 0 | | | | | |
| July | 0 | 17,879 | 46,139 | 0 | | | | | |
| August | 0 | 19,318 | 55,497 | 0 | | | | | |
| September | 0 | 11,656 | 37,194 | 0 | | | | | |
| October | 0 | 4,219 | 20,512 | 0 | | | | | |
| November | 0 | 9,904 | 69,415 | 0 | | | | | |
| December | 0 | 6 ,2 85 | 70,213 | 0 | | | | | |
| Yearly | 0 | 112,124 | 346,339 | 0 | | | | | |

WASTEWAY TO COLORADO RIVER AT COLONIA ELIAS IN MEXICO

ESCRIPTION: Wasteway structure located at Kilometer 7*570 of the Barrote Canal on the right bank of the Colorado River in Colonia Elias about 20.5 miles downstream from the southerly international boundary and the town of San Luis Rio Colorado, Sonors; about 10 miles upstream from the Sonora-Baja California railroad bridge and 4.3 miles upstream from the Miguel C. Rodriguez Gaging Station. The wasteway gates are located about 2,500 feet from the right bank of the Colorado River.

ECORDS: Data obtained by the Ministry of Hydraulic Resources and furnished by the Mexican Section of the Commission are based on gate openings. Records available: January 1957 through 1971.

EMARKS: The wasteway structure has 3 manually operated rectangular gates which discharge directly from the Barrote Canal into a wasteway leading to the Colorado River. DESCRIPTION:

RECORDS: REMARKS:

Barrote Canal into a wasteway leading to the Colorado River.

| Month | Current Year 1971 | | Period 1957-1971 | |
|-----------|-------------------|-------------|------------------|---------|
| Month | Current Year 1971 | Average | Maximum | Minimum |
| January | 0 | 526 | 3,201 | 0 |
| February | 0 | 347 | 4,097 | 0 |
| March | o | 554 | 6,850 | 0 |
| April | 0 | 427 | 3,707 | 0 |
| Мау | 0 | 97-3 | 1,163 | 0 |
| June | 0 | 50.5 | 625 | 0 |
| July | o | 286 | 4,296 | 0 |
| August | o | 275 | 1,926 | 0 |
| September | o | 332 | 1,548 | 0 |
| October | 0 | 99.7 | 791 | 0 |
| November | 0 | 23 8 | 1,891 | 0 |
| December | 0 | 293 | 3,047 | 0 |
| Yearly | 0 | 3,526 | 13,429 | 0 |

COLORADO RIVER AT MIGUEL C. RODRIGUEZ IN MEXICO - DISCHARGES

DESCRIPTION: Water-stage recorder and cableway located in Mexico on the left bank of the Colorado River about 24.5 miles downstream from the southerly international boundary, 44.5 miles downstream from Morelos Dam and 4.5 miles upstream from the Sonora-Baja California railroad bridge. Zero of gage is at mean sea level, U. S. C. & G. S. datum.

RECORDS: Based on current meter measurements made during the year and a continuous record of gage heights. Data obtained and furnished by the Mexican Section of the Commission. From June 1951 to July 1954, discharges were computed from gage height records based on daily gage readings at 8:00 a.m., Pacific Standard Time. A continuous record of gage heights obtained since July 21, 1954. Records available: June 1951 through 1971.

REMARKS: Diversions and return flows modify the flow of the river at this station. On many occasions the flow at this station consists solely of seepage from canals which run parallel and adjacent to the river at a higher elevation.

EXTREMES: Since January 1, 1952: Maximum mean daily gage height, 53.28 feet on January 4, 1958 with a discharge of 18,500 second-feet; minimum mean daily gage height, 37.73 feet on July 18, 1970 with a discharge of 2.8 second-feet; maximum mean daily discharge, 20,200 second-feet on December 19,1952 with a gage height of 52.30 feet; minimum mean daily discharge, no flow on various occasions.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|--|--------------------------------------|--|---------------------------------|--|---------------------------------|---------------------------------|---------------------------------|---------------------------------|--|--------------------------------------|--|
| 1 2 3 4 5 | 52.3 55.1 55.1 53.3 55.1 | 137 135 137 137 138 | 7.1 7.1 7.1 7.1 7.1 | 7.8 7.8 8.1 8.1 8.5 | 7.4 7.4 7.4 7.4 7.4 | 6.7 6.7 6.7 6.7 6.7 | 5.7 5.7 6.0 6.0 6.4 | 6.4 6.4 6.0 6.0 5.7 | 4.9 4.6 4.6 4.6 | 4.9 4.2 14.8 86.5 113 | 79.1 79.1 81.9 85.5 86.9 | 114 112 111 114 114 |
| 6 7 8 9 | 52.3 48.7 48.7 50.1 53.3 | 117 91.8 77.7 74.9 73.5 | 7.1 7.1 7.1 7.1 7.4 | 8.5 8.5 8.5 8.5 | 7.4 7.4 7.4 7.4 7.4 | 6.7 6.7 6.4 6.4 | 6.4 6.4 6.4 6.4 | 5.7 5.3 5.3 4.9 4.9 | 4.66222 | 68.2 50.9 46.3 45.2 44.5 | 88.6 90.4 88.6 88.6 90.4 | 119 123 128 121 119 |
| 11 12 13 14 15 | 56.2 66.4 78.0 93.9 106 | 69.2 65.0 60.7 57.9 48.4 | 7.4 7.4 7.4 7.8 7.8 | 8.8 8.8 8.8 8.8 | 7.4 7.1 7.1 7.1 7.1 | 6.4 6.0 6.0 6.0 | 6.4 6.0 6.0 6.0 | 4.9 4.9 5.3 5.3 | 4.2 3.9 3.9 3.9 4.2 | 42.4 43.4 47.0 48.0 47.0 | 90.4 88.6 86.9 92.5 94.6 | 112 98.2 85.5 72.0 56.2 |
| 16 17 18 19 20 | 115 123 126 129 131 | 60.7 57.9 42.0 33.2 25.8 | 7.8 7.4 7.4 7.1 7.1 | 8.5 8.5 8.1 7.8 7.8 | 6.7 6.7 6.7 6.7 | 6.0 6.0 6.0 6.0 | 6.0 6.0 6.0 6.0 | 5.3 5.3 5.3 5.3 5.7 | 4.6 4.6 4.6 4.9 | 45.2 45.2 47.0 48.7 52.6 | 107 113 110 104 107 | 42.7 34.6 29.0 22.2 18.4 |
| 21 22 23 24 25 | 131 133 121 131 133 | 20.1 16.2 11.3 8.5 7.4 | 6.7 6.7 6.7 6.7 6.7 | 7.8 7.8 7.8 7.8 7.8 | 7.1 7.1 7.1 7.1 7.1 | 6.0 6.0 5.7 5.7 5.3 | 6.0 6.0 6.0 6.0 | 5.7 5.7 5.7 5.7 5.3 | 4.6 4.6 4.2 4.2 3.9 | 54.7 54.7 55.8 59.3 60.4 | 107 113 116 116 113 | 17.7 16.2 14.5 14.5 13.8 |
| 26 27 28 29 30 31 | 139 139 138 136 133 135 | 7.4 7.4 7.4 | 7.1 7.1 7.1 7.1 7.4 7.4 | 7.4 7.4 7.4 7.4 7.4 | 7.1 7.1 6.7 6.7 6.7 6.7 | 5.3 4.9 4.9 5.3 5.3 | 6.0 6.0 6.0 6.4 6.4 | 5.3 5.3 5.3 4.9 4.9 | 3.9 3.5 3.9 4.6 4.9 | 62.2 63.2 64.3 63.2 63.2 66.7 | 113 116 116 126 126 | 12.7 11.3 11.3 11.3 13.8 15.5 |
| Sum | 3,017.6 | 1,724.8 | 222.1 | 243.3 | 219.7 | 181.5 | 188.6 | 167.7 | 131.4 | 1,612.8 | 3,015.2 | 1,898.5 |

Period 1951-1971 Current Year 1971 Extreme Gage Extreme Second Feet Average Total Acre Feet Month Feet Second High Low High Day Feet Acre Feet Average Maximum Minimum Low Day 5,985 3,421 440 41.34 39.07 26 97.5 61.4 241,078 1,047,732 Jan. 151,772 106,748 70,074 696,461 807,342 588,983 7.4 41.34 38.09 5 14 140 25 21 317 Feb. Mar. 7.8 38.12 38.06 7.1 0 38.32 8.8 126 8.1 7.4 482 0 Apr. 38.06 **†**11 38.12 7.4 116 6.7 435 97,586 732,815 0 May 38.09 June 38.12 38.06 6.7 127 4.9 6.0 360 42,427 555,460 264,561 0 374 † 5 † 1 22,819 July 38.32 38.12 6.4 † 1 † 9 5.7 6.0 ۵ 39.50 38.55 38.32 38.48 5.3 4.2 332 33,833 309,320 0 6.4 Aug. 4.9 127 3.5 260 52,875 572,551 0 Sept. 1 41.90 2 4.2 51.9 3,199 87,152 769,939 2,459 Oct. 38.52 5 113 41.60 40.94 29 13Ž 1 79.1 101 5,981 145,052 909,399 5,981 687 Nov. 27 3,766 1.060,767 41.80 38.52 8 133 11.3 61.1 195,701 1,211,241 7,923,600 25,036 Yearly 41.90 38.06 3.5 34.6 25,036

f And other days

COLORADO RIVER AT MIGUEL C. RODRIGUEZ IN MEXICO - STAGES

(See Preceding Page For Description)

Mean Daily Gage Height in Feet 1971

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|--|---|--|---|--|---|--|--|---|--|---|--|
| 1 | 39.21 | 41.27 | 38.09 | 38.06 | 38.09 | 38.09 | 38.12 | 38.32 | 38.55 | 38.55 | 40.94 | 41.54 |
| 2 | 39.30 | 41.24 | 38.09 | 38.06 | 38.09 | 38.09 | 38.12 | 38.32 | 38.55 | 38.52 | 40.94 | 41.50 |
| 3 | 39.30 | 41.27 | 38.09 | 38.06 | 38.09 | 38.09 | 38.16 | 38.32 | 38.55 | 39.01 | 41.01 | 41.47 |
| 4 | 39.24 | 41.27 | 38.09 | 38.06 | 38.09 | 38.09 | 38.19 | 38.35 | 38.55 | 41.40 | 41.08 | 41.54 |
| 5 | 39.30 | 41.31 | 38.09 | 38.06 | 38.09 | 38.09 | 38.19 | 38.35 | 38.55 | 41.90 | 41.11 | 41.54 |
| 6 | 39.21 | 40.85 | 38.09 | 38.09 | 38.09 | 38.09 | 38.22 | 38.39 | 38.48 | 40.94 | 41.14 | 41.60 |
| 7 | 39.11 | 40.29 | 38.09 | 38.09 | 38.09 | 38.09 | 38.22 | 38.39 | 38.48 | 40.42 | 41.17 | 41.67 |
| 8 | 39.11 | 39.96 | 38.09 | 38.22 | 38.09 | 38.09 | 38.22 | 38.39 | 38.48 | 40.26 | 41.14 | 41.73 |
| 9 | 39.14 | 39.90 | 38.09 | 38.12 | 38.09 | 38.09 | 38.25 | 38.42 | 38.48 | 40.22 | 41.14 | 41.63 |
| 10 | 39.24 | 39.86 | 38.09 | 38.09 | 38.09 | 38.09 | 38.25 | 38.42 | 38.48 | 40.19 | 41.17 | 41.60 |
| 11 | 39.34 | 39.76 | 38.09 | 38.06 | 38.09 | 38.09 | 38.25 | 38.45 | 38.48 | 40.12 | 41.17 | 41.50 |
| 12 | 39.63 | 39.67 | 38.09 | 38.06 | 38.09 | 38.09 | 38.25 | 38.48 | 38.48 | 40.16 | 41.14 | 41.24 |
| 13 | 39.96 | 39.57 | 38.09 | 38.06 | 38.09 | 38.06 | 38.29 | 38.48 | 38.48 | 40.29 | 41.11 | 40.98 |
| 14 | 40.35 | 39.50 | 38.09 | 38.09 | 38.09 | 38.06 | 38.29 | 38.48 | 38.48 | 40.32 | 41.21 | 40.62 |
| 15 | 40.62 | 39.27 | 38.06 | 38.09 | 38.12 | 38.06 | 38.29 | 38.48 | 38.48 | 40.29 | 41.24 | 40.16 |
| 16 | 40.81 | 39.57 | 38.06 | 38.09 | 38.12 | 38.06 | 38.29 | 38.48 | 38.48 | 40.22 | 41.40 | 39.73 |
| 17 | 40.98 | 39.50 | 38.06 | 38.09 | 38.12 | 38.06 | 38.29 | 38.48 | 38.48 | 40.22 | 41.47 | 39.44 |
| 18 | 41.04 | 39.11 | 38.06 | 38.09 | 38.12 | 38.06 | 38.29 | 38.48 | 38.48 | 40.29 | 41.44 | 39.24 |
| 19 | 41.11 | 38.88 | 38.06 | 38.09 | 38.12 | 38.06 | 38.29 | 38.52 | 38.48 | 40.35 | 41.37 | 38.98 |
| 20 | 41.14 | 38.68 | 38.06 | 38.09 | 38.12 | 38.09 | 38.29 | 38.55 | 38.48 | 40.49 | 41.40 | 38.81 |
| 21 22 23 24 25 | 41.14 41.17 40.94 41.14 41.17 | 38.52 38.39 38.22 38.12 38.09 | 38.06 38.06 38.06 38.06 38.06 | 38.09 38.06 38.06 38.06 38.06 | 38.12 38.12 38.12 38.12 38.12 | 38.09 38.09 38.09 38.09 38.09 | 38.29 38.29 38.29 38.29 38.29 | 38.91 39.21 38.91 38.88 38.88 | 38.48 38.48 38.48 38.48 38.48 | 40.55 40.55 40.58 40.68 40.72 | 41.40 41.47 41.50 41.50 41.47 | 38.78 38.71 38.65 38.65 38.65 38.62 |
| 26 27 28 29 80 31 | 41.31 41.31 41.27 41.24 41.17 41.21 | 38.09 38.09 38.09 | 38.06 38.06 38.06 38.06 38.06 38.06 | 38.06 38.06 38.06 38.06 38.06 | 38.09 38.09 38.09 38.09 38.09 38.09 | 38.12 38.12 38.09 38.09 38.12 | 38.29 38.29 38.29 38.29 38.29 38.32 | 38.71 38.65 38.62 38.58 38.58 38.55 | 38.48 38.48 38.48 38.52 38.52 | 40.78 40.81 40.85 40.81 40.81 40.91 | 41.47 41.50 41.50 41.57 41.57 | 38.58 38.52 38.52 38.52 38.62 38.62 |
| Avg | 40.32 | 39.50 | 38.06 | 38.09 | 38.09 | 38.09 | 38.25 | 38.55 | 38.48 | 40.39 | 41.31 | 40.06 |

WASTEWAY TO COLORADO RIVER AT UNION IN MEXICO

DESCRIFFION: Wasteway structure located at Kilometer 21*736 of the Barrote Canal in the Colonia Hidalgo about 1,500 feet from right bank of the Colorado River. The wasteway discharges into the Colorado River at a point about 0.6 mile upstream from the Sonora-Baja California reliroad bridge and 30 miles downstream from the southerly international boundary.

RECORDS: Data obtained by the Ministry of Hydraulic Resources and furnished by the Mexican Section of the Commission are based on gate openings. Records available: January 1957 through 1971.

REMARKS: The wasteway structure has 3 manually operated rectangular gates which discharge from the Barrote Canal into a wasteway leading to the Colorado River.

| 44 -1 | C | | Period 1957-1971 | |
|-----------|-------------------|-------------|------------------|---------|
| Month | Current Year 1971 | Average | Maximum | Minimum |
| January | 0 | 795 | 3,166 | 0 |
| February | 0 | 432 | 2,788 | 0 |
| March | 0 | 1,075 | 7,074 | 0 |
| April | 0 | 783 | 4,462 | 0 |
| May | 0 | 967 | 4,413 | 0 |
| June | 0 | 201 | 1,505 | 0 |
| July | 0 | 438 | 4,296 | 0 |
| August | 0 | 233 | 1,857 | 0 |
| September | 0 | 32 9 | 1,800 | 0 |
| October | 0 | 717 | 6,997 | 0 |
| November | o | 230 | 3,413 | 0 |
| December | 0 | 2 68 | 1,205 | 0 |
| Yearly | 0 | 6,469 | 24,526 | 0 |

COLORADO RIVER AT EL MARITIMO IN MEXICO - STAGES

Water-stage recorder and cableway in Mexico, 47.6 miles downstream from the southerly international boundary, 18.6 miles downstream from the Sonore-Baja California realroad bridge and 3.7 miles east of Kilometer 70 of the Mexicali-San Felipe highway. The recorder is located on the right bank of the Colo-

Kilometer 70 of the Mexiceli-San Felipe highway. The recorder is located on the right bank of the Colorado River. Zero of gage is 9.84 feet above mean sea level, U.S. C. & G.S. datum.

ECORDS: Records obtained and computed by the Mexican Section of the Commission. Records available:

Mean daily discharges from January 1960 through 1968. Incomplete record of gage heights, March 1, 1946
through November 1947; twice daily readings of gage heights, January 1, 1948 through December 1949; continuous record of gage heights since installation of water-stage recorder February 8, 1956. Mean daily gage heights, January 1960 through 1971.

EMARKS: In former years the flow past this station was affected by the tides in the Gulf of California.

After July 1968, measurement by current meter was suspended; beginning in 1969, twice daily readings of gage heights and no record of mean daily discharges.

heights and no record of mean daily discharges.

EXTREMES: January 1960 through 1968: Maximum daily discharge, 4,410 second-feet, January 21 and December 7 and 8, 1960; minimum discharge, no flow on various occasions. Maximum monthly discharge, 225,224 acrefeet, January 1960; minimum monthly discharge, zero during various months of several years. Annual maximum discharge, 503,260 acre-feet during 1960; minimum 59,335 acre-feet in 1968. January 1960 through 1971: Maximum instantaneous gage height, 18.73 feet on January 21, 1960; minimum gage height, 12.47 feet on August 31 and September 1, 1960.

Mean Daily Gage Height in Feet 1971

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|---|---|--|---|--|---|---|--|---|--|---|--|
| 1 2 8 4 5 | 14.76 14.76 14.73 14.70 14.70 | 14.90 14.93 14.93 14.93 14.93 | 14.80 14.76 14.76 14.76 14.76 | 14.73 14.73 14.73 14.70 14.70 | 14.90 14.90 14.86 14.86 14.86 | 14.63 14.63 14.60 14.57 14.57 | 14.30 14.30 14.30 14.27 14.27 | 14.17 14.17 14.17 14.17 14.17 | 14.34 14.34 14.34 14.34 14.30 | 14.24 14.24 14.24 14.21 14.21 | 14.44 14.44 14.44 14.47 14.50 | 14.80 14.80 14.83 14.80 14.80 |
| 6 7 8 9 | 14.70 14.73 14.76 14.76 14.76 | 14.93 14.93 14.93 14.93 14.93 | 14.73 14.73 14.76 14.76 14.80 | 14.73 14.73 14.73 14.73 14.73 | 14.83 14.83 14.83 14.83 14.83 | 14.57 14.57 14.53 14.53 14.53 | 14.34 14.34 14.34 14.30 14.30 | 14.24 14.21 14.17 14.21 14.21 | 14.30 14.30 14.30 14.30 14.30 | 14.21 14.21 14.24 14.24 14.24 | 14.53 14.53 14.57 14.57 14.57 | 14.83 14.80 14.76 14.83 14.83 |
| 11 12 18 14 15 | 14.73 14.73 14.73 14.76 14.76 | 14.93 14.93 14.93 14.93 14.93 | 14.76 14.80 14.76 14.76 14.76 | 14.73 14.73 14.76 14.76 14.76 | 14.83 14.80 14.80 14.90 14.86 | 14.53 14.83 14.83 14.83 14.83 | 14.30 14.30 14.30 14.30 14.27 | 14.24 14.27 14.27 14.30 14.27 | 14.30 14.27 14.27 14.27 14.27 | 14.24 14.27 14.27 14.27 14.27 | 14.60 14.60 14.63 14.63 14.67 | 14.83 14.83 14.83 14.86 14.86 |
| 16 17 18 19 20 | 14.76 14.80 14.80 14.80 14.83 | 14.93 14.93 14.93 14.90 14.86 | 14.76 14.76 14.73 14.73 | 14.80 14.76 14.76 14.80 14.80 | 14.86 14.70 14.70 14.70 14.70 | 14.83 14.80 14.80 14.80 14.80 | 14.27 14.27 14.27 14.24 14.24 | 14.27 14.30 14.30 14.30 14.30 | 14.27 14.27 14.21 14.21 14.21 | 14.21 14.24 14.24 14.27 14.27 | 14.63 14.63 14.67 14.67 14.67 | 14.86 14.83 14.83 14.83 14.83 |
| 21 22 28 24 25 | 14.83 14.86 14.86 14.86 14.86 | 14.86 14.86 14.86 14.83 14.86 | 14.76 14.76 14.76 14.76 14.76 | 14.76 14.80 14.83 14.80 14.80 | 14.70 14.70 14.70 14.70 14.70 | 14.47 14.44 14.44 14.44 14.44 | 14.21 14.21 14.21 14.17 14.17 | 14.34 14.34 14.34 14.34 14.34 | 14.21 14.21 14.17 14.17 14.17 | 14.30 14.30 14.34 14.34 14.34 | 14.70 14.70 14.70 14.73 14.76 | 14.83 14.83 14.83 14.83 14.83 |
| 26 27 28 29 80 81 | 14.86 14.86 14.90 14.90 14.90 | 14.80 14.80 14.80 | 14.76 14.76 14.76 14.73 14.76 14.76 | 14.83 14.83 14.86 14.86 14.86 | 14.67 14.67 14.63 14.63 14.63 14.63 | 14.40 14.40 14.40 14.37 14.30 | 14.14 14.14 14.11 14.11 14.11 | 14.34 14.34 14.34 14.34 14.30 14.30 | 14.17 14.17 14.17 14.17 14.24 | 14.37 14.37 14.40 14.40 14.40 14.44 | 14.76 14.76 14.80 14.80 14.80 | 14.83 14.83 14.83 14.80 14.80 14.76 |
| \vg. | 14.80 | 14.90 | 14.76 | 14.76 | 14.76 | 14.57 | 14.24 | 14.27 | 14,24 | 14.27 | 14.63 | 14.83 |

STORED WATER IN LARGE RESERVOIRS OF THE COLORADO RIVER

Data are presented below for all large storage reservoirs in the Colorado River basin below Lee's Ferry, all of which are located in the United States. The monthly figures represent usable contents on the last day of the month, in thousands of acre-feet. The capacities indicated are usable capacities at the top of the spillway gates in closed postition, for those dams having controlled spillways; for all others, capacities indicated are at spillway level. Records furnished by the U.S. Geological Survey.

In Thousands of Acre-Feet

| Month | | E MEAD y 26,159.0) | | MOHAVE y 1,810.0) | | SU LAKE ty 619.4) | TOTAL IN UNITED STATES RESERVOIRS (Capacity 28,588.4) | | |
|---|--|--|--|--|--|--|--|--|--|
| | 1971 | Average 1935-1971 | 1971 | Average 1951-1971 | 1971 | Average 1939-1971 | 1971 | Estimated Average | |
| Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec. | 16,801.0 16,523.0 16,289.0 16,326.0 16,374.0 16,462.0 16,615.0 16,799.0 16,886.0 16,976.0 17,258.0 17,645.0 | 16,464.8 16,155.2 15,860.9 16,029.2 17,132.2 18,652.7 18,965.6 18,598.5 18,248.4 17,934.6 17,654.1 17,327.7 | 1,624.0 1,700.0 1,766.0 1,765.0 1,785.0 1,497.0 1,487.0 1,441.0 1,441.0 1,447.0 | 1,652.7 1,675.2 1,674.9 1,693.8 1,743.6 1,624.8 1,488.9 1,411.7 1,400.4 1,418.7 1,500.4 1,604.7 | 546.7 547.0 564.0 597.4 612.0 609.6 597.8 579.2 574.3 563.3 553.5 541.8 | 556.0 559.7 574.2 603.8 602.2 605.5 593.6 576.2 571.1 574.9 563.4 558.2 | 18,971.7 18,770.0 18,519.0 18,629.4 18,771.0 18,761.6 18,687.8 18,865.2 18,901.3 18,980.3 19,258.5 19,724.8 | 18,673.5 18,390.1 18,110.0 18,326.8 19,478.0 20,883.0 20,948.1 20,586.4 20,219.9 19,928.2 19,717.9 19,490.6 | |
| Avg. | 16,746.2 | 17,410.3 | 1,583.3 | 1,574.2 | 57 3 .9 | 578.2 | 18,903.4 | 19,562.7 | |
| Max. | 17,645.0 | 27,780.0 | 1,785.0 | 1,808.0 | 612.0 | 688.7 | 19,724.8 | 28,235.0 | |
| Min. | 16,289.0 | * 10,727.0 | 1,441.0 | 1,186.0 | 541.8 | 76.9 | 18,519.0 | 13,062.6 | |

^{*} Minimum since 1940

SUSPENDED SILT

The following tables are based on determinations of gravimetric percentages of dry silt in water samples taken at each station by one of the following methods:

- A. By lowering a D- 1 3 depth integrating sampler at verticals located at centers of sections of equal discharge in the river cross section, being careful to approach but not strike the bottom. The samples obtained in the section are combined to comprise a composite sample for that date.
- B. By lowering a D-43 depth integrating sampler at verticals located at centers of each span of the service bridge across the Alamo Canal, being careful to approach but not strike the bottom. The samples obtained in the section are combined to comprise a composite sample for that date.
- C. By sampling at the stream surface with a separate bottle at each of three points, spaced 1/6, 1/2, and 5/6 of the stream width. The gravimetric percentage in each sample is determined, a coefficient of 1.10 is applied to the average of the three, and the product applied to the volume of the stream flow represented by that set of samples.

For ease of comparison, the assumption is made that 1.847 tons of deposited silt would occupy a volume of one acre-foot, or one cubic foot of deposited silt would weigh 85 pounds.

| | | | | Period of Record | | | | | | |
|-------|------------|-----|-----------------------------|------------------|-------------------|-------------------|-------------------------------|---------|---------|---------|
| | T | ons | No. Gravimetric Percentages | | | | Acre-Feet at 1,847 Tons Per A | | | re Foot |
| Month | Water Silt | | of Sam- ples | Average | Maximum Sample | Minimum Sample | | Average | Maximum | Minimum |

Colorado River at Northerly International Boundary

Period 1956-1971

| Jan. | 95,578,000 | 5,600 | 14 | 0.0058 | 0.0129 | 0.0035 | 3.0 | 35.9 | 336 | 1.6 |
|--------|---------------|------------------|----|--------|--------|--------|------|------|-------|------|
| Feb. | 121,461,000 | | 4 | .0058 | .0090 | .0048 | 3.8 | 16.3 | 116 | 1.6 |
| Mar. | 259,014,000 | 28,600 | 5 | .0110 | .0123 | .0096 | 15.5 | 52.4 | 499 | 8.8 |
| Apr. | 238,042,000 | 17,500 | 14 | .0073 | .0100 | .0032 | 9.5 | 47.9 | 434 | 9.4 |
| May | 98,199,000 | | 4 | .0043 | .0071 | .0030 | 2.3 | 17.7 | 201 | 2.3 |
| June | 166,585,000 | 13,300 | 5 | .0080 | .0141 | .0057 | 7.2 | 17.4 | 92.6 | 4.9 |
| July | 239,418,000 | 16,100 | 4 | .0067 | .0081 | .0057 | 8.7 | 24.1 | 89.3 | 7.4 |
| Aug. | 222,139,000 | 29,200 | 5 | .0131 | .0362 | .0062 | 15.8 | 23.1 | 103 | 6.2 |
| Sept. | 84,996,000 | 7,100 | 6 | .0083 | .0355 | .0026 | 3.8 | 10.1 | 43.6 | 2.3 |
| Oct. | 62,288,000 | 3,200 | 5 | .0051 | .0107 | .0021 | 1.7 | 4.7 | 20.0 | .8 |
| Nov. | 56,267,000 | 1,000 | 4 | .0018 | .0020 | .0017 | .5 | 13.0 | 89.9 | .5 |
| Dec. | 144,719,000 | 6,000 | 5 | .0041 | .0052 | .0016 | 3.2 | 25.0 | 174 | .6 |
| Yearly | 1,788,706,000 | 1 3 8,900 | 55 | 0.0078 | 0.0862 | 0.0016 | 75.0 | 288 | 2,198 | 64.6 |

Samples by U. S. Section, and analyses by United States Bureau of Reclamation, Method A

Intake Canal at Morelos Diversion Structure

Period 1952-1971

| Jan. | 95,297,000 | 3,093 | 4 | 0.0032 | 0.0053 | 0.0023 | 1.7 | 5.7 | 22.3 | 0.2 | 1 |
|--------|---------------|----------------|----|--------|--------|----------------|------|------|------|------|---|
| Feb. | 120,983,000 | 10,185 | 4 | .0034 | .0222 | . 002 6 | 5.5 | 6.0 | 19.4 | .9 | П |
| Mar. | 258,461,000 | 43,709 | 4 | .0169 | .0337 | .0119 | 23.6 | 48.2 | 154 | 11.1 | ı |
| Apr. | 237,537,000 | 33,957 | 5 | .0143 | .0196 | .0071 | 18.3 | 43.5 | 121 | 13.2 | 1 |
| May | 97,773,000 | 6;9 5 8 | 4 | .0071 | .0089 | .0058 | 3.7 | 11.8 | 51.2 | 1.5 | Ĺ |
| lune | 166,003,000 | 10,475 | 4 | .0063 | .0071 | .0055 | 5.7 | 33.8 | 109 | 4.7 | ١ |
| July | 238,976,000 | 15,561 | 5 | .0065 | .0077 | .0052 | 8.4 | 49.0 | 156 | 8.3 | ı |
| Aug. | 218,213,000 | 15,137 | 7 | .0070 | .0237 | .0041 | 8.2 | 45.1 | 135 | 7.5 | ١ |
| Sept. | 82,477,000 | 8,615 | 5 | .0104 | .0334 | .0059 | 4.6 | 18.6 | 64.7 | 1.9 | 1 |
| Oct. | 56,439,000 | 5,984 | 5 | .0106 | .0401 | .0063 | 3.2 | 4.4 | 12.0 | .3 | ١ |
| Nov. | 56,087,000 | 3,800 | 4 | .0068 | .0077 | .0060 | 2.0 | 2.3 | 9.3 | .2 | Т |
| Dec. | 144,412,000 | 11,854 | 5 | .0088 | .0099 | .0069 | 6.4 | 4.9 | 14.8 | 1.1 | 1 |
| Yearly | 1,770,656,000 | 169,328 | 56 | 0.0088 | 0.0401 | 0.0023 | 91.4 | 273 | 696 | 68.4 | ĺ |

Samples and analyses by Mexican Section, Method B

SUSPENDED SILT

| | | | | Period of Record | | | | | | |
|-------|-------|------|-------------------------|------------------|-------------------|--------------------------------|--|---------|---------|---------|
| Month | T | No. | Gravimetric Percentages | | | Acre-Feet at 1,847 Tons Per Ac | | | re Foot | |
| Month | Water | Silt | ot Sam- ples | Average | Maximum Sample | Minimum Sample | | Average | Maximum | Minimum |

Colorado River at Southerly International Boundary

Period 1946-1971

| 17,993,000 | 600 | 14 | 0.0000 | 16 | | | | |
|------------|---|--|---|--|---|--|---|-----------|
| 0 000 000 | | T . | 0.0033 | 0.0046 | 0.0018 | 0.3 | ı | 1 |
| | 500 | 4 | .0050 | .0061 | .0030 | ٠ <u>3</u> | ŀ | |
| 1,084,000 | 40 | 4 | .0037 | .0048 | .0030 | 0 | | |
| 149,000 | 0 | 2 | | .0040 | .0030 | 0 | i | |
| 7,345,000 | 800 | 4 | .0109 | .0131 | .0048 | .4 | | 1 |
| 3,143,000 | 300 | 3 | .0095 | | .0065 | .2 | | |
| 1,074,000 | 60 | ì | .0056 | .0060 | .0050 | 0 | | l |
| 6,756,000 | 700 | 2 | .0103 | .0115 | .0088 | .4 | | 1 |
| 9,906,000 | 600 | 4 | .0060 | .0085 | .0053 | .3 | | |
| 24,478,000 | 1,500 | 2 | .0061 | .0066 | .0056 | .8 | 1 | |
| 20,252,000 | 1,500 | 0 | * .0074 | * .0079 | * .0067 | .8 | l . | l |
| 13,579,000 | 1,100 | .3 | .0081 | .0102 | .0077 | .6 | İ | |
| 15,748,000 | 7,700 | 33 | 0.0066 | 0.0131 | 0.0018 | 4.1 | | |
| | 1,084,000 149,000 7,345,000 3,143,000 1,074,000 6,756,000 9,906,000 24,478,000 20,252,000 13,579,000 | 1,084,000 40 149,000 0 7,345,000 800 3,143,000 300 1,074,000 60 6,756,000 700 9,906,000 600 24,478,000 1,500 20,252,000 1,500 13,579,000 1,100 | 1,084,000 40 4 149,000 0 2 7,345,000 800 4 3,143,000 300 3 1,074,000 60 1 6,756,000 700 2 9,906,000 600 4 24,478,000 1,500 2 20,252,000 1,500 0 13,579,000 1,100 3 | 1,08\(\daggregarrightar | 1,08\(^1\),000 40 4 0037 0048 14\(^1\),000 0 2 0034 7,3\(^1\),000 800 4 0109 1,07\(^1\),000 60 1 0095 1,07\(^1\),000 60 1 0095 6,75\(^1\),000 700 2 0103 9,96\(^1\),000 600 22\(^1\),100 0 0 0 006 22\(^1\),100 0 0 0 0074 1,500 2 0061 20\(^2\),25\(^1\),000 1,500 3 0081 0102 | 1,084,000 40 4 .0037 .0048 .0030 149,000 0 2 .0034 .0040 .0030 7,345,000 800 4 .0109 .0131 .0048 3,143,000 300 3 .0095 .0129 .0065 1,074,000 60 1 .0056 .0060 .0050 6,755,000 700 2 .0103 .0115 .0088 9,906,000 600 4 .0060 .0085 .0093 24,478,000 1,500 2 .0061 .0066 .0056 20,252,000 1,500 0 * .0074 * .0079 * .0067 13,579,000 1,100 3 .0081 .0102 .0077 | 1,084,000 40 4 .0037 .0048 .0030 0 149,000 0 2 .0034 .0040 .0030 0 7,345,000 800 4 .0109 .0131 .0048 .4 3,143,000 300 3 .0095 .0129 .0065 .2 1,074,000 60 1 .0056 .0060 .0050 .0050 .0050 6,756,000 700 2 .0103 .0115 .0088 .4 9,906,000 600 4 .0060 .0085 .0053 .3 24,478,000 1,500 2 .0061 .0066 .0056 .0056 20,252,000 1,500 0 *.0074 *.0079 *.0067 .8 13,579,000 1,100 3 .0031 .0102 .0077 .6 | 1,084,000 |

Samples and analyses by U. S. and Mexican Sections, Method A * Estimated

Colorado River at Miguel C. Rodriguez Gaging Station

| | | | | | | | | | Period 19 | 60-1971 |
|--------|------------|--------------|----|--------|--------|--------|-----|------|-----------|---------|
| Jan. | 8,138,000 | 568 | 4 | 0.0070 | 0.0134 | 0.0016 | 0.3 | 23.5 | 251 | 0 |
| Feb. | 4,652,000 | 390 | 4 | .0084 | .0141 | .0050 | .2 | 3.5 | 13.9 | 0 |
| Mar. | 599,000 | 55.1 | 5 | .0092 | .0111 | .0051 | 0 | .6 | 4.1 | 0 |
| Apr. | 656,000 | 52.9 | 4 | .0080 | .0168 | .0039 | 0 | .2 | 1.0 | 0 |
| May | 592,000 | 35.3 | 5 | .0060 | .0129 | .0020 | 0 | .2 | 1.5 | 0 |
| June | 489,000 | 3 8.6 | 4 | .0080 | .0126 | .0069 | 0 | .4 | l .i | 0 |
| July | 508,000 | 29.8 | 3 | .0058 | .0073 | .0039 | 0 | 0 | .2 | 0 |
| Aug. | 452,000 | 36.4 | 5 | .0080 | .0113 | .0049 | 0 | 0 | .2 | 0 |
| Sept. | 354,000 | 29.8 | 5 | .0083 | .0152 | .0062 | 0 | .1 | 4.5 | 0 |
| Oct. | 4,350,000 | 651 | 12 | .0150 | .0281 | .0079 | .3 | .4 | 20.7 | .1 |
| Nov. | 8,132,000 | 563 | 5 | .0094 | .0109 | .0073 | .4 | 2.5 | 35.8 | .2 |
| Dec. | 5,120,000 | 599 | 4 | .0117 | .0138 | .0069 | •3 | 4.1 | 12.9 | 0 |
| Yearly | 34,042,000 | 3,049 | 60 | 0.0087 | 0.0281 | 0.0016 | 1.6 | 39.2 | 289 | 1.6 |

Samples and analyses by Mexican Section, Method C

CHEMICAL ANALYSES OF WATER SAMPLES 1971

The tables below are based on chemical analyses of weekly samples from the Colorado River at the Northerly International Boundary taker by the United States Section of this Commission and analyzed by the U.S. Geological Survey. Samples from the Intake Canal at Morelos Diversion Structure were taken by the Mexican Section of the Commission and analyzed by the Ministry of Hydraulic Resources.

To convert milligram equivalents to parts per million by weight, multiply each ion by its appropriate conversion factor. These factors are: Ca, 20.04; Mg, 12.16; Na, 22.99; (CO3 plus HCO3) expressed as CO3, 30.00; SO4, 48.03; Cl, 35.45; NO3, 62.00. To convert tons per acre-foot to parts per million, multiply tons per acre-foot by 735.5. Electrical conductivity, reported in the tables as ECx10⁶ at 25°C, is a relative measure of the total salt concentration.

| | | No. | Disso | lved Solids | | | | | | Mea | n Mil | ligram | Equiva | lents p | er Lite | r |
|---|------|--------------------|------------------------------|---------------|-----------------|-------------------|----|---------|---------|-----|-------|--------|-------------|---------|---------|-----|
| М | onth | of Sam- ples | Tons Per Acre- Foot | Total Tons | ECx106 @25°C | Boron p. p. m. | ρН | % Na | % CI | Ca | Mg | Na | со, нсо, | so, | CI | но, |

Colorado River at Northerly International Boundary

| | | | | | _ | | | | | | | | | | _ |
|---------------------------|------|--------|---------------------|-------|---|-----|----|------------|---------|--------|---------|---------|---------|---------|---|
| Jan. | 4 | 1.59 | 112,000 | 1,960 | l | 8.1 | 52 | 36 | 5.92 | 3.47 | 10.30 | 3.53 | 9.05 | 7.11 | |
| Feb. | 4 | 1.59 | 142,000 | 1,930 | l | 9.1 | 52 | 36 | 5.87 | 3.43 | 9.92 | 3.47 | 8.85 | 6.90 | |
| Mar. | 5 | 1.59 | 303,000 | 1,950 | l | 8.2 | 52 | 37 | 5.88 | 3.46 | 9.98 | 3.39 | 8.84 | 7.08 | |
| Apr. | 4 | 1.54 | 269,000 | 1,880 | l | 8.2 | 50 | 35 | 5.81 | 3.49 | 9.38 | 3.32 | 8.75 | 6.62 | |
| May | 4 | 1.63 | 118,000 | 1,980 | l | 8.1 | 52 | 35 | 6.05 | 3.57 | 10.36 | 3.57 | 9.35 | 7.06 | |
| June | 5 | 1.61 | 197,000 | 1,900 | ļ | 8.2 | 51 | 35 | 5.81 | 3.44 | 9.74 | 3.41 | 8.91 | 6.67 | |
| July | 4 | 1.58 | 279,000 | 1,910 | | 8.2 | 52 | 37 | 5.76 | 3.44 | 9.98 | 3.29 | 8.86 | 7.03 | |
| Aug. | 5 | 1.54 | 252,000 | 1,900 | | 8.1 | 52 | 37 | 5.72 | 3.34 | 9.98 | 3.28 | 8.80 | 6.96 | 1 |
| Sept. | 4 | 1.58 | 98,800 | 1,960 | 1 | 8.1 | 53 | 36 | 5.84 | 3.49 | 10.34 | 3.50 | 9.04 | 7.12 | |
| Oct. | 4 | 1.50 | 68,800 | 1,840 | | 8.0 | 50 | 35 | 5.80 | 3.55 | 9.42 | 3.62 | 8.61 | 6.54 | |
| Nov. | 5 | 1.56 | 64,700 | 1,850 | i | 8.0 | 49 | 35 | 5.92 | 3.57 | 9.27 | 3.76 | 8.41 | 6.59 | |
| Dec. | 4 | 1.65 | 176,000 | 2,030 | | 8.1 | 52 | 39 | 5.90 | 3.91 | 10.79 | 3.65 | 8.93 | 8.03 | |
| Mean • | ø52 | 1.58 | ø2,080, 30 0 | 1,930 | | 8.1 | 51 | 3 6 | 5.84 | 3.49 | 9.95 | 3.42 | 8.87 | 6.99 | |
| Period | Avg. | 1.73 | 2,576,000 | 2,110 | | 7.9 | | | 6.22 | 3.88 | 11.02 | 3.31 | 8.64 | 9.17 | |
| Tons of Constituents 1971 | | | | | | | | | 209,000 | 75,900 | 410,000 | 184,000 | 762,000 | 444,000 | |
| Avg. To | ns | Period | 1 1962-1971 | | | | | | 251,000 | 95,100 | 513,000 | 198,000 | 831,000 | 665,000 | |

Intake Canal at Morelos Diversion Structure

| Jan. | 31 | 1.70 | 119,200 | 1,868 | 1,251 | 7.9 | 49 | | 5.48 | 3.81 | 9.00 | 3.57 | 7.60 | 7.12 | - 1 |
|---------------------------|----------------------------|------|------------|-------|-------|-----|----|---|---------|---------|---------|-----------------|---------|---------|-----|
| Feb. | 28 | 1.71 | 152,800 | 1,938 | 1,263 | 7.8 | 50 | | 5.68 | 3.96 | 9.52 | 3.61 | 7.78 | 7.74 | ŀ |
| Mar. | 31 | 1.66 | 316,700 | 1,897 | 1,225 | 7.8 | 49 | | 5.57 | 3.94 | 9.32 | 3.45 | 7.82 | 7.56 | 1 |
| Apr. | 30 | 1.69 | 294,100 | 1,936 | 1,238 | 8.0 | 50 | | 5.53 | 3.99 | 9.60 | 3.51 | 7.79 | 7.81 | - 1 |
| May | 31 | 1.70 | 122,000 | 1,944 | 1,248 | 8.0 | 50 | | 5.57 | 4.10 | 9.48 | 3.67 | 7.87 | 7.59 | - 1 |
| June | 30 | 1.77 | 215,100 | 2,017 | 1,296 | 8.0 | 51 | | 5.57 | 4.10 | 10.24 | 3.65 | 7.98 | 8.27 | |
| July | 31 | 1.79 | 316,400 | 2,065 | 1,324 | 8.0 | 52 | 1 | 5.54 | 4.26 | 10.69 | 3.59 | 3.08 | 8.82 | - 1 |
| Aug. | 31 | 1.79 | 286,200 | 2,036 | 1,324 | 8.0 | 52 | | 5.54 | 4.11 | 10.50 | 3.55 | 8.01 | 8.59 | . 1 |
| Sept. | 30 | 1.77 | 106,800 | 1,958 | 1,295 | 7.9 | 51 | ļ | 5.51 | 3.97 | 9.96 | 3.71 | 8.17 | 7.69 | |
| Oct. | 20 | 1.62 | 67,000 | 1,819 | 1,187 | 8.0 | 49 | 1 | 5.36 | 3.86 | 8.74 | 3.63 | 7.82 | 6.64 | |
| Nov. | 5 | 1.67 | 68,800 | 2,338 | 1,227 | 8.0 | 49 | | 5.64 | 3.80 | 9.15 | 3.76 | 8.06 | 6.80 | |
| Dec. | 4 | 1.94 | 206,100 | 2,231 | 1,427 | 8.0 | 54 | | 6.00 | 4.05 | 11.90 | 3.80 | 3.68 | 9.48 | |
| Mean & | ø302 | 1.74 | Ø2,271,100 | 2,004 | 1,275 | 7.9 | 50 | | 5.58 | 4.00 | 9.84 | 3.62 | 7.97 | 7.84 | |
| Period | Avg. | 1.79 | 2,530,900 | 2,093 | 1,319 | 8.0 | 50 | | 5.82 | 4.41 | 10.44 | 3.39 | 8.08 | 8.20 | |
| Tons of Constituents 1971 | | | | | | | | • | 198,000 | 150,000 | 407,000 | 3 83,000 | 678,000 | 506,000 | |
| Avg. To | Avg. Tons Period 1962-1971 | | | | | | | | | 119,000 | 417,000 | 376,000 | 726,000 | 514,000 | |
| | | | | | | | | | | | | | 4 | • | |

^{**} Percent of total cations

^{***} Percent of total anions

Weighted mean

Ø Total

The following tables show electrical conductivity, expressed in mhos per centimeter x 10⁶ at 25°C, of individual water samples taken at Colorado River stations and in Mexican canals. Samples were taken at the Northerly and Southerly International Boundary stations by the United States Section of the Commission and conductivity determinations were made by the United States Geological Survey. Samples for the Intake Canal at Morelos Dam, Sanchez Mejorada Canal, and Miguel C. Rodriguez Gaging Station were taken by the Mexican Section of the Commission and determinations were made by the Ministry of Hydraulic Resources.

| 1 | D. ECx106 | _ ECx106 | D. ECx106 | Data ECx106 | D . ECx106 | D. ECx106 | Data ECx106 | D. ECx106 | ١ |
|---|------------|------------|------------|-------------|------------|------------|-------------|------------|---|
| ļ | Date @25°C | Date @25°C | Date @25°C | Date @25°C | Date @25°C | Date @25°C | Date @25°C | Date @25°C | ı |

Colorado River at Northerly International Boundary

| г | 7 | | D-1- | | ۸ | 1 | | | - | | | | 0.4 | ., . | | |
|---|------|------|----------|---------------|--------|-------------|------------|---------------|----------|-------------|------------|--------------|------------|-------|--------|-------|
| | | uary | | ruary 1980 | | ril 1810 | 16 | lay 1930 | | uly 1900 | | gust 2020 | | ober | | ember |
| İ | 1 | 1950 | 15 | | 1 | | | | 1 | | 16 | | 1 | 1310 | 16 | 1910 |
| | 2 | 1950 | 16 | 1940 | 2 | 1870 | 17 | 1980 | 2 | 1910 | 17 | 2030 | 2 | 1480 | 17 | 1860 |
| | 3 | 1980 | 17 | 1930 | 3 | 1860 | 18 | 1970 | 3 | 1830 | 18 | 1960 | 3 | 1670 | 18 | 1840 |
| | 4 | 2150 | 18 | 1990 | 4 | 1770 | 19 | 1960 | 4 | 1900 | 19 | 1790 | 4 | 1750 | 19 | 1870 |
| | 5 | 2070 | 19 | 2020 | 5 6 | 1810 | 20 | 2010 | 5 6 | 1900 | 20 | 1790 | 5 | 1830 | 20 | 1890 |
| | 6 | 2090 | 20 | 1810 | | 1850 | 21 | 2010 | 6 | 1900 | 21 | 1660 | 6 | 1860 | 21 | 1840 |
| Ì | 7 | 1970 | 21 | 1760 | 7 | 1810 | 22 | 1930 | 7 | 1930 | 22 | 1650 | 7 | 1870 | 22 | 1840 |
| 1 | 8 | 1990 | 22 | 1960 | 8 | 1830 | 23 | 1950 | 8 | 1910 | 23 | 1620 | 8 | 1870 | 23 | 1850 |
| | 9 | 1770 | 23 | 1950 | 9 | 1810 | 24 | 2010 | 9 | 1900 | 24 | 1620 | j ĝ | 1870 | 24 | 1850 |
| | 10 | 1900 | 24 | 2050 | 10 | 1820 | 25 | 1950 | 1ó | 1910 | 25 | 1560 | 10 | 1890 | 25 | 1860 |
| | 11 | 1970 | 25 | 2070 | 11 | 1860 | 26 | 1940 | 11 | 1840 | 26 | 1580 | 11 | 1880 | 26 | 1840 |
| | 12 | 1760 | 26 | 2100 | 12 | 1820 | 27 | 1920 | 12 | 1960 | 27 | 1590 | 12 | 1900 | 27 | 1850 |
| 1 | 13 | 1720 | 27 | 1830 | 13 | 1800 | 28 | 1940 | 13 | 1710 | 28 | 1550 | 13 | 1860 | 28 | 1860 |
| 1 | 14 | 1700 | 28 | 1870 | 14 | 1780 | 29 | 1940 | 14 | 1740 | 29 | 1490 | 14 | 1850 | 29 | 1850 |
| | 15 | 1730 | | rch | 15 | 1830 | 30 | 1900 | 15 | 1750 | <u>3</u> ó | 1910 | 15 | 1850 | 30 | 1870 |
| 1 | 16 | 1760 | 1 | 2050 | 16 | 1840 | 31 | 1910 | 16 | 1740 | 31 | 1920 | 16 | 1820 | | ember |
| | 17 | 1750 | 2 | 2030 | 17 | 1890 | | une | 17 | 1740 | | ember | 17 | 1860 | 1 | 1890 |
| | 13 | 1780 | 3 | 1980 | 18 | 1900 | 1 | 1960 | 18 | 1730 | 1 | 1980 | 18 | 1840 | 2 | 1890 |
| 1 | 19 | 1780 | 4 | 1970 | 19 | 1880 | 2 | 1950 | 19 | 1790 | 2 | 1980 | 19 | 1840 | 3 | 1870 |
| | 20 | 1790 | | 2000 | 20 | 1860 | 3 | 1970 | 20 | 1920 | 3 | 1990 | 20 | 1840 | 4 | 1880 |
| | 21 | 1770 | 5 | 1980 | 21 | 1920 | 4 | 1890 | 21 | 1950 | 4 | 1900 | 21 | 1790 | | 1890 |
| 1 | 22 | 1780 | 7 | 1940 | 22 | 1920 | 5 | 1860 | 22 | 2000 | 5 | 1900 | 22 | 1800 | 5 6 | 1940 |
| 1 | 23 | 1780 | 8 | 1960 | 23 | 1920 | 6 | 1960 | 23 | 2000 | 6 | 1930 | 23 | 1850 | | |
| | 24 | 1740 | | | 24 | | | 1970 | 24 24 | | 7 | | 24 | | 7 | 1930 |
| | | | .9 | 1990 | | 1950 | 7 | | | 1930 | | 2050 | | 1860 | 8 | 1930 |
| | 25 | 1750 | 10 | 1980 | 25 | 2010 | 8 | 1940 | 25 | 1940 | 8 | 1980 | 25 | 1870 | 9 | 1980 |
| 1 | 26 | 1780 | 11 | 1930 | 26 | 2020 | 9 | 1960 | 26 | 1970 | 9 | 1940 | 26 | 1910 | 10 | 1960 |
| ı | 27 | 1770 | 12 | 1970 | 27 | 1920 | 10 | 1930 | 27 | 2000 | 10 | 1950 | 27 | 1890 | 11 | 1870 |
| | 28 | 1720 | 13 | 1920 | 28 | 1820 | 11 | 1940 | 28 | 2000 | 11 | 1820 | 2 8 | 1850 | 12 | 1800 |
| | 29 | 1740 | 14 | 1950 | 29 | 1820 | 12 | 1880 | 29 | 2040 | 12 | 1840 | 29 | 1840 | 13 | 5050 |
| 1 | 30 | 1740 | 15 | 1900 | 30 | 1860 | 13 | 19 3 0 | 30 | 2010 | 13 | 1900 | 30 | 1820 | 14 | 1920 |
| | 31 | 1740 | 16 | 1880 | | kay . | 14 | 1970 | 31 | 1990 | 14 | 1880 | 31 | 1800 | 15 | 1950 |
| 1 | Febr | | 17 | 1960 | 1 | 1940 | 15 | 1970 | | gust | 15 | 1910 | | ember | 16 | 1960 |
| | 1 | 1750 | 18 | 1910 | 2 | 1880 | 16 | 2020 | 1 | 1960 | 16 | 1780 | 1 | 1830 | 17 | 2010 |
| | 2 | 1770 | 19 | 1860 | 3 | 1950 | 17 | 1990 | 2 | 1990 | 17 | 1820 | 2 | 1880 | 18 | 2090 |
| | 3 | 1750 | 20 | 1860 | 4 | 1950 | 18 | 1970 | 3 | 1990 | 18 | 1920 | 3 | 1910 | 19 | 2070 |
| | 4 | 2040 | 21 | 1900 | 5 | 2000 | 19 | 2000 | 4 | 1980 | 19 | 1910 | | 1890 | 20 | 2100 |
| | 5 | 2020 | 22 | 1920 | 6 | 1970 | 20 | 1940 | 5 | 1990 | 20 | 1940 | 5 | 1860 | 21 | 2000 |
| 1 | | 1890 | 23 | 1870 | 7 | 2000 | 21 | 1740 | | 1990 | 21 | 1920 | | 1860 | 22 | 2080 |
| 1 | 7 | 1830 | 24 | 1840 | 8 | 1950 | 22 | 2030 | 7 | 1910 | 22 | 1930 | 7 | 1880 | 23 | 1980 |
| | 8 | 2000 | 25 | 1840 | 9 | 1930 | 23 | 1950 | 8 | 1810 | 23 | 1940 | 8 | 1860 | 24 | 2000 |
| | 9 | 1960 | 26 | 1870 | 10 | 1980 | 24 | 1930 | 9 | 1980 | 24 | 1900 | 9 | 1880 | 25 | 2000 |
| 1 | 10 | 1820 | 27 | 1930 | 11 | 1910 | 25 | 1900 | 10 | 1990 | 25 | 1950 | 10 | 1870 | 26 | 2070 |
| | 11 | 1760 | 28 | 1880 | 12 | 1930 | 2 6 | 1840 | 11 | 1970 | 26 | 1940 | 11 | 1860 | 27 | 2060 |
| | 12 | 1770 | 29 | 1960 | 13 | 1920 | 27 | 1940 | 12 | 1960 | 27 | 1930 | 12 | 1870 | 28 | 2020 |
| | 13 | 1680 | 30 | 19 3 0 | 14 | 1950 | 28 | 1960 | 13 | 1930 | 28 | 1860 | 13 | 1870 | 29 | 1930 |
| | 14 | 1900 | 31 | 1840 | 15 | 1830 | 29 | 1910 | 14 | 1780 | 29 | 1880 | 14 | 1880 | 30 | 1930 |
| | | | l | | ŀ | | 30 | 1920 | 15 | 1940 | 30 | 1390 | 15 | 1880 | 31 | 1970 |
| 1 | | | | | ı | | 1 . | | 1 | | | | | | | |

| Date @25°C Date @25°C Date @25°C | Date @25°C Date @25 | Date @25°C Date @25°C | Date @Cx106 @25°C |
|----------------------------------|---------------------|-----------------------|----------------------|
|----------------------------------|---------------------|-----------------------|----------------------|

Intake Canal at Morelos Diversion Structure

| | | | | Т | | | | | | | | | | 1 | |
|------------|---------|----|--------|----|-------|-----|-------|------------|-------|------------|-------|----|--------|------|--------|
| | anuary | | bruary | | March | | April | J | une | J | uly | A: | ugust | Sep | tember |
| 1 | 2,150 | 8 | 2,000 | 18 | 1,800 | 25 | 2,300 | 1 | 1,875 | 9 | 2,300 | 17 | 2,350 | 24 | 1,950 |
| 2 | 2,200 | 9 | 1,900 | 19 | 1,800 | 26 | 2,100 | 2 | 2,075 | 10 | 2,300 | 18 | 2,250 | 25 | 1,950 |
| 3 | 2,100 | 10 | 1,825 | 20 | 1,875 | 27 | 2,025 | 3 | 1.850 | 11 | 1,850 | 19 | 1,950 | 26 | 1,950 |
| 4 | 2,100 | 11 | 1,750 | 21 | 1,750 | 28 | 1,975 | 4 | 2,000 | 12 | 1,850 | 20 | 1.850 | 27 | 2,000 |
| 5 | 2,200 | 12 | 1,800 | 22 | 1,750 | 29 | 1.825 | 5 | 2,100 | 13 | 1,950 | 21 | 2,000 | 28 | 1,900 |
| 6 | 1,975 | 13 | 1,875 | 23 | 2,250 | 30 | 2,050 | 6 | 2,100 | 14 | 2,000 | 22 | 1,950 | 29 | 1,950 |
| 7 | 2,100 | 14 | 1,900 | 24 | 1.750 | 1 | May | 7 | 1,800 | 15 | 2,000 | 23 | 1,800 | 30 | 1,300 |
| 8 | 2,000 | 15 | 2,000 | 25 | 2,200 | 1 | 2.050 | 9 | 1,800 | 16 | 2,000 | 24 | 1,750 | | tober |
| 9 | 2,200 | 16 | 1,850 | 26 | 1,700 | 2 | 1,900 | 9 | 2,100 | 17 | 1,950 | 25 | 1,650 | 1 | 1,325 |
| 10 | 1,950 | 17 | 2,000 | 27 | 2,000 | 3 | 1.875 | l 1ó | 1,800 | 18 | 2,050 | 26 | 1,625 | 2 | 1,500 |
| 11 | 2,050 . | 18 | 1,900 | 28 | 1,850 | 1 4 | 1,925 | 11 | 2,100 | 19 | 1,650 | 27 | 1,700 | 3 | 1,675 |
| 12 | 1,800 | 19 | 1,975 | 29 | 1,900 | 5 | 1,900 | 12 | 2,100 | 2ó | 2,250 | 28 | 1,650 | 14 | 1,800 |
| 13 | 1,700 | 20 | 1,975 | 36 | 1,750 | 6 | 2,050 | 13 | 2,100 | 21 | 2,300 | 29 | 1,500 | | 1,850 |
| 14 | 1,700 | 21 | 1,975 | 31 | 2,200 | 7 | 1,900 | 14 | 1,800 | 22 | 1,800 | 30 | | 5 | |
| 15 | 1,700 | 22 | 2,000 | | April | Ьġ | 1,875 | 15 | 2,100 | 23 | 2,300 | | 2,075 | | 1,900 |
| 16 | 1,700 | 23 | 2,050 | 1 | 1.700 | و ا | 1,900 | 16 | 1,850 | 24 | | 31 | 1,975 | 7 | 1,900 |
| 17 | 1,750 | 24 | 1,950 | 2 | 1,700 | 10 | 1,900 | 17 | | | 1,950 | | tember | 8 | 1,900 |
| 18 | 1,750 | 25 | 2,100 | 3 | 2,200 | 11 | | 18 | 2,150 | 25 | 2,300 | 1 | 2,100 | .9 | 1,875 |
| 19 | 1,750 | 26 | 2,150 | 4 | | 12 | 2,050 | | 2,150 | 2 6 | 2,050 | 2 | 2,000 | 10 | 1,900 |
| 20 | | 27 | | | 1,750 | | 1,850 | 19 | 1,875 | 27 | 2,300 | 3 | 2,150 | 11 | 1,900 |
| 21 | 1,775 | 28 | 2,200 | 5 | 1,900 | 13 | 1,850 | 20 | 2,275 | 28 | 1,800 | 4 | 2,150 | 12 | 1,875 |
| | 1,775 | | 2,100 | 6 | 1,700 | 14 | 2,000 | 21 | 1,925 | 29 | 2,025 | 5 | 2,100 | 13 | 1,875 |
| 22 | 1,775 | | March | 7 | 1,775 | 15 | 2,000 | 22 | 1,850 | 30 | 2,300 | | 2,000 | 14 | 1,900 |
| 23 | 1,775 | 1 | 2,100 | 8 | 1,850 | 16 | 1,850 | 23 | 2,200 | A) | ugust | 7 | 2,000 | 15 | 1,850 |
| 24 | 1,725 | 2 | 1,950 | 9 | 1,700 | 17 | 2,050 | 24 | 1,875 | 1 | 2,300 | 8 | 2,100 | 16 | 1,850 |
| 25 | 1,725 | 3 | 1,950 | 10 | 1,850 | 18 | 1,850 | 25 | 1,850 | 2 | 2,100 | 9 | 2,050 | 17 | 1,900 |
| 2 6 | 1,775 | 4 | 1,900 | 11 | 1,825 | 19 | 1,875 | 2 6 | 2,200 | 3 | 2,300 | 10 | 2,000 | 18 | 1,850 |
| 27 | 1,750 | 5 | 1,900 | 12 | 1,700 | 20 | 1,875 | 27 | 2,300 | 4 | 2,000 | 11 | 2,000 | *19 | 1,850 |
| 28 | 1,700 | 6 | 1,900 | 13 | 2,200 | 21 | 2,100 | 28 | 1,850 | 5 | 2,300 | 12 | 1,900 | 25 | 1,900 |
| 29 | 1,750 | 7 | 1,900 | 14 | 1,800 | 22 | 1,850 | 29 | 2,200 | 6 | 2,000 | 13 | 1,975 | | mber |
| 30 | 1,750 | 8 | 1,900 | 15 | 2,150 | 23 | 2,000 | 30 | 2,250 | 7 | 2,025 | 14 | 1,950 | 1 | 1.850 |
| 31 | 1,750 | 9 | 1,900 | 16 | 1,900 | 24 | 2,100 | | July | 8 | 2,250 | 15 | 1,900 | 8 | 1,875 |
| | bruary | 10 | 2,050 | 17 | 1,975 | 25 | 2,050 | 1 | 1,800 | 9 | 2,300 | 16 | 1,750 | 15 | 1,900 |
| 1 | 1,750 | 11 | 1,875 | 18 | 2,000 | 26 | 1,850 | 2 | 2,250 | 1ó | 1,950 | 17 | 1,900 | 22 | 1,850 |
| 2 | 1,700 | 12 | 1,750 | 19 | 2,000 | 27 | 2,025 | 3 | 2,250 | 11 | 2,275 | 18 | 2,000 | 29 | 1,875 |
| 3 | 1,725 | 13 | 1,800 | 20 | 1,975 | 28 | 1,900 | 4 | 2,000 | 12 | 2,100 | 19 | 1,950 | | mber |
| 4 | 1,850 | 14 | 1,950 | 21 | 1,950 | 29 | 1,875 | 5 | 2,250 | 13 | 2,250 | 20 | 1,950 | 6 | 1,950 |
| 5 | 1,900 | 15 | 1,750 | 22 | 2,000 | 36 | 1,875 | 6 | 1,825 | 14 | 2,300 | 21 | 1,900 | 13 | 2,000 |
| 6 | 2,000 | 16 | 1,900 | 23 | 2,100 | 31 | 2,100 | 7 | 2,250 | 15 | 2,300 | 22 | 1,950 | 20 | |
| 7 | 2,050 | 17 | 1,750 | 24 | 2,100 | _ ا | _, | 8 | 1,800 | 16 | 2,300 | 23 | | 27 | 2,500 |
| <u> </u> | -,-,- | | -,.,- | | _,_00 | i | | - 0 | -,000 | -10 | ∪∪ورء | 23 | 1,950 | _ 2/ | 2,475 |

^{*} Sample collection changed from daily to weekly

Colorado River at Southerly International Boundary

| 1 | January | March | April | May | July | September | October | November |
|---|--------------------|-----------------|----------------|-----------------|--------------------|-------------------|-------------------|--------------------|
| | 8 5500 | 2 2790 April | 30 2350 May | 18 4500 June | 20 5460 23 4430 | 7 4220 21 5260 | 5 6160 26 6540 | 2 6650 December |
| | February 2 6830 | 7 1850 | 4 4560 | 1 4670 | August | 21 9200 | 20 0940 | 7 6340 |
| | · - | 20 2130 | 11 4620 | 22 5060 | 24 4470 | l | | 28 6000 |

| Date @25°C Date @25°C Date @25°C Date @25°C | Date @25°C Date @25 | | 10€ °C |
|---|---------------------|--|-----------|
|---|---------------------|--|-----------|

Sánchez Mejorada Canal

| Jan | uary | Feb | ruary | A | pril | | May | J | uly | Aug | gust | 0c | tober | Nov | ember |
|-----|-------|-----|-------|-----|--------------|-----|------|----|------|------|-------|-----|-------|-----|-------|
| 8 | 2400 | 19 | 2400 | 2 | 2500 | 21. | 2400 | 2 | 2600 | 27 | 2500 | 9 | 2500 | 26 | 2500 |
| 15 | 2400 | 26 | 2500 | 12 | 2400 | 28 | 2500 | 9 | 2350 | Sept | ember | 16 | 2300 | Dec | ember |
| 22 | 2400 | l M | arch | 23 | 2 600 | J | une | 16 | 2400 | 3 | 2400 | 22 | 2600 | 3 | 2500 |
| 29 | 2550 | 5 | 2500 | 30 | 2400 | 4 | 2500 | Au | gust | 10 | 2450 | 29 | 2500 | 10 | 2550 |
| Feb | ruary | 12 | 2400 | l M | lay | 11 | 2400 | 6 | 2500 | 17 | 2950 | Nov | ember | 17 | 2400 |
| 4 | 2500 | 19 | 2500 | 7 | 2400 | 18 | 2600 | 13 | 2700 | 24 | 2500 | 8 | 2400 | 24 | 2400 |
| 12 | 2400 | 26 | 2500 | 14 | 2400 | 25 | 2600 | 20 | 2400 | Oct | ober | 12 | 2400 | 31 | 2550 |
| 1 | | | | | | l | | | | 1 | 2500 | | | _ | |

Colorado River at Miguel C. Rodriguez Gaging Station

| Ja | nuary | Feb | ruary | | April | | May | J | uly | Sept | ember | Oc. | tober | Nove | mber |
|----|--------|-----|-------|----|-------|----|------|----|------|------|-------|-----|-------|------|------|
| 4 | 5600 | 22 | 4000 | 12 | 3200 | 31 | 3100 | 19 | 3100 | 6 | 3200 | 11 | 5600 | 8 | 6500 |
| 11 | 5000 | Ma | rch | 19 | 3200 | j | une | 26 | 3200 | 20 | 3300 | 13 | 6500 | 15 | 6250 |
| 18 | 6000 | 1 | 3500 | 26 | 3200 | 7 | 3300 | Au | gust | 27 | 3100 | 20 | 5750 | 29 | 6100 |
| 25 | 2900 | 8 | 3600 | | May | 14 | 3200 | 2 | 3300 | 30 | 3200 | 21 | 5750 | Dece | mber |
| Fe | bruary | 15 | 3500 | 3 | 3200 | 21 | 3400 | 9 | 3200 | 0ct | ober | 22 | 6000 | 6 | 6200 |
| 1 | 6000 | 22 | 3300 | 10 | 3200 | 28 | 3200 | 16 | 3200 | 4 | 2500 | 23 | 5600 | 13 | 6000 |
| 8 | 6000 | 29 | 3400 | 17 | 3200 | J | uly | 23 | 3100 | 7 | 5500 | Nov | ember | 20 | 4100 |
| 15 | 4000 | 31 | 3400 | 24 | 3200 | 5 | 3200 | 30 | 3200 | 9 | 5700 | 6 | 6000 | 27 | 4900 |

RAINFALL ON THE COLORADO RIVER WATERSHED IN INCHES

Tabulated below are monthly records of rainfall at stations located in California and Arizona in the United States and in Baja California and Sonora in Mexico, with averages for their periods of record. Records of daily rainfall amounts, where available, are on file in the offices of the United States or Mexican Sections of the Commission. For location, elevation, period of record, and the observer, see alphabetical listings of these stations on page 52 in this bulletin.

In United States

| | | awley, Ifo rni a | | Centro, formia | | lythe, Ifornia | | Dam No. 2, izona | | a Citrus n, Arizona |
|--------|------|----------------------------|------|----------------------|------|----------------------|------|----------------------|------|------------------------|
| Month | 1971 | Average 1931-1971 | 1971 | Average 1931-1971 | 1971 | Average 1931-1971 | 1971 | Average 1955-1971 | 1971 | Average 1931-1971 |
| Jan. | 0.03 | 0.31 | 0.03 | 0.34 | 0.08 | 0.45 | 0 | 0.38 | 0 | 0.37 |
| Feb. | -03 | .30 | •03 | •34 | T | .38 | ,60 | .43 | .03 | .34 |
| Mar. | 0 | .16 | 0 | .18 | .03 | .40 | 0 | •35 | ٥ | .21 |
| Apr. | .07 | .08 | .08 | .10 | .05 | .15 | 0 | .31 | .30 | .12 |
| May | T | .01 | 0 | 0 | T | .02 | .46 | .14 | .11 | .01 |
| June | 0 | .01 | 0 | .01 | 0 | .02 | 0 | .03 | 0 | .02 |
| July | T | •04 | 0 | •10 | 0 | .18 | .02 | ,21 | .02 | .17 |
| Aug. | •85 | .30 | .04 | .32 | 1.35 | .80 | .61 | .53 | .23 | .41 |
| Sept. | .22 | -33 | .24 | .26 | .72 | -33 | .09 | .29 | 1.35 | •39 |
| Oct. | .23 | .21 | .02 | .22 | .05 | .27 | .14 | .29 | .04 | .37 |
| Nov. | 0 | .15 | 0 | .17 | 0 | .25 | .04 | .44 | 0 | .19 |
| Dec. | .19 | •43 | 0 | .444 | .01 | •54 | .76 | -54 | .10 | .40 |
| Yearly | 1,62 | 2.33 | 0.44 | 2.48 | 2.29 | 3.79 | 2.72 | 3.94 | 2.18 | 3.00 |


| | | Lgodones, California | Mexicali, Baja California | | | aques, alifornia | | Luis, Sonora | Delta, Baja California | | |
|--------|------|-------------------------|------------------------------|----------------------|------|----------------------|------|----------------------|---------------------------|----------------------|--|
| Month | 1971 | Average 1948-1971 | 1971 | Average 1926-1971 | 1971 | Average 1948-1971 | 1971 | Average 1949-1971 | 1971 | Average 1948-1971 | |
| Jan. | T | 0.39 | 0.04 | '0.35 | 0 | 0.35 | 0 | 0.28 | 0 | 0.35 | |
| Feb. | 0 | .20 | T | •31 | 0 | .08 | .04 | .20 | 0 | .08 | |
| Mer. | 0 | .12 | 0 | .20 | 0 | .04 | T | .16 | 0 | .12 | |
| Apr. | .31 | •08 | .08 | .08 | .28 | .03 | .98 | •08 | -39 | .04 | |
| May | 0 | 0 | T | T | 0 | 0 | 0 | T | 0 | 0 | |
| June | 0 | 0 | 0 | 0 | 0 | -04 | 0 | 0 | 0 | 0 | |
| July | 0 | .09 | T | .12 | .08 | .04 | .04 | .20 | T | .04 | |
| Aug. | •39 | .20 | .16 | •31 | .08 | .12 | •67 | -39 | .63 | .16 | |
| Sept. | •94 | .24 | •59 | •39 | 0 | •04 | 1.26 | .24 | .79 | .16 | |
| Oct. | .08 | .28 | .16 | .24 | 0 | .20 | .47 | .20 | •08 | .12 | |
| Nov. | 0 | .16 | 0 | •16 | 0 | .16 | 0 | .63 | 0 | .16 | |
| Dec. | .08 | •31 | •08 | .79 | .08 | .20 | .16 | -55 | .16 | .28 | |
| Yearly | 1.81 | 2.06 | 1.10 | 2.95 | 0.51 | 1.34 | 3.62 | 2.05 | 2.05 | 1.46 | |

| | | Kilometer 50, Baja California | | Riito, Sonora | | Mayor, Salifornia | | Felipe, California | | |
|--------|------|----------------------------------|------|----------------------|------|----------------------|-------|-----------------------|--|---|
| Month | 1971 | Average 1952-1971 | 1971 | Average 1959-1971 | 1971 | Average 1949-1971 | 1971 | Average 1948-1971 | | |
| Jan. | 0 | 0.55 | 0 | 0.24 | 0 | 0.20 | 0 | 0,28 | | |
| Feb. | 0 | .24 | •04 | .08 | 0 | .12 | 0 | .12 | | |
| Mar. | 0 | .28 | 0 | •08 | 0 | .12 | #0 | .16 | | 1 |
| Apr. | •35 | .16 | .31 | .04 | .16 | •04 | * | .08 | | |
| May | 0 - | •04 | 0 | 1 0 | - 0 | 0 | * | T | | 1 |
| June | 0 | 0 | 0 | 0 | 0 | 0 | * | .08 | | |
| July | .08 | .16 | .12 | .08 | T | •08 | #0 | .12 | | 1 |
| Aug. | .63 | •35 | 1.30 | .16 | 1.14 | •35 | 1.61 | -35 | | |
| Sept. | 1.06 | .28 | 1.14 | .67 | .79 | .55 | .31 | .43 | | |
| Oct. | 0 | •35 | .08 | .04 | T | .20 | .12 | .28 | | |
| Nov. | lo | .28 | 0 | •31 | 0 | .16 | # .24 | .16 | | |
| Dec. | •08 | •35 | .04 | •39 | ō. | •31 | # .08 | •35 | | |
| Yearly | 2.20 | 2.01 | 3.03 | 2.20 | 2.09 | 2.17 | * | 2.48 | | |

T Trace * Registered

^{*} Registered incomplete

[#] Some days missing





LOCATION OF RAINFALL STATIONS ON THE COLORADO RIVER WATERSHED

The precipitation records of the stations listed alphabetically below began on the date shown and extend through 1971.

In United States

| | NAME OF STATION | LATI- TUDE | LONGI- TUDE | SELEV. (FT.) | RECORD BEGAN | Obser v er |
|---|------------------------------|---------------|----------------|-----------------|-----------------|--|
| * | Blythe, California | 33° 37' | 114° 36' | 2 68 | 1909 | State Division of Forestry |
| | Brawley, California | 32° 57' | 115° 33' | 100 | 1908 | Agricultural Research Service |
| * | Davis Dam No. 2, Arizona | 35° 12' | 114° 34' | 657 | 1954 | U. S. Bureau of Reclamation |
| | El Centro, California | 32° 46' | 115° 34' | 30 | 1930 | El Centro Water Department |
| | Yuma Citrus Station, Arizona | 32° 37' | 114° 39' | 191 | 1923 | University of Arizona Experimental Farm |

| NAME OF STATION | LATI- TUDE | LONGI- TUDE | | EV. | RECORD BEGAN | OBSERVER |
|--------------------------------|---------------|----------------|----|-----|-----------------|---------------------|
| Bataques, Baja California | 32° 33' | 115° 04' | ** | 66 | 1948 | Hydraulic Resources |
| Delta, Baja California | 32° 21' | 115° 11' | ** | 39 | 1948 | Hydraulic Resources |
| El Mayor, Baja California | 32° 03' | 115° 15' | ** | 33 | 1949 | Hydraulic Resources |
| Kilometer 50, Baja California | 32° 15′ | 115° 03' | | 49 | 1952 | Hydraulic Resources |
| Los Algodones, Baja California | 32° 42' | 114° 44' | | 115 | 1948 | Hydraulic Resources |
| Mexicali, Baja California | 32° 40' | 115° 28' | | 13 | 1926 | Hydraulic Resources |
| Riito, Sonora | 32° 10' | 114° 57' | ** | 39 | 1959 | Hydraulic Resources |
| * San Felipe, Baja California | 31° 02' | 114° 53' | | 33 | 1948 | Hydraulic Resources |
| San Luis, R.C., Sonora | 32° 28' | 114° 47' | | 131 | 1949 | Hydraulic Resources |

^{*} Not shown on map 8 Elevation above mean sea level except Brawley and El Centro which are elevations below mean level

vations below mean level
** Elevations obtained from International Boundary and Water Communission topographic maps

EVAPORATION IN THE COLORADO RIVER BASIN IN INCHES

Tabulated below are records of evaporation observed at two stations in Arizona and at nine stations in Baja California and Sonora, Mexico. The stations in the United States are operated by the U.S. Bureau of Reclamation and by the University of Arizona Experimental Farm. The stations in Mexico are operated by the Ministry of Hydraulic Resources. The type of pan used at all these stations was the National Weather Service standard pan, four feet in diameter. For specific location of these stations, refer to data opposite the same station name shown in "Location of Rainfall Stations", page 52 in this bulletin.

In United States

| | Davis Da Ariz | | Yuma Citru Ariz | s Station, |
|--|--|--|---|--|
| Month | 1971 | Average 1955-1971 | 1971 | Average 1931-1971 |
| Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec. | 8.27 7.81 13.00 13.19 15.73 18.38 21.42 15.99 17.60 11.30 8.46 5.78 | 7.41 7.63 10.35 13.42 17.12 19.64 20.23 18.17 15.17 12.31 8.89 7.81 | 4.46 5.41 8.09 9.88 11.33 12.91 15.02 11.73 10.34 6.61 4.15 2.95 | 3.92 4.92 7.87 10.28 13.31 14.54 15.73 13.89 11.04 7.79 5.07 3.66 |
| Yearly | 156.93 | 0158.15 | 102.91 | 0 112.02 |

| | | lgodones, alifornia | | cali, difornia | | aques, alifornia | San Luis, R. C., Sonora | | |
|--------|--------|--------------------------|---------------|----------------------|--------|----------------------|----------------------------|----------------------|--|
| Month | 1971 | Av. 1949-55 1961-1971 | 1971 | Average 1926-1971 | 1971 | Average 1963-1971 | 1971 | Average 1953-1971 | |
| Jan. | 4.72 | 4.21 | 2.80 | 2.60 | 3.78 | 3.86 | 3.86 | 3.31 | |
| Feb. | 5.63 | 5.16 | 3.82 | 3.50 | 4.53 | 5.08 | 4.33 | 4.02 | |
| Mar. | 9.72 | 7.36 | 6 .3 8 | 5.83 | . 7.68 | 7.44 | 7.56 | 6.30 | |
| Apr. | 10.00 | 9.76 | 7.72 | 7.91 | 8.23 | 9.21 | 8.27 | 8.39 | |
| May | 12.52 | 12.44 | 10.16 | 10.51 | 11.22 | 12.05 | 10.39 | 10.98 | |
| June | 15.20 | 13.03 | 11.81 | 11.54 | 12.56 | 12.32 | 12.68 | 12.56 | |
| July | 14.61 | 13.07 | 12.64 | 11.73 | 13.15 | 12.72 | 14.84 | 14.17 | |
| Aug. | 12.05 | 11.81 | 10.00 | 10.08 | 10.35 | 10.51 | 11.65 | 12.83 | |
| Sept. | 11.34 | 9.84 | 8.50 | 8.15 | 9.45 | 9.13 | 9.96 | 10.04 | |
| Oct. | 7.72 | 7.80 | 4.49 | 5.59 | 5.67 | 6.22 | 5.94 | 6.65 | |
| Nov. | 4.88 | 4.88 | 3.70 | 3.39 | 4.21 | 4.80 | 3.98 | 4.41 | |
| Dec. | 3.86 | 3.94 | 2.56 | 2.44 | 3.11 | 3.39 | 2.95 | 3.23 | |
| Yearly | 112.24 | 104.90 | 34.57 | 83.31 | 93.94 | 96.77 | 95.24 | 98.31 | |

| | Del Baja Ca | ta, lifornia | | ter 50, lifornia | | ito, nora | | Mayor, alifornia | | Felipe, Lifornia |
|---|--|--|--|--|--|--|---|--|--|--|
| Month | 1971 | Average 1959-1971 | 1971 | \$ Average 1950-1959 1961-1971 | 1971 | Average 1963-1971 | 1971 | Average 1953-1971 | 1971 | Average 1952-1971 |
| Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec. | 3.66 3.78 6.26 7.83 8.98 11.73 13.58 12.48 10.39 6.10 4.53 2.20 | 3.23 4.21 6.38 8.15 10.28 11.18 11.42 10.16 8.19 5.83 3.74 2.68 | 3.31 4.09 7.28 6.97 9.02 10.43 11.42 8.90 8.23 6.02 4.61 2.80 | 3.23 4.02 6.38 6.85 9.65 10.71 11.81 9.13 8.19 5.75 4.29 2.76 | 3.03 3.90 6.73 7.44 9.84 11.46 13.58 9.80 8.43 5.20 3.31 2.60 | 3.15 4.13 6.02 7.24 9.51 10.91 12.01 9.53 7.50 5.16 3.35 2.68 | 3.03 3.62 5.39 5.63 7.99 6.50 5.71 † 6.26 4.06 3.46 | 3.50 4.21 6.10 7.91 9.92 10.79 12.01 11.73 10.04 7.60 4.53 3.78 | 5.00 5.24 * † † 10.83 9.76 8.82 5.91 4.13 3.07 | 5.20 5.91 7.09 8.54 10.59 10.94 11.81 10.94 9.92 8.50 6.26 5.16 |
| Yearly | 91.54 | 86 .2 6 | 83.07 | 82.72 | 85.31 | 84.57 | * | 92.17 | * | 101.81 |

O One year missing

^{*} Record incomplete

f Did not register \$ 1969 missing

TEMPERATURE IN THE COLORADO RIVER BASIN IN DEGREES FAHRENHEIT

The maximum, minimum, and monthly mean temperature observations for United States stations are from daily readings of thermometers generally exposed in a shelter located a few feet above sod-covered ground. The maximum and minimum temperatures shown for the stations in Mexico are from daily maximum and minimum thermometer observations, with maximum and minimum for their periods of record. For specific location, elevation, period of record, and the observer, refer to data opposite same station name as shown in "Location of Rainfall Stations", page 52 in this bulletin.

In United States

| | I | Slythe, Ca | aliforni | 9. | Dav | is Dam No | . 2, Ar | izona | Yuma (| Citrus St | ation, A | rizona |
|--------|------|------------|----------|--------------------|------|-----------|----------------------|---------|--------|-----------|------------|---------|
| Month | | 1971 | | 4 | | 1971 | | Average | | 1971 | | Average |
| | Mean | Max. | Min. | Average 1931-71 | Mean | Max. | Min. | 1955-71 | Mean | Max. | Min. | 1931-71 |
| Jan. | 51.9 | 87 | 22 | 52.6 | 53.0 | 83 | 28 | 52.9 | 53.5 | 88 | 2 6 | 53.1 |
| Feb. | 57.8 | 87 | 33 | 57.3 | 57.0 | 79 | 38 | 56.7 | 56.8 | 88 | 35 | 57.0 |
| Mar. | 63.5 | 99 | 28 | 63.0 | 62.0 | 95 | 38 38 38 34 | 62.1 | 62.0 | 97 | 30 | i |
| Apr. | 67.5 | 97 | 42 | 70.2 | 68.1 | 95 | 38 | 69.5 | 66.2 | 96 | 41 | 68.8 |
| May | 74.0 | 101 | 48 | 77.4 | 72.6 | 102 | 34 | 78.3 | 70.4 | 101 | 45 | 75.9 |
| June | 85.1 | 114 | 50 | 84.9 | 87.2 | 114 | 58 | 88.2 | 81.4 | 112 | 50 63 | 83.3 |
| July | 94.0 | 120 | 66 | 92.1 | 96.1 | 118 | 72 | 94.9 | 91.1 | 114 | 63 | 91.2 |
| Aug. | 92.1 | 111 | 71 | 91.2 | 93.1 | 112 | 73 | 93.6 | 90.0 | 112 | 71 | 90.6 |
| Sept. | 84.7 | 116 | 50 | 85.1 | 83.8 | 114 | 50 | 85.9 | 84.7 | 115 | 51 | 85.2 |
| Oct. | 68.6 | 102 | 29 | 73.2 | 68.9 | 100 | 33 | ł l | 68.0 | 99 86 | 33 | 73.6 |
| Nov. | 58.7 | 85 | 37 | 60.3 | 58.6 | 80 | 33 38 | 1 . 1 | 58.6 | | 34 | 61.6 |
| Dec. | 50.6 | 75 | 26 | 53.3 | 49.3 | 70 | 29 | 54.0 | 50.9 | 75 | 29 | 54.6 |
| Yearly | 70.7 | 120 | 22 | 71.7 | 70.8 | 118 | 28 | | 69.5 | 115 | 26 | |

| | В | rawley, C | aliforni | .а | Е | l Centro, | Califor | nia |
|--|--|---|--|--|---|--|--|--|
| Month | | 1971 | | Average | | 1971 | | Average |
| | Mean | Max. | Min. | 1931-71 | Mean | Max. | Min. | 1931-71 |
| Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec. | 53.4.4.4.9.8.9.9.6.8.8.9.9.8.8.9.9.8.8.9.9.8.8 | 89 89 96 92 99 112 113 110 116 101 | 20 34 28 40 50 20 67 52 36 27 | 53.7 58.0 63.4 70.4 70.7 85.0 92.2 91.9 86.6 75.2 62.6 55.1 | 54.7 58.3 62.9 66.8 73.3 83.8 92.4 869.6 60.6 51.5 | 90 90 95 94 100 114 115 115 119 104 88 74 | 20 35 39 39 46 50 51 53 34 27 | 53.7 57.8 63.1 69.9 77.3 84.7 91.9 91.3 85.8 74.6 62.2 54.8 |
| Yearly | 69.9 | 116 | 20 | 72.6 | 71.0 | 119 | 20 | 72.3 |

| | Los Al | godones, | Baja Cal | ifornia | Mexi | icali, Ba | ja Califo | rnia | Bat | aques, B | aja Calif | ornia |
|--|--|--|---|--|--|--|--|--|--|--|--|--|
| Month | 1 | .971 | 1948 | -1971 | 19 | 71 | 1926- | 1971 | 1 | 971 | 1948- | 1971 |
| ŀ | Max. | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Max. | Min. |
| Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec. | 88 88 99 95 99 111 113 109 115 99 88 | 27 37 34 43 50 52 68 75 53 34 | 88 95 100 109 117 126 118 120 122 111 100 88 | 23 28 32 37 43 52 61 61 54 32 28 | 90 86 97 99 100 111 113 115 115 100 84 75 | 21 34 30 39 48 48 66 68 54 32 37 28 | 93 93 100 106 117 120 118 118 122 109 99 | 19 23 30 34 43 49 55 48 28 28 23 | 88 90 95 97 102 113 115 111 113 104 88 77 | 16 28 32 39 50 52 66 70 52 32 36 25 | 113 99 113 118 124 135 133 129 135 118 115 97 | 16 21 25 16 34 43 45 46 39 32 32 25 |
| Yearly | 115 | 27 | 126 | 23 | 115 | 21 | 122 | 19 | 115 | 16 | 135 | 1 |

TEMPERATURE IN THE COLORADO RIVER BASIN IN DEGREES FAHRENHEIT

| | Sea | n Luis, R | . C., Son | nora. | De | elta, Baj | a Califor | nia | Kilom | eter 50, | Baja Cal | ifornia |
|--------|----------|-----------------|-----------|-----------------------------------|-------|----------------|-----------|----------------------------|-------|----------------|-----------|----------------------------|
| Month | 1 | 971 | 1949 | 1971 | 19 | 71 | 1948 | -1971 | 19 | 71 | 1950-5 | 9 & 61-71 |
| ļ | Mex. | Min. | Max. | Min. | Me.x. | Min. | Mex. | Min. | Mex. | Min. | Max. | Min. |
| Jan. | 86 | 23 | 100 | 19 | 91 | 27 | 104 | 27 | 81 | 19 | 91 | 19 |
| Feb. | 88 | 28 | 109 | 27 | 91 | 3 6 | 104 | 28 | 88 | 32 | 97 | 21 |
| Mar. | 95 | 28 | 108 | 28 | 102 | 32 | 113 | 28 | 97 | 32 25 | 99 106 | 25 |
| Apr. | 95 | 41 | 115 | 37 | 97 | 32 45 | 118 | 32 | 99 | 37 43 46 | 106 | 25 30 36 39 45 |
| May | 95 99 | 50 | 115 | 41 | 102 | 52 54 64 | 129 | 32 32 36 45 | 100 | 43 | 117 | 36 |
| June | 111 | 52 | 126 | 45 | 115 | 54 | 133 | 36 | 117 | 46 | 118 | 39 |
| July | 113 | 52 68 | 126 | 59 | 115 | 64 | 135 | 45 | 117 | 64 | 120 | 45 |
| Aug. | 109 | 64 | 122 | 55 | 111 | 72 | 140 | | 117 | 64 | 118 | 50 |
| Sept. | 115 | 50 | 118 | 50 | 115 | 54 | 135 | 39 | 122 | 50 | 122 | 39 |
| Oct. | | 32 | 118 | 55 50 32 30 23 | 102 | 54 34 | 117 | 52 39 34 32 27 | 118 | 39 | 118 | 50 39 36 25 |
| Nov. | 97 86 | 32 36 | 113 | 30 | 97 | 39 28 | 120 | 32 | 99 | 37 32 | 104 | 25 |
| Dec. | 75 | 28 | 102 | 23 | 82 | 28 | 104 | 27 | 73 | 32 | 97 | 19 |
| Yearly | 115 | 23 | 126 | 19 | 115 | 27 | 140 | 27 | 122 | 19 | 122 | 19 |

| | | Riito, | Sonora | | El M | layor, Ba | ja Califo | rnia | San Felipe, Baja California | | | | |
|--------|------|------------|-----------|------------|------|------------------|-----------|------------------------|-----------------------------|------|------|----------------------------|--|
| Month | 19 | 971 | 1949-1971 | | 1971 | | 1949 | -1971 | 19 | 71 | 1948 | 3-1971 | |
| | Max. | Min. | Max. | Min. | Max. | Min. | Mex. | Min. | Max. | Min. | Mex. | Min. | |
| Jan. | 88 | 21 | 91 | 19 | 91 | 3 ¹ 4 | 108 | 23 | 75 | 32 | 99 | 30 32 33 37 41 | |
| Feb. | 88 | | 95 | 2í | 88 | 34 | 93 | 27 | 82 | 32 | 102 | 32 | |
| Mar. | 100 | 32 28 | 100 | 25 | 99 | 37 | 100 | 32 | * | * | 104 | 32 | |
| Apr. | 95 | 3 9 | 109 | 37 | 104 | 41 | 108 | 32 36 | * | * | 113 | 37 | |
| May | 100 | 45 | 115 | 43 | 108 | 43 | 113 | 37 | * | * | 120 | | |
| June | 113 | 46 | 124 | 45 | 106 | 48 | 122 | 37 | * | * | 124 | 50 | |
| July | 117 | 64 | 140 | 5 <u>2</u> | 120 | 43 | 122 | 39 | 100 | 66 | 124 | 50 | |
| Aug. | 109 | 64 | 122 | 52 46 | 122 | 54 | 122 | 41 | 113 | 63 | 135 | 41 | |
| Sept. | 115 | 50 | 118 | 39 | 117 | 52 | 120 | 34 | 95 | 63 | 126 | 37 | |
| Oct. | 102 | 30 | 115 | 30 | 99 | 45 | 120 | 3 ¹ 4 37 | 93 | 54 | 117 | 41 | |
| Nov. | 88 | 32 | 118 | 27 | 88 | 32 | 120 | 32 | †86 | 43 | 118 | 21 | |
| Dec. | 75 | 27 | 86 | 21 | 86 | 23 | 106 | 32 19 | †82 | 39 | 97 | 28 | |
| Yearly | 117 | 21 | 140 | 19 | 122 | 23 | 122 | 19 | * | * | 135 | 21 | |

^{*} Record incomplete

[†] Some days missing

IRRIGATED AREAS ALONG COLORADO RIVER BELOW IMPERIAL DAM 1971

The total drainage area within the Colorado River basin is about 246,000 square miles, of which 184,600 square miles lie above Imperial Dam and about 61,400 square miles are below the dam. Of the area below Imperial Dam, 59,400 square miles are in the United States and about 2,000 square miles are in Mexico. The area below Imperial Dam includes the Gila River watershed with a total area of about 58,200 square miles, of which about 1,100 square miles are in Mexico.

The irrigated areas tabulated below comprise the areas in the United States and Mexico which are served by diversions from the Colorado River at or below Imperial Dam. The diversions are supplemented by some pumping from wells in both countries. The areas in the United States include: 1) those within the U.S. Bureau of Reclamation Projects and in the North and South Gila Valleys located near Yums, Arizons, the data for which are furnished by the U.S. Bureau of Reclamation; 2) those within the Coachella Valley, California, the data for which are furnished by the Coachella Valley County Water District and State of California Department of Water Resources; and 3) those within the Imperial Valley, California, the data for which are furnished by the Imperial Irrigation District. The areas in Mexico include those in the Mexicali Valley located in the states of Baja California and Sonora, the data for which are furnished by the Ministry of Hydraulic Resources of Mexico. The areas tabulated below refer to the total areas farmed, and insofar as possible, duplication of irrigated areas because of double cropping has been eliminated.

| Point of Diversion from Colorado River and Designation of Areas | Total Irrigated Areas Acres |
|---|---|
| IN UNITED STATES: | |
| Imperial Dam | |
| Yuma Valley Division Reservation Division Yuma Mesa Yuma Aux. Project Unit "B" (Yuma Mesa) South Gila Valley North Gila Valley Wellton-Mohawk Coachella Valley Imperial Valley Warren Act Non-Project lands adjacent to Colorado River Total in United States | 45,312 11,368 17,189 3,116 10,223 5,904 61,152 52,371 441,783 80 10,200 658,698 |
| IN MEXICO: | |
| Morelos Dam | |
| Mexicali Valley | * 429,088 |
| Total in United States and Mexico | 1,087,786 |

^{*} An estimated one-third of total acreage is served by pumping from ground water in Mexicali Valley

ALAMO RIVER AT INTERNATIONAL BOUNDARY

DESCRIPTION: Staff gage located on the right bank of the river, about 7 miles east of Calexico, California, immediately downstream from the international land boundary between the United States and Mexico and a few feet upstream from a 4-foot Cipolletti weir set in the throat of a twin-tube concrete culvert which carries the river flow under the All-American Canal.

RECORDS: Computed on the basis of head on the Cipolletti weir from daily staff gage readings, and weir ratings as determined by monthly current meter measurements. Records obtained and furnished by Imperial Irrigation

District. Records available: June 1942 through 1971.
REMARKS: The flow at this station normally comprises seepage from the All-American Canal and drainage water from the Mexicali Valley which enters the United States.

CUTTED SET VALUE AND THE STATE OF THE STATE

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|--------------------------------------|--------------------------------------|--|--------------------------------------|--|--------------------------------------|--|--|--------------------------------------|--|--|--|
| 1 2 3 4 5 | 2.44 2.55 2.67 2.44 2.55 | 1.49 1.39 1.58 1.58 1.58 | 2.00 1.68 1.68 1.68 1.68 | 1.20 1.39 1.39 1.49 1.58 | 1.39 1.39 1.49 1.49 1.89 | 2.21 2.67 2.67 2.00 1.89 | 1.68 1.68 1.68 1.58 1.58 | 2.00 1.79 1.79 1.89 1.89 | 3.15 3.15 2.79 3.03 3.41 | 2.21 2.21 2.55 2.44 2.32 | 1.79 1.89 2.67 2.79 2.55 | 2.21 2.21 2.32 2.55 2.55 |
| 6 7 8 9 | 1.39 2.00 2.00 2.00 2.00 | 2.00 2.00 2.00 2.00 2.21 | 1.68 2.00 1.79 2.10 2.55 | 1.89 2.00 1.89 1.79 1.89 | 2.00 1.89 1.89 1.79 2.00 | 1.89 1.89 2.00 1.68 1.68 | 1.58 1.89 1.89 1.68 1.89 | 1.79 1.79 1.79 1.79 1.89 | 3.03 3.15 3.03 3.15 3.03 | 3.03 3.03 2.79 2.67 3.15 | 2.55 2.79 2.67 2.44 2.67 | 2.44 2.21 2.67 2.67 2.67 |
| 11 12 13 14 15 | 2.10 2.32 1.89 2.00 2.00 | 2.00 2.00 2.00 1.79 1.79 | 2.32 2.21 2.00 2.32 2.21 | 1.68 1.89 1.89 2.21 2.10 | 1.89 2.00 1.89 1.89 2.10 | 1.79 1.79 1.89 2.00 1.89 | 1.89 1.79 2.00 1.79 1.79 | 2.00 2.00 2.00 1.79 1.68 | 2.00 2.00 2.00 2.44 2.55 | 2.44 2.44 2.55 2.55 2.55 | 2.55 2.55 2.67 2.44 2.44 | 2.55 2.55 2.55 2.55 2.10 |
| 16 17 18 19 20 | 1.89 1.79 1.39 1.49 1.79 | 1.68 1.68 2.00 1.89 2.00 | 1.89 2.00 2.00 2.00 1.79 | 2.21 2.21 2.21 2.21 2.89 | 1.89 2.00 1.39 1.03 | 2.91 2.67 2.79 2.44 2.44 | 1.58 1.68 1.68 1.79 2.10 | 1.79 1.89 2.00 2.00 1.89 | 2.21 2.21 2.44 2.32 2.44 | 2.79 2.79 2.91 2.91 3.03 | 2.67 2.79 2.79 2.79 2.79 1.89 | 2.00 2.00 1.89 2.21 2.00 |
| 21 22 23 24 25 | 1.79 2.00 3.03 1.79 1.79 | 2.00 2.00 2.00 1.58 1.68 | 2.00 1.79 1.68 1.68 1.68 | 1.89 1.58 1.58 1.58 1.89 | 1.20 1.20 1.39 1.58 2.21 | 2.67 2.21 1.58 1.03 1.49 | 2.00 2.21 1.89 2.00 2.00 | 1.89 2.00 2.10 2.67 2.67 | 3.03 3.15 3.15 3.03 2.79 | 2.91 2.79 2.91 3.15 2.91 | 1.89 2.00 2.00 2.21 2.21 | 2.21 1.89 2.00 2.00 2.00 |
| 26 27 28 29 30 31 | 1.68 1.30 1.30 1.39 1.39 | 1.79 1.79 1.89 | 1.49 1.49 1.58 1.68 1.39 1.20 | 1.89 1.79 1.58 1.39 1.39 | 2.00 2.00 2.00 2.21 2.10 2.21 | 1.03 1.03 1.39 1.39 1.39 | 2.00 2.00 3.41 1.68 1.68 2.00 | 2.91 3.03 3.15 3.15 3.03 1.89 | 3.15 3.03 1.89 2.21 2.21 | 3.03 1.49 1.58 1.58 1.58 1.68 | 2.44 2.44 2.67 2.44 2.21 | 2.10 2.21 1.89 2.00 2.00 1.89 |
| Sum | 59.65 | 51.39 | 57.24 | _53.57 | 54.43 | 58.40 | 58.09 | 65.94 | 81.17 | 78.97 | 72.90 | 69.09 |

Current Year 1971 Period 1943-1971 Extreme Gage ø Extreme Second Feet Average Acre Feet Total Month Feet Second High Average Acre Feet Maximum Minimum Feet Day Day High Low 2,790 99 100 Jan. 0.37 0.21 23 3.03 127 1.30 1.92 2,822 3,154 2,222 1,799 1,686 352 394 423 1.39 .30 .30 .30 .36 .22 10 2.21 2 1.84 102 Feb. 111 2.55 1.85 114 Mar. .20 10 31 1.20 97 114 Apr. .20 .18 †25 16 2.21 119 1.03 1.76 108 326 323 73 61 Мау 1.95 June .18 2.91 124 1.03 116 115 297 1,712 1,672 59 83 .24 28 3.41 1 4 1.58 July 356 .38 .40 28 3.15 15 28 2.13 131 .25 Aug. 1,406 1,845 2,080 91 102 3.41 2.71 161 337 .27 1.89 Sept. 5 .23 .38 110 3.15 27 1.49 2.55 157 364 Oct. 86 .26 2.79 1.79 2.43 145 371 .35 Nov. 1,686 80 2.23 137 342 118 .27 18 2.67 1.89 Dec. 1,251 2,09 1,510 4,273 22.146 1.03 Yearly 0.40 0.18 3.41

Mean daily † And other days

NEW RIVER AT INTERNATIONAL BOUNDARY

Water-stage recorder located on the left (west) bank of the river in the limits of the city of

DESCRIPTION: Water-stage recorder located on the left (west) bank of the river in the limits of the city of Calexico, California, 1,400 feet downstream (north) of the international land boundary between the United States and Mexico. Measurements are made from a foot bridge at the gage.

RECORDS: Based on a continuous record of gage heights and weekly current meter measurements, supplemented by additional measurements during periods of high flow by the Imperial Irrigation District. Measurements are also made generally once each month by the United States Section of the Commission. Records computed by shift thought measurements untrue periods of magnitude of the Commission. are also made generally once each month by the United States Section of the Commission. and furnished by the District. Records available: June 1942 through 1971.

and nurnished by the District. Records available: June 1942 through 1971.

REMARKS: The New River flows northward from Mexico into the United States and thence into the Salton Sea. The flow at this station normally comprises 1) a portion of the waste and drainage water from the irrigation system in the Mexicali Valley, and 2) sewage and other wastes from Mexicali, Baja California. Flood waters enter the river from local drainage in Mexico and such waters can reach damaging rates during wishland desert strong World flows from the Mexican system of capals are limited to an avarage graph quantity violent desert storms. Waste flows from the Mexican system of canals are limited to an average annual quantity of 35,000 acre-feet during any successive five-year period under the provisions of Minute No. 197 of the

CTREMES: Maximum mean daily discharge, 691 second-feet on December 3, 1962; minimum mean daily discharge, 2 second-feet on May 14, 1945. Prior to the period of record, and since 1900, much higher flows occurred. During the years 1905 to 1907, when Colorado River flowed into the Salton Sea, a considerable part of its EXTREMES: flow passed through the New River channel.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| | 14100 | ii Daily | Discina | . Se m r | | reet 13 | | | | | | | T - |
|----------------------------------|--|---------------------------------|---|--|---------------------------------|---|---|--|--|--|---|---|-----------------------|
| Day | Jan. | Feb. | March | April | May | June | July | | Aug. | Sept. | Oct. | Nov. | Dec. |
| 1 2 3 4 5 | 135 142 139 146 136 | 124 123 125 125 125 | 145 145 145 145 145 | 168 167 166 162 167 | 177 176 172 165 169 | 137 133 135 135 136 | 14 15 15 15 16 | 52 | 158 169 158 154 152 | 186 206 184 179 177 | 143 145 145 148 161 | 109 117 126 128 130 | 129 |
| 6 7 8 9 | 128 131 135 137 135 | 120 118 118 119 120 | 151 151 150 154 158 | 167 168 169 160 162 | 172 161 160 158 | 135 133 | 14 | 51 +7 +9 +9 50 | 149 156 164 174 176 | 173 168 158 157 157 | 151 151 156 169 215 | 134 140 131 127 130 | 128 127 126 |
| 11 12 13 14 15 | 139 137 140 140 138 | 124 124 128 127 130 | 160 161 160 162 160 | 164 167 170 174 177 | 155 151 149 144 141 | 126 127 137 | 15 15 15 | 51 55 54 54 56 | 177 175 177 179 178 | 155 155 158 156 151 | 192 160 163 169 182 | 130 126 129 129 130 | 118 120 122 |
| 16 17 18 19 20 | 140 141 143 144 147 | 132 136 136 134 133 | 159 163 163 179 179 | 179 187 185 188 193 | 134 132 132 130 134 | 141 138 131 | 19 | 58 53 51 48 48 | 184 171 162 162 163 | 148 146 138 133 129 | 158 133 139 131 129 | 121 123 125 121 126 | 124 125 127 |
| 21 22 23 24 25 | 140 137 134 123 118 | 127 131 119 105 111 | 175 179 182 175 170 | 200 207 209 200 187 | 135 138 145 154 | 139 151 148 | 1 ¹ 1 ¹ 1 ¹ | 45 45 49 53 58 | 169 178 185 192 195 | 136 145 142 141 138 | 13 ⁴ 131 133 132 135 | 13: 136 13; 14: 13; | 139 135 133 |
| 26 27 28 29 30 31 | 125 133 133 129 127 123 | 117 128 136 | 168 168 165 168 169 168 | 182 177 177 184 182 | 138 131 135 137 137 | 139 137 139 144 | 1 1 | 63 62 56 52 55 55 | 215 254 259 260 195 179 | 138 139 135 145 136 | 133 131 125 120 112 109 | 13 ¹ 130 120 130 130 | 130 9 124 0 116 |
| Sum | 4,195 | 3,492 | 5,026 | 5,345 | 4,61 | 4,110 0 | 4,7 | 734 | 5,619 | 4,609 | 4,535 | 3,87 | 3,936 4 |
| | | | | Current ' | | | | | | P | eriod 19 | 4 3- 1971 | |
| | | treme Gag Feet | e 9 | Extreme S High | econd Fe | | Average Second | T | otal | | Acre | Feet | |
| Moi | Hi | | w Day | rugo | Day | 200 | Feet | Acr | e Feet | Average | Maxi | mum | Minimum |
| Aug Sej Oct | an. 41.83 42.04 20 147 25 118 eb. 41.85 42.09 117 136 24 105 ar. 41.52 41.85 23 182 1 1 145 pr. 41.12 41.69 23 209 9 160 ay 41.43 42.01 1 177 19 130 author 41.83 42.10 23 151 110 126 ulty 41.61 41.81 26 163 121 145 | | 105 145 160 130 126 145 149 129 109 | 135 125 162 178 149 137 153 181 154 146 | | 8,321 6,926 9,969 10,602 9,144 8,152 9,390 11,145 9,142 8,995 7,684 | 7,080 5,845 6,524 6,704 5,917 5,112 5,054 6,357 6,357 6,538 6,264 | 17 12 14 10 9 9 11 12 | ,160 ,845 ,960 ,489 ,618 ,689 ,390 ,145 ,688 ,710 ,323 | 1,751 1,258 1,008 1,390 629 1,087 817 1,139 1,795 2,081 2,483 1,763 | | | |

^{41.69} # And other days Ø Mean daily

260

29

Dec.

Yearly

41.85

24,573

138,906

6,906

74,376

,811

281, 107

¹⁴⁸ ** Feet below mean sea level

WASTES FROM MEXICALI POTABLE WATER PLANT TO NEW RIVER IN MEXICO

DESCRIPTION: The Potable Water Plant of Mexicali, Baja California, discharges waste water into a canal, approximately 2.5 miles long, that empties into the Rivera Drain and thence into New River, approximately 0.9 mile above the international boundary. The measurements are taken in the wasteway canal 0.4 mile above the confluence with Rivers Drain, 1.2 miles below the plant, and 1.2 miles south of the international boundary.

RECORDS: Based on 49 double current meter measurements made during the year by wading. Data obtained and furnished by the Mexican Section of the Commission. Data available: January 1968 through 1971.

REMARKS: The Potable Water Flant is operated by the State Commission of Public Services of Mexicali and water Data obtained and

in the resolute was related to operated by the best of canals in the Colorado River Irrigation District. The plant was completed in 1963 and began operation on September 28, 1963. Prior to 1968, the volumes wasted were small and infrequent.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|---------------------------------|-----------------------------------|---------------------------------|---------------------------------|--|--|---|--|-------------------------------------|--|---------------------------------|--|
| 1 2 3 4 5 | 4.9 5.7 6.0 6.4 6.7 | 3.5 3.5 3.2 3.2 3.2 | 4.6 4.2 3.5 3.2 2.8 | 3.5 3.9 4.6 4.6 4.6 | 3.5 3.5 3.5 3.5 3.9 | 9.9 8.1 9.2 9.9 6.7 | 6.4 6.4 6.7 5.7 | 9.9 9.9 6.7 7.4 11.7 | 7.8 8.1 8.1 7.8 9.2 | 30.4 9.9 9.9 6.0 4.2 | 8.1 7.1 8.1 6.4 6.0 | 4.6 6.0 3.5 4.9 |
| 6 7 8 9 | 6.4 6.4 6.0 5.7 5.3 | 3.2 3.2 3.2 3.2 2.8 | 2.5 3.2 3.5 4.2 4.6 | 4.6 4.2 4.2 4.2 4.2 | 3.9 3.9 3.9 4.6 6.7 | 6.4 5.7 6.7 6.7 6.7 | 5.7 5.7 5.7 5.7 5.7 | 8.1 9.9 11.7 10.6 8.1 | 7.8 6.0 6.0 5.7 6.4 | 4.9 6.0 4.9 5.7 7.8 | 6.4 7.1 4.9 6.4 7.1 | 5.7 4.6 4.6 4.2 |
| 11 12 13 14 15 | 5.3 4.9 4.6 4.2 4.2 | 2.8 2.8 2.8 2.8 5.3 | 5.3 5.7 6.4 6.0 | 4.2 4.2 3.9 3.9 | 5.3 5.3 6.0 5.7 5. 7 | 7.1 5.3 6.7 4.9 5.3 | 6.7 5.7 6.4 6.4 6. 4 | 13.8 12.4 10.6 10.6 12.4 | 5.7 6.4 6.4 5.7 5.7 | 4.2 4.2 4.9 21.2 6.4 | 5.7 5.7 4.9 6.0 6.0 | 4.2 4.2 3.5 3.5 |
| 16 17 18 19 20 | 3.9 4.2 4.6 4.9 | 6.7 7.8 9.2 10.2 11.7 | 5.7 5.3 4.9 4.6 | 3.9 3.9 3.5 3.5 | 6.4 5.3 7.1 7.1 4.9 | 5.3 6.4 6.4 6.4 6.7 | 8.8 5.7 7.1 5.3 4.9 | 12.4 5.3 6.7 7.4 8.1 | 6.4 6.4 7.8 9.9 12.0 | 6.4 9.9 8.8 6.0 6.0 | 7.8 7.1 7.1 7.1 6.4 | 4.9 5.7 4.6 5.7 4.2 |
| 21 22 23 24 25 | 5.3 5.7 6.0 5.7 5.3 | 10.6 9.9 8.8 8.1 7.1 | 4.2 4.2 3.9 3.5 3.2 | 3.5 3.5 3.2 3.2 3.2 | 5.3 4.6 6.4 6.0 5.7 | 6.7 6.4 6.4 6.7 6.7 | 6.7 6.4 7.1 6.7 8.1 | 10.6 13.8 13.4 8.8 8.1 | 8.1 7.1 10.6 9.2 8.8 | 5.7 6.4 7.8 8.8 8.1 | 7.1 4.2 4.6 4.6 4.9 | 4.2 4.2 4.2 4.9 |
| 26 27 28 29 30 31 | 4.9 4.6 4.2 3.9 3.5 | 6.4 5.3 4.9 | 3.8 2.8 2.8 2.8 2.8 | 3.2 3.5 3.5 3.5 3.5 | 6.4 9.5 10.2 10.2 9.5 8.8 | 6.7 7.1 6.4 7.1 6.7 | 6.7 6.4 6.4 7.1 7.8 6.4 | 6.7 8.8 8.1 9.9 8.8 9.9 | 17.0 14.8 9.9 19.8 25.8 | 9.2 8.8 7.8 8.8 7.8 6.4 | 4.2 4.9 4.0 4.2 | 5.7 4.6 3.5 4.2 4.2 3.5 |
| Sum | 157.9 | 156.8 | 127.5 | 115.5 | 182.2 | 203.1 | 198.5 | 300.5 | 276.5 | 253.2 | 178.2 | 139.8 |

Current Year 1971 Period 1968-1971 Extreme Second Feet Extreme Gage Average Total Acre Feet Feet Second Month High Low Acre Feet Average Maximum Minimum Feet High Day Day 1 1 1.44 0.20 22.6 †12 1.4 4.9 313 203 366 311 871 Feb. 311 157 .23 28 21.2 26 1.4 5.7 1.38 1.28 Mar. .20 6 19.1 1.4 4.2 253 132 233 362 403 Apr. 1.28 .23 8 19.1 3 22 1.4 3.9 229 208 135 238 May 3 6.0 362 290 1.38 .26 21.2 1.8 June 15 † 5 26 403 230 116 1.4 6.7 1.61 -20 26.8 July 6.4 283 394 198 16 1.8 394 1.12 .26 15.5 21.2 596 549 Aug. 1 2 2.1 596 366 200 .30 9.5 1.38 131 Sept. .33 30 46.3 **†**10 2.5 9.2 549 502 388 2.59 308 236 502 139 Oct. 2.99 1 54.7 **†** 5 8.1 Nov. 2í 6.0 354 354 151 6 32.1 .4 1.4 1.90 .10

6.4

0.4

4,543

14.8

54.7

215

3,307

277

4,543

149

2,745

Yearly

1.08

2.99

.23

0.10

[†] And other days

WISTERIA WASTEWAY TO NEW RIVER IN MEXICO

DESCRIPTION: Staff gage located near operator's house upstream from wasteway gates, 1,000 feet downstream from the confluence of the Cerro Prieto and West Main Canals of the Colorado River Irrigation District in Colonia Wisteria, 4.3 miles upstream from the international boundary, 1.9 miles east of the highway to Tijuans at the Tijuana-San Felipe junction, 3.0 miles west of the highway to San Felipe, and 3.1 miles south of Mexicall. The wasteway structure is composed of three rectangular gates, two of which operate manually and one automatically.

OUR SUCROB: Based on gate openings and water surface elevations upstream from the wasteway gates obtained by the Ministry of Hydraulic Resources and 49 check measurements during the year at various locations by the Mexican Section of the Commission. Records computed and furnished by the Mexican Section of the Commission. the Ministry of mydraulic Resources and a check measurements and making the Mexican Section of the Commission. Records computed and furnished by the Mexican Section of the Commission. Records available: January 1951 through 1971. Records reported below are part of the waste flows from the Mexican system of canals discharging into the territory of the United States, which wastes are not to exceed an average annual quantity of 35,000 acre-feet during any successive five-year period under the provisions of Minute No. 197 of the Commission.

EXTREMES: Maximum instantaneous discharge, 675 second-feet on January 24, 1962; minimum discharge, no flow

on various occasions.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| | 14169 | п рапу | Discha | rge m | Second | reet 10 | •• | | | | | |
|----------------------------------|------------------------|------------------|------------------|------------------|-----------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
| 12345 | 1.4 1.1 .7 .4 | 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 |
| 6 7 8 9 | 0 0 0 0 | 0 0 0 | 0000 | 0 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 |
| 11 12 13 14 15 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 |
| 16 17 18 19 20 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 |
| 21 22 23 24 25 | 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 | 0 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 |
| 26 27 28 29 30 31 | 00000 | 0 | 0 0 0 0 0 | 0 0 0 0 | 0 0 0 0 0 | 0 0 0 0 | 00000 | 0 0 0 0 0 | 0 0 0 0 | 0 0 0 0 0 0 | 0 0 0 0 | 0 0 0 0 0 |
| Sum | 3.5 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |

| | | | | Current Y | ear 19 | 971 | | | Per | iod 1951-197: | L |
|---------|---------|-----|--|------------|--------|-----|---------|-----------|---------|---------------|---------|
| | Extreme | | Ø | Extreme Se | cond F | eet | Average | Total | | Acre Feet | |
| Month _ | Fe | et | | High | - | Low | Second | | Average | Maximum | Minimum |
| 1 | High | Low | Day | | Day | | Feet | Acre Feet | Average | Maximum | Minimum |
| Jan. | | | Ι, | 1.4 | 1 5 | ۱ ، | 0 | 7.0 | 1,645 | 8,735 | 0 |
| Feb. | | | 1 1 | 0 | 1 1 | 1 0 | 0 | 0 | 1,021 | 7,218 | 0 |
| Mar. | | | 1 | ŏ | 1 | Ō | 1 0 | 0 | 758 | 2,568 | 0 |
| Apr. | | | | ő | | l o | l ō | 0 | 734 | 4,433 | 0 |
| May | | Ì | | ŏ | 1 | l ŏ | ō | 0 | 516 | 1,892 | 0 |
| June | | | | l ő | ĺ | 0 | 0 | 1 0 | 303 | 1,450 | 0 |
| July | | | | ŏ | 1 | l o | l ò | 0 | 239 | 2,040 | 0 |
| Aug. | | | 1 | ١٠٥ | 1 | l ŏ | . 0 | 0 | 464 | 1,926 | 0 |
| Sept. | | ļ | 1 | ١٥ | | l ŏ | 1 0 | 0 | 643 | 2,915 | 0 |
| Oct. | | | 1 | ١٥ | | ŏ | l o | 0 | 880 | 2,993 | 0 |
| Nov. | | | | ۱ŏ | 1 | l o | 0 | 0 | 983 | 3,768 | 0 |
| Dec. | | | 1 | ő | 1 | 0 | 0 | 0 | 1,445 | 8,669 | 0 |
| Yearly | | | | 1.4 | | 0 | 0 | 7.0 | 9,630 | 27,083 | 7.0 |

[#] And other days

WASTE WATERS FROM MEXICAN SYSTEM OF CANALS ENTERING THE UNITED STATES

DESCRIPTION: During 1971, the discharge to the New River in Mexico was from Wisteria Wasteway, located 2.9 miles upstream from the international boundary in Colonia Wisteria, and from the Mexicali Potable Water Plant which discharges, by canal, into the Rivera Drain thence to New River.

RECORDS: Computations of flows from Wisteria Wasteway are based on gate openings and water-stage elevations upstream from the wasteway made by the Ministry of Hydraulic Resources, and of weekly measurements taken downstream from the weir by the Mexican Section of the Commission. Computation of flows from the Potable Water Plant are based on weekly readings from the discharge canal. Data obtained and furnished by the Mexican Section of the Commission. Records available: Wisteria Wasteway, January 1951 through 1971; Sifon Wasteway, January 1952 through April 1964; Fueblo Nuevo Wasteway, January 1955 through 1971; Sifon Wasteway, January 1968 through 1971. Water Plant, January 1968 through 1971.

REMARKS: Mean daily discharges for Wisteria Wasteway and the Potable Water Flant are shown on pages 60 and 59, respectively in this bulletin. Records for Pueblo Nuevo and Sifon Wasteways are shown in previously published bulletins, 1960 through 1965; flows from these two wasteways are used for irrigation and no longer reach New River.

| 14 -1 | C Y 1051 | | Period 1956-1971 | |
|--------------------|-------------------|---------|------------------|---------|
| Month | Current Year 1971 | Average | Maximum | Minimum |
| January | 320 | 1,583 | 8,758 | 15.4 |
| February | 311 | 1,070 | 7,281 | 19.6 |
| March | 253 | 669 | 2,610 | 21.7 |
| Ap r il | 229 | 480 | 2,843 | 16.1 |
| May | 362 | 337 | 1,141 | 9.1 |
| June | 403 | 246 | 1,477 | 0 |
| July | 394 | 173 | 394 | 0 |
| August | 596 | 383 | 1,413 | 0 |
| September | 549 | 454 | 2,081 | 21.0 |
| October | 502 | 593 | 2,024 | 8.4 |
| November | 354 | 834 | 3 , 784 | 0 |
| December | 277 | 1,493 | 8,691 | 0 |
| Yearly | 4,550 | 8,315 | 27,430 | 399 |

SALTON SEA - ELEVATIONS OF WATER SURFACE

DESCRIPTION: Water-stage recorder and staff gage located on the western shore of the Salton Sea, 15.5 miles northwest of Westmoreland, Imperial County, California. The Salton Sea is the sink of a closed basin which has a drainage area of 8,360 square miles. Zero of the gage is 250.00 feet below mean sea level, U. S. C. & G. S. datum.

RECORDS: Records of water surface elevations available from November 1904 through 1971. From January 1925 to October 22, 1951, once monthly records of elevations were collected by Imperial Irrigation District from a bench mark at Figtree John's Spring about 22 miles northwest along the western shore from the present gage. Since October 24, 1951, a continuous record of gage heights has been obtained by the U. S. Geological Survey at new gaging station published as "Salton Sea near Westmoreland, California". The elevation of the old station is at a datum of one foot higher than that of the present station. All records reported below and the area and capacity table are adjusted to the datum of the present station.

and the area and capacity cause are adjusted to the datum of the present scattor. REMARKS: Runoff from the basin, irrigation drainage and waste water from Imperial and Coachella Valleys in the United States, and drainage and waste water from part of the Mexicali Valley in Mexico discharge into the Salton Sea. Water from Mexico enters the United States in the Alamo and New River channels. The bottom of the sea is 277.7 feet below mean sea level, U. S. C. & G. S. datum.

GOLDON OF THE SER IS 211.1 Feet SELOW MERAN SER IEVEL, O. S. C. & C. S.
Mean Daily Water Surface Elevation in Feet below Mean Sea Level - 1971

| | 172 | ean Da | | | | | | | | | | |
|----------------------------------|--|---|--|---|--|---|--|--|---|--|---|--|
| Day | Jan. | Feb | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
| 1 2 3 4 5 | 232.6 232.6 232.6 232.6 232.5 | 232.3 232.3 232.3 232.3 232.3 | 232.0 232.0 232.0 232.0 232.0 | 231.8 231.8 231.8 231.8 231.8 | 231.8 231.8 231.8 231.8 231.8 | 231.9 231.9 231.9 231.9 231.9 | 231.9 231.9 231.9 231.9 231.9 | 232.1 232.1 232.1 232.1 232.1 | 232.3 232.3 232.3 232.3 232.3 | 232.5 232.5 232.5 232.5 232.5 | 232.6 232.6 232.6 232.6 232.6 | 232.5 232.5 232.5 232.5 232.5 |
| 6 7 8 9 | 232.5 232.5 232.5 232.5 232.5 | 232.3 232.2 232.2 232.2 232.2 | 232.0 232.0 232.0 232.0 232.0 | 231.7 231.7 231.7 231.7 231.7 | 231.8 231.8 231.8 231.8 231.8 | 231.9 231.9 231.9 231.9 231.9 | 231.9 232.0 232.0 232.0 232.0 | 232.1 232.1 232.1 232.1 232.1 | 232.3 232.3 232.3 232.3 232.3 | 232.5 232.5 232.5 232.5 232.5 | 232.6 232.6 232.6 232.6 232.6 | 232.5 232.5 232.5 232.5 232.5 |
| 11 12 13 14 15 | 232.5 232.5 232.5 232.5 232.5 | 232.2 232.2 232.2 232.2 232.1 | 232.0 232.0 231.9 231.9 231.9 | 231.7 231.7 231.7 231.7 231.7 | 231.8 231.8 231.8 231.8 231.8 | 231.9 231.9 231.9 231.9 231.9 | 232.0 232.0 232.0 232.0 232.0 | 232.1 232.1 232.1 232.1 232.1 | 232.4 232.4 232.4 232.4 232.4 | 232.5 232.5 232.5 232.5 232.5 | 232.6 232.6 232.6 232.5 232.5 | 232.5 232.5 232.5 232.5 232.5 |
| 16 17 18 19 20 | 232.5 232.5 232.5 232.5 232.5 | 232.1 232.1 232.1 232.1 232.1 | 231.9 231.9 231.9 231.9 231.9 | 231.7 231.7 231.8 231.8 231.8 | 231.8 231.8 231.8 231.8 231.8 | 231.9 231.9 231.9 231.9 231.9 | 232.0 232.0 232.0 232.0 232.0 | 232.1 232.1 232.1 232.1 232.1 | 232.4 232.4 232.4 232.4 232.4 | 232.5 232.5 232.5 232.6 232.6 | 232.5 232.5 232.5 232.5 232.5 | 232.5 232.5 232.4 232.4 232.4 |
| 21 22 23 24 25 | 232.4 232.4 232.4 232.4 232.4 | 232.1 232.1 232.1 232.1 232.0 | 231.8 231.8 231.8 231.8 231.8 | 231.8 231.8 231.8 231.8 231.8 | 231.8 231.8 231.8 231.8 231.8 | 231.9 231.9 231.9 231.9 231.9 | 232.1 232.1 232.1 232.1 232.1 | 232.2 232.2 232.2 232.2 232.2 | 232.4 232.4 232.4 232.4 232.4 | 232.6 232.6 232.6 232.6 232.6 | 232.5 232.5 232.5 232.5 232.5 | 232.4 232.4 232.4 232.4 232.4 |
| 26 27 28 29 30 31 | 232.4 232.4 232.4 232.4 232.3 232.3 | 232.0 232.0 232.0 | 231.8 231.8 231.8 231.8 231.8 231.8 | 231.8 231.8 231.8 231.8 231.8 | 231.8 231.8 231.8 231.8 231.9 231.9 | 231.9 231.9 231.9 231.9 231.9 | 232.1 232.1 232.1 232.1 232.1 232.1 | 232.2 232.2 232.2 232.2 232.2 232.2 | 232.5 232.5 232.5 232.5 232.5 | 232.6 232.6 232.6 232.6 232.6 232.6 | 232.5 232.5 232.5 232.5 232.5 | 232.4 232.4 232.4 232.4 232.4 232.3 |
| Avg | . 232.5 | 232.2 | 231.9 | 231.8 | 231.8 | 231.9 | 232.0 | 232.1 | 232.4 | 232.5 | 232.5 | 232.5 |

| | • / | -3/ | | | |
|--|--|--|--|--|---|
| C | urrent Yes | r 1971 | p | eriod 19 35-1 9 | 1 |
| | | me Elev. eet | | Elevation Feet | |
| Month | High | Low | Average | # Max. | ‡ Min. |
| Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec. | 232.3 232.0 231.8 231.7 231.8 231.9 231.9 232.1 232.3 232.5 232.5 232.5 | 232.6 232.3 232.0 231.8 231.9 231.9 232.1 232.2 232.5 232.6 232.6 232.6 | 238.63 238.42 238.95 237.87 237.86 238.03 238.19 238.39 238.58 238.66 238.66 238.49 | 232.05 231.79 231.57 231.54 231.71 231.92 232.17 232.49 232.49 232.30 232.23 | 249.3 248.8 248.6 248.7 248.5 248.8 249.1 249.4 249.8 250.0 249.6 |

238.14

| Area | and Capaci | ty Table |
|---|---|---|
| Elevation | Area | Capacity |
| Feet below M.S.L. | Acres | Acre-Feet |
| 277.7 274.0 270.0 266.0 266.0 256.0 252.0 244.0 240.0 235.0 230.0 220.0 210.0 | 0 20,600 62,900 94,600 122,600 134,700 148,800 179,700 196,900 221,800 235,800 262,000 288,500 315,500 | 25,700 188,700 510,600 1,170,000 2,250,000 4,315,000 4,315,000 5,360,000 6,504,000 8,993,000 11,740,000 |

232.6

231.7

Yearly

232.06

250.0

Ø Mean daily # Mean monthly

[#] Reading near first day of month

CHEMICAL ANALYSES OF WATER SAMPLES 1971

The tables below are based on quarterly samples from the Alamo and New Rivers taken and analyzed by the State of California Department of Water Resources. Beginning December 1971, not all constituents analyzed.

Samples from the Alamo River are taken north of the international boundary at upstream end of box culvert under the All-American Canal. Flow at this point includes drainage flows across international boundary and flows from drain intercepts along toe of south bank of All-American Canal. Samples from New River are taken from the right bank at road bridge 450 feet north of international boundary. Records of sampling extend from April 1951 through 1971.

To convert milligram equivalents to parts per million by weight, multiply each ion by its appropriate conversion factor. These factors are: Ca, 20.04; Mg, 12.16; Na, 22.99; (CO₃ plus ECO₃) expressed as CO₃, 30.00; SO₁, 48.03; Cl, 35.45; NO₃, 62.00 To convert tons per acre-foot to parts per million, multiply tons per acre-foot by 73.5. Electrical conductivity, reported in the tables as ECX10⁵ at 25°C, is a relative measure of the total salt concentration.

| | No. | Disso | lved Solids | | | | | Mea | n Mil | ligram | Equiva | lents p | er Lite | r |
|-------|-----|------------------------------|---------------|-----------------|--|---------------|-----------------|-----|-------|--------|--|-----------------|---------|----|
| Month | of | Tons Per Acre- Foot | Total Tons | ECx106 @25°C | | % Na ** | % CI **** | C. | Mg | Na | со, + † + † + | so ₄ | CI | ю, |

Alamo River

| Jan. Feb. | | | | | | | | | | | | | | |
|-----------------------|----|------|-------|------|-----|----|----|------|------|-------|------|-------|-------|------|
| Mar. Apr. | 1 | 2.94 | 3,281 | 0.82 | 7.8 | 57 | 44 | 7.83 | 6.91 | 19.49 | 4.38 | 14.40 | 15.09 | 0.06 |
| May June July | 1 | 3.36 | 3,533 | .84 | 8.3 | 56 | 49 | 9.43 | 7.89 | 21.75 | 4.08 | 15.72 | 19.15 | .06 |
| Aug. Sept. Oct. | 1 | 2.54 | 2,852 | .66 | 7.7 | 55 | 45 | 7.19 | 6.08 | 16.31 | 4.27 | 12.01 | 13.54 | .06 |
| Nov. Dec.* | 1 | 3.02 | 3,600 | | 7.9 | | | | | | | 14.44 | 16.22 | |
| Total | Į. | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

New River

| | | | | _ | | | Ĺ. | | | | | | | |
|-----------------------|---|------|-------|---|-----|----|----|-------|-------|-------|-------|-------|-------|------|
| Total | 4 | | | ĺ | | l | | i | | | l | | | |
| Oct. Nov. Dec.* | 1 | 6.31 | | | | | | | | | | 14.93 | 54.85 | |
| July Aug. Sept. | 1 | 5.51 | 6,234 | | 7.3 | 65 | 68 | 12.18 | 10.52 | 42.85 | 4.98 | 16.35 | 44.83 | .02 |
| Apr. May June | 1 | 5.29 | 6,427 | | 7.7 | 70 | 74 | 9.68 | 10.77 | 46.93 | 13.86 | 3.89 | 49.53 | .02 |
| Jan. Feb. Mar. | 1 | 5.74 | 6,560 | | 7.2 | 65 | 67 | 4.59 | 18.74 | 43.94 | 5.30 | 17.12 | 44.98 | 0.08 |

^{*} Partial analysis

^{**} Percent of total cations

^{***} Percent of total anions

The following tables show electrical conductivity expressed in mhos per centimeter x 10⁶ at 25°C of individual water samples from the wasteway canal at the Potable Water Plant in Mexicali, Baja California and the New River in Mexico at the international boundary. Samples from the Potable Water Plant and the New River are taken by the Mexican Section of the Commission, and determinations are made by the Ministry of Hydraulic Resources of Mexico.

Electrical conductivity is a relative indication of the concentration of dissolved solids in the water samples.

| Date @25°C Date @25°C Date @25°C Date @25°C | Date @25°C Date @25°C | Date @25°C | Date @25°C |
|---|-----------------------|------------|------------|
|---|-----------------------|------------|------------|

Mexicali Potable Water Plant to New River

| 16 1700 28 1600 9 1850 | | January 5 2600 16 1900 30 1875 February 6 1850 13 2200 | February 20 2100 March 6 2000 13 2000 20 2000 27 1950 | April 3 1900 30 2050 May 8 2000 13 2000 22 1950 | June 5 2150 11 2000 18 2100 July 2 2000 9 1900 | July 24 2300 30 2200 August 6 2200 14 2125 21 2125 | September 4 2100 10 2000 18 2000 25 2000 October 2 1800 | October 16 1900 23 2000 30 1900 November 6 1900 13 1900 | November 27 2200 December 4 2000 11 2000 18 2150 31 2100 |
|------------------------|--|--|---|---|--|--|---|---|--|
|------------------------|--|--|---|---|--|--|---|---|--|

New River at International Boundary

| January 5 7500 16 6500 30 7250 February 6 6100 13 6500 | February 20 6500 March 6 6000 13 6100 20 6500 27 6500 | April 3 6500 30 6000 May 8 6500 22 6500 29 6500 | June 5 6500 11 6500 18 6500 July 2 6500 9 6000 | July 24 6000 31 6000 August 6 6000 14 6500 21 6400 | September 4 5900 10 6000 18 6250 25 6000 October 2 6500 | October 16 5000 23 6500 30 6500 November 6 6500 13 6500 | November 27 6500 December 4 6500 11 6250 18 7000 31 7000 |
|--|---|---|--|--|---|---|--|
| 13 6500 | 31 6500 | 29 0,00 | 17 6000 | 28 4900 | 9 6000 | 19 6500 | |



COTTONWOOD CREEK ABOVE MORENA DAM, CALIFORNIA

DESCRIPTION: Staff gage located on east side of outlet tower immediately upstream from face of Morena Dam. The dam is located on Cottonwood Creek 1.8 miles upstream from the mouth of Hauser Creek, 8.5 miles upstream from Barrett Dam, and about 20 miles upstream from the international boundary. Zero of gage is 2,882.4 feet above mean sea level, U. S. C. & G. S. datum.

2,002.4 feet above mean sea level, U.S. C. & G. S. Catum.

RECORDS: Reservoir inflows shown below were computed from monthly reservoir records of storage, releases, spills, leakage, evaporation, and rainfall, by the International Boundary and Water Commission, United States Section. They represent all water reaching Morens Reservoir, including rainfall on reservoir water surface. Basic data were furnished by the city of San Diego, California. Records available: April 1911 through 1971.

REMARKS: Storage began in Morena Reservoir March 1910. Reservoir capacity and area ratings date from 1910 when Morena Dam was completed. Records for 1971 computed on basis of area-capacity curves determined from 1948 resurvey. Various changes have been made to the spillway section since construction of the dam. Elevation of present crest of ungsted spillway is 157.00 feet, gage datum. Reservoir capacity at spillway crest, 1948 survey, is 50,210 acre-feet. The entire capacity of Morena Reservoir is used to furnish a part of the water supply of the city of San Diego, California. Water is released from Morena Reservoir days of the city of San Diego, California.

ervoir down Cottomwood Creek to Barrett Reservoir as required.

EXTREMES: Prior to 1937, maximum monthly inflow, 37,200 acre-feet, January 1916; minimum, no flow during parts of many years.

| | | | Period 1937-1971 | |
|-----------|-------------------|---------|------------------|---------|
| Month | Current Year 1971 | Average | Maximum | Minimum |
| January | 33.7 | 459 | 3,520 | 4.8 |
| February | 69.0 | 1,131 | 16,700 | 8.0 |
| March | 67.2 | 1,682 | 13,220 | 19.3 |
| April | 23.4 | 1,067 | 11,490 | 3.3 |
| May | 47.6 | 378 | 3,550 | 0 |
| June | 37.0 | 193 | 1,660 | 0 |
| July | 6.0 | 136 | 1,010 | 0 |
| August | 96.0 | 99.6 | 1,260 | 0 |
| September | 5.0 | 67.9 | 1,070 | 0 |
| October | 61.0 | 79.9 | 1,270 | 0 |
| November | 3.3 | 146 | 1,380 | 0 |
| December | 209 | 485 | 3,590 | 4.4 |
| Yearly | 658.2 | 5,924.4 | 39,439 | 121 |

COTTONWOOD CREEK BELOW MORENA DAM, CALIFORNIA

DESCRIPTION: Two water-stage recorders, one on the upstream side of the southeast abutment of Morena Dam for measuring head on the spillway crest and one immediately below the dam with a rectangular control weir for measuring ordinary reservoir releases, and cableway located about 0.8 mile downstream from the dam. Dis-

for measuring ordinary reservoir releases, and cableway located about 0.8 mile downstream from the dam. Discharge measurements made at the cableway include leakage, controlled releases, and spillway discharges.

RECORDS: Monthly records shown below represent the water available immediately below Morena Dam, consisting of spillway waste, draft, and leakage from the dam. They are computed by the International Boundary and Water Commission, United States Section, from basic data furnished by the city of San Diego, California. Records available: January 1911 through 1971.

REMARKS: Flows at this station are regulated by Morena Dam; storage began March 1910. Water is released from Morena Reservoir as required and flows down the natural channel of Cottonwood Creek to Barrett Reservoir. There are no major diversions above Morena Dam.

EXTREMES: Prior to 1937, maximum monthly discharge, 21,400 acre-feet, February 1916; minimum, zero during December 1936.

December 1936.

| N11 | C Y 1071 | | Period 1937-1971 | |
|-----------|-------------------|-------------------|------------------|---------|
| Month | Current Year 1971 | Average | Maximum | Minimum |
| January | 0.2 | 124 | 1,700 | 0.2 |
| February | 6.1 | 348 | 4,260 | .2 |
| March | 0 | 283 | 1,731 | 0 |
| April | 0 | 863 | 12,950 | 0 |
| May | 0 | 235 | 3,040 | 0 |
| June | 0 | 323 | 7,360 | 0 |
| July | 0 | 184 | 2,340 | 0 |
| August | 0 | 153 | 1,550 | 0 |
| September | 0 | 301 | 5,880 | 0 |
| October | 0 | 89.4 | 529 | 0 |
| November | 23.7 | 121 | 1,260 | 0 |
| December | 0 | 33 ¹ 4 | 5,350 | 0 |
| Yearly | 30.0 | 3,358.4 | 24,825 | 15.6 |

COTTONWOOD CREEK ABOVE BARRETT DAM, CALIFORNIA

ESCRIPTION: Staff gage located immediately upstream from face of dam on west side of outlet tower. Bar-rett Dam is located on Cottonwood Creek 8.5 miles downstream from Morena Dam, 1 mile downstream from the mouth of Pine Valley Creek and about 12 miles upstream from the international boundary. Zero of gage DESCRIPTION: is 1,446.12 feet above mean sea level, U. S. C. & G. S. datum.

RECORDS: Records reported below represent all water reaching Barrett Dam from the sub-basin below Mo-rena Dam including rainfall on the reservoir water surface. Leakage, releases, and spills from Morena Reservoir are not included. The inflows were computed from monthly reservoir records of storage, releases, spills, leakage, evaporation and rainfall furnished by the city of San Diego, California. Records available: January 1921 through 1971. Records of stream flow for a station at the dam site are also available for the periods 1906-1915 and 1917-1920.

able for the periods 1906-1915 and 1917-1920.

REMARKS: Storage began at Barrett Reservoir in January 1921. The area-capacity-elevation curves used in the inflow calculations are dated 1948, 1951 and 1955 and were furnished by the city of San Diego, California. Capacity of reservoir at top of flash gates on spillway (gage height, 163.83) is 14,755 acre-feet. Capacity at spillway crest (gage height, 160.88 feet) is 37,950 acre-feet. Dead storage, 719 acre-feet below lowest outlet (gage height, 58.88 feet) is included in these capacities. The entire capacity of Barrett Reservoir is used to furnish a part of the water supply of the city of San Diego, California.

EXTREMES: Prior to 1937, maximum monthly discharge, 54,800 acre-feet, February 1927; minimum, no flow during several months of various years.

| | | - | Period 1937-1971 | |
|-----------|-------------------|---------|------------------|---------|
| Month | Current Year 1971 | Average | Maximum | Minimum |
| January | 171 | 597 | 3,430 | 5.2 |
| February | 130 | 1,642 | 26,790 | 7.6 |
| March | 115 | 2,702 | 18,860 | 14.1 |
| April | 79.8 | 1,787 | 21,630 | 10.2 |
| May | 60.9 | 548 | 5,130 | 0 |
| June | 8.6 | 225 | 1,730 | 0 |
| July | 3.9 | 144 | 1,010 | 0 |
| August | 10.7 | 86.9 | 579 | ٥ |
| September | 1.0 | 99.4 | 759 | 0 |
| October | 9.1 | 62.8 | 645 | .1 |
| November | 3.0 | 130 | 1,200 | 0 |
| December | 84.3 | 493 | 3,380 | 5.5 |
| Yearly | 677.3 | 8,517.3 | 59,387 | 129 |

DULZURA CONDUIT BELOW BARRETT DAM, CALIFORNIA

DESCRIPTION: Water-stage recorder 0.5 mile downstream from Barrett Dam on right bank of Dulzura Conduit 50 feet upstream from road crossing to Barrett Dam. Elevation of gage has not been determined.

Computed on basis of head on control section of flume, as measured by water-stage recorder, and curve determined from current meter measurements. Records obtained and furnished by the city of San RECORDS: rating

rating curve determined from current meter measurements. Records obtained and rurmisned by the city of san Diego, California. Records available: January 1909 through 1971.

EMARKS: Barrett Dam was completed in 1921. Prior to this date the intake of Dulzura Conduit was located 1.5 miles upstream. The conduit carries diversions from Barrett Reservoir on Cottomwood Creek westerly across the divide into Otey Reservoir for municipal use by the city of San Diego. Prior to September 30, 1958, station was located 8 miles along the conduit from Barrett Dam, being reported as "Dulzura Conduit Near Dulzura" and the draft from Barrett Reservoir was computed from the discharges obtained at the conduit gaging station, multiplied by the factor 1.05 to allow for channel losses in the reach from the reservoir to the gaging station.

TREMES: Since 1937: Maximum mean daily discharge, 55 second-feet on March 15, 1954; minimum discharge,

no flow for long periods on many occasions.

Mean Daily Discharge in Second Feet 1971 — Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|------------------|---------|-----------------------|------------------|-----------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| 1 2 3 4 5 | 0 0 0 | 0 0 0 0 | 00000 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 |
| 6 7 8 9 | 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 |
| 11 12 13 14 15 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 | 00000 | 0 0 0 0 |
| 16 17 18 19 20 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 |
| 21 22 23 24 25 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 |
| 26 27 28 29 30 31 | 0 0 0 0 0 | 0 0 0 | 0 0 0 0 0 | 0 0 0 0 | 0 0 0 0 0 | 0 0 0 0 | 0 0 0 0 0 | 0 0 0 0 0 0 | 0 0 0 0 | 0 0 0 0 0 0 | 0 0 0 0 | 0 0 0 0 0 0 |
| Sum | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |

| | | | Extreme Second Feet | | | | | | iod 1937-197 | 1 | |
|---------|---------|-----|---------------------|------|------|---------|--------|-----------|--------------|---------|---------|
| | Extreme | | Extreme Second Feet | | | Average | | Acre Feet | | | |
| Month _ | Feet | | ٠ | High | High | | Second | | | | T |
| | High | Low | Day | | Day | Day | Feet | Acre Feet | Average | Maximum | Minimum |
| Jan. | | | | | | | | 0 | 406 | 2,350 | |
| Feb. | | | | | 1 | | | 0 | 408 | 2,130 | 0 |
| Mar. | | | | | | | | 0 | 547 | 2,330 | 0 |
| Apr. | | | 1 | | | | - | 0 | 880 | 2,860 | 0 |
| May | | | | | | | | 0 | 1,003 | 3,040 | 0 |
| June | | | | | 1 | | | 0 | | 2,920 | 0 |
| July | | | | | 1 | | | 1 0 | 842 | 2,920 | 0 |
| Aug. | | | | | | 1 | | 0 | 729 | 2,820 | 0 |
| Sept. | | | | | | 1 | | 0 | 473 | 2,320 | 0 |
| Oct. | | | 1 ' | | | | 1 | 0 | 362 | 2,450 | 0 |
| Nov. | | | 1 | | - | İ | | 0 | 499 | 2,760 | 0 |
| Dec. | | | | | | | | 0 | 461 | 2,305 | 0 |
| Yearly | | | | | | | | 0 | 7,629 | 27,170 | 0 |

COTTONWOOD CREEK BELOW BARRETT DAM, CALIFORNIA

DESCRIFTION: Water-stage recorder and cableway located about 2.5 miles downstream from Barrett Dam and 0.5 mile upstream from Rattlesnake Canyon for measuring Barrett Dam spills, and staff gage and control weir located immediately below the dam for measuring leakage. The elevation of the gage is about 1,000 feet (from topographic map).

topographic map). EECORDS: Data furmished by the city of San Diego, California. Prior to January 1953, the records were furnished by the city of San Diego and reviewed and revised by the United States Section of the Commission. The recorder is to be operated only when Barrett Reservoir is near or above spillway level. There have been no spillway discharges since May 1943. Spillway discharges included in the period record below were computed by the city of San Diego from the head on the spillway crest, read on the reservoir gage, and applied to a broad-crested weir formula. Records available: January 1921 through 1971. Storage began in Barrett Reservoir in January 1921.

RDMARKS: Records reported below represent the water available in the natural channel of Cottonwood Creek immediately below Barrett Dem. Records of draft from Barrett Reservoir are not included inasmuch as all releases are made to Dulzura Condmit which transports water outside the basin. Leakage is mainly through the orbitary against

the spillway gates. EXTREMES: Prior to 1937, meximum monthly discharge 38,400 acre-feet February 1927; minimum, no flow during several months of various years.

| | A | | Period 1937-1971 | | |
|-----------|-------------------|---------|------------------|---------|--|
| Month | Current Year 1971 | Average | Maximum | Minimum | |
| January | o | 17.2 | 590 | o | |
| February | 0 | 29.4 | 990 | 0 | |
| March | 0 | 791 | 13,390 | 0 | |
| April | o | 1,161 | 33,400 | 0 | |
| May | o | 263 | 7,520 | 0 | |
| June | 0 | 37.1 | 890 | 0 | |
| July | 0 | 2.1 | 21 | 0 | |
| August | 0 | 1.8 | 21 | 0 | |
| September | 0 | 1.5 | 21 | 0 | |
| October | 0 | 1.2 | 21 | 0 | |
| November | 0 | 1.0 | 15 | 0 | |
| December | 0 | 1.5 | 21 | 0 | |
| Yearly | 0 | 2,307.8 | 50,364 | 0 | |

COTTONWOOD CREEK ABOVE TECATE CREEK NEAR DULZURA, CALIFORNIA

DESCRIPTION: Water-stage recorder and cableway located 1.6 miles upstream from the international land boundary between the United States and Mexico, 0.8 mile upstream from the confluence with Tecate Creek, and 5.1 miles south of Dulzura, California. Low water discharge measurements are made by wading at the gage; high water measurements are made from the cableway which is located 700 feet downstream from the gage. Zero of gage is 560.40 feet above mean sea level. U. S. C. & G. S. datum.

gage is 569.40 feet above mean sea level, U.S.C. & G.S. datum.

RECORDS: Based on a continuous record of gage heights and current meter measurements or observation of no flow generally made twice each month. Records obtained and furnished by the U.S. Geological Survey. Records evel below. October 1024 through 1021

ords available: October 1936 through 1971.

REMARKS: Flow is largely controlled by Barrett and Morena Reservoirs, 10 and 18 miles, respectively, upstream from this station. During 1971, there were no releases or spills to the natural channel of Cottonwood Creek at Barrett Dam, the lowermost dam in Cottonwood Creek Basin.

EXTREMES: Maximum discharge 4,340 second-feet February 7, 1937 (gage height 9.65 feet), from rating curve extended above 1,500 second-feet by logarithmic plotting. Minimum discharge, no flow during part of each year.

Mean Daily Discharge in Second Feet 1971 --- Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|---------------------------------|----------------------------------|---------------------------------|-----------------------------|---------------------------------|---------|---------|-----------|------------------|------------------|------------------|-----------------------|
| 1 2 3 4 5 | 0.06 2.00 .77 .27 | 0.08 .07 .07 .06 .07 | 0.22 .13 .10 .12 | 0.03 .01 0 0 | 0.04 .03 .02 .01 | 0000 | 0000 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 |
| 6 7 8 9 | .19 .17 .19 .19 | .07 .08 .08 .07 .06 | .07 .04 .03 .04 .06 | 0 0 0 0 | .01 .07 .25 .14 .09 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 |
| 11 12 13 14 15 | .19 .19 .32 .20 | .05 .05 .05 .05 | .09 .09 .47 .47 | 0 0 0 0 | .05 .04 .03 .02 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 |
| 16 17 18 19 20 | .12 .10 .09 .06 | .12 .96 .61 .37 | .25 .22 .17 .10 | 0 0 .12 .12 .07 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 |
| 21, 22, 23, 24, 25 | .07 .10 .09 .08 | .24 .22 .71 .58 .37 | .09 .07 .09 .10 | .07 .06 .04 .03 | 0 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 |
| 26 27 28 29 30 31 | .08 .07 .06 .06 .06 | .23 .18 .17 | .10 .09 .07 .05 .05 | .07 .09 .07 .07 | 0 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 0 | 0 0 0 | 0 0 0 0 0 | 0 0 0 0 | 0 0 0 0 0 |
| Sum | 6.53 | 6.18 | 4.11 | 0 .94 | 0,82 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |

| | | | | Current Y | ear | 1971 | | 1 | Peri | od 1937-1971 | | |
|---------|----------------------|-----|-------------|------------|-----------|------|---------|-----------|--------------|--------------|---------|--|
| | Extreme Gage Feet | | ø | Extreme Se | cond Feet | | Average | Total | Acre Feet | | | |
| Month _ | | r | High | | - | Low | Second | Acre Feet | Average | Maximum | Minimum | |
| | High | Low | Day | | Day | Feet | Average | | Maximum | Minimum | | |
| Jan. | | i | 2 | 2.0 | 7 1 | 0.06 | 0.21 | 13 | 200 | 1,190 | 0 | |
| Feb. | | | 17 | .96 | 711 | .05 | .22 | 12.3 | 6 3 9 | 9,940 | 0 | |
| Mar. | | | f13 | .47 | 8 | .03 | .13 | 8.2 | 1,707 | 20,880 | 0 | |
| Apr. | | | 1 18 | .12 | f 3 | 0 | .031 | 1.9 | 610,6 | 40,240 | 0 | |
| May | | 1 | 8 | .25 | 116 | 0 | .027 | 1.6 | 374 | 10,040 | 0 | |
| June | | | | 0 | 1 | 0 | 0 | 0 | 71.1 | 1,590 | 0 | |
| July | | İ | | Э | 1 | 0 | 0 | 0 | 8.0 | 206 | 0 | |
| Aug. | | l . | | 0 | 1 1 | 0 | 0 | 0 | .14 | 7.7 | 0 | |
| Sept. | | 1 | 1 | 0 | | 0 | 0 | 0 | 2.1 | 72 | 0 | |
| Oct. | | | | 0 | | 0 | 0 | 0 | 4.1 | 101 | 0 | |
| Nov. | | | | Ó | 1 | 0 | 0 | 0 | 22.6 | 440 | 0 | |
| Dec. | | | | Ō | | 0 | 0 | 0 | 145 | 1,316 | 0 | |
| Yearly | | | | 2.0 | 1 | 0 | 0.05 | 37.0 | 4,783.3 | 66,700 | 0 | |

f And other days

Ø Mean daily

CAMPO CREEK NEAR CAMPO, CALIFORNIA

DESCRIPTION: Water-stage recorder and broad-crested weir on left bank, 0.5 mile upstream from the international land boundary between the United States and Mexico, just upstream from bridge on California State Highway 94, 3.5 miles southwest of Campo, California. Low water discharge measurements are made by wading at the gage; high water measurements are made from the bridge. Zero of gage is 2,178.92 feet above mean sea level, U.S. C. & G. S. datum.

RECORDS:

O.S. C. actum.

SCORDS: Based on current meter measurements and observation of no flow. Records obtained and furnished by the U.S. Geological Survey. Records available: October 1936 through 1971.

MARKES: Campo Creek originates in the United States and flows southwestward into Mexico where it joins Tecate Creek. The flow at this station is partially regulated by a small conservation reservoir a quarter REMARKS: of a mile upstream, completed in August 1956.

of a mire upstream, completes in August 1971, 12.0 c. f. s. on August 10 (gage height 1.82 feet); no flow October 7, 8, 10-13. Maximum discharge 830 second-feet, February 6, 1937 (gage height 4.80 feet, present datum), from rating curve extended above 110 second-feet on beat of velocity-depth relation and cross-section area at the control. Minimum discharge, no flow during part of most years.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|---------------------------------|----------------------------------|---------------------------------|----------------------------------|----------------------------------|---------------------------------|--|----------------------------------|---------------------------------|----------------------------------|---------------------------------|---------------------------------|
| 1 2 3 4 5 | 0.09 .20 .09 .09 | 0.09 .09 .10 .08 .09 | 0.11 .10 .09 .08 | 0.08 .09 .09 .08 .08 | 0.06 .06 .06 .06 .07 | 0.06 .07 .07 .07 | 0.09 .08 .08 .08 | 0.03 .02 .01 .02 .02 | 0.02 .02 .02 .02 | 0.02 .02 .02 .02 .01 | 0.02 .02 .02 .02 | 0.03 .03 .04 .06 |
| 6 7 8 9 | .09 .09 .09 .09 | .09 .07 .07 .07 | .06 .07 .06 .06 | .07 .09 .09 .10 | .07 .06 .07 .05 .05 | .06 .05 .05 .06 | .05 .04 .04 .04 | .01 .01 .01 .01 | .02 .03 .03 .03 | .01 0 0 .01 | .02 .02 .02 .02 | .05 .05 .05 .05 |
| 11 12 13 14 15 | .09 .09 .10 .09 | .06 .06 .06 .06 | .06 .06 .10 .10 | .09 .08 .09 .15 | .05 .05 .05 .05 | .05 .05 .04 .04 .04 | .04 .04 .03 .04 | .04 .03 .02 .02 .01 | .01 .01 .01 .01 | 0 0 0 .01 .01 | .03 .03 .03 .03 | .05 .05 .06 .05 |
| 16 17 18 19 20 | .09 .09 .09 .03 | .09 .15 .13 .11 .12 | .08 .09 .07 .08 | .10 .09 .15 .09 | .06 .06 .05 .05 | .05 .06 .06 .06 | .06 .05 .05 .05 | .02 .02 .03 .04 | .02 .02 .01 .01 | .03 .04 .03 .02 | .03 .03 .03 .03 | .05 .05 .05 .05 |
| 진 22 23 24 25 | .09 .09 .09 .09 | .11 .11 .15 .12 | .09 .08 .08 .09 | .06 .08 .11 .11 | .08 .08 .06 .05 | .06 .06 .07 .08 | .05 .05 .04 .04 .04 | .04 .04 .03 .03 .02 | .03 .02 .02 .02 .03 | .02 .02 .02 .02 .02 | .03 .03 .03 .03 | .05 .07 .05 .05 |
| 26 27 28 29 30 31 | .06 .06 .06 .05 .06 | .10 .10 .11 | .08 .08 .10 .10 .10 | .10 .10 .10 .07 | .05 .06 .10 .10 | .09 .09 .07 .07 | .04 .04 .03 .04 .03 .03 | .02 .02 .02 .02 .02 | .03 .04 .03 .03 .02 | .02 .02 .03 .02 .02 | .03 .03 .03 .03 .03 | .05 .06 .05 .05 .05 |
| Sum | 2.74 | 2.62 | 2.57 | 2.83 | 1.91 | 1.90 | 1.47 | 0.89 | 0.61 | 0.50 | 0.81 | 1.57 |

| Current Year 1971 | | | | | | | | | Period 1937-1971 | | | |
|-------------------|----------------------|-----------|-----------------------|----------|-----|------|----------------|-----------|------------------|---------|---------|--|
| | Extreme Gage Feet | | Ø Extreme Second Feet | | | | Average | Total | Acre Feet | | | |
| Month | High | et Low | Day | Day High | | Low | Second Feet | Acre Feet | Average | Maximum | Minimum | |
| Jan. | | | 2 | 0.20 | 29 | 0.05 | 0.088 | 5.4 | 134 | 906 | 0 | |
| Feb. | | ļ | † 17 | .15 | 110 | .06 | .094 | 5.2 | 237 | 1,730 | 0 | |
| Mar. | | 1 | 1 | .11 | 1 6 | .06 | .083 | 5.1 | 339 | 2,360 | 0 | |
| Apr. | | | 114 | .15 | 30 | .05 | .094 | 5.6 | 238 | 3,250 | 0 | |
| May | | 1 | †2 8 | .10 | 19 | .05 | .062 | 3.8 | 109 | 1,540 | 0 | |
| June | | | † 25 | .09 | 113 | .04 | .063 | 3.8 | 43.0 | 719 | 0 | |
| July | | 1 | 1 | .09 | 113 | .03 | .047 | 2.9 | 17.4 | 361 | 0 | |
| Aug. | | | 10 | ,20 | 1 3 | .01 | .029 | 1.8 | 12.8 | 321 | 0 | |
| Sept. | | | 27 | .04 | 111 | .01 | .020 | 1.2 | 12.1 | 264 | 0 | |
| Oct. | | | 17 | .04 | 1 7 | 0 | .016 | 1.0 | 21.0 | 543 | 0 | |
| Nov. | | | 110 | .03 | 1 1 | .02 | .027 | 1.6 | 38.7 | 542 | 0 | |
| Dec. | | | 122 | .07 | 1 1 | .03 | .051 | 3.1 | 107 | 808 | 0 | |
| Yearly | | | 1 | 0.20 | Ī | 0 | 0.056 | 40.5 | 1,309 | 11,141 | 0 | |

Ø Mean daily f And other days

COTTONWOOD CREEK NEAR INTERNATIONAL BOUNDARY

DESCRIPTION: Water-stage recorder and cableway, 0.6 mile upstream from the international land boundary between the United States and Mexico, 0.5 mile downstream from the confluence of Cottonwood Creek and Tecate Creek, and 5.5 miles south of Dulzura, California. Low water discharge measurements are made by wading at the gage. Zero of gage is 542.42 feet above mean sea level, U.S. C. & G. S. datum.

RECORDS: Based on a continuous record of gage heights and current meter measurements or observation of no flow generally made twice each month. Records obtained and furnished by the U. S. Geological Survey. Records available: October 1936 through 1971.

REMARKS: Flow is partially controlled by Barrett and Morena Reservoirs, 11 and 19 miles respectively, upstream from this station. The flow at this station represents the amount of water passing the Marron Dam site.

EXTREMES: Maximum discharge, 4,700 second-feet, February 7, 1937 (gage height 8.50 feet) from rating curve extended above 300 second-feet on basis of velocity, mean-depth and area computations. Minimum discharge, no flow for part of most years.

Mean Daily Discharge in Second Feet 1971 — Annual and Period Summary

| $\overline{}$ | | | | | | | | | | | | |
|----------------------------------|---------------------------------|----------------------------------|----------------------------------|----------------------------------|---------------------------------|----------------------------------|----------------------------------|----------------------------------|---------------------------------|----------------------------------|----------------------------------|----------------------------------|
| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
| 1 2 3 4 5 | 0.28 6.1 3.7 .75 | 0.32 .33 .30 .30 .34 | 0.35 .34 .32 .32 .29 | 0.19 .18 .17 .17 .16 | 0.23 .23 .21 .22 | 0.13 .15 .15 .14 .14 | 0.16 .15 .15 .17 .18 | 0.07 .06 .07 .06 .06 | 0.05 .05 .05 .05 | 0.08 .08 .08 .07 .07 | 0.12 .12 .12 .12 .12 | 0.18 .15 .18 .21 .18 |
| 6 7 8 9 | .46 .38 .40 .45 .47 | .32 .30 .31 .33 .35 | .24 .24 .25 .21 .19 | .15 .16 .15 .16 | .21 .23 .21 .17 .13 | .12 .12 .13 .11 | .17 .17 .16 .18 | .06 .05 .05 .04 .04 | .04 .05 .04 .04 .03 | .04 .03 .03 .03 .03 | .12 .12 .12 .12 .12 | .18 .18 .18 .18 |
| 11 12 13 14 15 | .48 .52 .70 .75 | .29 .30 .30 .23 | .17 .15 .26 .55 .40 | .18 .17 .21 .20 | .14 .13 .13 .13 .13 | .11 .10 .13 .12 | .14 .12 .13 .15 | .04 .03 .04 .04 .05 | .02 .02 .01 .01 | .01 .01 .01 .02 .04 | .12 .15 .12 .12 .12 | .15 .15 .18 .18 |
| 16 17 18 19 20 | .37 .37 .37 .37 | .23 1.3 1.9 1.0 | .28 .24 .19 .16 .17 | .19 .22 .24 .24 .24 | .15 .13 .14 .15 .14 | .10 .11 .10 .10 | .19 .15 .12 .11 | .05 .04 .05 .05 | .03 .04 .04 .04 .04 | .08 .10 .10 .10 | .12 .12 .15 .12 .12 | .18 .18 .18 .15 |
| 21 22 23 24 25 | .36 .36 .32 .29 .28 | .82 .54 1.2 1.6 | .15 .15 .13 .11 | .25 .23 .20 .20 .23 | .14 .13 .13 .14 .14 | .11 .11 .11 .11 | .10 .09 .10 .10 | .04 .05 .05 .04 .05 | .05 .05 .05 .04 .06 | .08 .08 .10 .10 | .12 .12 .12 .15 .15 | .15 .25 .21 .21 .21 |
| 26 27 28 29 30 31 | .88 .32 .33 .33 .32 | .62 .48 .37 | .19 .21 .22 .23 .20 | .21 .22 .21 .21 .23 | .15 .14 .15 .15 .14 | .12 .15 .15 .15 | .08 .10 .09 .09 .09 | .05 .05 .04 .04 .05 | .06 .06 .06 .07 .09 | .12 .12 .15 .15 .15 | .12 .12 .15 .15 | .34 .25 .34 .29 .25 |
| Sum | 21.90 | 16.84 | 7.26 | 5.93 | 4.96 | 3.68 | 4.01 | 1.51 | 1.29 | 2.40 | 3.81 | 5,19 |

| | | | | Current Y | ear 197 | '1 | | - | Peri | od 1937-1971 | |
|--------|------|--------|-------|------------|-------------|------|---------|-----------|----------|--------------|---------|
| Month | | e Gage | ø | Extreme Se | cond F | eet | Average | Total | | Acre Feet | |
| Month | Fe | et | + | High | | Low | Second | | A | | |
| | High | Low | Day | | Day | | Feet | Acre Feet | Average | Maximum | Minimum |
| Jan. | | | 2 | 6.1 | 1 1 | 0.28 | 0.71 | 43.4 | 425 | 2,750 | 0 |
| Feb. | | | 18 | 1.9 | 114 | .23 | .60 | 33-4 | 1,149 | 13,680 | . 0 |
| Mar. | | | 14 | •55 | 24 | .11 | .23 | 14.4 | 2,711 | 27,140 | 0 |
| Apr. | | | 21 | .25 | 16 | -15 | .20 | 11.8 | 2,201 | 51,060 | 0 |
| May | | | 1 1 1 | .23 | 110 | .13 | .16 | 9.8 | 556 | 14,110 | 0 |
| June | | ļ | 1 2 | .15 | 112 | .10 | .12 | 7,3 | 114 | 2,630 | 0 |
| July | | | 16 | .19 | 31 | .07 | .13 | 8.0 | 18.6 | 312 | 0 |
| Aug. | | | 11 | .07 | 12 | .03 | .049 | 3.0 | 6.8 | 171 | 0 |
| Sept. | | | 30 | .09 | † 13 | .01 | .043 | 2.6 | 9.4 | 152 | 0 |
| Oct. | | İ | 128 | .15 | † 11 | .01 | .077 | 4.8 | 23.6 | 705 | 0 |
| Nov. | | ĺ | 112 | .15 | 7 1 | .12 | .13 | 7.6 | 45.9 | 839 | 0 |
| Dec. | | 1 | 126 | •34 | 1 2 | .15 | .20 | 12.3 | 356 | 3,330 | ٥ |
| Yearly | | | | 6.1 | | 0.01 | 0.22 | 158.4 | 7,629.3 | 97,900 | 0 |

[†] And other days Ø Mean daily

INFLOWS TO RODRIGUEZ RESERVOIR, BAJA CALIFORNIA

DESCRIPTION: Rodriguez Dam is located in Mexico on Rio de las Palmas, the principal tributary to the Tijuana River, about 5.5 miles upstream from its confluence with Cottonood Creek, 11 miles upstream from the point where the Tijuana River crosses the international boundary between the United States and Mexico, and 10 miles southeast of Tijuana, Baja California.

100, and 10 miles sourceast of Tijuana, maja california.

BOORUS: Computed from monthly reservoir records of storage, releases, spills, leakage, evaporation and rainfall. Records obtained by the Ministry of Hydraulic Resources through May 1961; from June 1961 through March
1966 by the Junta de Agua Rotable y Alcantarillado del Distrito Urbano of Tijuana, Baja California, and from
April 1966 by the State of Baja California Commission of Public Services for Tijuana. Records furnished by
the Mexican Section of the Commission. Records available: May 1937 through 1971. Storage began in
Rodriguez on September 22, 1936. RECORDS:

Records of rumoff represent all water reaching Rodriguez Reservoir including rainfall on the res-REMARKS: MANKNS: Records of runoil represent all water reaching Routiguez Reservoir including rainful of the reservoir water surface. A rea-capacity-elevation rating for reservoir used in the computations is dated 1927 when the reservoir area was initially surveyed. Elevation of crest of spillway 380.08 feet above mean sea level; at top of spillway gates 410.10 feet above mean sea level. Reservoir capacity at spillway crest 76,210 acre-feet; at top of spillway gates 111,070 acre-feet, are-feet, and monthly inflow, 77,320 acre-feet, April 1941; minimum, no flow during part of most years.

EXTREMES:

Monthly Discharge in Acre-Feet

| | 2 1071 | | Period 1938-1971 | |
|-----------|-------------------|---------------------|------------------|---------|
| Month | Current Year 1971 | Average | Maximum | Minimum |
| January | 61.5 | 861 | 6 ,56 9 | 0 |
| February | 67.4 | 2,38 ⁱ 4 | 41,295 | 5.8 |
| March | 45.7 | 5 ,93 4 | 68,321. | 4.2 |
| April | 58.2 | 3,104 | 77,790 | 0 |
| May | 34.3 | 396 | 9,962 | 0 |
| June | 19.0 | 74.1 | 891 | 0 |
| July | 26.1 | 76.0 | 32 6 | 0 |
| August | 11.0 | 50.3 | 770 | 0 |
| September | 40.9 | 50.4 | 466 | 0 |
| October | 122 | 63.6 | 344 | 0 |
| November | 79.5 | 160 | 1,940 | 0 |
| December | 73.2 | 929 | 15,686 | 12.8 |
| Yearly | 639 | 14,082 | 177,668 | 254 |

DIVERSIONS FROM RODRIGUEZ RESERVOIR, BAJA CALIFORNIA

DESCRIPTION: Sparling flow meter located immediately below the dam in the pipe line which carries water released from Rodriguez Reservoir to the North and South Canals.

leased from Modriguez Messervoir to the Morth and South Unnais.

RECORDS: Direct recording by Sparling flow meter. Records obtained by the Ministry of Hydraulic Resources through May 1961; from June 1961 through March 1966 by the Junta de Agua Potable y Alcantarillado del Distrito Urbano of Tijuana, Baja California, and from April 1966 by the State of Baja California Commission of Public Services for Tijuana. Records furnished by the Mexican Section of the Commission of Records aveilable. May 1837 through 1831

California Commission of Public Services for Tijuana. Records Turnished by the Mexican Section of the Commission. Records available: May 1937 through 1971.

REMARKS: Since the dam was completed in 1937, water has been diverted directly into the aqueduct for domestic use for Tijuana, Baja California and into the North and South Canals for irrigation in Mexico. The North Canal delivers water to lands in the Tijuana Valley north of the Rio de las Palmas and the South Canal delivers water to lands in the valley south of the Rio de las Palmas and the Tijuana River. During 1971, no water was released for irrigation of farm lands.

EXTREMES: Maximum monthly diversion, 1,963 acre-feet, July 1944; minimum, no flow March and April 1941, August 1960, and December 1962.

Monthly Discharge in Acre-Feet

| February | 1071 | | Period 1938-1971 | |
|-----------|-------------------|---------|------------------|---------|
| | Current Year 1971 | Average | Maximum | Minimum |
| January | 168 | 245 | 782 | 2.3 |
| February | 132 | 272 | 1,132 | 1.9 |
| March | 156 | 328 | 1,223 | 0 |
| April | 130 | 464 | 1,602 | 0 |
| May | 156 | 633 | 1,676 | 1.8 |
| June | 154 | 735 | 1,857 | 1.9 |
| July | 143 | 778 | 1,963 | 1.9 |
| August | 153 | 670 | 1,859 | 0 |
| September | 85.1 | 540 | 1,420 | 1.9 |
| October | 2.7 | 467 | 1,186 | 1.9 |
| November | 2.1 | 357 | 1,037 | 2.1 |
| December | 1.9 | 314 | 981 | 0 |
| Yearly | 1,284 | 5,801 | 15,317 | 59.6 |

TIJUANA RIVER AT INTERNATIONAL BOUNDARY

ESCRIPTION: Water-stage recorder on right bank about 550 feet downstream from the international boundary and about 0.8 mile west of the international gate at San Ysidro, California. Zero of gage is at mean sea

and about 0.3 mile west of the international gate at San Ysidro, California. Zero of gage is at mean sea level, U.S.C. & 6. S. datum.

RECORDS: Based on current meter and Parshall flume measurements and observations of no flow and a continuous record of gage heights. Records obtained and furnished by the United States Section of the Commission. Records available: May 1947 through 1971.

EXTREMES: Since May 1947: Maximum instantaneous discharge, 2,570 second-feet, March 15,1952; minimum discharge, no flow during part or all of each year since 1951.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| _ | | | | | | | J. I | | | | umary | |
|----------------------------------|---------------------------|----------------------------|-------------------|-------------------------|-----------------------------|------------------|------------------|------------------|------------------|-------------------|------------------|---------------------------------|
| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
| 1 2 3 4 5 | 0 1.4 .2 .1 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 1.5 |
| 6 7 8 9 | 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 15.4 3.7 .1 0 | 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 |
| 11 12 13 14 15 | 0 0 .7 .1 0 | 0 0 0 0 | 0 0 •4 0 | 0 0 0 1.1 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 |
| 16 17 18 19 20 | 0 0 0 0 | .1 5.7 .1 .3 | 0000 | 0000 | 00000 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | •5 0 0 0 | 0 0 0 0 | 0 0 0 0 0 |
| 21 22 23 24 25 | 0 0 0 0 | .1 0 2.1 .3 .1 | 0 0 0 0 | 0 0 0 0 | 00000 | 00000 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 3.7 .2 2.2 5.5 |
| 26 27 28 29 30 31 | 0 0 0 0 | 0 | 0 0 0 | 0 0 0 | 0 0 0 0 | 00000 | 00000 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 1.9 16.9 10.6 2.0 0 |
| Sum | 2.5 | 8.9 | 0.4 | 1.1 | 19.2 | 0 | 0 - | 0 | 0 | 0.5 | 0 | 44.5 |

| _ | | | | Current ' | Year 19 | 71 | | | Per | iod 1947-197 | 1 |
|--------|-------|---------|-----|-----------|------------|-----|---------|-----------|---------|--------------|---------|
| | | ne Gage | | Extreme S | econd F | eet | Average | Total | | Acre Feet | |
| Month | F | eet | Щ. | High | | Low | Second | 70141 | | Acre reet | |
| | High | Low | Day | | Day | | Feet | Acre Feet | Average | Maximum | Minimum |
| Jan. | 46.43 | 45.95 | 2 | 8.2 | 1 1 | 0 | 0.1 | 5.0 | 416 | 4,603 | 0 |
| Feb. | 46.85 | 45.95 | 17 | 26.4 | f 1 | 0 | •3 | 17.7 | 286 | 1,496 | l ŏ |
| Mar. | 46.31 | 45.95 | 13 | 4-3 | † 1 | 0 | ٥ | .8 | 870 | 13,309 | ō |
| Apr. | 46.55 | 45.95 | 14 | 12.4 | 1 1 | 0 | 0 | 2.2 | 250 | 2,926 | Ō |
| May | 47.88 | 45.95 | 7 | 127 | 11 | 0 | .6 | 38.1 | 42.4 | 312 | Ö |
| June | 45.95 | 45.95 | | 0 | | 0 | 0 | 0 | 26.7 | 309 | Ó |
| July | 45.95 | 45.95 | 1 | 0 | | 0 | 0 | 0 | 21.1 | 239 | 0 |
| Aug. | 45.95 | 45.95 | | 0 | | 0 | 0 | 0 | 18.3 | 193 | 0 |
| Sept. | 45.95 | 45.95 | | 0 | | 0 | 0 | 0 | 23.8 | 216 | 0 |
| Oct. | 46.40 | 45.95 | 16 | 7.2 | 1 1 | 0 | 0 | 1.0 | 35.3 | 305 | 0 |
| Nov. | 45.95 | 45.95 | | 0 | 1 | 0 | 0 | 0 | 106 | 1.084 | 0 |
| Dec. | 47.64 | 45.95 | 27 | 93.5 | † 1 | 0 | 1.4 | 88.3 | 291 | 2,725 | 0 |
| Yearly | 47.88 | 45.95 | | 127 | | 0 | 0.2 | 153 | 2,387 | 19,882 | 0 |

f And other days

TIJUANA RIVER NEAR NESTOR, CALIFORNIA

DESCRIPTION: Water-stage recorder on county road bridge 4.1 miles downstream from the international land boundary between the United States and Mexico, 2.9 miles upstream from mouth of the river, and 1.7 miles south of Nestor, California. Zero of gage is 15.14 feet above mean sea level, U. S. C. & G. S. datum. From April 10, 1953 to August 5, 1956, station was located 2 miles upstream at different datum. RECORDS: Based on current meter measurements or observation of no flow generally made twice a month. Records obtained and furnished by the U. S. Geological Survey. Records available: October 1914 through September 1915, and October 1922 through 1971 (October 1922 through May 1936 are from city of San Diego, California).

California).

REMARKS: The flow at this station is partially controlled by Morena and Barrett Reservoirs on Cottonwood Creek in the United States and by Rodriguez Reservoir on Rio de las Palmas in Mexico. Some diversions for irrigation are normally made in Mexico whenever surface runoff occurs in the river or in its two principal tributaries.

CITEMES: Since October 1, 1936: Maximum discharge, 17,700 second-feet, February 7, 1937 (gage height 8,20 feet), obtained from rating curve extended above 2,000 second-feet on basis of velocity-depth relationship, and cross section after peak of the flood. Minimum discharge, no flow during parts of most years.

Mean Daily Discharge in Second Feet 1971 --- Annual and Period Summary

| | | | - | | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------|------|------|---------------|-------|-----|----------|------|------|-------|------|------|------|
| Day | Jan. | Feb. | March | April | May | JUNE | July | vag. | Jept. | | | |
| 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 3 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 0 | 0 | 0 | 0 | ő | ő | o ! | ō | Ö | ŏ | ŏ | 0 |
| 5 | ő | ŏ | ō | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 6 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 7 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 8 | 0 | 0 | 0 | 0 | 0 | 0 | ŏ | ő | ő | ŏ | 0 | 0 |
| 10 | ő | 0 | ŏ | ō | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| п | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 12 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 13 14 | 0 | 0 | 0 | 0 | 0 | . 0 | 0 | .0 | 0 | 0 | 0 | 0 |
| 15 | ŏ | 0 | o | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 16 | 0 | 0 | 0 | 0 | 0 | ٥ | 0 | 0 | 0 | 0 | 0 | 0 |
| 17 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 18 19 | 0 | 0 | 0 | 0 | 0 | ŏ | 0 | 0 | 0 | ő | . 0 | 0 |
| 20 | ő | 0 | ŏ | ŏ | Ō | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 21 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 22 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 23 24 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | ŏ | 0 |
| 25 | 0 | 0 | ŏ | ŏ | ŏ | 0 | 0 | 0 | -0 | 0 | 0 | 0 |
| 26 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | o | 0 |
| 27 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 28 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 29 30 | 0 | 1 | 0 | 0 | 0 | ŏ | 0 | 0 | ō | 0 | 0 | 0 |
| 31 | ő | | Ō | 1 | 0 | <u> </u> | 0 | 0 | | 0 | L | 0 |
| Sum | | 0 | | 0 | | 0 | , | 0 | 0 | 0 | 0 | .0 |
| | 0 | | 0 | | 0 | | 0 | | 0 | | | |

| | | | | Current | Year 1 | 971 | | | Per | iod 1937-197 | 1 |
|---------|---------|------|-----|-----------|---------|-----|---------|-----------|---------|--|---------|
| | Extreme | Gage | | Extreme S | econd f | eet | Average | Total | | iod 1937-197 Acre Feet Maximum 4,070 66,920 107,000 181,900 183,340 3,060 523 242 234 1,340 1,490 7,930 | |
| Month _ | Fee | et | | High | ļ | Low | Second | | Average | Mauimum | Minimum |
| | High | Low | Day | | Day | | Feet | Acre Feet | Average | Maximum | Minimum |
| Jan. | | | | | 1 | | | 0 | 737 | | 0 |
| Feb. | i | | | | 1 | | 1 | 0 | 4,054 | 66,920 | 0 |
| Mar. | | | i | | 1 | | | 0 | 7,085 | 107,000 | 0 |
| Apr. | i | | | | | 1 | | 0 | 5,058 | | 0 |
| May | | | | | | | - | 0 | 676 | | 0 |
| June | | | 1 | i . | | 1 | | 0 | 114 | 060و3 | 0 |
| July | ļ | | | | - 1 | 1 | | 0 | 22.8 | 523 | 0 |
| Aug. | | | | ļ | - 1 | 1 | - (| 0 | 16.1 | | 0 |
| Sept. | | | | i | 1 | | | 0 | 23.7 | | 0 |
| Oct. | | | | | | | | 0 | 30.9 | 1,340 | 0 |
| Nov. | | | 1 | | 1 | | | 0 | 138 | | 0 |
| Dec. | | | | | | 1 | | 0 | 742 | 7,930 | 0 |
| Yearly | | | | | | | | 0 | 19,748 | 332,749 | 0 |

STORED WATER IN RESERVOIRS, TIJUANA RIVER BASIN

Data are presented below for all storage reservoirs in the Tijuana River Basin. The data represent contents on the last day of the month in acre-feet. The reservoir capacities indicated are total capacities, at the top of the spillway gates in closed position on the controlled spillways of Barrett and Rodriguez Dam, and at spillway level for Morena Dam, which has had an uncontrolled spillway since the spillway gates were removed at 1942. The records of storage reported below for Morena, Barrett, and Rodriguez Reservoirs are based on the capacities as determined by the following surveys: Morena 1948; Barrett 1948, 1951, and 1955; and Rodriguez 1927, when the reservoir area was initially surveyed.

Records for Morena and Barrett Reservoirs are obtained and furnished by the city of San Diego, the U. S. Geological Survey, and the National Weather Service. Records for Rodriguez Reservoir obtained and furnished by the State Department of Public Works and Services for Tijuana, Baja California.

In Acre-Feet

| Month | CAL | RESERVOIR, IFORNIA ity 50,210) | CAI | reservoir, Lifornia Lty 44,760) | BAJA CA | Z RESERVOIR, ALIFORNIA Ly 111,880) | TOTAL IN TIJUANA RIVER BASIN RESERVOIRS (Capacity 206,850) | | |
|--|--|--|---|--|--|--|--|--|--|
| | 1971 | Average 1937-1971 | 1971 | Average 19 3 7-1971 | 1971 | Average 1937-1971 | 1971 | Average 1937-1971 | |
| Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec. | 3,877 3,898 3,893 3,838 3,790 3,500 3,500 3,460 3,341 3,261 3,206 3,321 | 16,176 16,863 18,116 18,113 17,957 17,464 16,569 16,569 16,036 15,802 15,748 | 1,367 1,491 1,584 1,638 1,668 1,632 1,584 1,544 1,544 1,544 1,562 | 11,466 12,927 14,481 14,988 14,264 13,480 12,663 11,894 11,607 11,252 10,890 11,191 | 1,417 1,300 1,121 985 800 602 427 233 146 224 263 298 | 32,282 33,241 36,712 36,691 36,006 34,909 33,746 32,694 31,801 31,054 30,540 30,871 | 6,661 6,689 6,598 6,461 6,258 5,904 5,513 5,237 4,992 4,982 4,953 5,181 | 59,924 63,031 69,309 69,792 68,227 65,853 63,407 61,157 59,444 58,108 57,120 57,810 | |
| Avg. | 3,588 | 16,794 | 1,545 | 12,592 | 651 | 33,379 | 5,786 | 62,765 | |
| Max. | 3,898 | # 61,670 | 1,668 | 0 45,920 | 1,417 | 109,608 | 6,689 | 213,600 | |
| Min. | 3,206 | 10 | 1,367 | 106 | 146 | 0 | 4,953 | 1,264 | |

March 31, 1941 - Prior to removal of spillway gates April 30, 1937 - Sand bags were placed on crest of spillway

RAINFALL ON THE TIJUANA RIVER WATERSHED IN INCHES

Tabulated below are monthly records of rainfall with averages for their periods of record at stations located in California and Baja California. Daily records, where available, are on file in the offices of the United States and Mexican Sections of the Commission. For location, elevation, period of record, and the observer, see alphabetical listing of these stations on page 80.

In United States

| | | ena Dam, ifornia | | tt Dam, fornia | | Valley, formia | | rero, fornia | | ay Ranch, Ifornia |
|-------------------------------------|--|---|---|---|--|---|--|---|---|---|
| Month | 1971 | Average 1906-1971 | 1971 | Average 1907-1971 | 1971 | Average 1951-1971 | 1971 | Average 1914-1971 | 1971 | Average 1950-1971 |
| Jan. Feb. Mar. Apr. May | 1.24 1.50 .18 1.22 | 3.79 3.79 3.35 1.80 | 1.18 1.75 .50 1.35 | 3.34 3.39 2.88 1.61 | 0.95 2.00 .54 1.43 | 2.55 1.92 2.23 1.44 .43 | 1.46 1.63 .71 2.29 1.05 | 3.39 3.70 2.91 1.86 .65 | 1.67 1.42 .62 1.56 .46 | 3.03 2.30 2.66 1.84 .45 |
| June July Aug. Sept. Oct. Nov. Dec. | 0 0 2.15 .28 1.22 .20 4.43 | .14 .37 .55 .34 .86 1.55 3.33 | 0 .01 .07 .14 1.24 .41 3.96 | .06 .10 .20 .25 .69 1.33 2.94 | 0 0 0 .10 .97 .11 4.09 | .04 .03 .12 .19 .30 1.53 2.37 | 0 .04 .21 1.50 .23 4.62 | .08 .20 .19 .25 .72 1.45 3.24 | 0 .30 .92 .27 1.23 T 4.67 | .04 .47 .75 .36 .39 1.74 2.53 |
| Yearly | 13.12 | 20.50 | 11.54 | 17.37 | 10.88 | 13.15 | 13.78 | 18.64 | 13.12 | 16.56 |

| | | empo, ifornia, | | Vista, fo rnia | | | | |
|--|--|--|--|---|--|-------|--|--|
| Month | 1971 | Average 1900-1971 | 1971 | Average 1930-1971 | | | | |
| Jan. Feb. Mar. Apr. Msy June July Aug. Sept. Oct. Nov. | 1.12 1.22 .40 1.46 .67 0 .07 1.00 .25 1.18 .05 | 3.00 3.32 2.73 1.50 .54 .07 .53 .52 .33 .62 1.35 2.61 | 0.31 .72 .13 .54 .63 .06 T T .13 .33 .33 | 1.79 1.72 1.46 .87 .24 .05 .02 .07 .16 .39 1.06 | | | | |
| Dec. Yearly | 11.02 | 17.12 | 5.87 | 9.59 | | + | | |

| | | morosa, alifornia | Tecate, Baja California | | | uana, alifornia | | uez Dam, alifornia | Valle de Las Palmas, Baja Calif. | | |
|--------|------|----------------------|----------------------------|-------------------------------|------|-------------------------------|------|-----------------------|-------------------------------------|----------------------|--|
| Month | 1971 | Average 1945-1971 | 1971 | Average 1946-59 1961-71 | 1971 | Average 1948-59 1961-71 | 1971 | Average 1938-1971 | 1971 | Average 1948-1971 | |
| Jan. | 0.39 | 0.67 | 0.94 | 2.32 | 0.35 | 1.77 | 0.51 | 1.42 | 0.08 | 1.42 | |
| Feb. | .79 | -35 | 1.34 | 1.34 | .94 | 1.26 | -59 | 1.26 | -55 | .98 | |
| Mar. | 0 | •51 | •39 | 1.85 | .24 | 1.14 | .16 | 1.34 | .16 | 1.06 | |
| Apr. | -39 | .35 | 1.42 | 1.22 | -51 | .67 | .79 | .79 | .87 | .63 | |
| May | .39 | .08 | .31 | .31 | .51 | .24 | •39 | .12 | .12 | .12 | |
| June | 0 | .04 | 0 | .03 | T | .04 | T | T | 0 | T | |
| July | 0 | .28 | 0 | .08 | 0 | .04 | T | T | T | .04 | |
| Aug. | 1.06 | .63 | 0 | .16 | 0 | .04 | T | .04 | .91 | .12 | |
| Sept. | .31 | .28 | 0 | .12 | T | .12 | •O14 | .24 | .16 | .16 | |
| Oct. | .16 | ,31 | .31 | .28 | .31 | .28 | .47 | .28 | .47 | .16 | |
| Nov. | 0 | .47 | 0 | 1.22 | T | 1.02 | .08 | .87 | .08 | .75 | |
| Dec. | .55 | .71 | 3.35 | 2.17 | 2.01 | 1.38 | 1.57 | 1.65 | 1.54 | 1.02 | |
| Yearly | 4.06 | 4.69 | 8.07 | 11.85 | 4.88 | 8.50 | 4.61 | 7.91 | 4.92 | 6.65 | |

RAINFALL ON THE TIJUANA RIVER WATERSHED IN INCHES

In Mexico

| | El Pinal, Baja California | | | n de Dios, alifornia | | | |
|---|--|--|---|---|--|--|--|
| Month | 1971 | Average 1964-1971 | 1971 | Average 1956-1971 | | | |
| Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec. | 0.47 2.05 .35 2.13 1.18 0 .12 .67 .63 0 1.81 .39 4.45 | 2.24 2.44 1.97 2.17 .28 0 .75 .79 .55 .31 1.81 | 0.79 1.42 .43 1.30 .55 0 1.38 2.13 .16 .75 9.47 2.56 | 2.01 1.97 1.65 1.26 .31 .20 1.06 .75 .43 .51 1.26 2.09 | | | |
| Yearly | 14.25 | 17.17 | 11.93 | 15.20 | | | |

⁹ Partially registering

LOCATION OF RAINFALL STATIONS ON THE TIJUANA RIVER WATERSHED

In United States

| NAME OF STATION | LATI- TUDE | LONGI- TUDE | ë elev. (FT.) | RECORD BEGAN | OBSERVER |
|---------------------------|---------------|----------------|------------------|-----------------|----------------------|
| Barrett Dam, California | 32° 41' | 116° 40' | 1,750 | 1907 | City of San Diego |
| Campo, California | 32° 37′ | 116° 28' | 2,630 | 1877 | Archie C. Leach |
| Chula Vista, California | 32° 36' | 117° 06' | 9 | 1930 | Western Salt Company |
| Marron Valley, California | 32° 34' | 116° 46' | 550 | 1951 | Fred Mellor |
| Morena Dam, California | 32° 41' | 116° 32' | 3,010 | 1906 | City of San Diego |
| Potrero, California | 32° 37' | 116° 37' | 2,390 | 1914 | L. W. Whitehouse |
| Sawday Ranch, California | 32° 45' | 116° 29' | 3,200 | 1950 | William Tulloch |

| NAME OF STATION | LATI- TUDE | LONGI. TUDE - | S ELEV. | RECORD BEGAN | OBSERVER |
|---|---------------|------------------|----------------|-----------------|---------------------|
| El Pinal, Baja California | ±32° 12' | "116° 17' | <u>44,429</u> | 1964 | Hydraulic Resources |
| La Rumorosa, Baja California | 32° 33' | 116° 03' | 3,937 | 1946 | Hydraulic Resources |
| Rodriguez Dam, Baja California | 32° 26' | 116° 55' | 459 | 1938 | Hydraulic Resources |
| San Juan de Dios, Baja California | 32° 08' | 116° 10' | #3,28 0 | 1956 | Hydraulic Resources |
| Tecate, Baja California | 32° 32' | 116° 39' | 1,690 | 1946 | Hydraulic Resources |
| Tijuana, Baja California | 32° 31' | 117° 02' | 180 | 1948 | Hydraulic Resources |
| Valle de las Palmas, Baja California | 32° 23' | 116° 40' | 148 | 1948 | Hydraulic Resources |

⁸ Elevation above mean sea level 2 Estimated from topographic maps

EVAPORATION IN THE TIJUANA RIVER BASIN IN INCHES

Tabulated below are records of evaporation observed at three stations in California and at five stations in Baja California, with averages for their periods of record. The stations in California are observed by Western Salt Company, city of San Diego, California, and the United States Section of the Commission; those in Baja California are observed by the Ministry of Hydraulic Resources. For specific location of these stations, refer to data opposite same station name shown in "Location of Rainfall Stations", page 80 in this bulletin.

- 1. Barrett Reservoir: January 1921 through September 1926, square 3-foot by 3-foot by 18-inch deep floating pan. October 1926 through 1971, square 3-foot by 3-foot by 18-inch deep land pan set 15 inches in ground.
- 2. Chula Vista: September 1918 through 1971, National Weather Service 4-foot diameter pan, 10 inches deep, set on 2- by 4-inch-timber grill.
- 3. Marron Valley: Records available February 1951 to December 1970, at which time the station was discontinued.
- 4. Morena Reservoir: October 1915 through December 1921, square 3-foot by 3-foot by 18-inch deep floating pan. January 1922 through August 1926 records are the average of evaporation in a square 3-foot by 3-foot by 18-inch deep floating pan and a land pan of the same dimensions. September 1926 through 1971, square 3-foot by 3-foot by 18-inch deep land pan set 15 inches in ground.

In United States

| | | na Dam, fornia | | tt Dam, fornia | Chula Vista, California | | |
|--------|-------|----------------------|--------------|----------------------|----------------------------|----------------------|--|
| Month | 1971 | Average 1916-1971 | 1971 | Average 1921-1971 | 1971 | Average 1919-1971 | |
| Jan. | 1.55 | 2.25 | 1.58 | 1.87 | 2.83 | 2.83 | |
| Feb. | 1.94 | 2.30 | 2.12 | 2.22 | 3.45 | 3.34 | |
| Mar. | 3.34 | 3.60 | 3.69 | 3.59 | 5.19 | 5.01 | |
| Apr. | 3.53 | 4.87 | 4.21 | 4.84 | 6.44 | 5.93 | |
| May | 4.52 | 6.85 | 4.98 | 6.94 | 6.18 | 6.86 | |
| June | 7.64 | 8.75 | 7.18 | 8.47 | 6.64 | 6.97 | |
| July | 8.93 | 10.20 | 8.48 | 10.14 | 7.11 | 7.61 | |
| Aug. | 7.17 | 9.51 | 8.42 | 9.58 | 7.59 | 7.33 | |
| Sept. | 6.41 | 7.71 | 6 .52 | 7.81 | 6.77 | 6.11 | |
| Oct. | 7.89 | 5.48 | 4.42 | 5.51 | 5.77 | 4.92 | |
| Nov. | 1.98 | 3.54 | 2.29 | 3.46 | 3.27 | 3.63 | |
| Dec. | 2.96 | 2.53 | 1.06 | 2.10 | 2.45 | 2.74 | |
| Yearly | 57.86 | 67.59 | 54.95 | 66.53 | 63.69 | 63.28 | |

| | | ate, lifornia | Tijuana, Baja California | | | guez Dam, alifornia | | las Palmas, lifornia | San Juan de Dios, Baja California | |
|--|---|--|--|--|--|--|---|--|---|--|
| Month | 1971 | Average 1961-71 | 1971 | Av. 1952-59 1961-1971 | 1971 | Av. 1939-42 1946-1971 | | Average 1948-71 | 1971 | Average 1956-71 |
| Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. | 2.48 3.11 6.77 4.72 3.15 8.58 6.50 * 6.85 5.63 3.82 | 3.31 3.35 4.45 5.24 6.03 8.36 8.31 6.39 6.39 3.70 | 2.95 3.46 4.88 5.04 5.75 6.22 7.20 5.55 5.04 2.52 | 2.87 3.39 4.06 4.72 5.75 5.71 6.69 7.01 5.98 4.76 3.31 2.91 | 3.15 3.35 5.39 5.63 5.91 7.56 7.90 8.43 6.81 5.75 3.11 2.20 | 3.62 3.82 5.00 5.79 7.32 7.91 8.98 8.31 7.09 5.98 4.96 | 2.64 3.94 6.81 6.73 7.20 9.57 10.16 9.84 8.35 6.30 3.86 | 3.70 3.66 5.31 6.46 7.44 9.21 10.71 10.16 8.78 6.42 4.53 3.90 | 3-35 0 6.02 5.91 6.97 9.11 9.72 7.80 8.23 4.76 | 2.72 2.60 4.13 4.72 6.46 6.89 8.58 7.40 7.91 5.20 3.62 3.11 |
| Yearly | * | 67.76 | 57.20 | 55.63 | 65.08 | 73.11 | 77.40 | 79.72 | * | 60.71 |

^{*} Record incomplete

[•] Tank frozen

TEMPERATURE IN THE TIJUANA RIVER BASIN IN DEGREES FAHRENHEIT

The maximum, minimum, and monthly average temperature observations for United States stations are from daily readings of thermometers generally exposed in a shelter located a few feet above sod-covered ground. The maximum and minimum temperatures shown for the stations in Mexico are from daily maximum and minimum thermometer observations, with maximum and minimum for their periods of record. For specific location, elevation, period of record, and the observer, refer to data opposite same station name as shown in "Location of Rainfall Stations", page 80 in this bulletin.

In United States

| | Bar | rett Dam, | Califor | rnia | Chu. | la Vista | , Califor | rnia | | Campo, C | aliforni | a. |
|--------|------|-----------|------------|-----------------------|--------------|----------|-----------|------------------------|------|----------|----------|---------------|
| Month | | 1971 | | Average | | 1971 | | Average | | 1971 | | Average |
| | Mean | Max. | Min. | 19 31- 1971 | Mean | Max. | Min. | 19 3 1- 1971 | Mean | Mex. | Min. | 1951- 1971 |
| Jan. | 50.0 | 90 | 25 | 48.6 | 52.6 | 76 | 29 | 52.5 | 47.8 | 84 | 23 | 46.8 |
| Feb. | 50.6 | 85 | 31 | 50.4 | 53.6 | 77 | 37 | 53.8 | 47.3 | 85 | 22 | 47.9 |
| Mar. | 54.1 | 89 | 28 | 53.2 | 53.9 | 69 | 32 | 55.2 | 50.8 | 84 | 23 26 | 49.3 |
| Apr. | 55.2 | 87 | 3 6 | 57.8 | 56.8 | 81 | 42 | 57.9 | 50.9 | 84 | | ļ |
| May | 58.8 | 86 | 42 | 62.7 | 58.3 | 78 | 47 | 60.6 | 54.9 | 85 | 29 | 58.0 |
| June | 67.7 | 101 | 41 | 67.9 | 61.0 | 72 | 49 | 62.8 | 63.7 | 99 | 31 | 64.4 |
| July | 76.4 | 105 | 49 | 76.1 | 66.4 | 79 | 57 | 1 | 73.3 | 100 | 37 | 73.4 |
| Aug. | 79.4 | 103 | 48 | 76.4 | 72.2 | 82 | 60 | | 75.6 | 100 | 39 | 73.7 |
| Sept. | 72.8 | 110 | 39 | 72.3 | 68.8 | l | | | 69.1 | 105 | 29 | 69.1 |
| Oct. | 60.2 | 97 | 28 | 64.1 | 61.7 | 89 | 36 | 62.8 | 56.5 | 94 | 22 | 60.8 |
| Nov. | 52.8 | 86 | 30 | 55.9 | 55.5 | 75 | 41 | 1 | 50.3 | 87 | 21 | 52.7 |
| Dec. | 44.4 | 65 | 25 | 50.4 | 50.9 | 65 | 33 | 54.2 | 43.1 | 66 | 19 | ļ <u>.</u> |
| Yearly | 60.2 | 110 | 25 | 61.3 | 59. 3 | | 29 | 1 | 56.9 | 105 | 19 | |

| | La Rur | morosa, B | aja Calif | ornia | Tec | eate, Ba | ja Califo | rnia | Tiju | ana, Baj | a Califor | nia |
|--------|------------|-----------|-----------|-------|------|----------|-----------|------------------|----------|----------|-----------|------------------------|
| Month | 19 | 71 | 1946-1971 | | 19 | 1971 | | & 61 - 71 | 19 | 71 | 1948-59 | & 61 - 71 |
| İ | Max. | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Max. | Min. |
| Jan. | 75 | 14 | 81 | 5 | 90 | 27 | 100 | 21 | 93 86 | 37 | 93 | 27 |
| Feb. | 72 | 27 | 82 | 10 | 84 | 32 | 100 | 21 | 86 | 41 | 102 | 32 34 34 |
| Mar. | 75 | 25 | 88 | 16 | 90 | 32 34 | 93 | 25 | 86 | 43 | 90 | 34 |
| Apr. | 79 | 30 | 91 | 23 | 90 | 34 | 99 | 32 36 | 90 | 45 | 97 | 34 |
| May | 79 | 36 | 97 | 28 | 82 | 34 | 100 | 36 | 97 | 54 | 97 | 43 |
| June | 95 | 39 | 113 | 34 | 100 | 32 | 104 | 32 | 93 | 50 | 99 | 41 |
| July | . 99 | 55 | 104 | 39 | * | * | 115 | 36 | 97 | 57 | 120 | 46 |
| Aug. | 93 | 59 | 102 | 46 | * | * | 113 | 32 36 34 | 100 | 59 | 106 | 52 46 |
| Sept. | 97 | 43 | 104 | 34 | * | * | 115 | 36 | 100 | 54 | 120 | |
| Oct. | 8 6 | 28 | 93 | 25 | 97 | 27 | 106 | 27 | 108 | 41 | 117 | 41 |
| Nov. | 75 | 30 | 88 | 14 | 84 | 27 | 97 | 27 | 97 | 43 | 108 | 3 ¹ 4 25 |
| Dec. | 6í | 25 | 81 | 10 | 75 | 30 | 97 | 23 | 75 | 34 | 99 | 25 |
| Yearly | 99 | 14 | 113 | 5 | * | * | 115 | 21 | T08 | 34 | 120 | 25 |

| | Rodrigu | ez Dam, | Baja Cali | fornia | Valle de | las Palm | as,Baja C | alifornia | El P. | inal, Ba | ja Califo: | rnia |
|---|---|---|---|--|---|--|---|--|---|---|---|--|
| Month | 197 | '1 | 1938-1971 | | 1971 | | 1948 | 1971 | 19 | 71 | 1964. | -1971 |
| ŀ | Max. | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Max. | Min. |
| Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec. | 86 90 84 93 90 91 93 104 109 102 88 70 | 34 37 39 41 48 46 54 54 49 34 328 | 83 91 38 93 99 108 104 104 109 108 99 | 27 32 32 36 37 46 48 52 48 34 30 27 | 91 90 93 93 90 104 108 104 117 102 90 70 | 21 27 34 37 37 45 48 50 46 32 30 27 | 91 99 100 104 108 118 120 111 117 108 100 91 | 12 23 28 32 36 39 45 43 43 32 19 | 73 75 75 79 77 97 97 97 100 | 21 27 28 27 27 28 36 54 25 * | 73 75 77 82 90 99 102 104 102 95 84 | 12 21 23 18 27 28 36 39 25 30 25 21 |
| Yearly | 109 | 28 | 109 | 27 | 117 | 21 | 120 | 12 | 100 | 21 | 104 | 12 |

^{*} Record incomplete

TEMPERATURE IN THE TIJUANA RIVER BASIN IN DEGREES FAHRENHEIT

| | San Jua | n de Dios | ,Baja Ca | lifornia | | | | | | | |
|--------|---------|----------------------|----------|----------------------------|-----|--|---|---|---|---------|----------|
| Month | 1 | 971 | 1956. | -1971 | | | | | | | |
| | Max. | Min. | Max. | Min. | | | | | | | |
| Jan. | 79 | 21 | 88 | 7 | | | | | | | |
| Feb. | 77 | 21 | 84 | 16 | | | 1 | | ĺ | | 1 |
| Mar. | 79 | 19 | 84 | 18 | . 1 | | 1 | ļ | | l. | |
| Apr. | 77 | 23 | 102 | 19 | | | | 1 | | ļ | |
| May | 77 | 19 | 91 | 19 | | | 1 | | | 1 | |
| June | 95 | 3 9 | 106 | 28 | i | | | | 1 | | l |
| July | 97 | 36 | 120 | 36 | | | i |] | | | |
| Aug. | 102 | 39 36 39 25 | 106 | 28 36 32 25 18 | | | l | 1 | | ļ | |
| Sept. | 99 | 25 | 100 | 25 | | | 1 | | | i | ŀ |
| Oct. | 90 | 18 | 100 | | ļ. | | 1 | 1 | 1 | | 1 |
| Nov. | 79 | 18 | 99 | 15 | | | | 1 | | | |
| Dec. | 68 | 14 | 88 | 14 | | | | | 1 | | <u> </u> |
| Yearly | 102 | 14 | 120 | 7 | | | | | | | |

DRAINAGE AREAS ABOVE GAGING STATIONS AND IRRIGATED AREAS ALONG TIJUANA RIVER AND TRIBUTARIES 1971


The total area within Tijuana River basin is 1,731 square miles, as determined from the best available maps from both the United States and Mexico. The drainage areas shown below are tabulated according to their downstream sequence.

The irrigated areas, tabulated in downstream sequence, are from the most reliable sources available. Those in the United States were furnished by the United States Department of Agriculture and the State Engineer, State of California, or estimated from aerial photographs. Those in Mexico were furnished by the Ministry of Rydraulic Resources of Mexico through the Mexican Section of the Commission. All irrigation in the Tijuana Basin in 1971 was by pumping from ground water.

| Danie mandela de Amara | Drainag | e Basin-Squar | Irrigated Areas-Acres | | | | | |
|---|------------------|----------------|-----------------------|------------------|-----|-----|-----|-------|
| Designation of Areas | United States | Mexico | Total | United States | Mex | ico | т | otal |
| Cottonwood Creek | | | | | | | | |
| above Morena Dem | 114 | l 0 | 114 | (a) 75 | | 0 | (a) | 75 |
| Morena Dam to Barrett Dam | 133 | l ŏ | 133 | 1 '0' | | õ | \"' | ó |
| above Barrett Dam | 247 | l ō | 247 | (a) 75 | | ō | (a) | 75 |
| below Barrett Dam and above | | | | ` ' | | - | '-' | |
| Tecate Creek | 65 | | 65 | (a) 145 | | 0 | (a) | 145 |
| above Tecate Creek | 312 | 0 | 312 | (a) 220 | | 0 | (a) | 220 |
| Campo Creek | | | | | - | | | |
| above International Boundary | 82 | 4 | 86 | (a) 320 | | 0 | (a) | 320 |
| Tecate Creek above International Boundary (not including Campo Creek) | 19 | 64 | 83 | 0 | | 0 | | 0 |
| Cottonwood Creek above International Boundary Station | 413 | 68 | 481 | (a) 540 | | 0 | (a) | 540 |
| Rio de las Palmas above Rodriguez Dam | 7 | 981 | 988 | 0 | (b) | 0 | | 0 |
| Tijuana River above Nestor Gaging Station above the Mouth | 458 462 | 1,266 1,269 | 1,724 1,731 | 3,000 | (c) | 0 | | 3,000 |

⁽a) Estimated. During extremely dry years these areas may be materially reduced.
(b) Areas in upper valleys may be irrigated by pumning from proving the control of the con

Areas in upper valleys may be irrigated by pumming from ground water. There was no irrigation in 1971 in the Tijuana Irrigation District, Tijuana Valley, Baja California, Mexico, from the Rodriguez Reservoir.



WHITEWATER DRAW NEAR DOUGLAS, ARIZONA

DESCRIPTION: Water-stage recorder located on U. S. Highway 80 bridge between Douglas and Bisbee, Arizona, about 450 feet upstream from the Southern Pacific Reilroad bridge, 1.5 miles upstream from the international boundary, and 2 miles west of Douglas, Arizona. Zero of gage is 3,906.94 feet above mean sea level, U. S. C. & G. S. datum of 1929.

RECORDS: Based on current meter measurements or observations of no flow during the year. Computations by shifting control methods. Records obtained and furnished by the U. S. Geological Survey. Records fair. Records available: August to October 1911 (gage heights and discharge measurements only), July to October 1912, January to June 1913, October 1913, December 1913 to June 1914, February to June 1915, October 1915 to September 1919, October 1919 to April 1922 (gage heights and discharge measurements only), June 1930 to December 1933, May 1935 to July 1947, October 1947 through 1971 (July 1954 to March 1955 monthly discharge only).

REMARKS: Diversions above this station are mainly by pumping from ground water for irrigation. Records show flow at the international boundary into Mexico except for some smelter waste water entering the stream a short distance below this station.

ashort distance below this station.

EXTREMES: Prior to 1936: Meximum recorded discharge, 3,450 second-feet August 10, 1931 (gage height 12.15 feet); maximum estimated discharge, 4,050 second-feet July 27, 1919; minimum discharge, no flow for several days of many years. Since 1936: Meximum discharge, 5,060 second-feet August 7, 1955; maximum gage height 16.55 feet July 29, 1966; minimum daily discharge, no flow at times during most years.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| | | The Daily District of the Control of | | | | | | | | | | |
|----------------------------------|------------------|--|------------------|------------------|------------------|------------------|------------------------------------|---------------------------------|----------------------------------|--------------------------------|------------------|------------------|
| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
| 1 2 3 4 5 | 0 0 0 0 | 0 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0000 | 102 20 13 99 7.1 | 0.10 4.5 111 3.8 1.0 | 0.05 0 0 .05 .05 | 0 0 0 | 0 0 0 0 |
| 6 7 8 9 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 6.0 5.4 5.1 4.6 9.1 | .70 .66 .63 .59 | 0 69 26 3.4 .31 | 0 0 0 | 0 0 0 0 |
| 11 12 13 14 15 | 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 832 440 427 717 375 | .60 .60 .58 .55 | 28 2.3 .40 .31 .25 | 0 0 0 0 | 0 0 0 0 |
| 16 17 18 19 20 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 2.6 1.4 | 84 37 94 193 128 | •55 9.6 25 55 5.4 | .25 .25 .15 0 | 0 0 0 0 | 0 0 0 0 0 |
| 21 22 23 24 25 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 157 63 11 40 27 | 58 30 14 18 20 | 1.0 .50 .20 .15 | 0 0 0 0 | 0 0 0 | 0 0 0 0 |
| 26 27 28 29 30 31 | 0 0 0 0 0 | 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 0 | 0 0 0 0 | 13 13 10 75 130 579 | 3.0 1.0 .40 .20 .12 | .05 0 0 0 0 | .10 0 0 0 0 | 0 0 0 0 | 0 0 0 0 0 |
| Sum | 0 | 0 | 0 | 0 | 0 | 0 | 1,122.0 | 3,743.12 | 224.01 | 131.18 | 0 | 0 |

| | | | | Current Y | ear 19 | 71 | | | Peri | od 1936-1971 | |
|---------|------|--------|-----|------------|--------|-----|---------|-----------|---------|--------------|---------|
| | | e Gage | ø | Extreme Se | cond F | eet | Average | Total | | Acre Feet | |
| Month _ | Fe | et | | High | | Low | Second | | | | |
| | High | Low | Day | | Day | | Feet | Acre Feet | Average | Maximum | Minimum |
| Jan. | | | | 0 | | 0 | 0 | 0 | 44.6 | 451 | 0 |
| Peb. | | | 1 1 | 0 | | 0 | 0 | 0 | 23.8 | 132 | 0 |
| ter. | | | | 0 | | 0 | 0 | 0 | 26.5 | 130 | 0 |
| pr. | | ļ | | 0 | 1 | 0 | 0 | 0 | 23.8 | 173 | 0 |
| May | | 1 | 1 | 0 | | 0 | 0 | 0 | 17.3 | 138 | 0 |
| June | | | | 0 | | 0 | 0 | 0 | 150 | 1,590 | 0 |
| July | | | 31 | 579 | 1 1 | 0 | 36.2 | 2,225 | # 2,175 | 8,110 | 39 |
| lug. | | | 111 | 832 | 31 | .10 | 121 | 7,424 | # 3,552 | 14,480 | .3 |
| Sept. | | | 3 | 111 | 127 | 0 | 7.47 | երիր | # 757 | 170ر 3 | .8 |
| Oct. | | | 7 | 69 | † 2 | 0 | 4.23 | 260 | 159 | 2,210 | .4 |
| lov. | | | | Ó | | 0 | 0 | 0 | 43.5 | 352 | 0 |
| Dec. | | | | 0 | | 0 | 0 | 0 | 143 | 2,363 | 0 |
| /annly | | | | 832 | | 0 | 14. | 10,353 | 7,115,5 | 22,321 | 900 |

^{# 1947} records not available

SEWAGE INFLUENT, DOUGLAS, ARIZONA INTERNATIONAL TREATMENT PLANT

DESCRIPTION: Parshall flume in influent line to the international treatment plant, equipped with Simplex digital meter for measuring combined sewage flows from Douglas, Arizona and Agua Prieta, Sonora; and Parshall flume with recorder for measuring the sewage from Douglas. Flows from Agua Prieta are deduced from total flows and the city of Douglas flows; however, since April 8, 1968, all sewage flows from Agua Prieta have been diverted to new oxidation ponds located in Mexico, 1.6 miles south of the international boundary.

RECORDS: Continuous monthly records since March 1948; daily records from March 18, 1948 through 1950 and from January 1952 through 1971.

REMARKS: The Douglas-Agua Prieta International Treatment Plant was constructed by the governments of the United EXPANANCE: The Douglas-Agua Frieds Intermstands Treatment Fight was constructed by the governments of the Officer States and Mexico on 1947 to correct a serious intermstand sanitation problem. The plant is located in the United States adjacent to the international boundary about one mile west of the Douglas-Agua Prieta Port of Entry. Prior to December 1970, the treatment of sewage was complemented by the use of old oxidation ponds in Mexico adjacent to the international boundary. Since December 1970, sewage effluent from the plant flows into Mexico and then across to the right bank of the Agua Prieta Arroyo, by means of a canal bridge, to be used for irrigation.

| | Total | Monthly F | lows | Mea | ın Daily Fl | ows-Milli | ions of Ga | llons Per I | Day |
|--------|---------|------------|---------|---------|-------------|-----------|------------|-------------|-------|
| Month | Milli | ons of Gal | ons | Curr | ent Year | 1971 | Peri | od 1952-1 | 971 |
| | U.S. | Mexico | Total | Maximum | Minimum | Mean | Maximum | Minimum | Mean |
| Jan. | 32.720 | 0 | 32.720 | 1.280 | 0.930 | 1.056 | 1.618 | 0.619 | 1.058 |
| Feb. | 29.265 | 0 | 29.265 | 1.110 | 1.000 | 1.045 | 1.784 | .584 | 1.060 |
| Mar. | 32.510 | 0 | 32.510 | 1.115 | .940 | 1.049 | 1.598 | .590 | 1.062 |
| Apr. | 31.230 | 0 | 31.230 | 1.180 | .820 | 1.041 | 1.536 | .619 | 1.059 |
| May | 33.350 | 0 | 33.350 | 1.180 | 1.010 | 1.076 | 1.595 | .619 | 1.066 |
| June | 33.720 | 0 | 33.720 | 1.220 | 1.020 | 1.124 | 1.784 | .626 | 1.126 |
| July | 36.480 | 0 | 36.480 | 1.240 | 1.050 | 1.177 | 3.209 | .619 | 1.182 |
| Aug. | 37.700 | 0 | 37.700 | 1.350 | 1.040 | 1.216 | 1.985 | .619 | 1.200 |
| Sept. | 36.290 | 0 | 36.290 | 1.340 | 1.090 | 1.210 | 1.884 | .626 | 1.183 |
| Oct. | 35.210 | 0 | 35.210 | 1.200 | 1.040 | 1.136 | 1.667 | .626 | 1.119 |
| Nov. | 32.880 | 0 | 32.880 | 1.180 | 1.000 | 1.096 | 1.586 | .619 | 1.080 |
| Dec. | 33.470 | 0 | 33.470 | 1.170 | .910 | 1.030 | 1.736 | .619 | 1.084 |
| Yearly | 404.825 | 0 | 404,825 | 1.350 | 0.820 | 1.109 | 3.209 | 0.584 | 1.107 |

SEWAGE INFLUENT, AGUA PRIETA, SONORA INTERNATIONAL OXIDATION PONDS

DESCRIPTION: Parshall flume equipped with staff gage in influent line to oxidation ponds. Since April 8, 1968, all sewage from Agua Prieta, Sonora has been diverted to oxidation ponds, which are located in Mexico; if necessary, sewage from Douglas, Arizona may be included, but this has never been done.

RECORDS: Discharges are computed from daily 11:00 a.m. readings of the staff gage by applying an index for that hour, determined from 7 days of hourly measurements from which the relationship between mean daily readings and 11:00 a.m. readings was developed. Records available: Mean daily flows from April 8, 1968 through 1971.

REMARKS: The construction of the international oxidation ponds in Agua Prieta, Sonora was completed in April 1968 by the government of Mexico, fulfilling an international agreement to solve the problem of insufficient capacity at the international treatment plant in Douglas, where the combined flows from Douglas and Agua Prieta were treated. If necessary, sewage from Agua Prieta may be treated in this plant, but since the completion of the oxidation ponds, this has never been done. The ponds are located 1.6 miles south of international monument 85A.

| | Tota | Monthly | Flows | Mea | en Daily Fi | lows-Mill | ions of Ga | llons Per l | Day |
|---------|------|-------------|---------|---------|-------------|---------------|------------|---------------|-------|
| Month | Mil | ions of Gal | lons | Curr | ent Year | 19 7 1 | Peri | od 1968-1 | 971 |
| | U.S. | Mexico | Total | Maximum | Minimum | Mean | Maximum | Minimum | Mean |
| Jan. | 0 | 15.474 | 15.474 | 0.526 | 0.474 | 0.499 | 0.640 | 0.474 | 0.535 |
| Feb. | 0 | 15.053 | 15.053 | .726 | .526 | -538 | .726 | .474 | .560 |
| Mar. | 0 | 12.820 | 12.820 | .418 | -399 | .413 | .666 | • 3 99 | .520 |
| Apr. | 0 | 13.587 | 13.587 | .491 | .418 | •453 | .666 | .418 | .527 |
| May | 0 | 15.080 | 15.080 | .491 | .472 | .486 | .666 | .472 | .536 |
| June | 0 | 14.662 | 14.662 | .491 | .472 | .489 | .617 | .414 | •495 |
| July | 0 | 15.313 | 15.313 | -548 | .491 | .494 | .617 | .259 | .503 |
| Aug. | 0 | 8.597 | 8.597 | .609 | 0 | .277 | .967 | 0 | •399 |
| Sept. * | О | 0 | 0 | 0 | 0 | 0 | .617 | 0 | .415 |
| Oct. | 0 | 8.340 | 8.340 | .491 | 0 | .269 | -595 | 0 | •470 |
| Nov. | 0 | 14.717 | 14.717 | .491 | .491 | .491 | .717 | .414 | -543 |
| Dec. | 0 | 14.971 | 14.971 | .491 | .472 | .483 | .709 | .472 | .546 |
| Yearly | 0 | 148.614 | 148.614 | 0.726 | 0 | 0.408 | 0.967 | 0 | 0.504 |

^{*} No sewage flow from the plant as the effluent line was out of order

SAN PEDRO RIVER AT PALOMINAS, ARIZONA

SCRIPTION: Water-stage recorder located near left bank on the downstream side of pier on bridge on Highway 92, 0.7 mile east of Palominas, 2.5 miles upstream from Green Brush Draw, 4.5 miles downstream from international boundary, and 12 miles southwest of Bisbee, Arizona. Zero of gage is 4,187.62 feet above mean DESCRIPTION: sea level (State Highway bench mark).

RECORDS: Based on current meter measurements or observations of no flow during the year. Records available: May 1930 to October 1933, May 1935 to July 1941, and July 1950 through 1971. Records obtained and furnished by U. S. Geological Survey.

REMARKS: There are some small diversions for irrigation of a few hundred acres above this station, mostly in Mexico. Record shows approximate flow of river at international boundary.

EXTREMES: Maximum daily discharge, 22,000 second-feet on August 14, 1940 (gage height, 16.16 feet present datum), from rating curve extended above 5,600 second-feet on basis of slope-area measurement of peak flow; no flow at times in most summers. Greatest flood known occurred on September 28, 1926 (gage height, about 23.9 feet present datum, from floodmarks; discharge not determined).

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------|---------------------------------|----------------------|---|---|--|--|---------------------------------|--|
| 1 2 3 4 5 | 3.3 2.8 1.7 1.4 | 2.3 2.3 2.3 1.6 1.9 | 4.4 3.5 3.8 4.4 4.4 | 0.20 .10 .10 .10 | 0.10 .10 .10 0 | 0 .10 0 0 | 0 0 0 0 6.3 | 67.0 32.0 32.0 57.0 45.0 | 36.0 393 56.0 47.0 44.0 | 8.2 7.3 7.7 6.9 5.1 | 7.3 7.7 7.7 7.7 8.2 | 6.0 6.0 6.0 6.0 |
| 6 7 8 9 | 1.5 1.5 1.5 1.5 | 1.9 1.9 1.7 1.9 | 3.5 3.3 3.0 2.8 2.3 | .10 .10 .10 .20 | 0 0 0 0 | 0 0 0 0 | 0 0 0 | 14.0 8.6 5.8 32.0 519 | 42.0 40.0 67.0 54.0 46.0 | 4.1 10.0 7.3 6.5 6.5 | 8.2 8.6 8.2 7.3 | 6.0 6.0 6.0 6.0 |
| 11 12 13 14 15 | 1.7 1.7 1.7 1.4 1.1 | 1.2 1.0 1.1 1.2 | 2.3 2.1 1.9 1.4 2.1 | .30 .10 .10 0 | .10 .20 .50 .10 .20 | 1.0 1.0 0 0 | 0 0 0 0 | 2,140 391 1,680 346 1,090 | 38.0 35.0 33.0 30.0 | 6.5 6.5 5.8 5.8 | 6.9 6.9 6.5 7.3 | 6.0 6.0 6.0 6.0 |
| 16 17 18 19 20 | 1.1 1.6 1.6 1.2 1.4 | .6 .7 1.9 2.5 2.8 | 2.3 2.1 2.1 2.1 2.0 | .10 0 0 0 | 0 .20 .10 .10 | 0 0 0 0 | 82.0 49.0 27.0 4.9 | 236 113 199 892 1,980 | 26.0 28.0 151 33 ¹ 4 30.0 | 5.8 5.8 5.8 5.8 | 9.1 6.9 6.1 5.8 5.4 | 6.0 6.0 6.0 6.0 |
| 21 22 23 24 25 | .8 1.0 1.4 1.1 | 2.8 3.3 3.0 3.8 4.1 | .30 .30 .20 .20 | 0 0 0 0 | .10 0 0 .10 .30 | 0 0 0 7.3 | 289 206 22.0 1,300 240 | 1,010 400 250 395 102 | 20.0 10.0 10.0 9.6 12.0 | 5.8 5.8 5.8 14.0 119 | 6.1 6.0 6.0 6.0 | 6.0 6.0 6.0 6.0 |
| 26 27 28 29 30 31 | 1.1 1.0 1.0 1.2 1.9 | 4.1 4.1 4.1 | .60 .60 .50 .20 .20 | 0 0 .10 0 | .20 .30 .60 .70 .70 | 0 0 0 0 | 20.0 16.0 48.0 662 502 584 | 40.0 40.0 40.0 185 62.0 74.0 | 8.6 8.6 5.0 9.6 12.0 | 15.0 11.0 8.2 6.9 6.9 7.3 | 6.0 6.0 6.0 6.0 | 6.9 6.5 6.1 6.5 6.5 7.3 |
| Sum | 47.20 | 62.00 | 58.60 | 2.30 | 5.00 | 10.40 | 4,058.90 | 12,477.4 | 1,679.4 | 335 -4 | 206.7 | 190.7 |

| | | | | Current Y | ear 19 | 971 | | | Peri | od 1951-197 | 1 |
|---------|------|--------|------------|-----------|------------|---------|--------|-----------|-----------|-------------|---------|
| | | e Gage | ø | | | Average | Total | | Acre Feet | | |
| Month _ | Fe | et | ↓ | High | | Low | Second | | | | |
| | High | Low | Day | | Day | | Feet | Acre Feet | Average | Maximum | Minimum |
| Jan. | | i | 11 | 3.3 | 21 | 0.80 | 1.52 | 93.6 | 677 | 7,813 | 2.6 |
| Feb. | | | 125 | 4.1 | 16 | .60 | 2.21 | 123 | 368 | 1,577 | 3.0 |
| Mar. | | ļ | † 1 | 4.4 | 123 | .20 | 1.89 | 116 | 300 | 2,043 | 36.0 |
| Apr. | | | 10 | .50 | 114 | 0 | .08 | 4.6 | 83.2 | 330 | 0 |
| May | | | 129 | .70 | † 4 | 0 | .16 | 9.9 | 18.4 | 68.8 | 0 |
| June | | 1 | 24 | 7.3 | 1 1 | 0 | -35 | 20.6 | 176 | 1,391 | 0 |
| July | | | 24 | 1,300 | 11 | 0 | 131 | 8,051 | 6,428 | 17,238 | 184 |
| Aug. | | | 11 | 2,140 | 8 | 5.8 | 402 | 24,749 | 11,236 | 36,369 | 165 |
| Sept. | | | 2 | 393 | 28 | 5.0 | 56.0 | 3,331 | 1,780 | 16,344 | 28.4 |
| Oct. | | | 25 | 119 | 6 | 4.1 | 10.8 | 665 | 173 | 1,201 | 0 |
| Nov. | | | 16 | 9.1 | 20 | 5.4 | 6.89 | 410 | 141 | 609 | 0 |
| Dec. | | | 31 | 7.3 | 1 1 | 6.0 | 6.15 | 378 | 889 | 959,01 | 6.2 |
| Yearly | | | | 2,140 | | 0 | 51.6 | 37,952 | 22,270 | 55,364 | 4,400 |

Ø Mean daily

[†] And other days

SANTA CRUZ RIVER NEAR LOCHIEL, ARIZONA

ESCRIPTION: Water-stage recorder located in the United States near left bank on the downstream side of concrete bridge pier of county highway bridge, 2.5 miles northeast of Lochiel, Arizona, and 1.5 miles upstream from the international land boundary. The elevation of the zero of the gage has not been determined but top-DESCRIPTION:

ographic maps indicate the elevation of the steream bed at the gage is about 4,620 feet.

RECORDS: Based on current meter measurements or observations of no flow during the year. Records obtained and furnished by the U.S. Geological Survey. Records awailable: January 1949 through 1971.

REMARKS: There are small diversions by ground water pumping for irrigating about 200 acres above this station.

EXTREMES: Maximum discharge, 4,810 second-feet on September 12, 1965 (gage height 8.90 feet); minimum discharge, no flow for several days of each year.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|---------------------------------|----------------------------------|---------------------------------|---------------------------------|---------------------------------|----------------------------------|---------------------------------|--------------------------------------|---------------------------------|--|---------------------------------|---------------------------------|
| 12345 | 0.79 .78 .79 .69 | 0.32 .30 .26 .26 .30 | 0.47 .44 .46 .50 | 0.31 .25 .19 .17 | 0.07 .05 .05 .06 | 0.05 .04 .03 .03 .02 | .04 .04 .04 | 1.0 .22 .43 .26 .24 | 2.1 2.1 2.1 2.1 2.1 | 3.6 3.2 3.3 3.4 3.4 | 3.2 3.1 2.9 2.8 2.7 | 1.4 1.4 1.6 1.5 |
| 6 7 8 9 10 | .68 .62 .62 .60 | .32 .33 .35 .34 .30 | .43 .44 .50 .49 | .18 .16 .15 .13 | .06 .06 .06 .07 | .03 .03 .03 .01 | .04 .05 .04 .04 | .26 .26 .25 .28 | 2.5 48 31 3.9 3.6 | 3.5 4.0 3.8 4.0 4.3 | 2.5 2.3 2.2 2.1 2.2 | 1.4 1.4 1.3 1.3 |
| 11 12 13 14 15 | .55 .50 .50 .49 .47 | .30 .32 .37 .29 .22 | .49 .49 .49 .48 | .09 .09 .11 .16 .24 | .08 .08 .08 .09 | .03 .02 .02 .01 | .04 .03 .02 .04 .05 | 7.5 26 27 193 12 | 3.5 3.6 3.6 3.8 3.6 | 5.0 5.0 5.0 5.0 5.3 | 2.2 2.1 2.0 2.0 2.1 | 1.2 1.2 1.2 1.2 1.2 |
| .16 17 18 19 20 | .45 .45 .47 .45 | .19 .22 .22 .27 .36 | .47 •35 .29 .29 .25 | .30 .30 .38 .40 .33 | .08 .09 .09 .08 | 0 0 0 | 2.7 .19 .22 .26 | 2.5 3.5 29 118 46 | 3.5 7.0 4.2 4.2 3.6 | 4.8 6.5 4.5 3.7 3.7 | 2.6 2.1 1.9 1.8 1.8 | 1.2 1.1 1.1 1.1 |
| 지 않 않 같 살 참 참 참 참 참 하 | .32 .32 .34 .35 .32 | .32 .32 .31 .40 | .24 .27 .20 .21 .20 | .35 .30 .29 .15 | .06 .05 .06 .06 | 0 0 0 0. 0 | .13 .16 .15 .15 | 78 5.8 2.4 2.0 2.0 | 3.5 3.5 3.5 3.5 3.6 | 3.6 3.6 4.0 5.2 4.7 | 1.7 1.6 1.6 1.6 1.5 | 1.1 1.0 1.0 1.0 |
| 26 27 28 29 30 31 | .32 .32 .32 .32 .32 | _երեկ _երեկ _երեկ | .20 .20 .24 .27 .27 | .18 .14 .10 .09 | .06 .05 .04 .05 .04 | 0 0 0 0 | .15 .16 .17 .35 3.0 | 2.0 2.1 2.2 10 12 2.8 | 3.5 3.6 3.8 7.0 | 3.3 3.3 3.3 3.2 3.2 3.2 | 1.5 1.4 1.4 1.4 | 1.0 1.0 1.0 1.0 |
| Sum | 15.07 | 8.95 | 11.39 | 6.06 | 2.02 | 0.37 | 9.99 | 744.00 | 190.6 | 125.6 | 61.7 | 36.8 |

| | | | | Current 1 | ear 19 | 971 | | | Per | iod 1949-197 | 1 |
|---------|------|--------|-------------|-----------|-------------|------|---------|-----------|---------|--------------|---------|
| | | e Gage | ø | Extreme S | econd F | eet | Average | Total | | Acre Feet | |
| Month _ | Fe | et | | High | | Low | Second | | | r | |
| | High | Low | Day | | Day | | Feet | Acre Feet | Average | Maximum | Minimum |
| Jan. | | | 11 | 0.79 | ŧ21 | 0.32 | 0.49 | 29.9 | 47.2 | 226 | 1.3 |
| Feb. | | 1 | †25 | .44 | 16 | .19 | .32 | 17.8 | 40.8 | 261 | 1.8 |
| Mar. | | 1 | 7 4 | .50 | 123 | .20 | .37 | 22.6 | 35.8 | 250 | .7 |
| Apr. | | | 19 | .40 | 711 | .09 | .20 | 12.0 | 20.2 | 148 | 0 |
| May | | 1 | †1 4 | .09 | 128 | .04 | .065 | 4.0 | 9.1 | 49.5 | 0 |
| June | | 1 | 1 | .05 | † 15 | 0 | .012 | .7 | 2.8 | 22.3 | 0 |
| July | | | 30 | 3.0 | 11 | 0 | .32 | 19.8 | 502 | 4,270 | 1.6 |
| Aug. | | 1 | 14 | 193 | 2 | .22 | 24.0 | 1,476 | 1,134 | 10,120 | .08 |
| Sept. | | 1 | 7 | 48 | 1 1 | 2.1 | 6.35 | 378 | 344 | 2,634 | 0 |
| Oct. | | l | 17 | 6.5 | 1 2 | 3.2 | 4.05 | 249 | 93.5 | 448 | 0 |
| Nov. | | 1 | l | 3.2 | 127 | 1.4 | 2.06 | 122 | 45.0 | 182 | 0 |
| Dec. | | | 3 | 1.6 | 123 | 1.0 | 1.19 | 73.0 | 72.8 | 693 | 0 |
| Yearly | | | | 193 | | 0 | 3.29 | 2,405 | 2,347 | 12,633 | 126 |

Mean daily

f And other days

SANTA CRUZ RIVER AT EL CAJON, SONORA

SECRIPTION: Water-stage recorder, cableway, and Cipolletti weir with crest length of 26.25 feet and depth of 0.82 foot, 4.3 miles southwest of Santa Cruz, Sonora and approximately 30 miles southeast of Nogales, Sonora. Zero of gage is 4,270.24 feet above mean sea level, U. S. C. & G. S. datum, which is the same eleva-DESCRIPTION: and Cipolletti weir with crest length of 26.25 feet and depth tion as the crest of the weir.

RECORDS: Data is based on river stages and on current meter measurements made during the year. Data obtained and furnished by the Mexican Section of the Commission. Records available: January 14, 1954 through August 1959, October 1, 1959 through June 14, 1966; July 1960; January 6, 1961 through September 5, 1963; October 15, 1963 through August 3, 1964; January 9 through February 11 and April 1 through December 1965; January 1, 1966 through November 1967; February 8 through October 23 and December 13 through 31, 1968; January 1 through April 9, June 5 through July 30, August 15 through 24, and October 17 through December 1969; 1970; February 1 through May 23 and June 18 through November 1971.

REMARKS: Irrigation diversions above the station affect the regimen of the river. A flood in August 1955 de-

stroyed the weir which was repaired in February 1957. EXTERMES: Maximum instantaneous discharge, 4,590 second-feet on August 6, 1955 with stage of 6.00 feet. Minimum discharge, zero on several days during 1968, 1970, and 1971.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|-------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|--------------------------------------|--|--------------------------------------|--|---------------------------------|---|
| 1 2 3 4 5 | 99999 | 1.8 1.8 1.8 1.8 | 2.5 2.5 2.5 2.5 2.5 | 0 0 0 | 1.8 1.4 1.4 1.4 | 00000 | 4.6 5.3 5.7 5.7 4.9 | 4.9 2.1 .4 0 | 30.7 25.4 23.3 20.8 18.4 | 18.4 13.8 10.6 8.8 8.1 | 7.1 6.7 6.4 6.0 6.4 | 0 0 0 0 |
| 6 7 8 9 | 00000 | .7 0 0 0 | 2.5 2.1 1.4 1.4 1.4 | 0 1.1 1.1 1.4 1.1 | 1.8 1.8 1.8 2.1 1.8 | 00000 | 4.9 5.3 5.3 5.7 5.3 | 0 0 .7 9 8.1 | 17.0 18.8 44.5 24.0 24.0 | 7.4 6.7 7.1 6.4 6.0 | 6.4 6.4 5.7 5.7 4.9 | 0 0 0 0 |
| 11 12 13 14 15 | 9 9 9 | .4 1.1 .7 1.4 1.8 | 1.8 0 .7 1.4 | .7 .4 9 1.4 1.8 | 2.1 2.1 3.2 3.2 2.8 | 0 0 0 0 | 5.3 5.7 6.7 11.3 6.4 | 19.1 21.2 27.9 25.4 21.9 | 21.9 19.8 18.4 18.7 17.0 | 7.1 7.1 6.4 6.4 7.4 | 4.6 3.9 4.2 5.3 | 0000 |
| 16 17 18 19 20 | 9 9 9 | 1.4 1.4 1.1 2.1 2.1 | .7 1.4 .7 .7 | 3.5 3.9 3.2 2.8 2.1 | 2.8 2.8 2.8 2.5 2.1 | 9 9 2.8 3.5 3.5 | 6.7 4.6 4.2 3.2 3.5 | 11.3 8.1 24.7 26.8 21.9 | 17.3 20.5 21.2 19.4 12.7 | 8.5 16.2 14.1 8.5 7.1 | 7.1 6.4 5.7 5.3 4.9 | 00000 |
| रा २२ २५ २५ | 0 0 0 | 2.8 2.5 2.1 2.1 2.1 | 1.1 1.4 1.8 1.1 | 1.8 1.4 .4 .7 1.4 | 1.8 1.8 2.8 9 | 4.2 4.6 5.3 4.9 | 3.5 5.3 10.2 8.8 0 | 13.4 30.4 32.8 54.7 199 | 9.9 8.8 8.8 8.1 7.8 | 6.7 6.4 6.4 8.8 16.6 | 4.9 4.2 4.2 3.9 4.2 | 0 0 0 0 |
| 26 27 28 29 30 31 | 0 0 0 0 | 2.5 2.5 2.1 | .4 .7 .4 .4 | 1.8 1.8 1.8 1.8 | 9 9 9 9 | 5.3 4.9 4.6 4.2 4.2 | 0 1.1 5.3 4.2 5.3 8.5 | 171 159 155 156 163 133 | 7.1 7.1 7.1 26.1 26.8 | 9.5 7.1 6.7 6.4 6.7 7.1 | 3.9 3.5 3.5 4.2 3.5 | 000000000000000000000000000000000000000 |
| Sum | 9 | 41.5 | 38.6 | 39.6 | J | | 162.5 | 1,491.8 | 551.4 | 270.5 | 153.3 | 9 |

Current Year 1971 Period Ø 1954-1971 **Extreme Second Feet** Extreme Gage Average Total Acre Feet Second Feet Month High Low Average Maximum Minimum Feet Acre Feet Day Day High Low 1,486 1,598 885 203 Jan. 5**3**8 80.6 435 80.6 Feb. 21 3.5 2.5 4.2 0 1.4 .07 ٥ 74.4 Mar. **†2**6 1.1 74.4 392 .03 0 1 1 711 74.9 Apr. 16 **f** 1 0 1.4 76.0 255 188 ō .10 512 50.3 May ۵ 0 148 486 63.1 June ٥ 28.3 †25 † 4 315 630 1,227 83.5 July 0 5.3 .46 0 14 229 Aug. 30 8 237 0 48.0 2,961 4,666 32,608 1.90 0 3,000 1,165 106 935 413 Sept. 102 126 6.7 18.4 1,091 1.05 .13 78.5 Oct. 25 16 29.7 10 8.8 538 302 .13 .52 379 838 134 Nov. .20 .07 8.8 127 3.5 186 831 Dec. 454 38,895 2,317 10,904 Yearly

4

Ø Period includes only months and years completed

f And other days

SANTA CRUZ RIVER NEAR NOGALES, ARIZONA

DESCRIFTION: Water-stage recorder, cable with sit-down cable car located 5.5 miles east of Nogales, Arizona, 0.8 mile downstream from the international land boundary and 6 miles upstream from the Santa Cruz River bridge on State Highway No. 82. Zero of gage is 3,702.54 feet above mean sea level, U. S. C. & G. S. datum (levels by International Boundary and Water Commission).

(levels by International Boundary and Water Commission).

RECORDS: Based on current meter measurements or observation of no flow during the year. Computations by shifting control methods. Records obtained and furnished by the U.S. Geological Survey. Records available: March to November 1907 and April 1909 to December 1912 (discharge measurements and fragmentary gage height record). January 1913 to June 1922 (October 1915 to September 1916, monthly discharge only), May 1930 to December 1933, July 1935 through 1971.

REMARKS: Diversions in both countries affect the flow at this station. The major diversions occur in Mexico for domestic and irrigation uses. There are no storage dams above the station as of December 1971.

EXTREMES: Maximum discharge, 15,200 second-feet on December 20, 1967 (gage height 13.5 feet); minimum discharge, no flow for several days of many years.

Mean Daily Discharge in Second Feet 1971 - Annual and Period Summary

| Day | Jan. | Feb. | March | April | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |
|----------------------------------|---------------------------------|---------------------------------|--|---------------------------------|----------------------------------|------------------|--------------------------------------|--|--------------------------------|-----------------------------------|----------------------------|----------------------------|
| 1 2 3 4 5 | 4.5 4.5 6.1 4.9 | 3.4 3.4 3.0 3.0 | 4.9 4.9 4.2 4.2 3.7 | 3.7 3.4 3.7 3.4 3.4 | 0.50 .60 .50 .40 .40 | 0 0 0 0 | 0 0 0 0 | 14 14 122 8.8 1.8 | 321 157 81 61 48 | 25 19 15 15 13 | 29 27 26 23 26 | 18 17 17 18 23 |
| 6 7 8 9 | 4.5 4.9 5.3 4.5 4.5 | 3.0 3.0 2.6 2.6 3.0 | 3.4 3.4 3.7 4.2 | 3.0 1.8 1.6 1.3 1.1 | .40 .40 .40 .30 | 0 0 0 0 | 0 0 0 | .60 .20 3.0 51 22 | 52 29 48 34 22 | 12 14 13 11 7.6 | 23 22 23 20 20 | 21 20 36 33 31 |
| 12 13 14 15 | 3.7 3.4 3.7 4.2 | 3.0 2.6 2.6 3.0 3.0 | 4.2 4.5 4.2 3.7 3.4 | .90 1.1 .90 .70 1.1 | .30 .30 .30 .20 | 0 0 0 | 0 0 0 0 | 280 167 773 22 165 | 18 15 13 13 | 9.4 13 11 10 | 19 19 18 19 | 23 21 20 23 21 |
| 16 17 18 19 20 | 4.9 5.3 5.3 4.9 3.4 | 3.0 4.5 6.1 5.3 5.7 | 3.0 3.0 2.4 1.8 1.6 | 1.1 .90 1.1 2.4 1.3 | .10 .10 .10 .10 | 0 0 0 0 | 0 0 0 0 | 59 48 138 204 772 | 11 10 11 14 11 | 15 67 110 45 31 | 23 27 20 20 20 | 19 19 18 19 18 |
| 22 23 24 25 | 4.9 4.9 4.9 4.5 | 5.7 5.3 4.2 4.5 4.5 | 1.6 1.3 1.3 1.8 3.0 | 1.1 .70 .60 .60 | .10 .10 .10 .10 | 0 0 0 0 | 6.3 18 1.5 276 170 | 431 131 50 197 275 | 6.1 8.8 9.4 10 9.4 | 27 23 21 58 320 | 19 19 18 16 15 | 17 16 16 15 16 |
| 26 27 28 29 30 31 | 3.9 4.2 3.8 3.4 3.0 | 3.4 3.4 4.2 | 3.0 3.7 3.7 4.2 4.5 4.2 | .60 .60 .70 .70 | 000000 | 0 0 0 0 | 2.4 1.3 129 289 40 74 | 205 121 300 371 348 265 | 9.4 9.4 8.2 17 31 | 136 88 61 45 39 34 | 18 15 17 16 18 | 18 16 18 16 15 |
| Sum | 1 3 6.9 | 104.4 | 104.1 | 44.80 | 6.50 | 0 | 1,007.5 | 5,587.40 | 1,099.7 | L,319.0 | 614 | 614 |

| | | | _ | Current Y | ear 19 | 971 | | | Per | iod 1936-197 | 1 |
|--|------|-----|--|--|---|---|---|--|---|---|---|
| Month | | | | Extreme Se | cond F | | Average | Total | | Acre Feet | |
| Month | High | Low | Day | High | Day | Low | Second Feet | Acre Feet | Average | Maximum | Minimum |
| Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. | | | 3 18 1 1 1 2 29 13 1 25 | 6.1 6.1 4.9 3.7 .60 0 289 773 321 320 29 | 31 † 8 †22 †23 †26 † 1 7 21 10 †25 | 3.0 2.6 1.3 .60 0 0 .20 6.1 7.6 | 4.42 3.73 3.36 1.49 .21 0 32.5 180 36.7 42.5 20.5 | 272 207 206 88.9 12.9 0 1,998 11,082 2,181 2,616 1,218 | 1,209 868 626 216 68 70 2,468 6,485 1,402 397 298 | 16,710 11,129 2,692 1,186 338 1,020 15,610 45,790 7,507 2,616 1,218 | 62 59 95 19 2 0 45 91 17 1.2 27 |
| Dec. Yearly | | | 8 | 36 773 | 124 | 15 0 | 19.8 | 1,218 21,100 | 1,897 | 28,559 57,671 | 3,499 |

Ø Mean daily

† And other days

SEWAGE INFLUENT, NOGALES INTERNATIONAL TREATMENT PLANT

DESCRIPTION: Two 12-inch Parshall flumes, each with a recording flow meter and continuous totalizer, one located at the international boundary for measuring effluent coming from Nogales, Sonora and the second located at the treatment plant in the influent line of secondary settling tank; and two calibrated sludge pumps of which pumping times are recorded. One pumps from primary settling tank into digester and the other recirculates sludge from secondary tank to primary tank. Bypass of rew sewage may be made to Nogales Wash, the quantity being estimated on basis of head in a control box in influent line ahead of primary tank. Nogales international sewage treatment plant is located near the north edge of Nogales, Arizona on right bank of Nogales wash, approximately 2 miles downstream from the international boundary.

RECORDS: Total effluent is computed by adding to the flow measured in the flume from primary to secondary tank, the sludge pumped from primary tank into digester, which does not pass through this flume; subtracting the sludge recirculated from secondary to primary tank, which passes through this flume whice; and adding those flows of bypassed raw sewage into Nogales Wash. Flows from the United States are deduced from total measured flows less measured flows from Mexico. Records available: Continuous monthly record since the plant was placed in operation in August 1951, daily record January 1952 through 1971.

REMARKS: Nogales International Treatment Plant treats combined sewage from Nogales, Arizona and Nogales, Sono-

REMARKS: Nogales International Treatment Plant treats combined sewage from Nogales, Arizona and Nogales, Sonora by means of primary and secondary sedimentation, sludge digestion, and trickling filters. Chlorination of plant effluent, which may be used for irrigation of lands lying north of the plant, is carried out by the United States at its expense.

| | Total | Monthly F | lows | Mea | n Daily F | lows-Mill | ions of Ga | llons Per l | Day |
|--------|----------|-------------|-----------|---------|-----------|-----------|------------|-------------|-------|
| Month | Milli | ons of Gall | ons | Curr | ent Year | 1971 | Peri | od 1952-1 | 971 |
| | U.S. | Mexico | Total | Maximum | Minimum | Mean | Maximum | Minimum | Mean |
| Jan. | 43.280 | 50.724 | 94.004 | 3.217 | 2.737 | 3.032 | * 4.800 | 0.650 | 2.240 |
| Feb. | 39.550 | 45.913 | 85.463 | 3.460 | 2.756 | 3.052 | * 6.130 | .650 | 2.320 |
| Mar. | 44.386 | 47.946 | 92.332 | 3.162 | 2.538 | 2.978 | 4.610 | .750 | 2.211 |
| Apr. | 42.152 | 48.405 | 90.557 | 3.219 | 2.583 | 3.019 | 4.301 | .700 | 2.169 |
| May | 43.757 | 51.407 | 95.164 | 3.406 | 2.573 | 3.070 | 4.000 | .550 | 2.079 |
| June | 40.098 | 44.448 | 84.546 | 3.123 | 2.550 | 2.818 | 3.800 | .700 | 1.958 |
| July | 43.527 | 47.069 | 90.596 | 3.495 | 2.099 | 3.020 | 3.689 | .700 | 2.018 |
| Aug. | 8 27.708 | 58.923 | 86.631 | 3.857 | .750 | 2.795 | 4.928 | .750 | 2.309 |
| Sept. | 47.073 | 51.997 | 99.070 | 3.765 | 2.768 | 3.302 | 4.541 | .800 | 2.620 |
| Oct. | 55.429 | 51.061 | 106.490 | 3.804 | 3.106 | 3.435 | 3.999 | .700 | 2.474 |
| Nov. | 46.656 | 58.439 | 105.095 | 4.016 | 3.104 | 3.503 | 4.016 | .800 | 2,262 |
| Dec. | 42.693 | 65.867 | 108.560 | 3.894 | 3.202 | 3.502 | * 5.200 | -350 | 2.301 |
| Yearly | 516.309 | 622.199 | 1,138.508 | 4.016 | 0.750 | 3.127 | * 6.130 | 0.350 | 2.247 |

^{*} Partly estimated

⁸ Main line broken by contractor 8-10-71, back in operation 8-14-71

RAINFALL ON THE SANTA CRUZ RIVER WATERSHED IN INCHES

Tabulated below are the monthly records of rainfall with averages for their periods of record at stations located in the United States and Mexico. Two stations are operated and maintained by the United States Section of the Commission, three by the National Weather Service, and one by the Mexican Section of the Commission. For location, elevation, period of record, type of gage in use, and the observer, see alphabetical listing of stations on the following page.

In United States

| | | s Ranch, rizona | | anelo, rizona | | agonia, rizona | | gales, rizona | | Sanitation 2N, Arizona |
|--------|-------|----------------------|----------------|----------------------|-------|----------------------|-------|----------------------|-------|---------------------------|
| Month | 1971 | Average 1952-1971 | 1971 | Average 1930-1971 | 1971 | Average 1930-1971 | 1971 | Average 1914-1971 | 1971 | Average 1953-1971 |
| Jan. | 0 | 0.80 | 0.11 | 1.10 | 0.22 | 1.18 | 0.26 | 1.03 | 0.20 | 0.91 |
| Feb. | 0 | .49 | .97 | 1.08 | 1.20 | 1.03 | 1.03 | .84 | .98 | .60 |
| Mar. | 0 | .84 | 0 | .76 | 0 | .8ī | 0 | .75 | 0 | .74 |
| Apar. | 0 | .22 | .36 | -37 | .43 | -33 | .27 | .29 | .26 | .14 |
| May | 0 | .09 | 0 | .12 | 0 | .16 | 0 | .14 | 0 | .08 |
| June | .30 | .45 | 0 | .83 | .94 | .46 | .25 | .46 | .18 | .42 |
| July | 3.46 | 4.82 | 4.07 | 4.36 | 4.94 | 4.53 | 4.32 | 4.20 | 3.30 | 4.71 |
| Aug. | 7.44 | 4.94 | 5.92 | 4.58 | 6.20 | 4.30 | 7.89 | 4.01 | 8.25 | 4.37 |
| Sept. | 2.40 | 1.56 | 2.41 | 1.69 | 1.97 | 1.80 | 2.15 | 1.61 | 2.48 | 1.48 |
| Oct. | 1.99 | .72 | 2.04 | .86 | 2.45 | .81 | 1.76 | .71 | 1.71 | -84 |
| Nov. | .70 | .50 | .48 | .74 | 1.12 | .78 | 1.34 | .69 | -35 | .54 |
| Dec. | 1.80 | 1.23 | 2.03 | 1.44 | 2.26 | 1.45 | 2.20 | 1.33 | 1.37 | 1.43 |
| Yearly | 18.09 | 16.66 | 18 .3 9 | 17.93 | 21.73 | 17.64 | 21.47 | 16.06 | 19.08 | 16.26 |

| | | Lazaro, nora |
|--|---|--|
| Month | 1971 | Average 1961-1971 |
| Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. | 0.08 .63 0 .35 0 .08 5.91 3.54 1.65 1.89 | 0.71 .55 .67 .51 .16 .43 4.88 3.58 1.77 .71 |
| Dec. Yearly | 1.42 | 1.61 |

LOCATION OF RAINFALL STATIONS IN THE SANTA CRUZ RIVER BASIN

The precipitation records of the stations listed alphabetically below begin on the date shown and extend through 1971.

In United States

| NAME OF STATION | TYPE GAGE | LATITUDE | LONGITUDE | ELEV. (FT.) | RECORD BEGAN | OBSERVER |
|--|--------------|-------------------------------|--|---|--|--|
| Canelo, Arizona Meigs Ranch, Arizona Nogales, Arizona Nogales Sanitation Plant 2N, Arizona Patagonia, Arizona | សល្អ ស្ល | 31° 33' 31° 21' 31° 33' | 110° 32' 110° 36' 110° 55' 110° 56' 110° 45' | 4,985 4,836 3,808 3,757 4,044 | 1930 Mar. 1952 1914 June 1952 1930 | R. E. Ewing I. B. & W. C. Milford L. Noon I. B. & W. C. O. J. Rothrock |

| NAME OF STATION | TYPE GAGE | LATITUDE | LONGITUDE | ELEV. (FT.) | RECORD BEGAN | OBSERVER |
|--------------------|--------------|----------|-----------|----------------|-----------------|----------------------------------|
| San Lazaro, Sonora | S | * | * | 4,199 | Mar. 1954 | I. B. & W. C. Mexican Section |

S Standard 8" rain gage

R Recording rain gage

^{*} Unavailable

TEMPERATURE, HUMIDITY, EVAPORATION AND WIND IN THE SANTA CRUZ RIVER BASIN

Tabulated below are monthly records of temperature, humidity, evaporation, and wind at the station located at the Mogales Sanitation Plant in Arizona two miles morth of the international boundary. This station is operated and maintained by the United States Section of the Commission. Also tabulated below are the monthly records of temperature and evaporation for a station at San Lazaro, Sonora, located approximately 6.5 miles southwest of Santa Cruz, Sonora, and approximately 22 miles southeast of Nogales, Sonora. This station is operated and maintained by the Mexican Section of the Commission. The equipment at the Nogales Sanitation Plant. 2N consists of: Standard 8-inch rain gage, 48-inch diameter evaporation pan with stillwell and hook gage, maximum and minimum thermometer, anemometer (registers miles), hygrothermograph, and psychrometer, hand turbine type. The equipment at the station at San Lazaro, Sonora, consists of: Maximum and minimum thermometer, standard 8-inch rain gage and a 48-inch diameter evaporation pan.

For specific location of these two stations, refer to data opposite same station name shown in "Location of Rainfall Stations", page 95 of this bulletin.

In United States Temperature - Degrees Fahrenheit.

Nogales Sanitation Plant - 2N Month 1971 Mean Max. Min. Jan. 45.7 47.0 Feb. 81 90 89 90 21 Mar. 53.5 56.3 17 28 Apr. 62.8 Мау 32 39 57 48 June 73.5 79.4 102 July 104 97 97 87 75.5 72.4 Aug. 43 19 25 Sept. Oct. 59.6 51.3 82 Nov. Dec. 43.4 75 ī9 Yearly 60.0 104 А

Evaporation - Inches

| | Nogales Sanitation Plant - 2N | | | | |
|---|--|--|--|--|--|
| Month | 1971 | Average 1953-1971 | | | |
| Jam. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec. | * 3.47 5.01 8.94 10.26 13.14 15.99 10.76 7.50 7.83 5.70 4.41 * 3.34 | 3.52 4.67 7.28 9.93 12.60 14.03 9.95 7.53 7.66 6.87 4.39 3.27 | | | |
| Yearly | 96.35 | 91.62 | | | |

In Mexico

Temperature - Degrees Fahrenheit

| | San Lazaro, Sonora | | | | | | |
|---|--|--|--|--|--|--|--|
| Month | 19 | 971 | 1961-1971 | | | | |
| | Max. | Min. | Max. | Min. | | | |
| Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec. | 88 79 88 86 88 100 100 93 95 84 82 66 | 10 21 19 27 39 52 57 45 34 23 | 93 88 99 106 117 124 126 117 115 111 102 | 10 16 19 27 28 41 52 52 39 34 21 | | | |
| Yearly | 100 | 10 | 126 | 10 | | | |

^{*} Estimated

Mean Relative Humidity - Percent

| | Nogales Sanits | ation Plant - 2N | | |
|-------|----------------|------------------|--|--|
| Month | 1971 | | | |
| | Max. | Min. | | |
| Jan. | 100 | 1 | | |
| Feb. | 100 | 33 | | |
| Mer. | 100 | 23 | | |
| Apr. | 74 | 15 | | |
| May | 60 | 30 | | |
| une | 79 | 35 | | |
| uly | 95 | 42 | | |
| ug. | 100 | 77 | | |
| ept. | 95 | 52 | | |
| ct. | 100 | 65 | | |
| lov. | 100 | ĺ | | |
| Dec. | 100 | 51 | | |
| early | 100 | 1 | | |

Mean Wind Speed - Miles Per Hour

| | Nogales Sanitation Plant - 2N | | |
|--------|-------------------------------|----------------------|--|
| Month | 1971 | Average 1953-1971 | |
| Jan. | 1.8 | 2.0 | |
| Feb. | 2.4 | 2.3 | |
| Mar. | 1.9 | 2.6 | |
| Apr. | 2.9 | 2.5 | |
| May | 3.2 | 2.5 | |
| June | 2.7 | 2.3 | |
| July | 2.0 | 1.5 | |
| Aug. | 1.4 | .8 | |
| Sept. | 1.4 | 1.0 | |
| Oct. | 1.9 | 1.5 | |
| Nov. | 1.3 | 1.5 | |
| Dec. | * 1.8 | 1.7 | |
| (early | 2.1 | 1.8 | |

Evaporation - Inches

| | San Lazaro, Sonora | | | |
|--------|--------------------|----------------------|--|--|
| Month | 1971 | Average 1961-1971 | | |
| Jan. | 4.17 | 3.70 | | |
| Feb. | 5.51 | 4.33 | | |
| Mar. | 8.82 | 7.05 | | |
| Apr. | 9.61 | 9.76 | | |
| May | 11.69 | 12.05 | | |
| June | 13.07 | 12.87 | | |
| July | 9.76 | 8.19 | | |
| Aug. | 5.67 | 6.93 | | |
| Sept. | 7.72 | 7.17 | | |
| Oct. | 5.71 | 6.93 | | |
| Nov. | 4.09 | 4.65 | | |
| Dec. | 2.87 | 3.39 | | |
| Yearly | 88.70 | 87.44 | | |

DRAINAGE AREAS ABOVE GAGING STATIONS AND IRRIGATED AREAS ALONG SANTA CRUZ RIVER, SAN PEDRO RIVER, AND WHITEWATER DRAW 1971

The drainage basin areas tabulated below are derived from the best available maps from both the United States and Mexico.

Data on irrigated areas in the Whitewater Draw Basin were furnished by the Smoke Control Section, Phelps-Dodge Smelter at Douglas, Arizona.

| Designation of Areas | Drainage Basin-Square Miles | | | Irrigated Areas-Acres | | |
|--|-----------------------------|--------|-------|-----------------------|--------|--------|
| Designation of Areas | United States | Mexico | Total | United States | Mexico | Total |
| Santa Cruz River: | | | | | : | |
| Above Lochiel, Arizona Gaging Station | 82 | 0 | 82 | 200 | 0 | 200 |
| Above El Cajon, Mexico Gaging Station | 179 | 125 | 304 | ٥ | 2,300 | 2,300 |
| Above Nogales, Arizona Gaging Station | 185 | 348 | 533 | 200 | 2,300 | 2,500 |
| San Pedro River: | | | | | | |
| Above Palominas, Arizona Gaging Station | 92 | 649* | 741 | 412 | 3,460 | 3,872 |
| Whitewater Draw: | | | | | | |
| Above Douglas, Arizona Gaging Station | 1,023 | 0 | 1,023 | 20,000 | 0 | 20,000 |

^{*} An additional 47 square miles in Mexico is tributary to the San Pedro River downstream from this station

CORRECTIONS TO PREVIOUS WATER BULLETINS

| Water Bulletin and Page Numbers | <u>Station</u> | Reference | Published as | Correction |
|--|--|--|---|--|
| 1965-39 | Colorado River at Miguel C. Rodriguez in Mexico - Discharges | EXTREMES Minimum mean daily gage height Date Discharge | 37.96 feet January 8, 1964 19.4 second-feet | 37.86 feet June 11, 1965 1.4 second-feet |
| 1968-95 1969-94 | Location of Rainfall Stations - Santa Cruz | San Lazaro, Sonora Latitude Longitude | 31° 18' 54" 110° 38' 48" | * * Add footnote at bottom of table, * Unavailable |
| 1966-89 1967-87 1968-87 1969-86 | Whitewater Draw near Douglas, Arizona | EXTREMES Maximum gage height Date | 14.93 feet July 27, 1959 | 16.55 feet July 29, 1966 |